Engineering Conferences International ECI Digital Archives

Advances in Cosmetic Formulation Design

Proceedings

7-24-2018

Structural, nanomechanical, and nanotribological characterization of human hair and conditioner using atomic force microscopy and nanoindentation

Bharat Bhushan Ohio State University, USA, bhushan.2@osu.edu

Follow this and additional works at: http://dc.engconfintl.org/cosmetic Part of the <u>Engineering Commons</u>

Recommended Citation

Bharat Bhushan, "Structural, nanomechanical, and nanotribological characterization of human hair and conditioner using atomic force microscopy and nanoindentation" in "Advances in Cosmetic Formulation Design", ECI Symposium Series, (2018). http://dc.engconfintl.org/cosmetic/25

This Abstract and Presentation is brought to you for free and open access by the Proceedings at ECI Digital Archives. It has been accepted for inclusion in Advances in Cosmetic Formulation Design by an authorized administrator of ECI Digital Archives. For more information, please contact franco@bepress.com.

Structural, Nanomechanical, and Nanotribological Characterization of Human Hair and Conditioner using AFM and Nanoindentation

Bharat Bhushan

Ohio Eminent Scholar and Howard D. Winbigler Professor and Director NLBB

Bhushan.2@osu.edu <u>https://nlbb.engineering.osu.edu/</u>

Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics



© B. Bhushan




Outline

- Introduction
 - Hair structure
 - Why is tribology important to desired hair features?
 - Role of shampoos and conditioners
- Objective and Approach
- Experimental Techniques
 - Atomic force microscopy (AFM) and various operating modes
 - Nanoindentation technique
 - Hair samples
 - Contact angle of hair, human skin, and AFM tips
- Hair Cellular Structure Characterization
- Nanomechanical Property Characterization
- Nanotribological Characterization
- Conditioner Distribution Studies
- Surface Potential Measurements Using Kelvin Probe Microscopy (KPM)







2010. 295 p. 100 illus. (Biological and Medical Physics, Biomedical Engineering) Hardcover

ISBN 978-3-642-15900-8

B. Bhushan, The Ohio State University, Columbus, OH, USA

Biophysics of Human Hair

Structural, Nanomechanical, and Nanotribological Studies

This book presents the biophysics of hair. It deals with the structure of hair, its mechanical properties, the nanomechanical characterization, tensile deformation, tribological characterization, the thickness distribution and binding interactions on hair surface. It is the first book on the biophysical properties of hair.... *more on* <u>http://</u> <u>springer.com/978-3-642-15900-8</u>

▶ Presents the biophysics of human hair Contains nanostudies of the properties of hair Gives a macroscale tribological characterization of hair Discusses hair damage




Introduction

- Hair is nanocomposite biological fiber
- It is composed of dead cells, mostly keratin proteins (cystine) (65-95%), water, lipids, pigments.

Hair structure


Schematic of a human hair fiber structure with cuticle sublamellar structure



⁽Robbins, 1994; Smith and Swift, 2002)

Hair fiber consists of three main components: Cuticle, cortex, and medulla

- Cuticle is important in protection of hair.
- Cuticle consists of flat overlapping scales, and appears like tiles on a roof.
- Cuticle is multi-layered. The outermost epicuticle layer is covered with lipid layer (18-MEA) which provides lubrication.



B. Bhushan, Biophysics of Human Hair: Structural, Nanomechanical and Nanotribological Studies, Springer, 2010.

Why is tribology important to desired hair features?

Various functions requiring low friction and adhesion

Name of

Tangled

		Macroscale Micro/nanoscale
Desired hair feature	Tribological attributes	Hair Hair Feel
Smooth feel in wet and dry	Low friction between hair	bundle
environments	and skin in respective	Skin Hair
	environment	
Shaking and bouncing during	Low friction between hair	AN A
daily activities	fibers and groups of hair	Head shake
Easy combing and styling	Low friction between hair	
	and comb (plastic) and low	JAN DE
	adhesion.	
	Combing results in physical	Hair fibers
	damage such as scratching	Combing
	and hair stretching.	Comb tooth
	Note: More complex styles	(plastic)
	may require higher adhesion	Hair
	between fibers.	Entanglement
		* EAR V



N

Hair fibers

- Maintaining health, feel, shine, color, softness, and overall esthetics is highly desired.
- Natural weathering and normal grooming actions such as combing, cutting, blow drying with hot air, chemical dyeing, and permanent wave treatments result into

chemical, mechanical and chemomechanical damage which degrades mechanical and tribological properties.

Role of Shampoos and Conditioners

• Hair care products including shampoos and conditioners are used to clean and repair.


Shampoo – Cleans hair and scalp of oils and dirt.

Conditioner (gel network of cationic surfactants, fatty alcohols, silicones, and water)

 Repairs hair damage and make the hair easier to comb, prevent flyaway, add feel, shine and softness.

 This industry is about \$20 billion dollars in annual sales. Top three hair companies (P & G, L'Oréal and Unilever) all have annual sales on the order of \$5 billion each CB

Interaction of conditioner with hair surface



Hair is negatively charged.

Therefore, positively charged conditioner molecules (cationic surfactants) are attracted to the hair surface which results in conditioner deposition on the hair.

It is even more true for damaged hair, since hair gets even more negatively charged as a result of damaging processes.

C. LaTorre, B. Bhushan, et al., J. Cosmetic Sci. 57, 37 (2006)



Objective and Approach

Objective

• In order to develop better cosmetic products,

Objective of our study is to understand the effect of damage and treatments of hair on morphology, cellular structure, mechanical and tribological properties.

• Study various hair and skin as a function of ethnicity, damage, conditioning treatment, and various environments.




Approach

- Hair cellular structure characterization using SEM and AFM
 - Various ethnic hair including effect of location
 - Cross-section and longitudinal sections of human hair
- Nanotribological characterization using AFM
 - Surface roughness, friction, and adhesion
 - Directionality effects and scale effects on friction and adhesion
- Nanomechanical property characterization using nanoindenter and AFM
 Hardness, elastic modulus, creep, scratch resistance
 In-situ surface characterization of localized deformation of hair
- Macrotribological Characterization using tribometer
- Conditioner distribution studies using AFM
 TR mode, force calibration mode, and adhesive force mapping
- Surface potential studies using KPM
 - Electrostatic charge build-up on hair surface



Experimental Techniques

AFM and various operating modes




- Roughness measurements were made using the Tapping mode (constant amplitude).
- Adhesion, friction and durability studies were carried out in the Contact mode.
- Elastic and viscoelastic properties were measured using the Torsional resonance (TR) mode (constant load)





Nanoindenter



 Nanohardness, elastic modulus, creep, and scratch resistance measurements were made using a Nanoindenter II.


SEM imaging

- Philips XL-30 ESEM
- Hair sample sputtered with thin gold coating prior to SEM measurements



Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics


In situ surface characterization of localized deformation conducted using a tensile stage inside an AFM



I.P. Seshadri and B. Bhushan, Acta Mater. 56, 3585-3597 (2008); I.P. Seshadri and B. Bhushan, Acta Mater. 56, 774-781 (2008); M.S. Bobji and B. Bhushan, J. Mater. Res. 16, 844-855 (2001); M.S. Bobji and B. Bhushan, Scripta Mater. 44, 37-42 (2001).



Macrotribological Characterization Using Tribometer with an environmental chamber



• Macroscale friction and durability studies were carried at various temperature and humidity conditions were carried out using a tribometer.



Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics

Hair Samples

- Virgin and damaged
 - Virgin
 - Chemically damaged (bleached and colored)
 - Mechanically damaged (exposed to combing which shows high degree of cuticle damage)
- Ethnic Hair
 - Caucasian, Asian, and African
- Treatment
 - Polydimethylsiloxane (PDMS) silicon based conditioner
 - Aminosilicone based conditioner that attaches chemically to the surface
 - Soaked in DI water for 5 min (Time for water to penetrate)



Contact angle of hair, human skin, and AFM tips Contact angle affects wettability of hair; one also needs to know how care products


Contact angle affects wettability of hair; one also needs to know how care products affect contact angle.

Contact angles need to be simulated in our measurements.

Sample	Contact angle (°)		Surface energy (N/m)
	Dry	Soaked	
Virgin Caucasian hair Virgin treated Chemically damaged Chemically damaged, treated Mechanically Damaged Asian African	103 ^a 88 ^a 70 ^a 79 ^a 95 ^a 92 ^a 80 ^a	98ª 92ª 70ª 84ª	0.028 ^b
Human skin - forehead	55 ^c		0.043 ^c
- forearm	88 ^c 84 ^d		0.038 ^c 0.029 ^d
- finger	74 ^d 104 ^e (after soap washing) 58 ^e (before soap washing)		0.024 ^d 0.027 ^e
Si ₃ N ₄ film	48 ^f		
Si tip	51 ^g		15

Hair Cellular Structure Characterization

Various ethnic hair using SEM




- Cuticles consists of of flat overlapping scales, observed in all ethnic hair. These appear like tiles on a roof, attached at the root end and point toward the tip end of the hair fiber.
- Hair diameters are different in different ethnic hair.

G. Wei, B. Bhushan, and P. M. Torgerson, Ultramicroscopy 105, 248 (2005)




Hair cross section



SEM images of virgin hair cross section

Effect of location




G. Wei, B. Bhushan, and P. M. Torgerson, Ultramicroscopy 105, 248 (2005).

Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics

- Asian hair seems to be the thickest (~80-100 μm thick, nearly round), followed by African hair (~50-100 μm thick, significantly elliptical) and Caucasian hair (~50-80 μm thick, elliptical).
- Hair near the scalp (root) has complete cuticle scales while no scales are found near the tip.
- Near the tip, the hair experiences more mechanical damage during its lifetime than near the root.

17




The cortex region, the cuticle region (5 layers of cuticle cells, total ~2 μm) and epoxy resin region are easily identified.

Sublamellar structure of the cuticle is observed at high mag. (not shown).

Cortex region shows very fine circular structure of size ~50 nm, which represents the transverse face of the macrofibril and matrix.






Near the tip, parts of the cuticle outer sublamellar layers were removed and underneath layers (the A-layer, the endocuticle, the inner layer) are exposed.

N. Chen and B. Bhushan, J. Micros. 220, 96 (2005).

19

Damage process of hair surface



Due to natural weathering or mechanical/chemical damage,

parts of the cuticle outer sublamellar layers wear off and underneath layers are exposed.

Further damage will cause entire piece of cuticle to be broken off.

The ghost which delineate the original boundary of the cuticle edge is seen.

N. Chen and B. Bhushan, J. Micros. 220, 96 (2005).



Summary

- Various sublamellar cellular structures of cuticle are easily observed using AFM with TR mode technique because of their distinct stiffness and viscoelastic properties.
- Surface of virgin hair near its root end shows little damage and intact smooth cuticle edges.
- Damage occurs near tip end of hair surface because of natural weathering and mechanical/chemical damage, exposing various sublamellar cuticle layers.



Nanomechanical Property Characterization

Hardness and elastic modulus plots across various virgin hair




Table Summary of hardness and elastic modulus of human hair.

	Hardness (GPa)			Elastic modulus (GPa)		
	Cuticle ^a	Cortex ^b	Medulla ^b	Cuticle ^a	Cortex ^b	Medulla ^b
Caucasian	0.32 ± 0.04	0.27 ± 0.02	\sim 0.19	6.0 ± 0.4	6.5 ± 0.5	~ 5.5
Asian	0.39 ± 0.06	0.30 ± 0.02	~ 0.18	7.5 ± 0.8	6.7 ± 0.3	~ 5.8
African	0.24 ± 0.05	0.23 ± 0.06	~ 0.16	4.8 ± 0.6	5.8 ± 0.7	~ 5.0


^aObtained from the hair surface at normal load of 1.0 mN

^bObtained from the hair cross section at normal load of 1.0 mN

- Hardness and elastic modulus of hair decreased going from the surface to the core.
- The Caucasian, Asian and African hair have different nanomechanical properties.
- It appears that Asian hair has the highest hardness and elastic modulus, followed by Caucasian and African hair.

22

G. Wei, B. Bhushan, and P. Torgerson, Ultramicroscopy 105, 248 (2005).



Creep displacement vs. time curves for various hair


- In all cases, the displacement increases with time at a constant load, i.e., hair creeps.
- It is difficult to correlate the creep behavior of each hair to its ethnicity and condition (virgin, damaged, or virgin treated).



G. Wei, B. Bhushan, and P. Torgerson, Ultramicroscopy 105, 248 (2005).

Scratch resistance

Directionality effects on coefficient of friction and scratching



- Scratch depth during scratch is higher for the chemically damaged hair than virgin hair. Chemical damage softens the hair surface, which allows tip to plow into the hair easily.
- Scratch depth in treated hair is high because the tip can easily penetrate into a thin layer of conditioner.

G. Wei and B. Bhushan, Ultramicroscopy 106, 742 (2006)

Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics

- Damaged Caucasian hair, multiple cuticle cells Along cuticle Against cuticle Normal load (mN) 10 8 4 6 20 000 Before scratch Coefficient of friction Ĩ 1.2 1000 After scratch During scratch Scratch 0.8 2000 -3000 0.4 0.0 -4000 10 20 30 40 50 50 0 10 20 30 40 Tip location (µm) (a)
 - Coefficient of friction and damage to hair surface is higher when the tip is scratches the hair against the cuticle.

(b)




Cuticle response to tension – by using *in situ* surface characterization of localized deformation

Virgin Hair

Most significant effect of tension – cuticle lift off due to extensibility differences occurs at 20% strain


- Endocuticle and cell membrane weak, extensible;
- exocuticle, epicuticle cross linked, rigid
- Difference in extensibility interlayer shear forces
- 20% strain failure in endocuticle and delamination Outer cuticle lifts off



I.P. Seshadri and B. Bhushan, Acta Mater. 56, 3585-3597 (2008).



Damaged Hair



Mechanically damaged Caucasian hair

• In damaged hair, lift off of cuticle, and fracture and disappearance of cuticle edges occurs.



I.P. Seshadri and B. Bhushan, Acta Mater. 56, 3585-3597 (2008).

Summary


- The hardness and elastic modulus of hair decreased going from the surface to the core. The cystine content variations in cuticle substructures and cortex are believed to be responsible for the variations.
- The Caucasian, Asian and African hair have different nanomechanical properties. It appears that Asian hair has the highest hardness and elastic modulus, followed by Caucasian and African hair.
- Hair exhibits viscoelastic properties.
- Hair scratches and gets damaged at high loads. Scratch depth is higher for chemically damaged hair than virgin hair because it is softer.
- Tensile stresses cause lifting of outer cuticle at ~20% strain in virgin hair, due to interlayer shear forces and separation between inner and outer cuticle layers.
- Chemical and mechanical damage cause lift off and fracture of outer cuticle (at 10% strain in mech. damaged hair, 20% in chem. damaged).



Nanotribological Characterization

Surface Roughness and Friction

Virgin and chemo-mechanically damaged hair




- Virgin hair: Intact cuticle, low friction
- Damaged hair: Severe cuticle wear, high friction due to an increase in roughness and change in surface properties.
- True for all ethnicities

C. LaTorre and B. Bhushan, Ultramicroscopy 105, 115 (2005).



Virgin and virgin treated (commercial conditioner) hair



- Friction is similar between virgin and virgin treated hair
- Virgin treated hair: high friction contrast due to meniscus contributions due to accumulation of conditioner near cuticle edge

• True for all ethnicities

C. LaTorre and B. Bhushan, Ultramicroscopy 105, 115 (2005).

Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics

F_m

Liquid with surface tension γ

 $F_m = 2\pi R\gamma (\cos\theta_1 + \cos\theta_2)$


29

Sphere

Flat

Durability Test - Effect of cycling with hard Si AFM tip

- Simulation of wear such as by sand particles or combing
- Friction for virgin hair increased (lipid layer worn away)
- Virgin treated hair showed no increase of friction (protective covering)
- Friction of chemically damaged hair was high and remained high



C. LaTorre and B. Bhushan, J. Vac. Sci. Technol. A 23, 1034 (2005)


Summary

- Friction is higher on chemo-mechanically damaged hair than on virgin hair, due to an increase in surface roughness and change in surface properties.
- Friction is similar between virgin and virgin treated hair.
- Durability tests were performed to simulate wear such as by sand loose particles.
- Friction for virgin hair increased due to lipid layer being worn away.
- Virgin treated hair showed no increase of friction because of the presence of conditioner which serves as a protective covering.
- Friction of chemically damaged hair was high and remained high.




Conditioner Distribution Studies using AFM

Conditioner distribution mapping - treated damaged hair





Conditioner film thickness estimation



Separation between sample and tip (nm)


^b Force calibration plot technique

B. Bhushan and G.S. Blackman, ASME J. Tribol. 113, 452 (1991); N. Chen and B. Bhushan, J. Micros. 221, 203 (2006);
 R. Lodge and B. Bhushan, J. Vac. Sci. Technol. A 24, 1258 (2006)
 Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics

NLBE

Film thickness mapping

Film thickness maps of various hair samples



- Thickness of damaged hair (3.1 nm) is larger than virgin hair (2 nm).
- Damaging will partially remove the fatty-acid lipid layer and make surface hydrophilic and amount of water adsorbed on the hair surface increases.
- After conditioner treatment, thickness increases (4.6 nm and 5.5 nm)



N. Chen and B. Bhushan, J. Micros. **221**, 203 (2006)

R. Lodge and B. Bhushan, J. Vac. Sci. Technol. A 24, 1258 (2006) Nanoprobe Laboratory for Bio- & Nanotechnology and Biomimetics

Summary

- Conditioner unevenly distributes and thicker conditioner film is found near the cuticle edges.
- Amino silicones seem to attach to hair and give low friction (Data not shown).



Surface Potential Studies using KPM

Introduction

- Hair is a good insulator (~10¹⁸ ohms/cm), and tends to develop significant static surface charge.
- Surface charge on hair has significant effect on manageability, feel, and appearance "static flyaway effects"

Objective

- To measure local surface charge buildup on variety of hairs by Kelvin probe microscopy
- Investigate the effect of damage, conditioner treatments, and humidity

Triboelectric charging

- Voltage applied across hair sample (0 2 V)
- Macroscale charging hair rubbed with latex finger cot, 5 passes
- Nanoscale charging conducting tip rubbed at 750 nN. 6V bias applied internally to AFM to provide background potential contrast.
- Potential measured before and after rubbing using KPM (in-situ in nanoscale charging)


R. Lodge and B. Bhushan, J. Colloid Interf. Sci. 310, 321 (2007); R. Lodge and B. Bhushan, J. Vac. Sci. Technol. A 25, 893 (2007); I.P. Seshadri and B. Bhushan, J. Colloid Interf. Sci. 325, 580 (2008).






Voltage gradient applied across hair sample

- At 50% RH the potential change is near 1V for 1V change in applied potential. This indicates water vapor in the air improves the charge mobility.
- At 10% RH, the potential charge is less than 1V for 1V change in applied potential. The potential change in chemically damaged hair is lower than that for virgin and conditioner treated hair.
- Both humidity and conditioner treated hair increase the charge mobility which allows dissipation of charge.








R. Lodge and B. Bhushan, J. Vac. Sci. Technol. A 25, 893 (2007)

Triboelectric charging - Macroscale

- In chemically damaged hair with no lipid layer accumulated charge is not dissipated.
- The natural lipid layer on virgin hair surface and conditioner treatment increase mobility of surface charges. This allows dissipation of trapped charges and reduces its amount.


Average surface potential change





R. Lodge and B. Bhushan, J. Colloid Interface Sci. 310, 321 (2007).

Triboelectric charging - Nanoscale



- Average potential change magnitudes - lesser on nanoscale
- Surface potential change is highest in chemically damaged hair followed by virgin hair and conditioner treated hair.
- Lipid layer on virgin hair and conditioner increase the charge mobility responsible for decrease in charge accumulation.



I.P. Seshadri and B. Bhushan, J. Colloid Interface Sci. 325, 580 (2008).

Summary

- The Kelvin probe technique is a powerful tool to study the surface potential characteristics of human hair.
- Applying voltage gradient across hair shows that conditioner treatment and water vapor significantly increases charge mobility on the hair surface.
- Rubbing with latex finger cot and with an AFM tip increases charge on hair. Chemical damage increases charge accumulation, and lipid layer on virgin hair and conditioner treatment increases charge mobility (reduced accumulation).



Overall Summary

- Human hair is a nano-composite biological fiber. A lipid layer covers the outermost surface of cuticle which gets removed.
- For a good dry and wet feel and combing with ease and without entanglement, the hair surface should exhibit low friction and adhesion against various surfaces.
- Mechanical and chemical damage needs to be minimized. A conditioner with lubricating ingredients can be used to reduce damage.
- Nanoscale characterization of cellular structure and mechanical properties as well as morphological, friction, adhesion and wear properties and role of surface charge are needed.
- These studies have been successfully carried out using an AFM and nanoindenter.



References

- B. Bhushan, "Nanoscale Characterization of Human Hair and Hair Conditioners", *Progress Mat. Sci.* **53**, 585-710 (2008).
- B. Bhushan and C. LaTorre, "Structural, Nanomechanical, and Nanotribological Characterization of Human Hair and Skin using Atomic Force Microscopy and Nanoindentation" in *Springer Handbook of Nanotechnology* (B. Bhushan, ed.), 3rd Ed., pp. 1055-1170, Springer-Verlag, Heidelberg, Germany, 2010.
- Bhushan, B., *Biophysics of Human Hair : Structural, Nanomechanical and Nanotribological Studies*, Springer, 2010.
- Bhushan, B., *Biophysics of Skin and Its Treatments Structural, Nanotribological, and Nanomechanical Studies*, Springer, 2017.
- Bhushan, B., Introduction to Tribology, 2nd ed., Wiley, 2013.
- Bhushan, B., Nanotribology and Nanomechanics: An Introduction, 4th ed., Springer, 2017.

Bhushan.2@osu.edu https://nlbb.engineering.osu.edu/





springer.com

Biological and Medical Physics, Biomedical Engineering

Bharat Bhushan

Biophysics of Skin and Its Treatments

Structural, Nanotribological, and Nanomechanical Studies

2 Springer

B. Bhushan Biophysics of Skin and Its Treatments

Structural, Nanotribological, and Nanomechanical Studies

Series: Biological and Medical Physics, Biomedical Engineering

- > Covers all aspects of skin cream and its effect on the human skin
- ► Written for researchers and practicioners
- Provides guidance to professionals and students

This book provides a comprehensive overview of the structural, nanotribological and nanomechanical properties of skin with and without cream treatment as a function of operating environment. The biophysics of skin as the outer layer covering human or animal body is discussed as a complex biological structure. Skin cream is used to improve skin health and create a smooth, soft, and flexible surface with moist perception by altering the surface roughness, friction, adhesion, elastic modulus, and surface charge of the skin surface.

1st ed. 2017, XIV, 165 p. 77 illus., 26 illus. in color.



Hardcover

- ▶ 109,99 € | £82.00 | \$129.00
- *117,69 € (D) | 120,99 € (A) | CHF 121.00

eBook

Available from your library or

▶ springer.com/shop

МуСору

Printed eBook for just

- ▶ € | \$ 24.99
- springer.com/mycopy




Order online at springer.com ► or for the Americas call (toll free) 1-800-SPRINGER ► or email us at: customerservice@springer.com. ► For outside the Americas call +49 (0) 6221-345-4301 ► or email us at: customerservice@springer.com.

The first \in price and the \pm and \$ price are net prices, subject to local VAT. Prices indicated with * include VAT for books; the \in (D) includes 7% for Germany, the \in (A) includes 10% for Austria. Prices indicated with ** include VAT for electronic products; 19% for Germany, 20% for Austria. All prices exclusive of carriage charges. Prices and other details are subject to change without notice. All errors and omissions excepted.



springer.com

Bharat Bhushan



2010. IX, 192 p. 100 illus. (Biological and Medical Physics, Biomedical Engineering) Hardcover

- ▶ 99,95€
- \$129.00
- SFr. 143.50
- ▶ £90.00

ISBN 978-3-642-15900-8

B. Bhushan, The Ohio State University, Columbus, OH, USA

Biophysics of Human Hair

Structural, Nanomechanical, and Nanotribological Studies

This book presents the biophysics of hair. It deals with the structure of hair, its mechanical properties, the nanomechanical characterization, tensile deformation, tribological characterization, the thickness distribution and binding interactions on hair surface. It is the first book on the biophysical properties of hair.... *more on <u>http://</u>springer.com/978-3-642-15900-8*

► Presents the biophysics of human hair Contains nanostudies of the properties of hair Gives a macroscale tribological characterization of hair Discusses hair damage

			of Human Hair" 3-642-15900-8		
Methods of Payment Che	ck/Money Order enclosed	O AmEx	MasterCard VISA Exp. Date		
Please send orders to:	Outside the Americas:		Name		
Springer	Springer Customer Service Center GmbH Haberstrasse 7 69126 Heidelberg		Address		
Order Department PO Box 2485		GmbH	Street Address		
Secaucus, NJ 07096-2485			(Sorry, we cannot deliver to P.O. boxes)		
USA Germany			City / State / ZIP-Code		
 ► Call toll-free 1-800-SPRINGER ► Call: + 49 (0) 6221-345-4301 ► Fax: +49 (0) 6221-345-4229 			Country		
► Fax your order to (201) 348-4505	► Web: springer.com		Telephone / Email		
 Web springer.com Email: orders-hd-individuals@springer.com 		pringer.com	Date 🗙	Signature 🗙	

CA, MA, NJ, NY, and PA residents, please add sales tax. Canadian residents, please add 5% GST. Please add \$5.00 for shipping one book and \$1.00 for each additional book. Outside the US and Canada add \$10.00 for first book, \$5.00 for each additional book. All orders are processed upon receipt. If an order cannot be fulfilled within 90 days, payment will be refunded upon request. Prices are payable in US currency or its equivalent. Remember, your 30-day return privilege is always guaranteed. Pre-publication pricing: Unless otherwise stated, pre-pub prices are valid through the end of the third month following publication, and therefore are subject to change. All ϵ and \pm prices are net prices subject to local VAT, e.g. in Germany 7% VAT for books and 19% VAT for electronic products. Pre-publication pricing: Unless otherwise stated, pre-pub prices are valid through the end of the third month following publication, and therefore are subject to change. All prices exclusive of carriage charges. Prices and other details are subject to change without notice. All errors and omissions excepted. Please consult springer.com for information on postage.