

Optimization of co-culture inoculated microbial fuel cell performance using response surface methodology

M. Amirullslam^a; Huei RueyOng^{ab}; BaranitharanEthiraj^{ac}; Chin KuiCheng^{ad}; Md MaksudurRahman Khan^{ad}

^aFaculty of Chemical and Natural Resources Engineering, Universiti Malaysia Pahang, 26300 Gambang Pahang, Malaysia

^bFaculty of Engineering and Technology, DRB-HICOM University of Automotive Malaysia, 26607 Pekan Pahang, Malaysia

^cDepartment of Biotechnology, Bannari Amman Institute of Technology, Sathyamangalam, Erode District, India

^dCentre of Excellence for Advanced Research in Fluid Flow (CARIFF), Universiti Malaysia Pahang, 26300 Gambang Pahang, Malaysia

ABSTRACT

Microbial fuel cells (MFCs) are considered as promising technology to achieve simultaneous wastewater treatment and electricity generation. However, operational and technological developments are still required to make it as a sustainable technology. In the present study, response surface methodology (RSM) was used to evaluate the effects of substrate concentration, co-culture composition, pH and time on the performance of co-culture (*Klebsiella variicola* and *Pseudomonas aeruginosa*) inoculated double chamber MFC. From the statistical analysis, it can be seen that the performance of MFC was not influenced by the interaction between the initial COD and time, pH and time, pH and initial COD, time and initial COD. However, the interaction between the inoculum composition and time, pH and the inoculum composition, initial COD and inoculum composition significantly influenced the performance of MFC. Based on the RSM results, best performance (power density and COD removal efficiency) was obtained when the inoculum composition, initial COD, pH and time were about 1:1, 26.690 mg/L, 7.21 and 15.50 days, respectively. The predictions from the model were in close agreement with the experimental results suggesting that the proposed model could adequately represent the actual relationships between the independent variables generating electricity and the COD removal efficiency.

KEYWORDS:

Co-culture inoculum; Design of experiments; Box-behnken design; Mutualistic interactions; Chemical oxygen demand