## Experimental evaluation and empirical modelling of palm oil mill effluent steam reforming

Kim HoongNg<sup>a</sup>Yoke WangCheng<sup>bc</sup>; Zhan ShengLee<sup>bc</sup>; Maksudur R.Khan<sup>bc</sup>; Su ShiungLam<sup>d</sup>Chin KuiCheng<sup>bc</sup>

<sup>a</sup> Chemistry and Chemical Engineering, Xiamen University Malaysia, Jalan Sunsuria, Bandar Sunsuria, 43900, Sepang, Selangor, Malaysia

- <sup>b</sup> Centre of Excellence for Advanced Research in Fluid Flow, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300, Gambang Kuantan, Pahang, Malaysia
  - <sup>c</sup> Faculty of Chemical & Natural Resources Engineering, Universiti Malaysia Pahang, Lebuhraya Tun Razak, 26300, Gambang Kuantan, Pahang, Malaysia
  - <sup>d</sup> Eastern Corridor Renewable Energy Group (ECRE), School of Ocean Engineering, Universiti Malaysia Terengganu, 21030, Kuala Terengganu, Malaysia

## ABSTRACT

The current work describes a novel application of steam reforming process to treat palm oilmill effluent (POME), whilst co-generating H<sub>2</sub>-rich syngas from the treatment itself. The effects of reaction temperature, partial pressure of POME and gas-hourly-space-velocity (GHSV) were determined. High crystallinity 20 wt%Ni/80 wt%Al<sub>2</sub>O<sub>3</sub> catalyst with smooth surface was prepared via impregnation method. Baseline runs revealed that the prepared catalyst was highly effective in destructing organic compounds, with a two-fold enhancement observed in the presence of 20 wt% Ni/80 wt%Al<sub>2</sub>O<sub>3</sub> catalyst, despite its low specific surface area (2.09 m<sup>2</sup> g<sup>-1</sup>). In addition, both the temperature and partial pressure of POME abet the COD reduction. Consequently, the highest COD reduction of 99.7% was achieved, with a final COD level of 73 ± 5 ppm from 27,500 ppm, at GHSV of 40,000 mL/h.g<sub>cat</sub> and partial pressure of POME equivalent to 95 kPa at 1173 K. In terms of gaseous products, H<sub>2</sub> was found to be the major component, with selectivity ranged 51.0%–70.9%, followed by CO<sub>2</sub>(17.7%–34.1%), CO (7.7%–18.4%) and some CH<sub>4</sub> (0.6%–3.3%). Furthermore, quadratic models with high R<sup>2</sup>-values were developed.

## **KEYWORDS:**

Palm oil mill effluent; Steam reforming; Syngas; Quadratic models