

## Temperature-insensitive pressure transducer based on reflected broadened spectrum with enhanced sensitivity

*E. Vorathin<sup>a</sup>, Z.M. Hafizi<sup>a</sup>, A.M. Aizzuddin<sup>a</sup>, K.S. Lim<sup>b</sup>*

<sup>a</sup>Advanced Structural Integrity and Vibration Research (ASIVR), Faculty of Mechanical Engineering, Universiti Malaysia Pahang (UMP), 26600, Pekan, Pahang, Malaysia

<sup>b</sup>Photonics Research Centre, Faculty of Science, University of Malaya, 50603, Kuala Lumpur, Malaysia

### ABSTRACT

Pasting of half the grating of an FBG sensor on a natural rubber diaphragm was used to sense the pressure measurement. The pressure-induced strain on half of the grating resulted in bandwidth broadening. From the pressure range of 0 kPa to 20 kPa, the pressure sensitivity at 15 dB bandwidth changed was obtained at 77.7 pm/kPa with 99.94% of linearity. Through total reflected power monitoring via photodetector, the pressure transducer retrieved a sensitivity of 0.1686 dB m/kPa and evaded a complex demodulation technique. As a result of the temperature-independent bandwidth change, the pressure transducer was totally temperature insensitive.

**KEYWORDS:** Fibre Bragg grating (FBG); Pressure sensor; Pressure transducer; Temperature-insensitive

**DOI:** <https://doi.org/10.1016/j.sna.2019.01.028>