

Kent Academic Repository

Full text document (pdf)

Citation for published version

Lu, Gang (2018) Flame monitoring and characterisation through digital imaging and spectrometry.
In: IMEKO 2018- The XXII World Congress of the International Measurement Confederation.
Institute of Measurement and Control

DOI

Link to record in KAR

<https://kar.kent.ac.uk/69038/>

Document Version

Updated Version

Copyright & reuse

Content in the Kent Academic Repository is made available for research purposes. Unless otherwise stated all content is protected by copyright and in the absence of an open licence (eg Creative Commons), permissions for further reuse of content should be sought from the publisher, author or other copyright holder.

Versions of research

The version in the Kent Academic Repository may differ from the final published version.

Users are advised to check <http://kar.kent.ac.uk> for the status of the paper. **Users should always cite the published version of record.**

Enquiries

For any further enquiries regarding the licence status of this document, please contact:

researchsupport@kent.ac.uk

If you believe this document infringes copyright then please contact the KAR admin team with the take-down information provided at <http://kar.kent.ac.uk/contact.html>

Oral session preferred

Flame monitoring and characterisation through digital imaging and spectrometry

James Cugley¹, Gang Lu¹, Yong Yan¹, Ivan Searle²

jc887@kent.ac.uk

¹School of Engineering and Digital Arts, University of Kent, Canterbury, Kent CT2 7NT, UK

² British Sugar PLC, Wissington Sugar Factory, College Rd,

Wissington, King's Lynn PE33 9QG, UK

Fossil fuel fired boilers are often required to work under variable operation conditions. The variability in fuel diet and load conditions result in various problems in boiler performances. A methodology based on digital imaging and spectrometric techniques is proposed for flame monitoring and characterisation on utility boilers. The system developed consists of an optical probe/water jacket, a digital camera, a spectrometer covering a spectral range from 200nm to 900nm and an embedded computer with associated application software. Computer algorithms are established to determine flame characteristic parameters, including size, shape, temperature and spectral distributions. The spontaneous emissions of flame radicals (e.g., CH* and C₂*) and alkali elements such as Sodium (Na) and Potassium (K) are characterised and their relationships with the combustion inputs (e.g., fuel, air-to-fuel ratio) and pollutant emissions (e.g., NO_x) are studied. The methodology proposed are examined on a gas-fired heat recovery boiler under different operation conditions. The results obtained suggest there exist close correlations between flame parameters computed and boiler operation conditions. In particular, flame radicals (CH* and C₂*) and their ratio show a close relationship with the air-to-fuel ratio. The spectral intensities of Na (589nm) and K (767nm) also illustrate a strong link to the type of fuel. Current work focuses on quantifying the relationship between the flame parameters and the boiler operation conditions and establishing a computational model for online prediction of emissions from flame characteristic parameters.