



## Modification of Commercial Polyethersulfone Membranes

Zverina, Libor; Daugaard, Anders Egede

*Publication date:*  
2018

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*  
Zverina, L., & Daugaard, A. E. (2018). Modification of Commercial Polyethersulfone Membranes. Abstract from Nordic Polymer Days 2018, Copenhagen, Denmark.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Modification of Commercial Polyethersulfone Membranes

*Libor Zverina and Anders Egede Daugaard*

*Danish Polymer Center, Department of Chemical and Biochemical Engineering,  
Technical University of Denmark, Building 229, 2800 Kgs. Lyngby, Denmark*

Polyethersulfone is a widely used ultrafiltration membrane material thank to its good film-forming and membrane-forming properties, thermal stability, chemical inertness, and mechanical strength. Polyethersulfone membranes find a range of applications in food processing [1], biomedical field [2], and water-treatment technologies [3]. However, the hydrophobic nature of polyethersulfone brings a challenge of higher fouling propensity of these membranes.

In the presented work commercial polyethersulfone membranes have been surface-grafted with a hydrophilic polymer. The membranes were activated by a heterogeneous reaction introducing benzyl chloride functionality from which surface-initiated atom transfer radical polymerization was conducted (Figure 1) [4]. It has been shown that the graft density and chain length of the surface polymer graft can be controlled.

These results in combination with versatility of the used polymerization technique offer a tool to tailor the surface properties of commercial polyethersulfone membranes and open up for a wider range of their application.




Figure 1: Heterogeneous activation reaction of a commercial polyethersulfone membrane followed by grafting of a hydrophilic polymer via surface-initiated atom transfer radical polymerization.

## References

- [1] A.W. Mohammad, C.Y. Ng, Y.P. Lim, G.H. Ng, *Bioprocess Technol.* 5 (2012) 1143-1156.
- [2] T. Xiang, Y. Xie, R. Wang, M.B. Wu, S.D. Sun, C.S. Zhao, *Mater. Lett.* 137 (2014) 192-195.
- [3] A. Pagidi, R. Saranya, G. Arthanareeswaran, A.F. Ismail, T. Matsuura, *Desalination.* 344 (2014) 280-288.
- [4] C. Hoffmann, H. Silau, M. Pinelo, J.M. Woodley, A.E. Daugaard, *Mater. Today Commun.* 14 (2018) 160-168.