

**OPTIMIZATION OF BIOBUTANOL PRODUCTION BY *Clostridium* species
UPM-A1 WITH LIQUID PINEAPPLE WASTE USING CENTRAL COMPOSITE
DESIGN (CCD)**

AHMED, IBRAHIM GALADIMA

A dissertation submitted in partial fulfillment of the
requirements for the award of the degree of
Master of Science (Biotechnology)

Faculty of Biosciences and Medical Engineering
Universiti Teknologi Malaysia

JANUARY 2013

DEDICATION

This research work is specially dedicated to my late grandparents, both paternal (Alhaji Umar Galadima and Hajiya Aishatu Umar Galadima) and maternal (Mallam Aliyu Kwadon and Kaka Adda).

ACKNOWLEDGEMENT

Bismillahi, Alhamdulillah

I would like to express my profound gratitude to the Almighty Allah who spares my life to witness the completion of this great study.

Secondly, am expressing warmth appreciation to my dissertation supervisor, Assoc. Prof. Dr. Madihah Bnt Md Salleh, for her ceaseless help, assistance, kindness, encouragement and tolerant; whose sincere guidance and supervision made the completion of the thesis a wonderful one.

I equally appreciate the effort of all Biosciences and Medical Engineering (FBME) staff and Laboratory staff for their endless support and assistance towards the completion of this project.

The efforts of All Makmal Penyelidikan1 (Research Lab. 1) research colleagues were heartily appreciated, particularly that of Moh'd Fawwaz, Shankar Ramanathan, Ang Kuag, Nur-atiqah bnt Kamsani, Anisah bnt Jamil, Kak Huszilina bnt Hussein, Nana Fatimah. And to all members of my family for their patients, concerns, motivations, and prayers towards the completion of this research..

Lastly, am personally pleased to Alhaji Shuaibu Umar Galadima for his ceaseless financial support and aid until the end of this research.

ABSTRACT

Optimization of biobutanol production by *Clostridium* species UPM-A1 was conducted using Central Composite Design (CCD) with liquid pineapple waste as carbon source. The Design Expert[®] Software (State-Ease Inc., 2021 Ease Hennepin Ave, Suite 191, Minneapolis, MN, 55413) Version 6.0.4 was employed for generating the experimental design which consisted of three significant parameters, including temperature, yeast extract, and pH. The design consisted of twenty different experiments including six replicates at central points. The experiments were conducted in accordance with the conditions provided by the software, during which highest biobutanol production was attained at run three with temperature 42.50°C, yeast extract 2.14g/L, pH 5.5, and a total biobutanol concentration value of 0.441 g/L. Then, a model was generated to see the effects of the variables towards the biobutanol produced. Furthermore, the software suggested optimum value for each parameter as temperature 49.35°C, yeast extract 1.80 g/L, and pH 4 with a biobutanol concentration of 0.405 g/L. A laboratory experiment was conducted to test the predicted variables and eventually 0.417 g/L of biobutanol concentrations was achieved, which is slightly higher than the predicted values. Moreover, growth kinetics of the bacteria towards both solvents (biobutanol, acetone, and ethanol) and acids (acetic acid and butyric acid) production under the optimized conditions was conducted and found acetic acid with the highest yield ($Y_{p/s}$) value of 15.26 g/g with maximum productivity of 0.23g/L/h, while biobutanol has the lowest yield ($Y_{p/s}$) value of 1.29 g/g with maximum productivity of 0.01g/L/h. The specific growth rate (μ) and doubling time (t_d) were found as 0.021h^{-1} and 33h respectively. The research concluded that Central Composite Design (CCD) is a handy and promising approach for variable optimization towards biobutanol production. However, due to the kinetics evaluated results, the bacterial strain is not apposite for biobutanol production. Nevertheless, it could be used for acetic acid production.

ABSTRAK

Pengoptimuman penghasilan biobutanol oleh kumpulan spesies *Clostridium* UPM-A1 telah dijalankan menggunakan Rekabentuk Pusat Komposit (CCD) dengan sisa cecair nanas sebagai sumber karbon. Perisian Design Expert®, State-Ease Inc., (2021 Ease Hennepin Ave, Suite 191, Minneapolis, MN, 55413) Versi 6.0.4 telah digunakan untuk menghasilkan reka bentuk eksperimen yang terdiri daripada tiga parameter penting, termasuk suhu, ekstrak yis, dan pH. Reka bentuk terdiri daripada dua puluh eksperimen yang berbeza termasuk enam replikasi pada titik pusat. Eksperimen telah dijalankan selaras dengan syarat-syarat yang disediakan oleh perisian pada ketika penghasilan biobutanol tertinggi dicapai pada kendalian tiga, yang terdiri daripada suhu 42.50°C, ekstrak yis 2.14g/L, dan pH 5,5, dengan jumlah nilai kepekatan biobutanol 0.441 g/L. Setelah itu, satu model telah dibina untuk melihat kesan pembolehubah terhadap biobutanol yang dihasilkan. Tambahan pula, perisian telah mencadangkan nilai optimum bagi setiap parameter seperti suhu 49.35°C, ekstrak yis 1.80 g/L, dan pH 4 dengan kepekatan biobutanol 0.405 g/L. Satu eksperimen makmal telah dijalankan untuk menguji pembolehubah yang diramalkan dan akhirnya biobutanol berkepekatan 0.417 g/L telah dicapai, yang mana sedikit lebih tinggi daripada yang diramalkan. Selain itu, kinetik pertumbuhan bakteria terhadap kedua-dua penghasilan pelarut (biobutanol, aseton dan etanol) dan asid (asid asetik dan asid butyric) di bawah keadaan optimum telah dijalankan dan didapati bahawa asid asetik dengan nilai hasil tertinggi ($Y_{p/s}$) iaitu 15.26 g/g dengan produktiviti maksimum 0.23g/L/h, manakala biobutanol dengan nilai hasil terendah ($Y_{p/s}$) iaitu 1.29 g/g dengan produktiviti maksimum 0.01g/L/h. Kadar pertumbuhan tertentu (μ) dan masa penggandaan (t_d) telah ditemui masing-masing sebagai $0.021h^{-1}$ dan 33h. Penyelidikan ini pada akhirnya, membuat kesimpulan bahawa Rekabentuk Pusat Komposit (CCD) adalah satu pendekatan yang berguna dan menjanjikan harapan baik untuk pengoptimuman pembolehubah dalam penghasilan biobutanol. Walau bagaimanapun, kumpulan bakteria tersebut tidak sesuai untuk penghasilan biobutanol, namun ia boleh digunakan untuk penghasilan asid asetik.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	SUPERVISOR'S DECLARATION	
	AUTHOR'S DECLARATION	iv
	DEDICATION	v
	ACKNOWLEDGEMENTS	vi
	ABSTRACT	vii
	ABSTRAK	viii
	TABLE OF CONTENTS	ix
	LIST OF TABLES	xii
	LIST OF FIGURES	xiv
	LIST OF SYMBOLS/ABBREVIATIONS	xvii
	LIST OF APPENDICES	xx
1	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Statement of Problems	3
	1.3 Objectives of the Research	3
	1.4 Research Scope	4
2	LITERATURE REVIEW	6
	2.1 Butanol	6
	2.2 Biobutanol Potential Benefits and Applications	7

2.3	Microorganisms Producing Biobutanol	9
2.4	Morphology of <i>Clostridium</i> species during biobutanol production	13
2.5	Process of metabolism	15
2.5.1	Anaerobic digestion processes	17
2.6	Biomass as substrate for biobutanol production	18
2.7	Potential used of pineapple waste for biobutanol	21
2.8	Factors Influencing Biobutanol Production	23
2.9	Central Composite Design in Optimization of Biobutanol	25
2.10	Kinetics Parameters	28
2.10.1	Yield Coefficients	28
3	MATERIALS AND METHODS	32
3.1	Microorganism	32
3.2	Medium preparation.	33
3.2.1	Growth Medium (RCM)	33
3.2.2	Biobutanol Production Medium	35
3.3	Research Design and Methodology	36
3.4	Sampling	41
3.5	Analytical Procedures	41
3.5.1	Solvents and acids determination	41
3.5.2	Cell concentration determination	42
3.5.3	Determination of total reducing sugar using DNS Method	42
3.6	Kinetic Evaluation of Solvents and acid fermentation in Batch Culture.	43
4	RESULTS AND DISCUSSIONS	44
4.1	Biobutanol production optimization using CCD	44
4.1.1	Statistical Analysis	46
4.1.2	Model Development and Regression analysis	47
4.1.3.	Analysis of Variance (ANOVA)	50
4.1.4	Analytical Plots	51

	4.1.4.1 Normal Residuals and Plots	51
	4.1.4.2 Outlier T Plot	52
	4.1.4.3 Plot of Cook's Distance	53
	4.1.4.4 The plot of leverage Versus Runs	54
	4.1.4.5 Predicted Versus Actual Plot	55
	4.1.5 Model Graphical plots for the optimization of biobutanol production	56
	4.2 Kinetics Evaluation	56
5	CONCLUSION AND SUGGESTIONS	68
	5.1 Conclusions	68
	5.2 Suggestions	69
	REFERENCES	71
	APPENDICES	86
	APPENDIX A	86
	APPENDIX B	90
	APPENDIX C	94
	APPENDIX D	97

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Application of biobutanol into various industries	9
2.2	Categories <i>Clostridium</i> species	11
2.3	Morphological Characteristics of <i>Clostridium</i> species during Solventogenesis	14
2.4	Various carbon sources for Biobutanol Production	20
2.5	Pineapple nutrient contents	22
2.6	Chemical Composition of Pineapple Waste	23
2.7	Advantages of CCD Over conventional method	25
2.8	Application of Statistical method for optimization of biobutanol production in batch culture	27
3.1	Reinforced <i>Clostridium</i> Medium (RCM) Growth Medium composition	33
3.2	Vitamin and Cysteine Composition	34

3.3	Constituents of Production Medium	35
3.4	Values of the parameters used for Experimental design	36
3.5	Experimental conditions provided by the software	37
4.1	Actual and coded values of the design variables	45
4.2	Biobutanol Produced by <i>Clostridium</i> species UPM-A1 under optimized conditions Using CCD	45
4.3	Predicted and observed values for Biobutanol Concentration using UPM-A1 strain	48
4.4	Analysis of Variance (ANOVA) for variable Model	49
4.5	Regression (ANOVA) for Quadratic Model of Biobutanol Production	51
4.6	Inverse logarithm of Exponential Phase	09
4.7	Comparison of yield coefficients of biomass using various substrates	98
4.8	Yields Coefficients Concentration for both acids and solvents	98
4.9	Solvents and Acids produced by the <i>Clostridium</i> species UPM-A1 during optimization	09

4.10	Comparison of biobutanol produced by this work with various researches	97
------	---	----

LIST OF FIGURES

FIGURE NO.	TITLES	PAGE
2.1	Metabolism of Biomass by Solventogenic <i>Clostridium</i> species	16
3.1	Experimental Design Flow Chart	39
4.1	Normal plot of residuals for the optimization of biobutanol production	51
4.2	Outlier T plot for the optimization of biobutanol production	52
4.3	Cook's Distance plot of experiments for the Optimization of Biobutanol production.	53
4.4	Leverage plot of experiments for the optimization of biobutanol production	54
4.5	Predicted Versus Actual values towards biobutanol concentration	55

4.6	Graphical (3-D) representation for biobutanol yield ; effects of temperature and yeast extract with initial pH value of 5.50.	56
4.7	Graphical (3-D) representation for biobutanol yield ; effects of temperature and pH (yeast extract = 1.3 g/L)	57
4.8	Graphical (3-D) representation for biobutanol yield ; effects of yeast extract and pH (Temperature = 42.50)	58
4.9	Optimum numerical values for each parameter towards Biobutanol Optimization suggested by the software	59
4.10	Graph for the Inverse Logarithm of X at log phase versus sampling time	60
4.11	The time-route outline for substrate consumption and solvents culture by <i>Clostridium</i> species UPM-A1 in batch Culture	63

SYMBOLS AND ABBREVIATION LIST

ABE	-	Acetone-Butanol-Ethanol
ANOVA	-	Analysis of Variance
ATP	-	Standard Temperature and Pressure
CAS	-	Chemical Abstracts Services
CCD	-	Central Composite Design
CO ₂	-	Carbon Dioxide
DF	-	Degree of Freedom
DNS	-	Dinitrosalicylic acid
Fe ₂ S ₀ ₄ .H ₂ O	-	Iron anhydrous Sulphate
g	-	Gram
g/g	-	Gram per gram
g/L	-	Gram per Liter
g/L/h	-	Gram per Liter per Hour
h ⁻¹	-	Per Hour
H ₂	-	Hydrogen gas
HCL	-	Hydrochloric acid
Hrs	-	Hours

Hz	-	Hertz
IUPAC	-	International Union of Pure and Applied Chemistry
K_2HPO_4	-	Dipotassium Hydrogen Phosphate
Kcal	-	Kilo Calorie
KH_2PO_4	-	Potassium Dihydrogen Phosphate
KJ	-	Kilo Joule
LPW	-	Liquid Pineapple Waste
M	-	Molar
$MgSO_4 \cdot 7H_2O$	-	Manganesium Pentahydrate Sulphate
mL	-	Milli Liter
$MnSO_4 \cdot H_2O$	-	Manganese anhydrate Sulphate
NaCl	-	Sodium Chloride
NADH	-	Dinucleotide Nicotinamide Adenine
NaOH	-	Sodium hydroxide
NCIMB	-	National Collections of Industrial, Marine and Bacteria
NH_4NO_3	-	Ammonium nitrate
OD	-	Optical Density
R^2	-	R- Squared
RCM	-	Reinforced <i>Clostridium</i> Medium
rpm	-	Rotation per minutes
S_{max}	-	Maximum Substrate Concentration
STD	-	Standard Temperature and Pressure
t_d	-	Doubling time
UPM	-	University Putra Malaysia
UV	-	Ultra violet

V	-	Voltage
v/v	-	Volume per volume
w/v	-	weight per volume
X	-	Biomass/Cell mass
$Y_{p/s}$	-	Yield coefficients of products based on substrate Consumption
$Y_{p/x}$	-	Yield coefficients of products relating to biomass concentration
α	-	Alpha
β	-	Beta
%	-	Percentage
μ	-	Specific growth rate
μL	-	Micro Liter
μm	-	Micro meter
μ_{max}	-	Maximum specific growth rate
$^{\circ}\text{C}$	-	Degree Celsius

LIST OF APPENDICES

APPENDIX	TITLES	PAGE
A	Determination of Solvents/Acids Using Gas Chromatography (GC)	12
B	Determination of total reducing sugar using DNS Method	13
C	Determination of Cell Concentration by Dry-Cell Weight Method	15
D	Determination of Cell Concentration by Optical Density	17

CHAPTER 1

INTRODUCTION

1.1 Research Background

Butanol is an alcohol ($C_nH_{2n+1}OH$), colorless liquid with odor closely similar to that of fossil oil, containing four carbon atoms and has molecular formula C_4H_9OH . Other members of alcohol apart from butanol are methanol with a carbon atom- CH_3OH , ethanol with 2 carbon atoms- C_2H_5OH , and propanol with 3 carbon atoms- C_3H_7OH . Therefore, the term “Biobutanol” is the butyl alcohol produced from plant raw materials by means of microbial processes. Biobutanol obtained via microbial culture is highly fascinating nowadays. Since it has great achievements including automobiles as biofuels and many other applications, particularly in chemical industries which is used as solvent (Durre, 2007).

As a result of global increasing stipulate for the production of renewable fuels, more interests in microbial production of biobutanol are generated. This opened great opportunities for biologists, because anaerobic bacteria particularly *Clostridium* species

are capable of converting carbohydrates into a variety of solvents such as acetone, butanol, ethanol and more the like.

The production of solvents by *Clostridium acetobutylicum* is of increasing interest worldwide due to its potential significance commercially. One of the research interests intended for raw materials cost reduction towards solvent production is the use of starch and other related materials due to their availability and can be obtained at reasonable prices (Madihah et al., 2000). Qureshi and Blaschek (2001) reported that “the cost of the substrate (raw materials) is an integral part for the overall cost of biobutanol production”. It is equally important to note that biobutanol production by *Clostridium* species had been successful via Ethanol-Acetone-Biobutanol (EAB) culture processes (Durre, 2007).

In earlier generations, the substrates used for biobutanol productions includes sugar cane, raw potatoes, cereal grains etc.. It can be seen that these materials are food related which could cause a competition between utilizing them for food and at the same time for biobutanol production. As time goes on, food shortage became pronounced, because more interest is given to biobutanol production utilizing the food-related materials. This, therefore, necessitated the exploration of crop wastes and agricultural residues, including husks, shells, stovers, hulls, cobs, leaves, molasses, bagasse (Thaddeus et al., 2007), and many other materials that are non-food related, and at the same time, they are cost effective and relatively abundant.

1.2 Statement of Problems

The global demand for energy has been quite up surging exponentially, and fossil fuel reserves keep on dwindling. This could probably be due to the high utilization and turning on to fossil fuels as the foremost source of primary energy, which eventually contributed to global climate change, environmental degradation, and health problems. Nevertheless, biobutanol production from waste (agricultural raw materials, readily available and relatively less expensive) fermentation would enable a clean and environmental friendly technology for energy generation and waste treatment at the same time.

Majority of researches have been conducted to look at the effects of different factors on biobutanol production, but they confined only on conventional ways (one to one factor at a time). As well known that biobutanol production is influenced by two or more factors concurrently, hence the needs to explore the multi-factorial experimental design approach to optimize the production of biobutanol.

1.3 Objectives of the research

The study gives more concern towards the production of biobutanol from liquid pineapple wastes by *Clostridium* species UPM-A1. The study equally investigated Central Composite Design (CCD) to see the effects of the variables towards biobutanol production. Therefore, the main objectives of this work are:

- a) To optimize biobutanol production by locally isolated *Clostridium* species UPM- A1 in batch culture using Central Composite Design (CCD).
- b) To study the relationship between kinetics of solvents (biobutanol, acetone and ethanol) and acid (butyric and acetic acid) production in batch culture.

1.4 Research Scope

The research gives more priority on the optimization biobutanol production in batch culture using liquid pineapple waste. The significant factors that influence biobutanol production were equally investigated and optimized. The significant factors were evaluated through the exploration of statistical multi-factorial design method. The research investigated three significant parameters, which were previously screened by Nafizah (2010) influencing biobutanol production. The parameters include; temperature, pH, and yeast extracts. Each independent variable was studied at a high (+1) and a low (-1) level. The whole design, therefore, consisted of 20 experiments including replication at six center points. Moreover, Central Composite Design (CCD) was applied through investigating the effects of the variables for the optimization of biobutanol production.

Kinetic evaluations of products (acids and solvents) during biobutanol production were determined by identifying the value of the specific growth rate (μ), maximum specific growth rate (μ_{max}), doubling time (t_d), products productivity, yields

coefficients of product formation ($Y_{p/s}$) based on substrate utilization, and yields of biomass based on substrate utilization ($Y_{p/x}$).

REFERENCES

- Abdel-Fattah, Y.R. and Olama, Z.A. (2002). L-Asparaginase production by *Pseudomonas aeruginosa* in solid-state culture: Evaluation of culture conditions using factorial Designs. *Process Biochemistry* 38: 115 – 122.
- Abdul-Wahab, S. A. and Abdo, J. (2007). Optimization of multistage flash desalination process by using a two-level factorial design. *Applied Thermal Engineering*, 27. 413-421.
- Abou-Zied, A.A. and Yassein, M.Y. (1976). Fermentative production of acetone and butanol by *Clostridium acetobutylicum*. *Journal of Industrial Technology* 14 : 349 – 352.
- Ahmad, M. N. and Holland, C. R. (1995). Growth kinetics of single-cell protein in batch fermenters. *Journal of Food Engineering*. 26 (4), p. 443-452.
- Andel, J.G.V., Zoutberg, G.R., Crabbendam, P.M. and Breure, A.M. (1985). Glucose fermentation by *Clostridium butyricum* grown under a self generated gas atmosphere in chemostate culture. *Journal of Applied Microbiology Biotechnology* 23 : 21 – 26.
- Andreesen, J.R., Bahl, H., and Gottschalk, G. (1989). Introduction to the physiology and biochemistry of the genus *Clostridium* in *Biotechnology Handbooks* volume 3 by Minton N.P. and Clarke D. J pp: 27 – 42.

- Andrews, W.H. (ed) (1995). Microbial methods p. 1-119. In Official methods of analysis of AOAC International. 16th ed. European Pharmacopoeia. 7.0
- Antoni D, Zverlov VV, and Schwarz WH (2007). Biofuels from microbes. Applied Microbiology Biotechnology. 77:23–35.
- Antony, J. (2003). Design of Experiments for Engineers and Scientists. New York: Butterworth-Heinemann
- Attebery, H. R., and Finegold S. M. (1969). Combined Screw-Cap and Rubber-Stopper Closure for Hungate Tubes (Pre-reduced Anaerobically Sterilized Roll Tubes and Liquid Media). *Journal of Applied Microbiology*. 18, 558-56.
- Azaliza, S. W., Madihah, M. S., Suraini, A. A., Osman, H. and Nor, M. M. (2009). Medium optimization for chitinase production from *Trichoderma virens* using central composite design. *Biotechnology and Bioprocess Engineering*. 14. 781-787.
- Babu, K.R., and Satyanarayana, T. (1995). α -Amylase production by thermophilic *Bacillus coagulans* in solid-state fermentation. *Process Biochemistry*. 30, 305–309.
- Baut, F., Ficks, M., Viriot, M.L., Andre, J.C., and Engasser, J.M. (1994). Investigation of acetone-butanol-ethanol fermentation by fluorescence. *Journal of Applied Microbiology Biotechnology* 41 : 551 – 555.
- Bernd B; Georg H; Klaus M (1997). Waste Management. Springer, Berlin, ISBN: 31: 540-549.

- Bezerra, M.A., Santelli, R.E., Oliveira, E.P., Villar, L.S., and Escaleira, L.A. (2008). Response Surface Methodology (RCM) as a tool for optimization in analytical chemistry. *Talanta* 76 (5), 965 – 977.
- Box, G. E. P., and Behnken, D. W. (1960). Some new three level designs for the study of quantitative variables. *Technometrics*, 2, 455–475.
- Chauhan, S. (2010). Biomass resource assessment for power generation: a case study from Haryana state, India. *Biomass Bioenergy*. 04.003:1-9.
- Costa, C. C. Vaz, M. R. F.; Da Costa, J. G.; Santos, E. S.; and Macedo, G. R. (2011). Selection, Isolation, and Growth Kinetic Study of a Bacterail Consortium Obtained from the Potengi Mangrove in the Presence of Crude Oil. *Brazilian Journal of Petroleum and gas*. 5 (4): 217 – 225.
- Crabbendem, P.M, Neijssel, O.M., and Tempest, D.W. (1985). Metabolic and energetic aspect of the growth of *Clostridium butyricum* on glucose in chemostate culture. *Archive of Microbiology* 142 : 375 – 382.
- David Ramey,(2004). The light party.(<http://www.lightparty.com/Energy/Butanol.html>).
- Demirbas, A. (2008). Biofuels securing the planet's future energy needs. *Energy Conversion and Management* 50: 2239-2249.
- Dürre, P. (2007). Biobutanol: an attractive biofuel. *Biotechnology. Journal*. 2 (12), 1525–1534.
- Durre P. (1998). New insights and novel developments in *clostridial* acetone-butanol-isopropane fermentation. *Applied Microbiology and Biotechnology*. 49:639–48.
- Emmanuel Serna (2010). Introduction to WtERT Germany & Overview of Waste Management and WtE in the EU-12.

- Ennis, B.M., Gutierrez, N.A., and Maddox, I.S. (1986). The acetone-butanol-ethanol fermentation: A current assessment. *Process Biotechnology* 21 : 131 – 146.
- Ezeji TC, Qureshi N, and Blaschek H.P. (2007). Bioproduction of butanol from biomass: from genes to bioreactors. *Current Opinion on Biotechnology*. 18:220–7.
- Gan, C. Y., and Latiff, A. A. (2011). Extraction of antioxidant pectic-polysaccharide from mangosteen (*Garcinia mangostana*) rind: optimization using response surface methodology. *Carbohydrate Polymers*, 83, 600–607.
- Gan, C. Y., Manaf, N. H. A., and Latiff, A. A. (2010). Optimization of alcohol insoluble polysaccharides (AIPS) extraction from the *Parkia speciosa* pod using response surface methodology (RSM). *Carbohydrate Polymers*, 79, 825–831.
- Gapes, J.R. (2000). The economics of acetone–butanol fermentation: theoretical and market considerations. *Journal of Microbiology and Biotechnology*. 2(1):27–32.
- Gapes, J.R, Larsen, V.F and Maddox, I.S (1983). A note on procedures for inoculum development for the production of solvents by the strain of *Clostridium butylicum*. *Journal of Applied Bacteriology*. 55 : 363 – 365.
- Gasoline (2001). International Chemical Safety Card 1400. Geneva: International Labor Organization.
- Gheshlaghi, R., Scharer, J. M., Young, M. M., and Chou, C. P. (2009). Metabolic Pathways of *Clostridia* for Producing Butanol. *Journal of Biotechnology Advances*. **27**, 764–781.
- Girbal, L., and Soucaille, P. (1998). Regulation of solvent production in *Clostridium acetobutylicum*. *Trend Biotechnology*. 16 : 11 – 16.

- Goh, C. S., Tan, K. T., Lee, K. T. and Bhatia, S. (2009). Bio-ethanol from lignocellulose: Status, perspectives and challenges in Malaysia. *Bioresource Technology*. 1-8.
- Gottipati, R. and Mishra, S. (2010). Process optimization of adsorption of Cr(VI) on activated carbons prepared from plant precursors by a two-level full factorial design. *Chemical Engineering Journal*. 160. 99-107.
- Gottschalk, G., and Bahl, H. (1981). Feasible improvements of the butanol production by *Clostridium acetobutylicum*. *Basic Life Sciences* 18. Trends in the Biology of Fermentations for Fuels and Chemicals. Edited by Elaxander H., Rabson R., Rogers P., Pietro A.S, Valentine R., and Wolfe R. Plenum Press, New York: 463 – 471.
- Gottwald, M., Hippe, H., and Gottschalk, J.C (1984). Formation of n-butanol from D-glucose by strains of *C. tetanomorphum* group. *Journal of Applied Environmental Microbiology* 48 (3) : 573 – 576.
- Gressel, J. (2008). Transgenics are imperative for biofuel crops. *Plant Science*. 174:246–63.
- Green, E.M., and Stephens, G.M. (1996). Biotransformation by *Clostridium beijerinckii* NCIMB 8052 in pH-auxostat culture. *Journal of Applied Microbiology Biotechnology*. 44 : 553 – 556.
- Gutierrez, N. A., I. S. Maddox, K.C. Schuster, H. Swoboda and Gapes, s. (1997). Strain comparison and medium preparation for the acetone-butanol-ethanol (ABE) fermentation process using a substrate of potato. *Bioresource Technology* 66: 263-265.

- Huang H., Liu H., and Gan Y.R. (2010.). Genetic modification of critical enzymes and involved genes in butanol biosynthesis from biomass. *Journal of Biotechnology Advancement*. 20:10-15.
- Hoekman S.K. (2009). Biofuels in the US-challenges and opportunities. *Renew Energy*. 34:14–22.
- Jones, D.T., Westhuizen, A.V.D., Long, S., Allcock, E.R., Reid, S.J. and Woods, D.R. (1982). Solvent Production and Morphological changes in *Clostridium acetobutylicum*. *Journal of Applied Environmental Microbiology* 43(6) : 1434 – 1439.
- Jones, D.T, Woods D.R. (1986). Acetone–butanol fermentation revisited. *Microbiol Rev*. 50(4):484–524.
- Johnson JL, Toth J, Santiwatanakul S, and Chen J.S. (1997). Cultures of “*Clostridium acetobutylicum*” from various collections comprise *Clostridium acetobutylicum*, *Clostridium beijerinckii*, and two other distinct types based on DNA–DNA reassociation. *International Journal and System Bacteriology*. 47(2):420–4.
- Kamarulzaman, K. (2002). *Handbook for Experimenters*. A concise collection of handy tips and statistical tables to help you set up and analyze your designed experiments.
- Kim, S. and Dale, B. E. (2004). Global potential bioethanol production from wasted crops and crop residues. *Biomass and Bioenergy*, 26, 361-375.
- Kim, Y.J., and Weigand, W.A. (1992). Experimental analysis of a product inhibited fermentation in an aqueous two-phased system. *Journal of Applied Biochemistry and Biotechnology* 34/35: 419 – 429.

- Kinley, L. (1999). Design Expert Software version 6 user's guide. A statistics made easy. Stat-Ease, Incorporation.
- Kuehl, R.O. (2000). Design of Experiments: Statistical Principles of Research Design and Analysis, second edition. Duxbury Press, Pacific Grove, CA, pp. 2–225.
- Kumar, M. and Gayen, K. (2011). Developments in biobutanol production: New insights. Journal of Applied energy. 88 1999 – 2012.
- Koukiekolo R, Cho H.Y., Kosugi A., Inui M., Yukawa H., and Doi R.H. (2005). Degradation of corn fiber by *Clostridium cellulovorans* cellulases and hemicellulases and contribution of scaffolding protein CbpA. Applied Environmental Microbiology;71(7):3504–3511.
- Krouwel, P.G, Groot, W.J, Kossen, N.W.F, and Van der Laan (1983). Continuous isopropanol-butanol-ethanol fermentation by immobilized *Clostridium beijerinckii* cell in a packed bed fermenter. Journal of Enzyme Microbial Technology (5) : 46 – 54.
- Kuehl, R.O. (2000). Design of Experiments: Statistical Principles of Research Design and Analysis, second ed. Duxbury Press, Pacific Grove, CA, pp. 2–225.
- Lai, M.C. and Traxler, R.W. (1984). A coupled-stage continuous fermentation for solvent production by *Clostridium acetobutylicum*. Journal of Enzyme Microbial Technology 16 : 1021 – 1026.
- Lee, S.L., and Chen, W.C. (1997). Optimization of medium composition for the production of glucosyl-transferase by *Aspergillus niger* with response surface methodology. Enzyme Microbiology Technology 21: 436 – 440.

- Lenz T.G and Morelra A.R. (1980). Economic evaluation of the acetone–butanol fermentation. *Industrial and Engineering Chemistry Product Resource and Development*. 19:478–83.
- Li, X., Li, Z., Zheng, J., Shi, Z., and Li, L. (2012). Yeast extract promotes phase shift of bio-butanol fermentation by *Clostridium acetobutylicum* ATTC 824 using cassava as substrate. *Bioresource Technology* 125 (2012) 43 – 51.
- Liew, S.T., Arbakariya, A., Rosfarizan, M. and Raha, A.R. (2006). Production of Solvent (acetone-butanol-ethanol) in Continuous Fermentation by *Clostridium saccharobutylicum* DSM 13864 Using Gelatinised Sago Starch as a Carbon Source. *Malaysian Journal of Microbiology*, 2 (2).42-50.
- Liu, Z. Y., Ying, Y., Li, F. L., Ma, C.Q. and Xu, P. (2010). Butanol Production by *Clostridium beijerinckii* ATCC 55025 from wheat bran. *Journal of Industrial Microbial Biotechnology*. 37 (5), 495 – 501.
- Maddox, I.S., Steiner,E., Hirsch, S., Wessner, S., Gutierrez, N.A., Gapes, J.R., and Schuster, K.C. (2000). The cause of “acid crash” and “acidogenic fermentation” during the batch acetone-butanol-ethanol (ABE) fermentation process. *Journal of Molecular Microbiology and Biotechnology* 2 (1), 95 – 100.
- Madi, E., Antranikian, G., Ohmiya, K., and Gottschalk, G. (1987). Thermostable amylolytic enzymes from a new *Clostridium* isolate. *Journal of Applied Environmental Microbiology*. 53 : 1661 – 1667.
- Madigan, M. T., Martinko, J. M. and Parker, J. (2000). *Brock Biology of Microorganism*. 9th ed. Upper Saddle River, N. J.: Prentice-Hall.

- Madihah, M.S, Ariff, A. B, Khalil, M.S, Suraini A. A, and Karim M.I.A. (2000). Partial purification and some properties of alpha- amylase and Glucoamylase Obtained as by-product from Direct Fermentation of Sago Starch to Solvent by *Clostridium acetobutylicum*. *Pakistan Journal of Biological Sciences*, 3(5) 744-749.
- Madihah, M.S, Liew S.T., and Arbakariya B. A. (2008). The Profile of Enzymes Relevant to Solvent Production during Direct Fermentation of Sago Starch by *Clostridium saccharobutylicum* P262 Utilizing Different pH Control Strategies. *Biotechnology and Bioprocess Engineering*. 13: 33-39
- Madihah, M.S, Zainoha, Z., Nursuhanawati, A., and Madzlan, A. (2009). Isolation of Bacteria in Effective Microorganism (EM) Suitable for Degradation of Thiosulfate. Masters thesis, Universiti Teknologi Malaysia.
- Mata-Alvarez, J. (2003). Bio-methanization of the organic fraction of municipal solid wastes
- McAloon, A., Taylor, F., Yee, W., Ibsen, K., and Wooley, R. (2000). Determining the cost of producing ethanol from corn starch and lignocellulosic feedstocks. NREL/TP-580-28893. Colorado: National Renewable Energy Laboratory.
- McNeil, B. and Kristiansen, B. (1986). The Acetone-Butanol fermentation. *Advance Applied Microbiology* 31 : 61 – 90.
- Miller, T.L., and Wolin, M.A. (1976). A serum bottle modification of the Hungate technique for culturing obligate anaerobes. *Journal of Applied Microbiology Biotechnology* 37 : 533 – 538.
- Montoya, D., S, Spitia, E, Silver, W. H.,and Schwarz (200) Isolation of mesophilic solvent producing *clostridium* from Colombian sources: Physiological

characterization, solvent production and polysaccharide hydrolysis. *Journal of Biotechnology* 79: 117-126.

Morris, J. G. (1994). Obligate anaerobic bacteria in biotechnology. *Journal of Applied Biochemistry Biotechnology*. 48, 75-99.

Nafizah, M.D.A. (2010). Screening of Factors Influencing Biobutanol Production From Pineapple Waste Using 2-Level Factorial Design. Universiti Teknologi Malaysia: Masters thesis

Naik SN, Goud VV, Rout PK, Dalai AK (2010). Production of first and second generation biofuels: a comprehensive review. *Renewable and Sustainable Energy Reverse*. 14:578–97.

Noratiqah, B. K. (2012). Optimization of Oil palm Empty Fruit Bunch Degradation using Crude Cellulase From *Aspergillus niger* EFBI in Rotary Drum Bioreactor. Masters thesis. Universiti of Teknologi Malaysia

Oberoi, H. S., Sandhu, S. K. and Vadlani, P. V. (2011). Statistical optimization of hydrolysis process for banana peels using cellulolytic and pectinolytic enzymes. *Food and Bioproducts Processing*. doi:10.1016/j.fbp.2011.05.002.

Ooikaas, L.P., Wilkinson, E.C., Tramper, J., and Buitelaar (1999). Medium optimization for spore production of *Coniothyrium minutans* using statistically-based experimental designs. *Biotechnology and Bioengineering* 64: 92 – 100.

Ostrem, K. (2004). Greening Waste: Anaerobic Digestion For Treating The Organic Fraction Of Municipal Solid Wastes. Earth Engineering Center Columbia University.

- Patakova, p., Lipovsky, J., Cizkova, H., Fortova, J., Rychtera, M., and Melzoch, M. (2009). Exploitation of food feedstock and waste for production of biobutanol. *Czech Journal of Food Science*, 27: 276–283.
- Pfromm PH, Boadu VA, Nelson R, Vadlani P, Madl R. (2010). Bio-butanol vs. bioethanol: a technical and economic assessment for corn and switch grass fermented by yeast or *Clostridium acetobutylicum*. *Journal of Biomass and Bioenergy*. 10.1016.
- Qureshi, N. and Blaschek, H.P., (2001). ABE production from corn: a recent economic evaluation. *Journal of Industrial Microbiology and Biotechnology* 27 (5), 292–297.
- Qureshi N and Blaschek H.P.(2000). Economics of butanol fermentation using hyperbutanol producing *Clostridium beijerinckii* BA101. *Trans IChem E*. 78:139–44.
- Qureshi N, Maddox, I.S, and Fried, A. (1992). Application of continuous substrate feeding to the ABE fermentation: Relied of product inhibition, perstraction, stripping and pervaporation. *Biotechnology Progress* 8 : 382 – 390.
- Safety Assessment of n-Butyl Alcohol (2005). *Cosmetic Ingredient Review Expert Panel Meeting*, June 13-14,7-8
- Sanchez S, Lozano LJ, Godinez C, Juan D, Perez A, Hernandez F.J. (2010). Carbon as a feedstock for the production of bioethanol in Mediterranean areas. *Applield Energy*.87:3417–24.

- Sarin, D.M. Marchal, R. and Vandecasteele, J.P. (1990). Control of the selectivity of butyric acid fermentation and improvement of fermentation performance with *Clostridium tyrobutyricum* under phosphate limitation. *Journal of Applied Microbiology Biotechnology* 32: 387 – 392.
- Somrutai, G.L, Takagi, M. and Yoshida, T. (1996). Acetone-butanol fermentation by *Clostridium aurantibutyricum* ATCC 17777 from a model medium for palm oil mill effluent. *Journal of fermentation and Bioengineering* 81 (6) : 543 – 547.
- Stefanie, K., Shaheen R., Jones T.D. (2001). Emended descriptions of *Clostridium acetobutylicum* and *Clostridium beijerinckii*, and descriptions of *Clostridium saccharoper butylaceticum* sp. and *Clostridium saccharobutylicum* Sp. *International Journal System Evolution Microbiology*. 51:2095–103.
- Taherzadeh, M. J. (1999). Ethanol from lignocellulose: Physiological effects of inhibitors and fermentation strategies (PhD thesis). Chalmers University of Technology, Department of Chemical Reaction Engineering. Göteborg Sweden. 56pp.
- Thaddeus, E., Nasib, Q., and Hans, P. B. (2007). Butanol Production From Agricultural Residues: Impact of Degradation Products on *Clostridium beijerinckii* Growth and Butanol Fermentation. *Journal of Biotechnology and Bioengineering*. 9, 6.
- Thaddeus, E., Nasib, Q., and Hans, P. B. (2007). Bio production of Butanol from Biomass: from Genes to Bioreactors. *Current Opinion in Biotechnology*. 18, 220–227.
- Thang, V.H., Kanda, K., and Kobayashi, G. (2000). Production of acetone-butanol-ethanol (ABE) in direct fermentation of cassava by *Clostridium saccharoperbutylaceticum* N1-4. *Applied Biochemistry and Biotechnology* 161 (1-8), 157 – 170.

Technical Data Sheet (1998). BASF Corporation Chemicals Division 3000 Continental Drive – North Mount Olive, New Jersey 07828-1234 World Wide Web: <http://www.basf.com>

Tina L. E. and Hubert B. (2011). Metabolic engineering of *Clostridium acetobutylicum*: recent advances to improve butanol production. *Current Opinion in Biotechnology*. 22:634-647.

United Technology International. (2003). Anaerobic Digestion, UTI Web Design.

USDA (2009). National Nutrient Database for Standard Reference, Release 22

Verma, S. (2002). Anaerobic Digestion Of Biodegradable Organics In Municipal Solid Wastes. Department of Earth & Environmental Engineering (Henry Krumb School of Mines) Fu Foundation School of Engineering & Applied Science Columbia University.

Ward, E.M. , J.M. Fajen, A. M., Ruder, R. A., Rinsy, W. E, Halperin, C. A, and Fesslerflesch (1995). Mortality study of workers in 1, 3-butadiene production units identified from a chemical worker cohort. *Environmental Health Perspection* 103 (6): 598-603.

Wang, L. and Chen, H. Z. (2011). Increased fermentability of enzymatically hydrolyzed steam-exploded corn stover for butanol production by removal of fermentation inhibitors. *Process Biochemistry*. 46(2), 604 – 607.

Welsh, F.W. and Veliky, I.A. (1984). Nutritional requirements of *Clostridium acetobutylicum* ATCC 824. In *Energy from Biomass and Waste*. Klass D.L, Eliot H.H (ed). Institute of gas technology, Chicago: pp 164 – 167.

- Welsh, F.W, Williams, R.E, and Veliky, I.A (1987). Organic and inorganic nitrogen source effects on the metabolism of *Clostridium acetobutylicum*. Journal of Applied Microbiology Biotechnology 26 : 369 – 372.
- Winzer K., Lorenz K., Zickner B, Durre P. (2000). Differential regulation of two thiolase genes from *Clostridium acetobutylicum* DSM 792. Journal Molecular Microbiology and Biotechnology. 2(4):531–41.
- Xiulian Yin, Qinghong Y., Zhonghai J. (2011). Optimization of enzyme assisted extraction of polysaccharides from *Tricholoma matsutake* by response surface methodology. Journal of Applied Microbiology Biotechnology 30 : 569 – 572.
- Yan Q, Wang A, Yu W, and Wang L(2009). Development strategies of biofuel in China. In: International conference on energy and environment technology. IEEE computer society, 1:588–593.
- Yan, R.T., Zhu, C.X., Golemboski, C. and Chen, J.S. (1988). Expression of solvent forming enzymes and onset of solvent production in batch cultures of *Clostridium beijerinckii* (“*Clostridium butylicum*”). Journal of Applied Environmental Microbiology. 54 (3): 642 – 648.
- Yi W., and Blaschek, H P. (2011). Optimization of butanol production from tropical maize stalk juice by fermentation with *Clostridium beijerinckii* NCMB 8052. Bioresource Technology, 102: 9985-9990.
- Zhang Z, Lohr L, Escalante C, Wetzstein M (2010). Food versus fuel: what do prices tell us? Energy Policy 38:445–51.