

Supercontinuum generation from ultraviolet to mid-infrared

Møller, Uffe Visbech; Sørensen, Simon Toft; Petersen, Christian Rosenberg; Kubat, Irnis; Moselund, Peter M.; Bang, Ole

Published in:
15th Conference on Optical Fibers and Their Applications

Publication date:
2014

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Møller, U. V., Sørensen, S. T., Petersen, C. R., Kubat, I., Moselund, P. M., & Bang, O. (2014). Supercontinuum generation from ultraviolet to mid-infrared. In 15th Conference on Optical Fibers and Their Applications

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Supercontinuum generation from ultraviolet to mid-infrared

U. Møller¹, S.T. Sørensen², C.R. Pedersen¹, I. Kubat¹, P.M. Moselund², O. Bang^{1,2}

¹DTU Fotonik, Tech. Univ. of Denmark, Ørsteds Plads, 2800 Kgs. Lyngby, Denmark

²NKT Photonics A/S, Blokken 84, 3460 Birkerød, Denmark

Abstract. *The advent of photonic crystal fibers (PCFs) has paved the road for commercial high-power supercontinuum light sources. The air-hole structuring in the PCF manipulates the properties of light and gives a tremendous degree of design freedom, which has enabled pushing the properties of PCFs to limits that can never be achieved with standard step index fibers. For example, one can move the zero dispersion wavelength (ZDW) into the visible [1] and make them endlessly single moded [2]. For efficient supercontinuum generation it is of great importance that the pump wavelength is close to the ZDW. We demonstrate how the spectral blue-edge can be manipulated by careful fiber design and tapering of the PCF enabling supercontinuum generation spanning all the way from 380 nm to 2.4 μm [3]. We discuss the limiting factors of the supercontinuum bandwidth. Furthermore, we discuss how the fiber tapering influences the intensity noise of the supercontinuum source [4].*

Supercontinuum sources based on silica fibers are limited to the material loss edge at 2.4 μm. However, for wavelengths beyond 2.4 μm the attenuation of light in silica fibers is greatly increased making them useless for the mid-infrared region. Instead, other fiber materials such as fluoride-based glasses (ZBLAN) and chalcogenide glasses can be used for mid-infrared supercontinuum generation. We will show supercontinuum generation in ZBLAN fibers covering 1.5-4.5 μm [5] and supercontinuum generation in microstructured chalcogenide fibers out to 9 μm. We discuss the prospects for extending the supercontinuum generation beyond 10 μm and highlight useful applications such as cancer detection and food analysis.

[1] J.K. Ranka, R.S. Windeler, A.J. Stentz, *Opt. Lett.* **25**, 25 (2000).

[2] T.A. Birks, J.C. Knight, P.St.J. Russell, *Opt. Lett.* **22**, 961 (1997).

[3] U. Møller et al., *Opt. Fiber Technol.* **18**, 304 (2012).

[4] U. Møller et al., *Opt. Express* **20**, 2851 (2012).

[5] P.M. Moselund et al., *Proc. SPIE* **8381**, 83811A (2012).

Keywords: supercontinuum generation, photonic crystal fibers, soft glass fibers, noise properties

Corresponding author: Uffe Møller, DTU Fotonik, Technical University of Denmark, Ørsteds Plads, DK-2800 Kgs. Lyngby, Denmark. Email: ufmo@fotonik.dtu.dk