

International Multidisciplinary Scientific GeoConference Surveying Geology and Mining Ecology Management, SGEM 2017 vol.17 N14, pages 941-948

The influences of ultrasound waves on rheological and physico-chemical properties of extra heavy oil from “Ashalcha” field

Aliev F., Mukhamatdinov I., Kemalov A.
Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© SGEM 2017. All Rights Reserved. Extra-heavy oil is considered as one of alternative energy sources mainly because of reserve potentials, rich in organic compounds and rare transition metals like V and Ni. Extraction from this hydrocarbon resource has always been a challenge due to high oil viscosity and as a result low mobility within porous media. Conventionally the production from extra-heavy oil reservoirs is achieved by thermal methods such as SAGD, CSS, Insitu combustion, etc. However, these techniques do not consider the post productions' physical and chemical crude oil properties particularly its refinery values. Moreover, these methods are mainly restricted with onshore fields where there is enough working area exists. In addition, application of thermal methods are not reasonable for shallow and thin reservoirs primarily due to inoculation issues. This research study aims to introduce an alternative approach to thermal methods. In this approach, an ultrasound wave technology is used to enhance physico-chemical properties of extra-heavy oil. To examine the effectiveness of proposed technique a fluid sample from “Ashalcha” field is used. Initially, ultrasonic wave parameters like frequency, amplitude and wave generation time are optimized. The determined optimum wave parameters are then utilized to investigate the change in physico-chemical properties of fluid sample after ultrasound treatment. The results of study show that application of ultrasonic wave technology is able to reduce viscosity and improve the refinery values of extra-heavy oil from “Achalcha” field.

<http://dx.doi.org/10.5593/sgem2017/14/S06.087>

Keywords

Extra-heavy oil, Physico-chemical improvement, Ultrasound treatment, Viscosity reduction

References

- [1] International Energy Agency. “World Energy Outlook 2013 Factsheet”. How will global energy markets evolve to 2035, 1 (2013).
- [2] Sitnov S.A., Petrovnina M.S., Feoktistov D.A., Isakov D.R., Nourgaliev D.K., Amerkhanov M.I. Intensification of thermal steam methods of production of heavy oil using a catalyst based on cobalt// Neftyanoe Khozyaystvo - Oil Industry. - 2016. - №11. - P.106-108.
- [3] Vakhin A.V., Onishchenko Y.V., Chemodanov A.E., Sitdikova L.M., Nurgaliev D.K. Thermal transformation of bitumoid of domanik formations of Tatarstan// Neftyanoe Khozyaystvo - Oil Industry. - 2016. - V. 10. - P. 32-34.

- [4] Delong Xu, Jinjing D., Chao L., Lixin B., "The 21st International Congress on Sound and Vibration", Research On Viscosity Reduction of Oil in Water for Ultra Heavy Crude Oil by using of ultrasonic wave, 1-2 (2014).
- [5] Aliev F. A., Rahimov Kh., Amzayev B., Kemalov A. "International Journal of Applied Engineering Research", Comparison of Critical Rate Correlations, 10 (ISSN 1087-1090), pp. 44773-44779, (2015).
- [6] Meyer, R. F., and C. T. Steele. Future of heavy crude and tar sands. No. CONF- 790649-. McGraw-Hill, Inc., New York, NY, 1981.
- [7] Sitnov S.A., Feoktistov D.A., Kayukova G.P., Pronin N.V., Nosova F.F., Chemodanov A.E. Catalytic intensification of in-situ conversion of high-viscosity oil in thermal steam extraction methods// International Journal of Pharmacy and Technology. - 2016. - V. 8(3). - P.14884-14892.
- [8] Wu, Ta Yeong, et al. "Theory and fundamentals of ultrasound." Advances in Ultrasound Technology for Environmental Remediation. Springer Netherlands, pp. 5-12 (2013).
- [9] Hendee, William R., and E. Russell Ritenour. Medical imaging physics. John Wiley & Sons, pp. 304-307 (2003).
- [10] "Hielscher - Ultrasound Technology", 30 Jan. 2017, ww.hielscher.com/ultrasonichomogenizers-for-liquid-processing-3.htm
- [11] Stojanovic, Jelena, and Juan L. Silva. "Influence of osmotic concentration, continuous high frequency ultrasound and dehydration on antioxidants, colour and chemical properties of rabbiteye blueberries." Food chemistry 101.3 (2007): 898-906.
- [12] Al-Roomi, Yousef, et al. "Use of a novel surfactant for improving the transportability/transportation of heavy/viscous crude oils." Journal of Petroleum Science and Engineering 42.2 (2004): 235-243.
- [13] Berne, Bruce J., and Robert Pecora. Dynamic light scattering: with applications to chemistry, biology, and physics. Courier Corporation, pp. 2-10 (2000).
- [14] Mukhamatdinov I.I., Kemalov, A.F., Fakhretdinov, P.S., Bogdanova S.A. Estimation of bitumen adhesion to the mineral material on the basis of its wetting properties// International Journal of Applied Engineering Research - 2015. - 10(24). - P. 45075-45081.
- [15] Sitnov, S.A., Feoktistov, D.A., Petrovnina, M.S., Isakov, D.R., Darishchev, V.I., Akhmadeishin, I.A. Structural changes of heavy oil in the composition of the sandstone in a catalytic and non-catalytic aquathermolysis// International Journal of Pharmacy and Technology. - 2016. - 8(3). - P. 15074-15080