

International Multidisciplinary Scientific GeoConference Surveying Geology and Mining Ecology Management, SGEM 2017 vol.17 N14, pages 851-858

Rheology and wettability control of polymer solutions based on polyacrylamide in enhanced oil recovery

Mukhamatdinov I., Aliev F., Garifullina E., Vakhin A.
Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© SGEM 2017. All Rights Reserved. The current hard-to-recover oil reserves in Russia stand for more than 60% of total recoverable oil resources. These kind of reservoirs with acceptable technical and economic indicators are extracted only by applying physicochemical recovery techniques. Thus, an important relevance is given to selection of most effective EOR technology, which is directed to decrease the residual oil saturation in rock formations. Various chemical reagents including composites based on water-soluble polymers are injected both in Russia and worldwide in order to maintain reservoir pressure and to increase the oil recovery factor. The water-soluble polymers decrease the mobility difference between displacing and displaced fluids, reducing fingering effects. At the result of late water breakthrough oil recovery increases. It is highly important to introduce the model of rock matrices in order to combine the known phenomenon of natural chromatographic separation in reservoir rocks, which is characterized by heterogeneity of permeable rocks. Accordingly, heavy crude oil are located in large pores, as well as in small pores concentrated hydrocarbons. Therefore, the amount of hydrocarbon content describes the hydrophobic parameters. In this study, we combined the composite polymers with polydisperse rocks like calcite and dolomite. The different experimental results gained from using various types of rock, which is due to pore morphology and molecular interactions of polymers with rock surfaces. New laboratory results of processes, which are carried on interphase of a system: fluid reservoir - mineral matrix, are discussed..

<http://dx.doi.org/10.5593/sgem2017/14/S06.106>

Keywords

Contact angle, Heavy crude oil, Polymer flooding, Rheology, Wettability

References

- [1] Idahosa P.E.G., Oluyemi G.F., Oyenyin M.B., Prabhu R., Rate-dependent polymer adsorption in porous media, *Journal of Petroleum Science and Engineering*, United Kingdom, vol. 143, pp. 65-71, 2016.
- [2] Demikhova I.I., Likhanova N.V., Hernandez Perez J.R., D.A.L. Falcon, O. Olivares-Xometl, A.E. Moctezuma Berthier, I.V. Lijanova, Emulsion flooding for enhanced oil recovery: Filtration model and numerical simulation, *Journal of Petroleum Science and Engineering*, Mexico, vol. 143, pp. 235-244, 2016.
- [3] Al-Hashmi A.R., Luckham P.F., Grattoni C.A., Flow-induced-microgel adsorption of high-molecular weight polyacrylamides, *Journal of Petroleum Science and Engineering*, United Kingdom, vol. 112, pp. 1-6, 2013.
- [4] Lake, Larry W., et al. *Fundamentals of enhanced oil recovery*. Society of Petroleum Engineers, 1986.

- [5] Mahmoud A. Mohsin, Nuha F. Attia, Inverse emulsion polymerization for the synthesis of high molecular weight polyacrylamide and its application as sand stabilizer, International Journal of Polymer Science, United Arab Emirates, vol. 2015, Article ID 436583, 2015.
- [6] Baibekova L.R., Petrov S.M., Mukhamatdinov I.I., Burnina M.A. Polymer Additive Influence on Composition and Properties of Bitumen Polymer Compound//International Journal of Applied Chemistry. 2015. – 11(5). P. 593-599.
- [7] Mukhamatdinov I.I., Aliev F.A., Sitnov S.A., Vahin A.V., Solodov V.A., Study of rheological behavior of systems 'polymer solution - Rocks', Neftyanoe Khozyaystvo - Oil Industry, Russian Federation, vol. 2016/issue 11, pp. 121-123, 2016.
- [8] Korotkina O. Z., Polyacrylamide property investigation by light scattering methods//JPH - 1965. -№38., pp. 25-33.
- [9] Baydurdov T. A., Stupenkova L. L., Investigation of the process of obtaining spatially cross-linked copolymers of acrylamide in the presence of formaldehyde in concentrated aqueous solutions//Oil and Gas: novation. – 2015. - №6. – pp. 56-63
- [10] Surguchev M. L., Secondary and Tertiary Oil Production, Nedra, Moscow, 1985, p. 308.
- [11] Rao D.N: Wettability Effects in Thermal Recovery Operations, SPE Reservoir Evaluation and Engineering, United States, vol. 2/issue 5, pp. 420-430, 1999.
- [12] Abdallah W., Buckley J. S., Carnegie A., Edwards J., Herold B., Fordham E., Grau A., and etc: Fundamentals of wettability, Schlumberger Oilfield Review, Summer 2007, pp. 44-61, 2007