

2017 International Conference on Mechanical, System and Control Engineering, ICMSC 2017, 2017, pages 184-189

Humanoid robot kinematic calibration using industrial manipulator

Khusainov R., Klimchik A., Magid E.

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© 2017 IEEE. Kinematic calibration is a crucial task for humanoid robot locomotion. The paper proposes a novel technique for joint offset calibration using industrial manipulator. Corresponding procedure uses position and orientation data from the manipulator and requires fixing of robots bases and end-effectors with respect to each other. The full pose information is obtaining as the humanoid limbs are moved through predefined configurations. To find joint offsets the least-squares optimization problem is solved. The proposed method is accurate since the industrial manipulator provides high precision. The proposed approach was validated on the calibration of AR601M humanoid robot using Kuka iiwa 14 industrial manipulator.

<http://dx.doi.org/10.1109/ICMSC.2017.7959468>

Keywords

AR601M, calibration, humanoid, industrial manipulator, KUKA iiwa

References

- [1] F. Asano, H. Asoh, S. Kajita, "Online detection of calibration errors in humanoid robots", Signal and Information Processing Association Annual Summit and Conference (APSIPA), 2014 Asia-Pacific, 2014, pp. 1-6.
- [2] A. Roncone, M. Hoffmann, U. Pattacini, G. Metta, "Automatic kinematic chain calibration using artificial skin: Self-touch in the iCub humanoid robot, " 2014 IEEE International Conference on Robotics and Automation (ICRA), 2014, pp. 2305-2312.
- [3] N. Guedelha, N. Kuppaswamy, S. Traversaro, F. Nori, "Selfcalibration of joint offsets for humanoid robots using accelerometer measurements, " 2016 IEEE-RAS 16th International Conference on Humanoid Robots (Humanoids), 2016, pp. 1233-1238.
- [4] O. Birbach, B. Bäuml, U. Frese, "Automatic and self-contained calibration of a multi-sensorial humanoid's upper body, " 2012 IEEE International Conference on Robotics and Automation, 2012, pp. 3103-3108.
- [5] D. Maier, S. Wrobel, M. Bennewitz, "Whole-body self-calibration via graph-optimization and automatic configuration selection, " 2015 IEEE International Conference on Robotics and Automation (ICRA), 2015, pp. 5662-5668.
- [6] J.-H. Kim, J.-Y. Kim, J.-H. Oh, "Adjustment of Home Posture of Biped Humanoid Robot Using Sensory Feedback Control, Journal of Intelligent and Robotic Systems, 51 (2008) 421-438.
- [7] T. Asfour, K. Welke, P. Azad, A. Ude, R. Dillmann, "The karlsruhe humanoid head, " Humanoid Robots, 2008. Humanoids 2008. 8th IEEE-RAS International Conference on, IEEE, 2008, pp. 447-453.
- [8] K. Yamane, "Practical kinematic and dynamic calibration methods for force-controlled humanoid robots, " 2011 11th IEEE-RAS International Conference on Humanoid Robots, 2011, pp. 269-275.
- [9] G. Du, P. Zhang, D. Li, "Online robot calibration based on hybrid sensors using Kalman Filters, " Robotics and Computer-Integrated Manufacturing, 31 (2015) 91-100.

- [10] A. Klimchik, Y. Wu, S. Caro, B. Furet, A. Pashkevich, "Geometric and elastostatic calibration of robotic manipulator using partial pose measurements, " *Advanced Robotics*, 28 (2014) 1419-1429.
- [11] B. W. Mooring, Z. S. Roth, M. R. Driels, "Fundamentals of manipulator calibration, " Wiley New York, 1991.
- [12] A. Nubiola, I. A. Bonev, "Absolute calibration of an ABB IRB 1600 robot using a laser tracker, " *Robotics and Computer-Integrated Manufacturing*, 29 (2013) 236-245.
- [13] J. Santolaria, J.-J. Aguilar, J.-A. Yagüe, J. Pastor, "Kinematic parameter estimation technique for calibration and repeatability improvement of articulated arm coordinate measuring machines, " *Precision Engineering*, 32 (2008) 251-268.
- [14] N. Maru, H. Kase, S. Yamada, A. Nishikawa, F. Miyazaki, "Manipulator control by using servoing with the stereo vision, " *Intelligent Robots and Systems' 93, IROS'93. Proceedings of the 1993 IEEE/RSJ International Conference on, IEEE, 1993*, pp. 1866-1870.
- [15] R. Khusainov, I. Shimchik, I. Afanasyev, E. Magid, "Toward a human-like locomotion: Modelling dynamically stable locomotion of an anthropomorphic robot in simulink environment, " *Informatics in Control, Automation and Robotics (ICINCO)*, 2015 12th International Conference on, 2015, pp. 141-148.
- [16] J.-H. Borm, C.-H. Meng, "Determination of optimal measurement configurations for robot calibration based on observability measure, " *The International Journal of Robotics Research*, 10 (1991) 51-63.