

Society of Petroleum Engineers - SPE Russian Petroleum Technology Conference 2017, 2017

Interpretation of indicator studies of multistage fracturing

Mazo A., Sattarov R., Khamidullin M., Potashev K., Trifonov T.
Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

Copyright 2017, Society of Petroleum Engineers. The paper presents a technique for interpreting indicator studies of multi-stage hydraulic fracturing (MSHF) on horizontal wells (HW), based on numerical modeling of indicator transfer in the near-well zone. Two problems are distinguished in the simulation: the direct problem of calculating the pressure, water saturation, and concentration of the indicator at the given parameters of the well during the injection of the indicator and the further operation of the well; the inverse problem of selecting the parameters of the hydraulic fractures (geometry and permeability) from the measured curves of the indicator removal after the transfer of the well to the withdrawal. In the course of solving the inverse problem, the separation of the total water and oil rates along the fracturing intervals is determined. The direct problem is based on the mathematical model of a three-dimensional two-phase multicomponent filtration taking into account diffusion and sorption in the region of drainage of HW with MSHF. The case of water-soluble indicators is considered in the model. In the numerical implementation of this model, we use structured finite-volume grids with significant condensation near the fractures and wells, as well as fast-acting algorithms for the end-to-end solution of the problem for pressure in the reservoir and fractures and an explicit-implicit scheme for solving the tracer transfer problem. The solution of the inverse problem minimizes the deviation of the calculated tracer output curves, total production rate and water cut from the corresponding observation data. The minimization is performed iteratively (by modifying the Broyden-Fletcher-Goldfarb-Shanno method with the limitation of the memory used). The direct problem is solved at each iteration. In this case, a simplified model is used that takes into account the rectilinear-parallel structure of the filtration flow in the penetration region of the tracer, which makes it possible to expand the three-dimensional problem into a series of one-dimensional ones and substantially accelerate the calculation. The proposed algorithm for the interpretation of indicator studies is demonstrated by the example of processing real data obtained during the 4-interval transverse MSHF on a HW of a productive reservoir represented by the interlacing of sandy-siltstone rocks with dense interlayers of clays belonging to the terrigenous deposits of the Achimov strata of Western Siberia. The length of the horizontal section of the wellbore was 820 m. The water-soluble indicators DCT-WS-01, DCT-WS-03, DCT-WS-04, and DCT-WS-07 were used as tracers. The main hydraulic fracturing was preceded by mini-fracturing. The fractures contained 80 tons of ceramic proppant for the first three stages and 60 tons for the fourth stage. The average half-length of the hydraulic fractures was 100 m, height - 50 m, and thickness - 4 mm.

References

- [1] Appleyard, J., Cheshire, I., and Pollard, R. 1981. Special techniques for fully implicit simulators. Proceedings of the European Symposium on Enhanced Oil Recovery. Harwell: Atomic Energy Research Establishment, Computer Science and Systems Division: 395-408.
- [2] Asadi, M., Woodroof, R.A., and Dumas Jr, J.D. 2008. Post-frac analysis based on flowback results using chemical frac-tracers. SPE Paper 76677 presented at the International Petroleum Technology Conference Kuala Lumpur; Malaysia; 3-5 December.
- [3] Aziz, K., Settari, A. 1979. Petroleum reservoirs simulation. Appl. Sci. Publ., London.
- [4] Barenblatt, G.I., Entov, V.M., Ryzhik, V.M. 1990. Theory of Fluid Flow Through Natural Rocks. Kluwer Academic Publishers, London.
- [5] Bazan, L.W., Lattibeaudiere, M.G., and Palish, T.T. 1990. Hydraulic fracture design and well production results in the eagle ford shale: One operator's perspective. SPE paper 92530 presented at the SPE Americas Unconventional Resources Conference, Pittsburgh, PA; United States; 5-7 June.
- [6] Bouras, O., Bollinger, J.-C., Baudu, M., and Khalaf, H. 2007. Adsorption of diuron and its degradation products from aqueous solution by surfactant-modified pillared clays. Appl. Clay Science 37: 240-250.
- [7] Cheng, Y. 2009. Boundary element analysis of the stress distribution around multiple fractures: Implications for the spacing of perforation clusters of hydraulically fractured horizontal wells. SPE Paper 80654 presented at the 281SPE Eastern Regional Meeting 2009: Limitless Potential / Formidable Challenges; Charleston, W.V.; United States; 23-25 September.
- [8] Cipolla, C.L., Warpinski, N.R., Mayerhofer, M.J., Lolon, E.P., and Vincent, M.C. 2008. The relationship between fracture complexity, reservoir properties, and fracture treatment design. SPE Paper presented at the SPE Annual Technical Conference and Exhibition; Denver, C.O.; United States; 21-24 September.
- [9] Coats, K.H. 1982. Reservoir simulation. Petroleum Engineering Handbook, Texas.
- [10] Conlin, J.M., Hale, J.L., and Sabathier, J.C. 1990. Multiple-Fracture Horizontal Wells: Performance and Numerical Simulation. SPE 20960.
- [11] Dang, A. 2016. Post-treatment horizontal hydraulic fracture modeling with integrated chemical tracer analysis, a case study. SPE Paper 124062 presented at the SPE Annual Technical Conference and Exhibition, Dubai; United Arab Emirates; 26-28 September.
- [12] Eymard, R., Gallouet, T., and Herbin, R. 2000. Finite Volume Methods. Handbook of Numerical Analysis. Ph. Ciarlet, J.L. Lions eds, North Holland: 713-1020.
- [13] Economides, M.J., Deimbacher, F.X., Brand, C.W., and Heinemann, Z.E. 1991. Comprehensive simulation of horizontalwell performance. SPE Formation Evaluation 6 (4): 418-426.
- [14] Fletcher, R. 1987. Practical methods of optimization (2nd ed.). 436. New York: John Wiley & Sons
- [15] Fung, L., Collins, D.A, Nghiem, L.X, et al 1998. An adaptive implicit switching criterion based on numerical stability analysis. SPE Reservoir Engineering 4 (1): 45-52.
- [16] Gardien, C.J., Pope, G.A., and Hill, A.D. 1996. Hydraulic fracture diagnosis using chemical tracers. Proceedings-SPE Annual Technical Conference and Exhibition: 925-932.
- [17] Gidley, J.L., Holditch, S.A., Nierode, D.E., and Veatch, R.W. 1989. Recent Advances in Hydraulic Fracturing. 318. Monograph, SPE.
- [18] Goswick, R.A., and Larue, J.L. 2014. Utilizing oil soluble tracers to understand stimulation efficiency along the lateral. Proceedings-SPE Annual Technical Conference and Exhibition 6: 4608-4617.
- [19] Hackbusch, W. 1985. Multi-Grid Methods and Applications. 377. Springer, Berlin.
- [20] Henk, A. 2003. Iterative Krylov Methods for Large Linear System. 211. Cambridge University Press, Cambridge.
- [21] King, G.E., and Leonard, D. 2011. Utilizing fluid and proppant tracer results to analyze multi-fractured well flow back in shales: A framework for optimizing fracture design and application. SPE Hydraulic Fracturing Technology Conference: 146-164.
- [22] Langmuir, I. 1918. The adsorption of gases on plane surfaces of glass, mica and platinum. J. Am. Chem. Soc. 40: 1361-1403.
- [23] Levenberg, K. 1944. A Method for the Solution of Certain Non-Linear Problems in Least Squares. Quarterly of Applied Mathematics 2: 164-168.
- [24] Marquardt, D. 1963. An Algorithm for Least-Squares Estimation of Nonlinear Parameters. SIAM Journal on Applied Mathematics 11 (2): 431-441.
- [25] Mazo, AB, Khamidullin, M.R. 2017 (a). Explicitly-implicit algorithms for accelerating the calculation of a two-phase inflow to a horizontal well with multi-stage fracturing of a formation. Computational methods and programming 18: 204-213.
- [26] Mazo, A., Khamidullin, M., and Potashev, K. 2017 (b). Numerical simulation of a one-phase steady flow towards a multistage fractured horizontal well. Lobachevskii journal of mathematics 38 (in print).

- [27] Mazo, AB, Potashev, KA, Khamidullin, M.R. 2015. Filtration model of fluid flow to a horizontal well with multi-stage hydraulic fracturing of the formation. *Scientific notes of Kazan University. Series Physics and mathematics* 157 (4): 133-148.
- [28] Meyer, B.R., Bazan, L.W., Jacot, R.H., and Lattibeaudiere, M.G. 2010. Optimization of multiple transverse hydraulic fractures in horizontal wellbores. SPE Paper presented at the SPE Unconventional Gas Conference, Pittsburgh, PA; United States; 23-25 February.
- [29] Mironenko, V.A. 2001. *Dynamics of groundwater*. 519. Moscow: Izd-vo MGGU.
- [30] Fletcher, K. 1991. *Computational methods in the dynamics of liquids*. 552. Moscow: The World.
- [31] Ozkan, E., Brown, M., Raghavan, R., and Kazemi, H. 2009. Comparison of fractured horizontal-well performance in conventional and unconventional reservoirs. *SPE Western Regional Meeting 2009-Proceedings*, pp. 345-360.
- [32] Rickman, R., Mullen, M., Petre, E., Grieser, B., and Kundert, D. 2008. A practical use of shale petrophysics for stimulation design optimization: All shale plays are not clones of the Barnett Shale. Paper SPE 75281 presented at the SPE Annual Technical Conference and Exhibition, Denver, CO; United States; 21-24 September.
- [33] Shen, R., and Gao, S. 2012. Numerical simulation of production performance of fractured horizontal wells considered conductivity variation. in *Proc. 3rd Int. Conf. on Computer and Electrical Engineering (IACSIT Press, Singapore)*, 53 (2.36).
- [34] Spencer, J., Bucior, D., Catlett, R., and Lolon, E. 2013. Evaluation of horizontal wells in the Eagle Ford using oil-based chemical tracer technology to optimize stimulation design. Paper SPE 97882 presented at the SPE Hydraulic Fracturing Technology Conference, The Woodlands, TX, United States, 4-6 February.
- [35] Thomas, G.W., and Thurnau, D.H. 1983. Reservoir simulation using an Adaptive Implicit Method. *SPE Journal* 23: 759-768.
- [36] Tian, W., Wu, X., Shen, T., and Kalra, S. 2016. Estimation of hydraulic fracture volume utilizing partitioning chemical tracer in shale gas formation. *Journal of Natural Gas Science and Engineering* 33: 1069-1077.
- [37] Watts, J.W., and Shaw, J.S. 2005. A new method for solving the implicit reservoir simulation matrix equation. Paper SPE 93068 presented at the SPE Reservoir Simulation Symposium, The Woodlands, USA, January 31-February 2.
- [38] Wei, Y., and Economides, M.J. 2005. Transverse hydraulic fractures from a horizontal well. *Proceedings-SPE Annual Technical Conference and Exhibition*: 25-36.
- [39] Williams, R.L., and McCarthy, J.T. 1987. Using multiple radioactive tracers to optimize stimulation designs. Paper SPE 16383 presented at the SPE California Regional Meeting, Ventura, California 8-10 April.
- [40] Zhang, W., Ding, Y., Boyd, S.A., Teppen, B.J., and Li, H. 2010. Sorption and desorption of carbamazepine from water by smectite clays. *Chemosphere* 81: 954-960.
- [41] Zhuchkov, AN, Berlyand, AS, Alikhanyan, AS, Pleskaya, NA 2011. Study of the sorption properties of the new natural enterosorbent klimont. *Chemical and Pharmaceutical Journal* 45 (2): 49-52.