



ELSEVIER

Available online at www.sciencedirect.com

SCIENCE @ DIRECT®

Microelectronic Engineering 69 (2003) 330–335

MICROELECTRONIC
ENGINEERINGwww.elsevier.com/locate/mee

Ion synthesis and FMR studies of iron and cobalt nanoparticles in polyimides

B.Z. Rameev^{a,b}, F. Yıldız^a, B. Aktaş^a, C. Okay^c, R.I. Khaibullin^{a,b}, E.P. Zheglov^b,
J.C. Pivin^d, L.R. Tagirov^{a,b,e,*}

^a*Gebze Institute of Technology, 41400 Gebze-Kocaeli, Turkey*

^b*Kazan Physical-Technical Institute, Sibirsky Trakt 10/7, 420029 Kazan, Russia*

^c*Marmara University, 81040 Göztepe-Istanbul, Turkey*

^d*CSNSM, Batiment 108, IN2P3-CNRS, 91405 Orsay Campus, France*

^e*Kazan State University, Kremlevskaya str. 18, 420008 Kazan, Russia*

Abstract

Polyimide foils were implanted with 40 keV Fe⁺ and Co⁺ to doses of 0.25–1.5×10¹⁷ ions/cm². Electron microscopy studies showed the formation of iron and cobalt nanoparticles in the implanted polymer layer with a thickness of about 70 nm. The size and shape of the ion-synthesized metal nanoparticles depend on the implantation parameters and subsequent thermal annealing. A ferromagnetic resonance (FMR) response was found in the iron-implanted samples as well as in the annealed cobalt and iron samples. The effective magnetization values of the metal/polymer composite layers were extracted from the FMR spectra and plotted as a function of implantation dose. The magnetic properties of the iron and cobalt nanoparticles in polyimide are compared and discussed.

© 2003 Elsevier B.V. All rights reserved.

Keywords: Ion implantation; Magnetic nanoparticles; Granular magnetic films; Ferromagnetic resonance

PACS: 75.50.Tt; 75.70.-i; 76.30.Fc; 76.50.+g

1. Introduction

The synthesis and characterization of nanosize magnetic particles are the subject of intense scientific research. This activity is inspired by the crossover phenomena related to quantum-size effects as well as the important applications of nanostructured magnetic materials in magnetic recording and informa-

tion storage, magneto-sensor electronics, magnetic resonance imaging enhancement, ferrofluids, magnetic refrigeration, colour imaging, medical diagnostics, etc. [1].

Nanocrystalline cobalt and iron particles are among the most promising candidates for high-density recording media [2] and magnetic sensors based on the giant tunnel-type magnetoresistance effect [3]. Dielectric matrices are usually used as the host for the nanocrystalline particles, to stabilize the metal granules against oxidization and prevent coalescence. Among the different techniques, ion implantation is a very attractive and prospective preparation method because of its peculiar advantages, such as easy

*Corresponding author. Kazan State University, Kremlevskaya str. 18, 420008 Kazan, Russia. Tel./fax: +7-8432-381-573.

E-mail address: lenar.tagirov@ksu.ru (L.R. Tagirov).