Proceedings of SPIE - The International Society for Optical Engineering 2006 vol.6264

## On computational power of classical and quantum Branching programs

Ablayev F.

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

## Abstract

We present a classical stochastic simulation technique of quantum Branching programs. This technique allows to prove the following relations among complexity classes:  $PrQP-BP \subseteq PP-BP$  and  $BQP-BP \subseteq PP-BP$ . Here BPP-BP and PP-BP stands for the classes of functions computable with bounded error and unbounded error respectively by stochastic branching program of polynomial size. BQP-BP and PrQP-BP stands the classes of functions computable with bounded error and unbounded error respectively by quantum branching program of polynomial size. Second. We present two different types. of complexity lower bounds for quantum nonuniform automata (OBDDs). We call them "metric" and "entropic" lower bounds in according to proof technique used. We present explicit Boolean functions that show that these lower bounds are tight enough. We show that when considering "almost all Boolean functions" on n variables our entropic lower bounds gives exponential ( $2c(\delta)(n-logn)$ ) lower bound for the width of quantum OBDDs depending on the error  $\delta$  allowed.

http://dx.doi.org/10.1117/12.683111

## **Keywords**

Branching programs, Computational complexity, OBDD, Quantum computations