



ELSEVIER

Available online at www.sciencedirect.com

International Journal of Pressure Vessels and Piping 84 (2007) 582–587

INTERNATIONAL JOURNAL OF
Pressure Vessels
and Pipingwww.elsevier.com/locate/ijpvp

Reconstruction of the velocities and pressures for a viscous fluid in a hollow cylinder

E.A. Shirokova*

Department of Mechanics and Mathematics, Kazan State University, Kazan 420008, Russia

Received 16 November 2006; received in revised form 26 February 2007; accepted 27 February 2007

Abstract

We find the continuous velocities and pressures at all points of an incompressible viscous fluid flowing in a hollow cylinder from the given velocities at the points of some closed curves on the inner sides of the cylinder and the given pressures at two points on the inner sides of the cylinder. This solution can be named the interpolation solution. The solution is reduced to a succession of plane boundary problems for the elliptic differential equations. The method of solution is programmable and applicable for problems of piping, for example, for modelling a blood flow in a vessel with a fibrin on its inner surface. This method is illustrated by application to flow in a hollow circular cylinder with a rotation on the central level.

The interpolation solution is the basis for the method of restoration of continuous velocities and pressures in the flow of an incompressible viscous fluid from the given velocities at a finite number of points on the inner surface of the cylinder and given pressures at two points on the same surface.

© 2007 Elsevier Ltd. All rights reserved.

Keywords: Stokes equations; Velocity; Pressure; Analytic functions; Polynomials; Boundary conditions

1. Introduction

We examine slow stable flow at low Reynolds number for an incompressible viscous fluid in a hollow cylinder with some interference on the inner sides of the cylinder which influence the velocities. An example of such a flow is blood flow in a vessel with a fibrin on the inner surface. Given the velocities at the points of $n + 1$ closed curves on the inner side of the cylinder and the pressures at two points on the inner sides of the cylinder, it should be possible to find the velocities and pressures at any point inside the cylinder.

In the paper we obtain the differentiable solution of the problem. We interpolate the velocities and pressures at the points of the inner surface of the cylinder and find the velocities and pressures at the points of the flow.

In Section 2, the coordinates of the desired vector of velocity and the pressure are supposed to be polynomials with respect to the coordinate \tilde{z} when the generatrix of the

cylinder is parallel to the axis $O\tilde{Z}$. So the coefficients of the polynomials are the solutions of differential equations. These coefficients are found in Section 3 successively step by step beginning with the coefficients with the highest numbers. The following Section 4 contains the solution for the case when the velocities are given at three levels on the inner side of the circular cylinder with inner radius 1 and the axis of symmetry $O\tilde{Z}$. Section 5 reduces reconstruction of velocities and pressures for a viscous fluid from velocities given at a finite number of points on the inner surface to the method described in the previous sections.

This method is the analogue of the method, presented in [1,2], where the boundary value problems of the theory of elasticity have been solved.

2. Formulation of the problem and analysis

Let Ω be the inner surface of a hollow cylinder in the XYZ space with the generatrix parallel to the axis $O\tilde{Z}$. The intersection of Ω with the plane XOY is the closed curve C which is the boundary of the finite domain D . Consider

*Tel.: +7 843 2385953; fax: +7 843 2387418.

E-mail address: Elena.Shirokova@ksu.ru.