

ANZIAM Journal 2012 vol.53 N4, pages 308-320

Topology of steady heat conduction in a solid slab subject to a nonuniform boundary condition: The Carslaw-Jaeger solutionâ revisited

Kasimova R., Obnosov Y.

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

Temperature distributions recorded by thermocouples in a solid body (slab) subject to surface heating are used in a mathematical model of two-dimensional heat conduction. The corresponding Dirichlet problem for a holomorphic function (complex potential), involving temperature and a heat stream function, is solved in a strip. The Zhukovskii function is reconstructed through singular integrals, involving an auxiliary complex variable. The complex potential is mapped onto an auxiliary half-plane. The flow net (orthogonal isotherms and heat lines) of heat conduction is compared with the known Carslaw-Jaeger solution and shows a puzzling topology of three regimes of energy fluxes for temperature boundary conditions common in passive thermal insulation. The simplest regime is realized if cooling of a shaded zone is mild and heat flows in a slightly distorted resistor model flow tube. The second regime emerges when cooling is stronger and two disconnected separatrices demarcate the back-flow of heat from a relatively hot segment of the slab surface to the atmosphere through relatively cold parts of this surface. The third topological regime is characterized by a single separatrix with a critical point inside the slab, where the thermal gradient is nil. In this regime the back-suction of heat into the atmosphere is most intensive. The closed-form solutions obtained can be used in assessment of efficiency of thermal protection of buildings. © 2012 Australian Mathematical Society.

<http://dx.doi.org/10.1017/S1446181112000260>

Keywords

complex potential, conformal mappings, heat lines, isotherms, Laplace's equation, two-dimensional heat conduction