

High Frequency High Power Full Bridge Converter for Plasma Torches

Hakki A., Sadikov K., Kashapov N.

Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© Published under licence by IOP Publishing Ltd. This paper presents a full bridge converter with a high speed rectifier and filter for plasma torches. Full bridge circuit with high frequency pulse width modulation control is used and high frequency transformer to insulate is adopted. For Argon (Ar) gas Plasma Torches, and by increasing the pulse width the average power consumption has modified from 1KW to 5.6KW (positive load). For Nitrogen (N₂) gas Plasma Torches, and by increasing the pulse width the average power consumption has reduced from 7.7KW down to 3KW (negative load). For the Plasma Torches load the frequency of converter was steady at 50KHz.

<http://dx.doi.org/10.1088/1742-6596/789/1/012021>

Keywords

Filters, Full Bridge Converters, Mosfet, Plasma Torches, Power Pulse

References

- [1] Schonknecht A. and De Doncker R. 2003 Novel Topology for Parallel Connection of Soft-Switching High-Power High-Frequency Inverters IEEE Transactions on Industry Applications 39 550-555
- [2] Aggeler D., Biela J. and Kolar J. W. 2008 A compact, high voltage 25 kW, 50 kHz DC-DC converter based on sic jfets Twenty-Third Annual IEEE Applied Power Electronics Conference and Exposition APEC 2008 801-807
- [3] Alberto Guerra K. A. and Fimiani S. 2000 Ultra-fast recovery diodes meet todays requirements for high frequency operation and power ratings in smps applications International Rectifier, Tech. Rep.
- [4] R. Severns (2005). Design of Snubbers for Power Circuits. Available from: <http://www.cde.com/tech/design.pdf> - ref-separator -
- [5] Wang F., Kuthi A. and Gundersen M. A. 2005 Compact high repetition rate pseudo spark pulse generator 33 1177-1181
- [6] Magnetic Core. Wikipedia, Available from: <http://en.wikipedia.org/wiki/Magnetic-core> 2010
- [7] Design of Planar Power Transformers. Ferroxcube, Available from: <http://www.ferroxcube.com/appl/info/plandesi.pdf> - ref-separator -
- [8] Venkatachalam K., Sullivan C. R., Abdallah T. and Tacca H. 2002 Accurate prediction of ferrite core loss ith nonsinusoidal waveforms using only steinmetz parameters IEEE Workshop on Computers in Power Electronics 36-41
- [9] GavriloVA V A, Fazlyyyakhmatov M G and Kashapov N F 2013 J. Phys.: Conf. Ser. 479 012010
- [10] Fayrushin I, Kashapov N and Dautov I 2014 J. Phys.: Conf. Ser. 567 012009
- [11] Kashapov L N, Kashapov N F and Kashapov R N 2013 J. Phys.: Conf. Ser. 479 012011
- [12] Kashapov L N, Kashapov N F and Kashapov R N 2014 J. Phys.: Conf. Ser. 567 012025
- [13] Zaripov R G, Kashapov N F, Tkachenko L A and Shaydullin L R 2016 J. Phys.: Conf. Ser. 669 012053

- [14] Denisov D G, Kashapov N F and Kashapov R N 2015 IOP Conference Series: Materials Science and Engineering 86 012005
- [15] Saifutdinov A I, Fairushin I I and Kashapov N F 2016 JETP Lett. 104 180-185
- [16] Sadikov K, Fayrushin I, Shamsutdinov A and Kashapov N 2016 J. Phys.: Conf. Ser. 669 012048