International Multidisciplinary Scientific GeoConference Surveying Geology and Mining Ecology Management, SGEM 2018 vol.18 N6.1, pages 417-423

Properties of anti-corrosive ferrite pigment synthesized with the use of production waste

Stepin S., Garifullina E., Katnov V., Usmanov I., Tolstosheyeva S. Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

© 2018, International Multidisciplinary Scientific Geoconference. All rights reserved. Pigments of the inhibitory type are the active principle of most primers used to protect metals from corrosion. Developers of anticorrosive paint and varnish materials seek to replace chromiumcontaining pigments, which widely used until recently due to their toxicity, with more environmentally appropriate choices. These include ferrite pigments. It is known, that the most spread method for the synthesis of ferrites, which are complex oxides or salts of ferrous acid, is the joint calcination of iron oxides with oxides having basic properties. The aim of this work is an expansion of the raw material base to produce ferritic pigments by using as one of the initial components an aspiration dust (content of iron oxide exceeds 70 %) formed as a waste in steelcasting plants. Crushed brucite (natural magnesium oxide) was used as the second component. After their thorough mixing, the resulting mixture was calcined at the reaction temperature: MgO + Fe2O3 \rightarrow MgFe2O4 (1) 6MgO + 4Fe3O4 + O2 \rightarrow 6MgFe2O4 (2) with obtaining of magnesium ferrite. The course of the reaction was controlled by thermogravimetry and differential thermal analysis. Ferritic-magnetite structure formation was recorded by X-ray diffraction analysis. The variation of the synthesis's temperature-time conditions made it possible to find the optimal parameters for obtaining ferrite. The synthesized ferrite was ground on a planetary mill. The studying of the painting and technical properties of the grinding product showed that it can be used as a pigment in the production of paints and varnishes. The results of electrochemical studies of steel in contact with the aqueous extract of ferritic pigment containing 3% of sodium chloride led to the conclusion of the high ability of the resulting product to inhibit the corrosion processes.

http://dx.doi.org/10.5593/sgem2018/6.1/S24.056

Keywords

Coatings, Corrosion, Corrosion prevention, Ferrite, Paint, Pigments, Waste treatment

References

[1] Vakhitov T.R., Katnov V.E., Grishin P.V., Stepin S.N., Grigoriev D.O., Biofriendly nanocomposite containers with inhibition properties for the protection of metallic surfaces, Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences, vol. 473, issue 2199, pp 20160827-20160840, 2017.

- [2] Rodriguez M. T., Gracenea J. J., Garcia S. J., Saura J. J., Suay J. J., Testing the influence of the plasticizers addition on the anticorrosive properties of an epoxy primer by means of electrochemical techniques, Progress in Organic Coatings, vol. 50, issue 2, pp 123-131, 2004.
- [3] Ziganshina M. R., Peshkova M. S., Stepin S. N., Katnov V. E., The effect of synthesis conditions on the properties of precipitated manganese-based anticorrosive pigments, Lakokrasochnye materialy i ikh primenenie, vol. 10, pp 34, 2005.
- [4] Zubielewicz M., Gnot W., Mechanisms of non-toxic anticorrosive pigments in organic waterborne coatings, Progress in organic coatings, vol. 49, issue 4, pp 358-371, 2004.
- [5] de Lima-Neto P., de Araújo A. P., Araújo W. S., Correia A. N., Study of the anticorrosive behaviour of epoxy binders containing non-toxic inorganic corrosion inhibitor pigments, Progress in Organic Coatings, vol. 62, issue3, 344-350, 2008.
- [6] Jansen M., Letschert H. P., Inorganic yellow-red pigments without toxic metals, Nature, vol. 404/issue 6781, pp 980, 2000.
- [7] Del Amo B., Romagnoli R., Deyá C., González J. A., High performance water-based paints with non-toxic anticorrosive pigments, Progress in Organic Coatings, vol. 45, issue 4, pp 389-397, 2002.
- [8] Grigoriev D. O., Vakhitov T., Stepin S. N., Ferrites as Non-Toxic Pigments for Eco-Friendly Corrosion Protection Coatings, Biobased and Environmental Benign Coatings, Germany, 2016, pp 71-86.
- [9] Yegorova S. R., Ziganshina M. R., Karandashov S. A., Onishchenko Y. V., Lamberov A. A., Synthesis and Study of Inorganic Pigment Properties on the Basis of Dead Chrome Catalyst, Research Journal of Pharmaceutical, Biological and Chemical Sciences, vol. 6, issue 6, pp 1540-1548, 2015.
- [10] Magalhaes J. M., Silva J. E., Castro F. P., Labrincha, J. A., Physical and chemical characterisation of metal finishing industrial wastes, Journal of Environmental Management, vol. 75, issue 2, pp 157-166, 2005.