

# HYDROXYAPATITE COATING ON STAINLESS STEEL 316L USING INVESTMENT CASTING TECHNIQUE

ANDRIL ARAFAT SUHASRIL

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Doctor of Philosophy (Mechanical Engineering)

Faculty of Mechanical Engineering  
Universiti Teknologi Malaysia

JANUARY 2016

*I dedicate this thesis to my lovely parents, wife, and sons*

## ACKNOWLEDGEMENTS

It is with immense gratitude that I acknowledge the consistent support, encouragement, guidance and help of my supervisor Prof. Dr. Mohd Hasbullah Idris and my co-supervisor Prof. Ir. Dr. Mohammed Rafiq bin Dato' Abdul Kadir for their valuable suggestions, advice and motivation throughout this project. Indeed, this thesis would not have been possible without their continued helpful supervisions.

I would like to take this opportunity to extend my thanks to all my colleagues in Cast Metal Group and the staff in Foundry and Materials Science laboratories for their help and assistance in the course of conducting the experiments and fulfilling the requirements of this thesis.

Finally, I owe my deepest gratitude to my parents, wife and sons for their love, patience and many sacrifices.

## ABSTRACT

Decades of research had found that the use of hydroxyapatite (HA) could promote osseointegration and increase the mechanical stability and strength of the metallic implant. Currently, medical implants are produced by machining, metal forming and casting particularly investment casting technique. Comparatively, the investment casting technique is more practical to mass produced implant due to its simplicity, superior surface finish, relatively cheap process, capability to produce complex and near-net shape implants. Investment casting technique provides a single stage processing technique in producing coated implant i.e. HA coated on the cast implant. In this respect, the possibility of applying HA layer during casting for implant substrate using investment casting was explored. Previous studies used paint brush in applying HA layer onto the internal cavity of the ceramic mould. However, the layer thickness was inconsistent which affects the quality of the HA layer coated on the casting and impractical for small and complex shapes components. In this study, medical grade 316L stainless steel (316L-SS) was coated with HA using investment casting technique by pouring molten 316L-SS into a HA coated ceramic mould at temperature of 1650°C in argon gas. The coated samples were sintered in a furnace at four different temperatures (600, 800, 1000 and 1200°C) for 1 hour. The as-cast and sintered HA coated samples were characterised using scanning electron microscopy, energy dispersive x-ray spectroscopy and x-ray diffraction analysis. Results showed that the as-cast samples produced good HA coating bond, formed amorphous phases and complex calcium-chromium oxide (CaCrO) layer at the interface between HA and 316L-SS. Sintering process was conducted to recrystallise and improve the properties of the as-cast HA coating. The results confirmed that crystallinity and purity of the coating increased with increasing sintering temperature whilst Ca/P ratio and porosity decreased. Increasing sintering temperature from 600 to 800°C did not significantly alter the crystallinity and purity. The crystallinity and purity recorded at that temperature range were 57.35% - 58.55% and 61.80% - 63.21% respectively. This temperature range was considered insufficient to recrystallise and purify the coating to an acceptable value for implant applications. Increased of sintering temperature from 1000 to 1200°C increased the crystallinity from 73.52% - 74.47% and purity from 61.80% - 81.8%. Simultaneously, the Ca/P ratio and porosity were reduced to 1.51 and 14.14% respectively which is acceptable to human body. Sintered as-cast specimen at 1000°C immersed into Simulated Body Fluid (SBF) solution showed increased in Ca/P ratio with increasing immersion time indicating that the coating was bioactive.

## ABSTRAK

Penyelidikan sejak beberapa dekad telah mendapati bahawa penggunaan *hydroxyapatite* (HA) boleh menggalakkan *osseointegration* dan meningkatkan kestabilan mekanikal dan kekuatan pada implan logam. Pada masa ini, implan perubatan dihasilkan dengan kaedah pemesinan, pembentukan logam dan tuangan terutamanya teknik tuangan pelaburan. Secara perbandingan, teknik tuangan pelaburan adalah lebih praktikal untuk implan yang dihasilkan secara banyak kerana proses tersebut ringkas, kemasan permukaan yang unggul, proses yang agak murah, keupayaan untuk menghasilkan bentuk kompleks dan bentuk implan yang hampir tepat. Teknik tuangan pelaburan menyediakan pemprosesan satu peringkat untuk menghasilkan implan bersalut contohnya salutan HA pada tuangan implan. Dalam hal ini, kemungkinan untuk mengaplikasikan lapisan HA semasa penuangan logam pada substrat implan menggunakan teknik tuangan pelaburan telah diteroka. Kajian terdahulu menggunakan berus cat untuk mengaplikasikan lapisan HA pada rongga dalam acuan seramik. Walaubagaimanapun, ketebalan lapisannya tidak konsisten yang memberi kesan kepada kualiti lapisan HA yang terbentuk pada tuangan dan ia tidak praktikal digunakan pada komponen yang kecil dan berbentuk kompleks. Dalam kajian ini, keluli tahan karat gred perubatan 316L (316L-SS) telah disalut dengan HA menggunakan teknik tuangan pelaburan dengan menuang logam 316L-SS ke dalam acuan seramik bersalut HA pada suhu 1650°C dalam gas argon. Sampel bersalut disinter dalam relau pada empat suhu yang berbeza (600, 800, 1000 dan 1200°C) selama 1 jam. Sampel bersalut HA yang dituang dan yang disinter telah dicirikan menggunakan mikroskop elektron imbasan, tenaga serakan x-ray spektroskopi dan analisis pembelauan x-ray. Keputusan menunjukkan sampel hasil tuangan menghasilkan ikatan salutan HA yang baik, membentuk fasa amorfus dan lapisan kalsium kromium oksida (CaCrO) yang kompleks pada antara muka HA dan 316L-SS. Proses pesinteran telah dijalankan untuk penyusunan semula hablur dan menambah baik ciri-ciri lapisan HA hasil tuangan. Keputusan mengesahkan bahawa penghabluran dan ketulenan lapisan meningkat dengan peningkatan suhu pesinteran manakala nisbah Ca/P dan keliangan berkurang. Meningkatkan suhu sinter dari 600 ke 800°C tidak mengubah penghabluran dan ketulenan secara berkesan. Penghabluran dan ketulenan yang direkodkan pada julat suhu tersebut adalah 57.35%-58.55% dan 61.80%-63.21% masing-masing. Julat suhu ini dianggap tidak memadai untuk penyusunan semula hablur dan penulenan lapisan kepada nilai yang diterima bagi penggunaan implan. Peningkatan suhu pesinteran dari 1000 kepada 1200°C meningkatkan penghabluran daripada 73.52%-74.47% dan ketulenan dari 61.80%-81.8%. Pada masa yang sama, nisbah Ca/P dan keliangan telah dikurangkan kepada 1.51% and 14.14% masing-masing dimana dapat diterima oleh tubuh manusia. Spesimen yang disinter pada suhu 1000°C yang telah direndam di dalam larutan *Simulated Body Fluid* (SBF) menunjukkan peningkatan nisbah Ca/P dengan peningkatan tempoh rendaman yang menunjukkan bahawa salutan adalah bioaktif.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENTS</b>	iv
	<b>ABSTRACT</b>	v
	<b>ABSTRAK</b>	vi
	<b>TABLE OF CONTENTS</b>	vii
	<b>LIST OF TABLES</b>	xi
	<b>LIST OF FIGURES</b>	xii
	<b>LIST OF ABBREVIATIONS</b>	xvi
	<b>LIST OF SYMBOLS</b>	xvii
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.0 Background of the Research	1
	1.1 Problem Statement	3
	1.2 Objectives of the Research	4
	1.3 Scope of the Research	5
	1.4 Significance of the Research	5
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>6</b>
	2.1 Overview of Biomaterials	6
	2.2 Metallic Biomaterials	8
	2.2.1 Stainless Steel (SS)	9
	2.2.2 Cobalt Chromium (CoCr) Based Alloys	10
	2.2.3 Titanium (Ti) Based Alloys	11

2.3	Hydroxyapatite (HA)	13
2.3.1	General Structure and Chemistry of HA	14
2.3.2	Biological and Dissolution of HA	15
2.3.3	Physical and Mechanical Properties of HA	15
2.4	Hydroxyapatite Coating on Metallic Implant	16
2.4.1	Electrophoretic Deposition (EPD)	18
2.4.2	Ion Beam Assisted Deposition (IBAD)	19
2.4.3	Dip Coating	20
2.4.4	Plasma Spraying	21
2.4.5	Investment Casting Technique	23
2.5	Summary	24
<b>3</b>	<b>RESEARCH METHODOLOGY</b>	<b>25</b>
3.1	Introduction	25
3.2	Materials and Equipment	29
3.2.1	HA powder	29
3.2.2	Substrate	29
3.3	Preparation of HA Coated on Ceramic Shell Mould	30
3.3.1	Pattern Preparation	30
3.3.2	HA Slurry Preparation	31
3.3.3	Ceramic Shell Mould Preparation	32
3.3.4	Dewaxing and Mould Firing	32
3.4	Investigation on the HA Powder and Effect of Heating at Different Temperatures	34
3.5	Investigation on the Quality of the HA Coated on Ceramic Shell Mould and the Effect of HA Slurry Viscosities	35
3.6	Casting of 316L-SS into Ceramic Shell Mould Coated with HA	35
3.7	Effect of Sintering on as-cast Coated Specimens	37
3.8	Test, Characterisation and Analysis	38
3.8.1	Particle Morphology of HA Powder	38

3.8.2	Surface Morphology, Coating Thickness and Ca/P Ratio Analysis	38
3.8.3	Specimen Mounting, Grinding and Polishing	39
3.8.4	Phase Composition Analysis	39
3.8.5	Purity Analysis	40
3.8.6	Crystallinity Analysis	41
3.8.7	Porosity Analysis	41
3.9	Simulated Body Fluid (SBF) Test	42
3.9.1	Preparation SBF Solution	43
3.9.2	Immersing Specimens into SBF Solution	44
<b>4</b>	<b>RESULTS AND DISCUSSION</b>	<b>45</b>
4.1	Introduction	45
4.2	Preliminary Investigation on the HA Powder	45
4.2.1	Powder Morphology, Ca/P Ratio and Particle Size	46
4.2.2	Thermal Behaviour of HA Powder on Phase Composition, Ca/P Ratio, Purity and Crystallinity	47
4.3	Investigation and Analysis of HA Coated on Ceramic Shell Mould	51
4.3.1	Effect of Dewaxing Temperature	51
4.3.2	Effect of Preheating Temperature	53
4.3.3	Effect of HA Slurry Viscosity on the Quality of Ceramic Shell Mould Cavity	56
4.4	Casting	58
4.4.1	Surface Morphology, Porosity and Ca/P Ratio	58
4.4.2	Phase Composition, Purity and Crystallinity	64
4.5	Sintering	65
4.5.1	Surface Morphology, Porosity and Ca/P Ratio	66
4.5.2	Phase Composition, Purity and Crystallinity	70
4.6	In-vitro Test on Simulated Body fluid (SBF)	73



<b>5</b>	<b>CONCLUSION AND RECOMMENDATION FOR FUTURE WORKS</b>	<b>76</b>
	5.1 Conclusion	76
	5.2 Recommendations for Future Works	77
	<b>REFERENCES</b>	<b>79</b>
	Appendices A-G	89-100

**LIST OF TABLES**

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	Classification of biomaterials	7
2.2	The composition of 316L-SS	9
2.3	Compositions of CoCr based alloys in biomedical applications	11
2.4	Interstitial contents of titanium based alloys in biomedical applications	12
2.5	Summary of biometallic implant properties and its applications	13
2.6	Synthetic calcium phosphates	14
2.7	Various mechanical properties of HA	16
2.8	FDA and ISO requirements for HA coating on metallic implant	18
3.1	Comparison of chemical composition of 316L-SS	30
3.2	Parameters used for XRD scanning of HA powder and coating	40
3.3	The ions concentration of SBF and human body blood plasma	42
3.4	The reagents used for the preparation of 1 liter SBF solution	43

## LIST OF FIGURES

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	Illustrated example of implants and devices used in human body	8
2.2	General structure of HA	15
2.3	a) Example of implant part coated HA, b) Illustration of coated HA implant fixed in bone	17
2.4	Illustration the mechanism of electrophoretic deposition process	19
2.5	Illustration the mechanism of ion beam assisted deposition	20
2.6	Illustration the mechanism of dip coating process	21
2.7	Schematic illustration of the principle of plasma spraying	22
2.8	Steps in investment casting processes	24
3.1	Overall experimental activities conducted in this research	28
3.2	a) 3-sample cavity with pouring cup aluminium die, and b) wax pattern produced for the investigation	31
3.3	Ceramic mould preparation, a) wax pattern coated with HA, b) development of 1st back-up coat by dipping in investment slurry, c) stuccoed patterns, d) ceramic moulds ready for dewaxing	33
3.4	The electrical heating furnace used for dewaxing and firing of the ceramic moulds	33
3.5	The vacuum sintering furnace used for sintering the HA powder	34
3.6	Casting of 316L-SS samples a) schematic drawing of the casting set-up, b) actual casting set-up	36
3.7	Schematic drawing showing the position of the specimen cut from the sample	36

4.1	HA powder used in the investigation; a) Surface morphology, b) EDS spectra	47
4.2	XRD pattern of pure HA powder	48
4.3	XRD pattern of HA powder; a) pure HA powder, b) heat treated at 600°C, c) heat treated at 800°C, d) heat treated at 1000°C, e) heat treated at 1200°C	49
4.4	Ca/P ratio, purity and crystallinity of HA powder heated at different temperatures	50
4.5	a) Crack at the bottom part of shell ceramic mould, b) crack on the side part of shell ceramic mould	51
4.6	The movement of mould walls, illustrating the principle of inward expansion in convex region, and outward expansion on concave areas	52
4.7	a) Drilling of wax prior to dewaxing, b) bottom view of dewaxed moulds, c) top view dewaxed moulds, and d) mould fired at 800°C	53
4.8	XRD pattern of HA coated on the cavity of ceramic shell mould; a) pure HA powder, b) heat treated at 600°C, c) heat treated at 800°C, d) heat treated at 1000°C, and e) heat treated at 1200°C	54
4.9	EDS spectra of HA coated on the cavity of ceramic shell mould preheated at 800°C	56
4.10	Morphology of the HA coated surface of viscosity of a) 5sec, b) 10sec; cross-section of HA coating of viscosity c) 5sec, d) 10sec; porosity of HA coating of 5sec viscosity e) surface morphology area, f) porosity distribution; and porosity of HA coating of 10sec viscosity g) surface morphology area, h) porosity distribution	57
4.11	a) 3-D cross-section of the HA coating, b) exploded view of the surface morphology of the HA coating (point A), c) exploded view of the interfacial of HA coating (point B), and d) porosity of Fig. 4.11b	59
4.12	Elemental mapping of HA coating onto 316L-SS	60
4.13	EDS spectrum analysis of cross-section coating in Fig.4.11c	60
4.14	(a) Cross-section of the coated sample, (b) Exploded view of the penetrated area of 316L-SS into HA coating, (c) EDS of grey area, (d) EDS of white area	61
4.15	Schematic illustration of penetration of molten 316L-SS and, the formation of FeCrPO and CrCaO layers	62

4.16	Analysis of the presence of various elements at the stainless steel 316L-HA coating interface	63
4.17	(a) pure HA powder, (b) XRD pattern of the as-cast sample	65
4.18	HA coating sintered at 600°C a) Surface morphology b) porosity and c) EDS spectra of surface morphology	66
4.19	HA coating sintered at 800°C a) Surface morphology b) Porosity and c) EDS spectra of surface morphology	67
4.20	HA coating sintered at 1000°C a) Surface morphology b) Porosity and c) EDS spectra of surface morphology	68
4.21	HA coating sintered at 1200°C a) Surface morphology b) Porosity and c) EDS spectra of surface morphology	69
4.22	Relationship between sintering temperature and % porosity and Ca/P ratio of HA coating	70
4.23	XRD pattern of HA coated on 316L-SS; a) as-cast , b) heat treated at 600°C, c) heat treated at 800°C, d) heat treated at 1000°C, e) heat treated at 1200°C	71
4.24	The relationship of purity and crystallinity of sintered specimens at different temperatures	73
4.25	Surface morphology of coating specimens immersed in SBF solution; a) 7 days, b) 14 days, c) 21 days and d) 28 days	74
4.26	Schematic illustration of the mechanism of nucleation of bone-like apatite layers on HA coated specimen surface	75

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	Technical drawing of aluminium die used in this research	89
B	Certificate of HA powder used in this research	91
C	Details XRD spectrum of pure HA powder distribution peaks	92
D-1	Calculated of average Ca/P atomic% ratio of HA powder	96
D-2	Summaries of average Ca/P atomic% ratio of HA powder heated at 600, 800, 1000 and 1200°C	96
E	Calculated of average Ca/P atomic% ratio of ceramic shell mould coated HA	97
F	Calculated of average Ca/P atomic% ratio of as-cast specimen	98
G	Calculated of average Ca/P atomic% ratio of sintered as-cast coated HA specimens	99
H	Example EVA-XRD software on calculation of %purity and %crystallinity	100

**LIST OF ABBREVIATIONS**

ASTM	-	American Society for Testing and Materials
BS	-	British Standard
EDS	-	Energy Dispersive X-ray Spectroscopy
ISO	-	International Organization for Standardization
SEM	-	Scanning Electron Microscopy
XRD	-	X-ray Diffraction

**LIST OF SYMBOLS**

$\text{cm}^3$	-	Cubic centimetre
g	-	Gram
K	-	Thermal conductivity
lit	-	Litre
$\text{m}^2$	-	Square metre
min	-	Minute
ml	-	Millilitre
mm	-	Millimetre
wt. %	-	Weight percentage
$\mu\text{m}$	-	Micrometre
$^\circ$	-	Degree
$^\circ\text{C}$	-	Centigrade degree



## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Background of the Research**

An implant is a man-made medical device manufactured to replace a missing biological structure, support a damaged biological structure, or enhance an existing biological structure (Vedula, 2015). Currently, medical implants are produced by machining, metal forming and casting particularly investment casting technique. Comparatively, the investment casting technique is more practical to mass produced implant due to its simplicity, superior surface finish, relatively cheap process, capability to produce complex and near-net shape implants (ASM Handbook, 2008). The paramount important in implant device is that the material must be biocompatible such that it is not toxic and harmful to human body.

The materials especially metals currently widely accepted for implant devices are titanium and cobalt and its alloys and stainless steels, which not only have excellent biocompatibility but at the same time possess good mechanical properties (Paital and Dahotre, 2009). Other metallic biomaterials such as magnesium and iron based alloys as biodegradable materials are widely applied temporary implants i.e. cardiovascular, paediatric, orthopaedic and dental applications. It serves as structural mechanical support for a limited duration and diminishes gradually being adsorbed or resorbed by physiological metabolic reaction (Hermawan et al, 2010).

Further requirement of medical implant is that, it has the capability to promote tissue growth. The used of the aforementioned metals alone could not fulfill such requirement. Decades of research had found that the use of Hydroxyapatite (HA) could promote osseointegration (new bone formation), increase the mechanical fixation and mechanical stability of the metallic implant (Acton, 2013). HA can be applied as a layer on the surface of the implant (coating) or acts as bone filler.

In recent decades, plasma spraying (Kweh, 2000; Sun, 2003 and Heimann, 2006) is currently one of the most widely methods used for coating metallic implant with HA. Even though, plasma spraying of HA is a simple process, high deposition rate, low substrate temperature, variable coating porosity, and variable phase and structure (Shi, 2006). Its major problem is it high temperature during spraying (up to 10000°C) alters the HA and also metal substrate phases, causing the dehydroxylation, decrease crystallinity and phase decomposition into a mixture of HA. Other coating processes proposed to coat HA on substrate are electrophoretic deposition (Boccaccini *et al.*, 2010; Van, 1999 and Besra, 2007), sputtering (Ozeki, 2002; Yang, 2005 and Hao, 2011), dip coating (Mavis, 2000; Aksakal, 2008 and Shibli, 2008), sol-gel (Brinker, 1991; Weng, 1998 and Liu, 2001), hot pressing and hot isostatic pressing (Atkinson, 2000; Onoki, 2006 and 2011). These techniques have been used to improve the quality of HA coating since they are low temperature process techniques. However, low adhesion strength and relatively non-uniform layer of coatings are the disadvantages limiting these techniques although they have high deposition rate and low process cost (Shi, 2006).

All these techniques require two preparation processes; preparation of the implant part (substrate) and coating process, such that the implant is either prepared by machining or metal forming and finally coated with HA using the coating processes as mentioned earlier. Investment casting technique provides a single processing in producing the coated implant i.e. HA coated on the cast implant. In view of these procedures, the possibility of applying HA layer during casting for implant substrate using investment casting is an alternative promising method. The concept is by applying HA layer onto the inner wall of the ceramic mould cavity with the desired thickness and pouring of molten metal into it. During solidification, the HA particles that are coated on the cavity of the ceramic mould react with the molten

metal and creates a mechanical bonding between them. As a result, porous HA layer formed on the surface of substrate, promotes bioactive implant part and at the same time eliminates the post procedure for HA coating. This method promises an improvement to the manufacturing of implant as well as meeting the bioactivity requirement of high loading implant applications such as hip prostheses and dental implant.

In this research, stainless steel implant grade 316L (316L-SS) ASTM F-745 and HA powder was used as the biometallic implant and coating material respectively. The research covered issues on quality of HA coated on the cavity of the ceramic mould, interaction between HA-molten metal during casting and effect of post-heat treatment subjected to phase transformation of the coating. The coating bioactivity was also evaluated in vitro test by immersing specimens into Simulated Body Fluid (SBF). However, the main aim in this research was to establish the procedure in coating of HA by investment casting technique and evaluating the quality the properties of the HA coating.

## **1.2. Problem Statement**

Published reports regarding HA coating using investment casting technique are limited and not extensive. Previous studies reported the coating of HA on titanium and cobalt based alloys. Sohmura *et al.* (2001) were the first researchers to propose such technique, where medical grade titanium was poured into investment and graphite moulds coated with HA to produce implants coated with HA. Other researchers have also reported developing HA and biphasic calcium phosphate (BCP) coating on cobalt based alloys using the technique, in addition to investigating the effect of pre-heating mould and post sintering process on the enhancement of bioactive implants (Escobedo, 2006; Almanza, 2006 and Minouei, 2011). The researchers reported coating of the cavity of ceramic mould with water moisturised HA using a paintbrush before assembling the moulds. The use of paintbrush to coat the mould cavity maybe applicable to simple and non-delicate part but may be difficult when used on complex shape and small implants. Furthermore, the thickness

and consistency of HA adhered to the ceramic mould cavity are also of concern. The possibility of using dipping to coat HA onto the mould cavity could be used to overcome these problems. This method is likely to be more practical and applicable for coating of complex shape and small implant. Other aspects that have to be considered are effects of viscosity of HA mixture, coating thickness, HA binder, and sintering temperature.

Medical grade 316L-SS has been used in implant application which offers several advantages such as high corrosion resistance when implanted in the human body, low cost and ease of manufacturing compared to titanium and cobalt based alloys. For decades, this material has been successfully employed as implant, which requires it to be in contact with soft and hard tissues (Narushima, 2010). However, no study has been reported pertaining to the use of 316L-SS as substrate coated with HA using investment casting technique. Based on that facts, there is a need to explore into investigating how HA could be coated onto the 316L-SS substrate, evaluating the performance of the coating as well as investigating its bioactivity once coated through casting process.

### **1.3. Objectives of the Research**

The main aim of this research was to produce an ever ready HA coated medical grade 316L-SS using investment casting technique. The following specific objectives in this study are:

1. To study the effect of sintering temperature on the properties of HA powder.
2. To investigate the effect of HA slurry viscosities on the quality of HA coated on ceramic shell mould by dipping method.
3. To investigate the effect of mould firing and casting temperatures on the properties of HA coating.
4. To study the effect of sintering temperatures on the properties of coating.
5. To study the effect of different immersion duration on the bioactivity responses of the coating.

#### **1.4. Scope of the Research**

The research was conducted within the following limits:

1. The biometallic material used in this research was 316L-SS of medical grade.
2. The investment casting processes followed the ASM (2008) standard procedures. Refractories slurry used was zircon flour and colloidal silica as the binder.
3. The sintering temperature investigated was at 600, 800, 1000 and 1200°C for the duration of 1 hour.
4. In-vitro bioactivity immersion test used Kokubo solution for the duration of 7, 14, 21 and 28 days.
5. Properties investigated to establish the effect of sintering temperature includes crystallinity, purity, porosity, Ca/P ratio and bioactivity of the coated HA.

#### **1.5. Significant of the Research**

This research provides an alternative approach to coating of biomedical ceramic hydroxyapatite (HA) onto metallic implant using a widely acceptable technique for implant manufacture-investment casting technique. Current approaches used in embedding biomedical ceramics are by producing the implant by investment casting technique and using other coating techniques such as plasma spray, high velocity oxygen fuel (HVOF), sol gel, electrodeposition etc. However, with the finding of this research, a more practical and time saving approach could be developed through a single process in embedding the biomedical ceramics onto implants.

## REFERENCES

- Acton, Q. A. (2013). *Calcium Phosphates - Advances in Research and Application*. Edition: Scholarly Brief. Scholarly Editions.
- Aksakal, B., and Hanyaloglu, C. (2008). Bioceramic dip-coating on Ti-6Al-4V and 316L SS implant materials. *Journal of Materials Science: Materials in Medicine*.19. 2097-2104.
- Almanza, J. M. et al. (2006). Bioactivation of a cobalt alloy by coating with wollastonite during investment casting. *Journal of Biomedical Materials Research - Part A*. 78. 34-41.
- Atkinson, H., and Davies, S. (2000). Fundamental aspects of hot isostatic pressing: an overview. *Metallurgical and Materials Transactions A*. 31A. 2981-3000.
- ASM. (2008). *Casting*. ASM Handbook. Volume 15. Materials Park, OH: ASM International.
- ASTM D4212-10. (2014). *Standard test method for viscosity by dip-type viscosity cups*. American Society for Testing and Materials - ASTM International.
- ASTM E3-11. (2011). *Standard Guide for Preparation of Metallographic Specimens*. American Society for Testing and Materials - ASTM International.
- A957/A957M-11a. (2011). *Standard specification for investment castings, steel and alloy, common requirements, for general industrial use*. American Society for Testing and Materials - ASTM International.
- Balamurugan, A. et al. (2007). Elaboration of sol-gel derived apatite films on surgical grade stainless steel for biomedical applications. *Materials Letters*. 60(17). 2288-2293.
- Barthell, B. L., Archuleta, T. A., and Kossowsky, R. (1989). Ion beam deposition of calcium hydroxyapatite, *Materials Research Society Symposia*, 110. 709-714.
- Besra, L., and Liu, M. (2007). A review on fundamentals and applications of electrophoretic deposition (EPD). *Progress in Materials Science*. 52. 1-61.

- Boccaccini, A. R., Keim, S., Ma, R., Li, Y., and Zhitomirsky, I. (2010). Electrophoretic deposition of biomaterials. *Journal of the Royal Society, Interface / the Royal Society* 7 (5), S581-S613.
- Brinker, C. J., Frye, G. C., Hurd, A. J., and Ashley, C. S. (1991). Fundamentals of sol-gel dip coating. *Thin Solid Films*. 201. 97-108.
- BS ISO 14887. (2000). *Sample preparation - Dispersing procedures for powders in liquids*. International Organization for Standardization.
- BS ISO 13320-1. (1999). *Particle size analysis – Laser diffraction methods – Part 1: General principles*. International Organization for Standardization.
- BS ISO 13779-3. (2008). *Implants for surgery – Hydroxyapatite part 3: Chemical analysis and characterization of crystallinity and phase purity*. International Organization for Standardization.
- DD ENV - BS ISO 1071-5. (1995). *Advanced technical ceramics-Methods of test for ceramic coatings: Part 5: Determination of porosity*. International Organization for Standardization.
- Caja, V. L. and Moroni, A. (1996). Hydroxyapatite coated external fixation pins – An experimental study. *Clinical Orthopaedics and Related Research*, (325). 269-275.
- Carayon, M. T. and Lacout, J. L. (2003). Study of the Ca/P atomic ratio of the amorphous phase in plasma-sprayed hydroxyapatite coatings. *Journal of Solid State Chemistry*. 172. 339–350.
- Campbell, J. *Castings*. (2nd edition) Butterworth-Heinemann, Oxford, UK. 2003.
- Chen, Q., and Thouas, G. (2015). Metallic implant biomaterials. *Materials Science and Engineering R*. 87. 1-57.
- Christoffersen, M. R., Dohrup, J., and Christoffersen, J. (1998). Kinetics of growth and dissolution of calcium hydroxyapatite in suspensions with variable calcium to phosphate ratio. *Journal of Crystal Growth* 186, 283-290.
- Choi, J. M., Kim, H. E., and Lee, I. S. (2000). Ion-beam-assisted deposition (IBAD) of hydroxyapatite coating layer on Ti-based metal substrate. *Biomaterials* 21, 469-473.
- Cieslak, M. J. and Savage, W. F. (1980). Weldability and Solidification Phenomena of Cast Stainless Steel. *Paper presented at the AWS 61st Annual Meeting*. Los Angeles, California. April 14-18.

- Clark, A. E., Hench, L. L., and Paschall, H. A. (1976). The influence of surface chemistry on implant interface histology: a theoretical basis for implant materials selection. *Journal of biomedical materials research* 10, 161-174.
- Davies, J. R. *Metallic Materials*. In *Handbook of Materials for Medical Devices*, ASM International, Materials Park, Ohio, 2003, 21–50.
- Disam J, Luebbers K, Neudert K, Sickinger A. (1994). Effect of LPPS spray parameters on the structure of ceramic coatings. *Journal Thermal Spray Technology*, 3, 142-147.
- Dorozhkin, S. V., and Epple, M. (2002). Biological and medical significance of calcium phosphates. *Angewandte Chemie - International Edition* 41, 3130-3146.
- Dorozhkin, S. V. (2002). A review on the dissolution models of calcium apatites. *Progress in Crystal Growth and Characterization of Materials* 44, 45-61.
- Ducheyne, P., Van Raemdonck, W., Heughebaert, J. C., and Heughebaert, M. (1986). Structural analysis of hydroxyapatite coatings on titanium. *Biomaterials* 7, 97-103.
- Everhart, W., Lekakh, S., Richards, V., Chen, J., Li, H., and Chandrashekhara, K. (2013). Corner strength of investment casting shells. *International Journal of Metalcasting*. 7, 21-27.
- Escobedo, J. C., Ortiz, J. C., Almanza, J. M., and Cortés, D. A. (2006). Hydroxyapatite coating on a cobalt base alloy by investment casting. *Scripta Materialia* 54, 1611-1615.
- Fan, X., Chen, J., Zou, J. P, Wan, Q., Zhou, Z. C, and Ruan, J. M. (2009). Bone-like apatite formation on HA/316L stainless steel composite surface in simulated body fluid. *Transactions of Nonferrous Metals Society of China* (English Edition) 19, 347-352.
- Furlong, R. J. and Osborn J. F. (1991). Fixation of Hip Prostheses by Hydroxyapatite Ceramic Coatings. *Journal of Bone and Joint Surgery-British*, 73(5). 741-745.
- Geetha, M., Singh, A. K., Asokamani, R., and Gogia, A. K. (2009). Ti based materials, the ultimate choice for orthopedic implants. *Progress in Material Science* , 54(3). 397-425.
- Gibson, I. R., Best, S. M., and Bonfield, W. (1999). Chemical characterization of silicon-substituted hydroxyapatite. *Journal of Biomedical Materials Research* (44), 422-428.
- Hanawa, T. (2010). *Overview of metals and applications*. Niinomi. M. *Metals for Biomedical Devices*. (3-22). Cambridge, UK. Woodhead Publishing Limited.



- Hao, J. et al. (2011). Enhanced osteoblast and osteoclast responses to a thin film sputtered hydroxyapatite coating. *Journal of Materials Science: Materials in Medicine*. 22. 1489-1499.
- Hamadouche, M., and Sedel. L. (2000). Ceramics in orthopaedics. *Journal Bone Joint Surgery*, 82(8). 1095-1099.
- Heimann, R. B. (2006). Thermal spraying of biomaterials. *Surface and Coatings Technology*. 201. 2012-2019.
- Hench, L. L., and Wilson, J. (1993). *An Introduction to Bioceramics*. Singapore: World Scientific.
- Hermawan, H, Dube. D, and Mantovani. D. (2010). *Degradable metallic biomaterials for cardiovascular applications*. Niinomi. M. *Metals for Biomedical Devices*. (3-22). Cambridge, UK. Woodhead Publishing Limited.
- Horton, R.A.(1998). *Investment Casting*. ASM Handbook, Vol. 15; *Casting*. ASM International. Metals Park, OH.
- Idris, M. H., Ourdjini, A., Hamzah, E. (2000). Suppression of mold-metal reactions during investment casting. *In Magnesium Alloys and their Applications*. Wiley InterScience. Wurzburg. 628–634.
- Jafari, H, Idris, M. H., and Ourdjini, A. (2013) A review of ceramic shell investment casting of magnesium alloys and mold-metal reaction suppression. *Materials and Manufacturing Processes*. 28:8. 843-856.
- Javidi, M., Javadpour, S., Bahrololoom, M. E., and Ma, J. (2008). Electrophoretic deposition of natural hydroxyapatite on medical grade 316L stainless steel. *Materials Science and Engineering C* 28, 1509-1515.
- Kasuga, T. (2010). *Coating for Metallic Biomaterials*. Niinomi. M. *Metals for Biomedical Devices*. (260-282). Cambridge, UK. Woodhead Publishing Limited.
- Kim, H. M., Himeno, T., Kawashita, M., Kokubo, T., and Nakamura, T. (2004). The mechanism of biomineralization of bone-like apatite on synthetic hydroxyapatite: an in vitro assessment. *Journal of the Royal Society, Interface / the Royal Society* 1, 17-22.
- Kokubo, T., and Takadama, H. (2006). How useful is SBF in predicting in vivo bone bioactivity?. *Biomaterials*. 27. 2907-2915.
- Kopeliovich, D. (2013). *Electrophoretic deposition*. Internet source, link: [http://www.substech.com/dokuwiki/doku.php?id=electrophoretic\\_deposition&DokuWiki=e579a03e5](http://www.substech.com/dokuwiki/doku.php?id=electrophoretic_deposition&DokuWiki=e579a03e5)

- Kweh, S. W. K., Khor, K. A. and Cheang, P., (2000). Plasma-sprayed hydroxyapatite (HA) coatings with flame-spheroidized feedstock: Microstructure and mechanical properties. *Biomaterials*. 21(12). 1223-1234.
- Klein, C. P. A. T., Wolke J. G. C. and de Groot K., "Stability of calcium phosphate ceramics and plasma sprayed coating", in *An Introduction to Bioceramics*, L. L. Hench and J. Wilson, Eds., London: World Scientific, 1993, pp. 199-221.
- Lacout, J. L. *Calcium phosphates as bioceramics*, in *Biomaterials- Hard Tissue Repair and Replacement*, D. Muster, Ed., North- Holland: Elsevier Science Publishers, 1992, pp. 81-95.
- Lacefield, W. R., "Hydroxylapatite Coatings", in *An Introduction to Bioceramics*, L. L. Hench and J. Wilson, Eds., London: World Scientific, 1993, pp. 223-238.
- Le Geros, R. Z and Le Geros, J. P., *Dense hydroxyapatite*, in *An Introduction to Bioceramics*, L. L. Hench and J. Wilson, Eds., 1993, 139-180.
- Le Geros, R. Z and Le Geros, J. P. (2008). *Hydroxyapatite*. Kokubo. T. *Handbook of Bioceramics and their Clinical Applications*, (367-394). London: Woodhead Publishing.
- Levingstone, T. J. (2008). *Optimisation of plasma sprayed hydroxyapatite coatings*. Doctoral dissertation. Dublin City University.
- Lee, J. and H. Aoki. (1995). Hydroxyapatite Coating on Ti Plate by a Dipping Method. *Bio-Medical Materials and Engineering*, 5(2), 49-58.
- Leeuwenburgh, S. C. G., Wolke, J. G. C., and Jansen, J. A. (2008). *Calcium Phosphate Coatings*. In *Bioceramics and Their Clinical Applications*. Kokubo, T. Woodhead Publishing and Maney Publishing, CRC Press, New York. 464-484.
- Li, T., Lee, J., Kobayashi, T., and Aoki, H. (1996). Hydroxyapatite coating by dipping method, and bone bonding strength. *Journal of Materials Science: Materials in Medicine* 7, 355-357.
- Liao, C. J., Lin, F. H., Chen, K. S., and Sun, J. S. (1999). Thermal decomposition and reconstitution of hydroxyapatite in air atmosphere. *Biomaterials*. 20. 1807-1813.
- Liu, D. M., Troczynski, T., and Tseng, W. J. (2001). Water-based sol-gel synthesis of hydroxyapatite: Process development. *Biomaterials*. 22. 1721-1730.
- Mavis, B., and Cu, A. (2000). Dip coating of calcium hydroxyapatite on Ti-6Al-4V substrates. *Society*. 91. 989-991.
- Minouei, H. et al. (2011). Biphasic calcium phosphate coating on cobalt-base surgical alloy during investment casting. *Journal of Materials Science: Materials in Medicine*. 22. 2449-2455.

- Moritz, K., and Muller, E. (2006). Electrophoretic Deposition: Fundamentals and Applications II. *Trans Tech Publications Ltd.*
- Nag, S., Banerjee, R., and Fraser, H. L. (2005). Microstructural evolution and strengthening mechanisms in Ti–Nb–Zr–Ta, Ti–Mo–Zr–Fe and Ti–15Mo biocompatible alloys. *Materials Science and Engineering: C*, 25(3). 357–362.
- Narushima, T. (2010). *New-generation metallic biomaterials*. Niinomi, M. *Metals for Biomedical Devices*. 355-378. Woodhead Publishing Series in Biomaterials.
- Niinomi, M. (2008). Mechanical biocompatibilities of titanium for biomedical applications. *Journal of the Mechanical Behavior of Biomedical Materials*, 1. 30-42.
- Oguchi, H., Ishikawa, K., Ojima, S., Hirayama, Y., Seto, K., and Eguchi, G. (1992). Evaluation of a high-velocity flames spraying technique for hydroxyapatite. *Biomaterials* 13, 471-477.
- Oh, K. T., and Park, Y. S. (1998). Plasma-sprayed coating of hydroxylapatite on super austenitic stainless steels. *Surface and Coatings Technology*, 110, 4-12.
- Onoki, T., and Hashida, T. (2006). New method for hydroxyapatite coating of titanium by the hydrothermal hot isostatic pressing technique. *Surface and Coatings Technology*. 200. 6801-6807.
- Onoki, et al. (2011). New technique for bonding hydroxyapatite ceramics and magnesium alloy by hydrothermal hot-pressing method. *Materials Science and Engineering C*. 31. 499-502.
- Ong, J. L., Lucas, L. C., Lacefield, W. R., and Rigney, E. D. (1992). Structure, solubility and bond strength of thin calcium phosphate coatings produced by ion beam sputter deposition. *Biomaterials* 13, 249-254.
- Ortiz, J. C., Cortés, D., Escobedo, J., and Almanza, J. (2008). A heat treatment method for obtaining a bioactive cobalt base alloy. *Materials Letters*. 62. 1270-1274.
- Ostrowski, R. C. (1987). *Wax properties that affect ceramic shell cracking*. American Foundrymen's Society. Shell Cracking: A Complete and Detailed Compilation of Papers, Case Histories, and Discussions Presented at the AFS/CMI Symposium "Factors Affecting Shell Cracking". 43-51. American Foundrymen's Society, USA.
- Ozeki, K. et al. (2002). Phase composition of sputtered films from a hydroxyapatite target. *Surface and Coatings Technology*. 160. 54-61.

- Paital, S. R., and Dahotre, N. B. (2009). Calcium phosphate coatings for bio-implant applications: materials, performance factors, and methodologies. *Materials Science and Engineering: R: Reports*, 66(1), 1-70.
- Pattanayak, D. K., Dash, R., Prasad, R. C., Rao, B. T., and Rama Mohan, T. R. (2007). Synthesis and sintered properties evaluation of calcium phosphate ceramics. *Materials Science and Engineering C*. 27. 684-690.
- Park, J and Lakes, R. S. *Biomaterials – An Introduction*. Springer-Verlag New York, USA. 2007.
- Pereira, M. L., Abreu, A. M., Sousa, J. P. and Carvalho, G. S. (1995). Chromium accumulation and ultrastructural changes in the mouse liver caused by stainless steel corrosion products. *Journal of Materials Science: Materials in Medicine*. 6(9). 523-527.
- Perry, C. R. (1999). Bone repair technique, bone graft, and bone graft substitutes. *Clinical Orthopedic*, (360). 71-86.
- Pilliar, R. M. (2009). *Metallic Biomaterials*. Narayan. R. *Biomedical Materials*. (41-81). Springer US. Springer.
- Raut, H. K., Ganesh, V. A., Nair, A. S., and Ramakrishna, S. (2011). Anti-reflective coatings: A critical, in-depth review. *Energy & Environmental Science* 4, 3779.
- Ravaglioli, A. and Krajewik, A. *Bioceramics - Materials, Properties, Applications*. London: Chapman and Hall, 1992.
- Raynaud, S., Champion, E., Bernache-Assollant, D., and Thomas, P. (2002). Calcium phosphate apatites with variable Ca/P atomic ratio I. Synthesis, characterisation and thermal stability of powders. *Biomaterials* 23, 1065-1072.
- Rodriguez, B. et al. (2004). Biomaterials for orthopedics. *Applications of Engineering Mechanics in Medicine*. 1-26.
- Schiefelbein, G. W. (1987). *Ceramic shell production for controlling shell cracking*. *American Foundrymen's Society*. Shell Cracking: A Complete and Detailed Compilation of Papers, Case Histories, and Discussions Presented at the AFS/CMI Symposium "Factors Affecting Shell Cracking. 90-99. American Foundrymen's Society, USA.
- Schultz, O. (2000). Emerging strategies of bone and joint repair. *Arthritis Research* 2(6). 433-436.

- Serre, C. M., Papillard, M., Chavassieux, P., Voegel, J. C., and Boivin, G. (1998). Influence of magnesium substitution on a collagen-apatite biomaterial on the production of a calcifying matrix by human osteoblasts. *Journal of Biomedical Materials Research* 42, 626-633.
- Schwartz, M. M. (1996). Cast bone ingrowth surface. *United States Patent*. Patent no 5,524,695, New York, USA.
- Shi, D. (2006). *Introduction to biomaterials*. Tsinghua University, China. Tsinghua University Press.
- Shibli, S. M. A., and Jayalekshmi, A. C. (2008). Development of phosphate inter layered hydroxyapatite coating for stainless steel implants. *Applied Surface Science*. 254. 4103-4110.
- Shih, C. C., Shih, C. M., Su, Y. Y., Su, L. H. J., Chang, M. S., and Lin, S. J. (2004). Effect of surface oxide properties on corrosion resistance of 316L stainless steel for biomedical applications. *Corrosion Science*. 46(2). 427-441.
- Sohmura, T., Tamasaki, H., Ohara, T., and Takahashi, J. (2001). Calcium-phosphate surface coating by casting to improve bioactivity of titanium. *Journal of Biomedical Materials Research* 58, 478-485.
- Sopyan, I., Mel, M., Ramesh, S., and Khalid, K.A. (2007). Porous hydroxyapatite for artificial bone applications. *Science and Technology of Advanced Materials*. 8. 116-123.
- Sridhar, T. M., Kamachi, M. U., and Subbaiyan, M. (2003). Sintering atmosphere and temperature effects on hydroxyapatite coated type 316L stainless steel. *Corrosion Science*. 45. 2337-2359.
- Steffens, H. D and Brune. M. (1995). Vacuum-plasma-sprayed titanium-manganese electrode layers for MnO<sub>2</sub> deposition. *Journal Thermal Spray Technology*, 4, 85-88.
- Sun, L., Berndt, C. C., and Grey, C. P. (2003). Phase, structural and microstructural investigations of plasma sprayed hydroxyapatite coatings. *Materials Science and Engineering A*. 360. 70-84.
- Sudarsanan, K and Young, R. A. (1969). Significant precision in crystal structural details: Holly Springs hydroxyapatite, *Acta Crystallographica, Section B (Structural Crystallography and Crystal Chemistry)*, vol. b25, 1534-43.

- Uddin, M. H., Matsumoto, T., Okazaki, M., Nakahira, A., and Sohmura, T. (2010). *Biomimetic Fabrication of Apatite Related Biomaterials, Biomimetics Learning from Nature*, Amitava Mukherjee (Ed.), ISBN: 978-953-307-025-4, InTech, DOI: 10.5772/8777.
- Van der Biest, O. O., and Vandeperre, L. J. (1999). Electrophoretic deposition materials. *Annual Review of Materials Science*. 29. 327-352.
- Vallet, R. M., and Gonzalez C. J. M. (2004). Calcium phosphates as substitution of bone tissues. *Progress in Solid State Chemistry* (32), 1-31.
- Vedula, G. (2015). Implantable Orthopedic Smart Device. *Biomed Arena*, (1) 1, 7 – 10.
- Wang, C. X., Chen, Z. Q., Wang, M., Liu, Z. Y., Wang, P. L., and Zheng, S. X. (2001). Functionally graded calcium phosphate coatings produced by ion beam pattering/mixing deposition. *Biomaterials* 22, 1619-1626.
- Wang, C., Ma, J., Cheng, W., and Zhang, R. (2002). Thick hydroxyapatite coatings by electrophoretic deposition. *Materials Letters* 57, 99-105.
- Wang, R., and Hu, Y. X. (2003). Patterning hydroxyapatite biocoating by electrophoretic deposition. *Journal of biomedical materials research. Part A* 67, 270-275.
- Wang, G., and Zreiqat, H. (2010). Functional coatings or films for hard-tissue applications. *Materials*, 3(7), 3994-4050.
- Weng, W., and Baptista, J. L. (1998). Sol-gel derived porous hydroxyapatite coatings. *Journal of materials science: Materials in medicine*. 9. 159-163.
- Werner, J., Linner-Krcmar, B., Friess, W., and Greil, P. (2002). Mechanical properties and in vitro cell compatibility of hydroxyapatite ceramics with graded pore structure. *Biomaterials* 23, 4285-4294.
- Yang, Y., Kim, K. H., and Ong, J. L. (2005). A review on calcium phosphate coatings produced using a sputtering process-an alternative to plasma spraying. *Biomaterials*. 26. 327-337.
- Yasuda, H. Y., Mahara, S., Umakoshi, Y., Imazato, S., and Ebisu, S. (2000). Microstructure and mechanical property of synthesized hydroxyapatite prepared by colloidal process. *Biomaterials* 21, 2045-2049.
- Yuan, Q., and Golden, T. D. (2009). Electrochemical study of hydroxyapatite coatings on stainless steel substrates. *Thin Solid Films*. 518. 55-60.
- Zhitomirsky, I., and Gal-Or, L. (1997). Electrophoretic deposition of hydroxyapatite. *Journal of materials science. Materials in medicine* 8, 213-219.

Zyman, Z., Weng, J., Liu, X., Li, X., and Zhang, X. (1994). Phase and structural changes in hydroxyapatite coatings under heat treatment. *Biomaterials*. 15. 151-155.