ENHANCED COLLISION AVOIDANCE MECHANISMS FOR WIRELESS SENSOR NETWORKS THROUGH HIGH ACCURACY COLLISION MODELING

BEHNAM DEZFOULI

A thesis submitted in fulfilment of the requirements for the award of the degree of Doctor of Philosophy (Computer Science)

> Faculty of Computing Universiti Teknologi Malaysia

> > $\mathrm{MARCH}\ 2014$

To my wife, Marjan, to my parents, Hamid and Giti, to my brothers, Amir, Majid and Mehrdad, to my sister-in-law, Tahereh

ACKNOWLEDGEMENT

All praise and thanksgiving to God Almighty for His spiritual guidance, eternal love, divine protection, strength and wisdom that made this work possible.

I would like to express my thanks and appreciations to my supervisor, Dr. Shukor Abd Razak. He has always shown his full support in my research, and gave me the confidence to move on into the direction that I desired. I am thankful to him for his advice and support throughout this research. I am grateful as well to my co-supervisor, Dr. Kamalrulnizam Abu Bakar. He was always available to provide encouragement, advice and good company.

I would like to give my special thanks to Dr. Kamin Whitehouse (University of Virginia). He dedicated countless time and energy to advise and guide me. I am very thankful to Dr. Tan Hwee-Pink for giving me the opportunity to study, experience and research at Networking Protocols Department, Institute for Infocomm Research (I²R), A*STAR, Singapore. I very much appreciate his encouragement and support in various ways. I am also indebted to Dr. Chew Yong Huat and Dr. Yeow Wai Leong for their valuable comments during our meetings at the Institute for Infocomm Research (I²R).

My family, especially my father and my mother deserve great thanks for their inseparable support and help during my study by giving encouragement and providing the moral and emotional support I needed to complete my thesis. In particular, I would like to dedicate this thesis to my beloved wife, Marjan, who holds my hand during good and bad times. This journey would have not been possible without her love, encouragement and persistent confidence in me.

I would like to thank my thesis examination committee for the time they dedicate to read this work and provide advice.

Behnam Dezfouli, Malaysia

ABSTRACT

Wireless channel and multi-hop communications cause a significant number of packet collisions in Wireless Sensor Networks (WSNs). Although a collision may cause packet loss and reduce network performance, low-power wireless transceivers allow packet reception in the presence of collisions if at least one signal can provide a sufficiently high power compared with other signals. Therefore, with respect to the large number of nodes used in WSNs, which necessitates the use of simulation for protocol development, collisions should be addressed at two layers: First, collisions should be modeled at the physical layer through a high-accuracy packet reception algorithm that decides about packet reception in the presence of collisions. Second, collision avoidance mechanisms should be employed at the Medium Access Control (MAC) layer to reduce packet losses caused by collisions. Unfortunately, the existing packet reception algorithms exhibit low accuracy and impede the development of efficient collision avoidance mechanisms. From the collision avoidance perspective, existing contention-based MAC protocols do not provide reliable packet broadcasting, thereby affecting the initialization performance of WSNs. In addition, despite the benefits of schedule-based MAC protocols during the data-gathering phase, the existing mechanisms rely on unrealistic assumptions. The first major contribution of this work is CApture Modeling Algorithm (CAMA), which enables collision modeling with high accuracy and efficiency at the physical layer. The higher accuracy of CAMA against existing approaches is validated through extensive comparisons with empirical experiments. The second major contribution includes mechanisms that improve the reliability of packet broadcasting. In particular, adaptive contention window adjustment mechanisms and the Geowindow algorithm are proposed for collision avoidance during the initialization phases. These mechanisms considerably improve the accuracy of the initialization phases, without violating duration and energy efficiency requirements. As the third major contribution, a distributed and concurrent link-scheduling algorithm (called DICSA) is proposed for collision avoidance during the data-gathering phase. DICSA provides faster slot assignment, higher spatial reuse and lower energy consumption, compared with existing algorithms. Furthermore, evaluating DICSA within a MAC protocol confirms its higher throughput, higher delivery ratio, and lower end-to-end delay.

ABSTRAK

Komunikasi multi-lompatan dan saluran tanpa wayar menyebabkan sejumlah pelanggaran paket yang ketara dalam Rangkaian Penderia Tanpa Wayar (WSN). Walaupun pelanggaran boleh mengakibatkan kehilangan paket dan menurunkan prestasi rangkaian, penghantar-terima tanpa wayar berkuasa rendah membenarkan penerimaan paket dengan kehadiran pelanggaran jika sekurangkurangnya satu isyarat dapat menyediakan kuasa tinggi yang mencukupi berbanding dengan isyarat lain. Maka, bagi bilangan nod yang banyak digunakan di dalam WSN yang memerlukan penggunaan simulasi untuk pembangunan protokol, pelanggaran harus ditangani pada dua lapisan. Pertama, pelanggaran sepatutnya dimodel pada lapisan fizikal menerusi algoritma penerimaan paket yang tepat yang menentukan penerimaan paket dalam kehadiran pelanggaran. Kedua, mekanisme pengelakan pelanggaran seharusnya digunakan pada Medium Kawalan Akses (MAC) bagi mengurangkan kehilangan paket yang disebabkan pelanggaran. Malangnya, algoritma penerimaan paket sedia ada menunjukkan ketepatan yang rendah dan menghalang pembangunan mekanisme pengelakan pelanggaran yang efisien. Dari perspektif pengelakan pelanggaran, protokol MAC berasaskan perlumbaan yang ada tidak memberikan penyiaran paket yang boleh dipercayai, seterusnya memberi kesan kepada prestasi permulaan WSN. Di samping itu, walaupun ada kebaikan pada protokol MAC berasaskan penjadualan semasa fasa pengumpulan data, mekanisme sedia ada bergantung kepada andaian vang tidak realistik. Sumbangan utama kajian ini ialah Algoritma Permodelan Penangkapan (CAMA) yang memungkinkan permodelan pelanggaran dengan ketepatan dan keberkesanan yang tinggi pada lapisan fizikal. Ketepatan CAMA yang lebih tinggi berbanding kaedah sedia ada disahkan melalui perbandinganperbandingan yang menyeluruh dengan eksperimen empirikal. Sumbangan utama kedua adalah mekanisme yang meningkatkan kebolehpercayaan penyiaran paket. Khususnya, penyesuaian mekanisme pelarasan tetingkap pertelagahan dan algoritma *Geowindow* dicadangkan untuk pengelakan pelanggaran semasa fasa-fasa permulaan. Mekanisme tersebut dengan jelas meningkatkan ketepatan pada fasa permulaan tanpa menyalahi keperluan tempoh dan keberkesanan tenaga. Sumbangan ketiga penting ialah Algoritma Penjadualan Pautan Teragih dan Serentak (DICSA) dicadangkan bagi pengelakan pelanggaran semasa fasa DICSA menyediakan penentuan slot yang lebih cepat, pengumpulan data. penggunaan semula ruang yang lebih tinggi dan penggunaan tenaga yang lebih rendah dibandingkan dengan algoritma sedia ada. Tambahan pula, penilaian DICSA dalam protokol MAC membuktikan truput yang lebih tinggi, kadar penghantaran yang lebih tinggi dan nisbah kelewatan yang lebih rendah.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	V
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xiii
	LIST OF FIGURES	XV
	LIST OF ABBREVIATIONS	xix
	LIST OF SYMBOLS	xxi
	LIST OF APPENDICES	XXV
1	INTRODUCTION	1

			т
1.1	Overview	N	1
1.2	Problem	Background	3
	1.2.1	Collision Modeling	3
	1.2.2	Collision Avoidance	6
		1.2.2.1 Collision Avoidance during the	
		Initialization Phases	6
		1.2.2.2 Collision Avoidance during the	
		Data-Gathering Phase	8
1.3	Problem	Statement	9
	1.3.1	First Research Problem: Collision	
		Modeling with High Accuracy and	
		Efficiency	10
	1.3.2	Second Research Problem: Adaptive	
		and Efficient Collision Avoidance dur-	
		ing the Initialization Phases	11

		1.3.3	Third F	Research Problem: Fast and Dis-	
			A	I Link Scheduling for Collision	
			Avoidai	ice during the Data-Gathering	11
	1 /	Obiest	P hase		11
	1.4	Contril	ives		12
	1.0	Contri		- Deserved	14
	1.0	Signino	cance of th	le Research	14
	1.1	Scope	0	÷	10
	1.8	1 nesis	Organizat	.1011	10
2	LITE	RATUR	E REVIE	EW	17
	2.1	Introdu	uction		17
	2.2	Collisio	on Modelii	ng and Collision Relationship	18
		2.2.1	Charact	teristics of Low-Power RF	
			Transce	vivers	20
			2.2.1.1	Transceiver Synchronization	20
			2.2.1.2	The Capture Effect	23
			2.2.1.3	Bit Error Probability	26
			2.2.1.4	Noise Floor	26
		2.2.2	Packet	Reception Algorithms for Colli-	
			sion Mo	odeling	28
			2.2.2.1	Inter-Node Interference	28
			2.2.2.2	Packet Reception Algorithms of NS2	30
			2.2.2.3	Analyzing the Packet Recep-	00
				tion Algorithms of NS2	33
			2.2.2.4	Other Packet Reception Algo-	
				rithms	34
			2.2.2.5	Analytical and Trace-Based	
				Packet Reception Modeling	35
		2.2.3	Establis	shing Precise Collision Relation-	
			ship bet	tween Nodes	36
			2.2.3.1	Path Loss and Multipath	
				Channel	37
			2.2.3.2	Radio Irregularity	38
			2.2.3.3	Transmission Power and Noise	
				Floor Heterogeneity	41
		2.2.4	Implem	entation Architecture	42
	2.3	Collisio	on Avoidai	nce	43

	2.3.1	Operational Phases and the Traffic	
		Patterns	44
		2.3.1.1 Neighbor Discovery and Link	
		Estimation (NDLE)	45
		2.3.1.2 Collection Tree Construction	
		(CTC)	47
		2.3.1.3 Data Gathering	47
	2.3.2	Collision Avoidance during the NDLE	
		and CTC Phases	48
		2.3.2.1 Carrier Sense Multiple Access	
		(CSMA)	49
		2.3.2.2 Collision Avoidance with	
		CSMA	52
	2.3.3	Collision Avoidance during the Data-	
		Gathering Phase	57
		2.3.3.1 Time Slot Assignment	
		Schemes	58
		2.3.3.2 Collision Avoidance through	
		Scheduling Mechanisms	59
2.4	Findings	s of the Literature Review	69
2.5	Summar	У	71
RESEA	RCH M	IETHODOLOGY	73
3.1	Introduc	tion	73
3.2	Research	n Framework	73
	3.2.1	First Stage: Collision Modeling	75
	3.2.2	Second Stage: Collision Avoidance	
		during the Initialization Phases	78
	3.2.3	Third Stage: Collision Avoidance	
		during the Data-Gathering Phase	82
3.3	Performa	ance Evaluation	85
	3.3.1	Hardware Platforms and Parameters	85
	3.3.2	Simulation Tool	87
3.4	Summar	У	90

4 COLLISION MODELING THROUGH A PACKET RECEPTION ALGORITHM WITH HIGH ACCURACY AND EFFICIENCY

4.1	Introdu	uction	letion		
4.2	Collisio	on Modeling		93	
	4.2.1	Modeling	Signal Arrival and Reception	93	
	4.2.2	SINR Cha	racterization	95	
	4.2.3	Capture M	Iodeling Algorithm (CAMA)	97	
		4.2.3.1 I	Discussion	104	
	4.2.4	CAMA Co	orrectness	104	
4.3	Implen	nentation Ar	chitecture	106	
	4.3.1	Wireless (Channel Module	107	
	4.3.2	Physical L	ayer Module	108	
	4.3.3	Discussion	L	109	
4.4	Genera	l Configurat	ions for Performance Evalua-		
	tions			109	
4.5	Validat	tion and Con	nparison	109	
	4.5.1	Evaluation	n Metrics	110	
	4.5.2	The 3-Noc	le Experiment	111	
	4.5.3	The 3-Noc	le Experiment: Long Pream-		
		ble and C	omparison with CTMA and		
		SINRA		113	
	4.5.4	The 4-Noc	le Experiment	115	
	4.5.5	The 36-No	ode Experiment	118	
	4.5.6	Comparing	g the Efficiency of CAMA		
		versus SIN	NRA and CTMA	123	
4.6	Investi	gating Collis	ions and the Capture Effect		
	in Larg	ge-Scale Wire	eless Sensor Networks	125	
	4.6.1	Simulation	n Settings, Definitions, and		
		Evaluation	n Metrics	125	
	4.6.2	Packet Re	ception Analysis	127	
	4.6.3	Sensitivity	y Analyses	130	
		4.6.3.1 E	Invironmental Parameters		
		a	nd Carrier-Sensing		
		Г	Ihreshold	130	
		4.6.3.2	Contention Window Size	132	
		4.6.3.3 F	Preamble and Payload Size	132	
		4.6.3.4 E	Bit Rate	134	
4.7	Summa	ary		135	

5 ADAPTIVE AND EFFICIENT COLLISION

.1	Introdu	lction
.2	Collisio	on Avoidance for Improving Neighbor
	Discove	ery and Link Estimation
	5.2.1	Collision Detection and Partial Packet
		Reception
	5.2.2	Contention Window Adjustment Mech- anisms
	5.2.3	Utilizing Partially Received Packets for
		Accuracy Improvement
	5.2.4	Mathematical Modeling of Collision
		Probability during Packet Broadcast
	5.2.5	Performance Evaluation Configuration
		5.2.5.1 Simulation Settings
		5.2.5.2 Evaluated Mechanisms
		5.2.5.3 Evaluation Metrics
	5.2.6	Performance Evaluations and Discus-
		sions
3	Improv	ring Collection Tree Construction
	5.3.1	Child-Parent Cost Distribution
	5.3.2	Computation of the λ Value
		5.3.2.1 Mathematical Approach
		5.3.2.2 Adaptive Approach
	5.3.3	The Geowindow Algorithm
	5.3.4	Exploiting Collision Detection
	5.3.5	Performance Evaluation Configuration
		5.3.5.1 Simulation Settings
		5.3.5.2 Evaluated Mechanisms
		5.3.5.3 Evaluation Metrics
	5.3.6	Performance Evaluations and Discus-
		sions
.4	Summa	ary

6	DISTR	IBUTED	AND	CONCUL	RRENT	LINK-	
	SCHEI	DULING	ALGO	ORITHM	FOR	COLLI-	
	SION	AVOIDA	NCE	DURING	THE	DATA-	
	GATH	ERING P	HASE				171
	6.1	Introducti	on				171

6.2	Link S	cheduling versus Node Scheduling	172
	6.2.1	Formulation	172
	6.2.2	Requirements	173
6.3	Design	and Implementation of DICSA	173
	6.3.1	Forbidden Slots	173
	6.3.2	Algorithms	175
	6.3.3	Timing	181
6.4	Perform	nance Evaluation Configuration	183
	6.4.1	Simulation Settings	183
	6.4.2	Evaluated Algorithms	184
	6.4.3	Evaluation Metrics	184
6.5	Perform	nance Evaluations and Discussions	185
	6.5.1	One-Hop Scenario	185
	6.5.2	Multi-Hop Scenario	187
	6.5.3	Schedule Update	189
	6.5.4	Data-Gathering Applications	190
6.6	Summa	ary	193

7 CONCLUSIONS

195

 $\mathbf{202}$

7.1	Overvi	ew	195
7.2	Achiev	Achievements	
	7.2.1	Collision Modeling	195
	7.2.2	Collision Avoidance	197
7.3	Directi	ons for Future Work	199

REFERENCES

Appendices A – B 221 – 227

LIST OF TABLES

TABLE NO.

TITLE

PAGE

2.1	Low-power RF transceivers and their characteristics	21
2.2	The noise parameters, theoretical noise floor and empirical	
	noise floor of CC1000 and CC2420 transceivers	27
2.3	The input of the packet reception algorithms, the expected	
	real-world behavior, and the output of CTMA and SINRA	34
2.4	The characteristics of packet reception algorithms and	
	hardware and signal propagation models implemented on	
	existing simulation platforms	44
2.5	Overview of the mechanisms proposed for collision	
	avoidance through channel access scheduling	67
3.1	The research framework of the first stage of this research	76
3.2	The research framework of the second stage of this	
	research	80
3.3	The research framework of the third stage of this research	83
3.4	The characteristics and configuration of CC1000	
	transceiver (used in Mica2) for the empirical and	
	simulated experiments	86
3.5	The characteristics and configuration of CC2420	
	transceiver (used in TelosB) for the empirical and	
	simulated experiments	86
3.6	The default packet formats	87
3.7	Environmental parameters	87
4.1	Description of the variables and operations used by	
	CAMA	97
4.2	The input of the packet reception algorithms, the expected	
	real-world behavior, and the output of CAMA, CTMA	
	and SINRA for the scenario presented in Figure 4.4	103
4.3	Experimental Parameters	110
4.4	Evaluation scenarios of the 36-node experiment	120

4.5	The start (90% packet reception rate) and end (10% $$	
	packet reception rate) of the transitional region for the	
	indoor and outdoor environments	129
5.1	Simulation configuration	144
5.2	The networks used for performance evaluations	144
6.1	Simulation configuration	183

LIST OF FIGURES

FIGURE NO.

TITLE

PAGE

2.1	The overall structure of the literature review with respect	
	to a sample topology	18
2.2	The structure and main observations of the literature	
	review conducted with respect to collision modeling	19
2.3	The structure and main observations of the literature	
	review conducted with respect to collision avoidance	20
2.4	Sample packet formats using $CC1000$ and $CC2420$	22
2.5	Sample stronger-first and stronger-last capture scenarios	24
2.6	This figure shows how the stronger-last capture scenario	
	shown in Figure $2.5(b)$ results in partial packet reception,	
	collision detection, and collision recovery	25
2.7	The state machine of CTMA	31
2.8	The state machine of SINRA	32
2.9	A sample packet reception scenario to represent the	
	operation of CTMA and SINRA	33
2.10	Effect of radio irregularity on the size and shape of the	
	connected and transitional regions	40
2.11	Radio irregularity changes the interference relationship	
	between nodes, and affects the performance of collision	
	avoidance mechanisms	41
2.12	Sample node placement for analyzing collision avoidance	
	through carrier sensing and random backoff	50
2.13	The CSMA mechanism used in IEEE 802.11 DCF	51
2.14	The CSMA mechanism used in TinyOS CSMA MAC	
	protocol	51
2.15	Combining CSMA with beaconing rate reduces the	
	number of hidden-node collisions during the NDLE phase	54
2.16	The difference between node and link scheduling for a	
	sample topology	59
2.17	The state machine of DRAND	66

3.1	The overall research framework	74				
3.2	The overall architecture of the developed simulation tool					
4.1	Utilizing the messaging and self-messaging mechanisms for					
	modeling signal synchronization and packet reception	95				
4.2	Probability of signal synchronization and correct packet					
	reception against SINR (not in dB) for CC1000 and					
	CC2420	96				
4.3	The state machine of CAMA	98				
4.4	Sample packet reception with CAMA in the presence of					
	collision	102				
4.5	The overall architecture of the Wireless Channel and					
	Physical Layer modules	106				
4.6	The architecture of the Wireless Channel module	108				
4.7	The 3-node experiment conducted with Mica2 nodes	112				
4.8	The results of the empirical and simulated 3-node					
	experiment with 6-byte preamble	112				
4.9	The results of the empirical and simulated 3-node					
	experiment with 49-byte preamble	113				
4.10	The topology of the 4-node experiment conducted with					
	TelosB nodes	115				
4.11	Comparing the number of packet receptions obtained from					
	the empirical experiments and CAMA	116				
4.12	Comparing the number of packet receptions obtained from					
	the empirical experiments, SINRA and CTMA	118				
4.13	Comparing the number of collision detections obtained					
	from the empirical experiments and CAMA	119				
4.14	The results of empirical and simulated experiments for					
	evaluating packet reception, collision detection and MAC					
	Header recovery using 6-byte preamble in the 36-node					
	experiment	121				
4.15	The results of empirical and simulated experiments for					
	evaluating packet reception, collision detection and MAC					
	Header recovery using 719-byte preamble in the 36-node					
	experiment	122				
4.16	The simulation speeds of the scenarios of the 36-node					
	experiment	124				
4.17	The simulation speed of CAMA against CTMA and					
	SINRA for 4 network sizes	125				

4.18	The simulation speed of CAMA against CTMA and SINRA for 4 preamble sizes	126
4.19	The number of receptions and the number of receptions with high-power collision in Network1 (a) and Network2 (b)	198
4.20	The effects of environmental parameters and carrier-	120
	sensing threshold on collision detection and packet reception efficiency	131
4.21	The effects of contention window duration on collision	
	detection and packet reception efficiency	133
4.22	The effects of packet formatting on collision detection and	
	packet reception efficiency	134
4.23	The effects of transceiver bit rate on collision detection	
	and packet reception efficiency	135
5.1	Mathematical analysis of broadcasting success probability	143
5.2	Influence of the MAC mechanisms and number of beacons	
	on link estimation accuracy	146
5.3	The average packet reception percentage of the nodes from	
	those neighbors that their average link quality is higher	
	than 10%	147
5.4	The number of corruption-causing collisions and the	
	number of MAC Header recoveries	150
5.5	Influence of the MAC mechanisms and number of beacons	
	on neighbor discovery	151
5.6	Influence of the MAC mechanisms on NDLE duration	153
5.7	Influence of the MAC mechanisms on the average	
	percentage of battery consumption per node	154
5.8	Probability of cost broadcast with respect to the child-	
	parent link costs	156
5.9	Link cost distribution with various network deployments	157
5.10	The frequency of various λ values with three network	
	densities	159
5.11	The assigned sub-CW corresponding to various cost values	162
5.12	Influence of the MAC mechanisms on CTC accuracy	166
5.13	Influence of the MAC mechanisms on CTC duration	167
5.14	Percentage of packet delivery at the sink node	169
6.1	Primary State Machine (PSM)	176
6.2	Secondary State Machine (SSM)	179
6.3	A sample slot reservation scenario with DICSA	182

6.4	Evaluating the execution performance of DICSA and	
	DRAND in various-size one-hop networks	186
6.5	Evaluating the execution performance of DICSA and	
	DRAND in multi-hop scenarios with various two-hop	
	neighborhood sizes	187
6.6	The slot assignment efficiency of various scheduling	
	algorithms	189
6.7	Recovery cost of DICSA and DRAND versus the number	
	of nodes applying for slot update	190
6.8	Minimum time slot duration with respect to time	
	synchronization accuracy (τ) and transceiver switching	
	delay (ϖ)	191
6.9	Performance evaluation of various scheduling algorithms	
	versus traffic rate in data-gathering applications	192
6.10	Throughput evaluation of various scheduling algorithms	
	versus neighborhood size in data-gathering applications	193
A.1	Effects of propagation range confinement on network	
	$\operatorname{throughput}$	224
A.2	Effects of propagation range confinement on the number	
	of corruption-causing collisions and simulation speed	225
A.3	Effects of propagation range confinement on NDLE	
	performance	225

LIST OF ABBREVIATIONS

ACK	-	Acknowledgement
BEB	_	Binary Exponential Backoff
BER	—	Bit Error Rate
BFS	—	Breadth First Search
CAMA	—	CApture Modeling Algorithm
CDMA	—	Code Division Multiple Access
CI	—	Constant Interval
CRC	—	Cyclic Redundancy Check
CSMA	—	Carrier Sense Multiple Access
CSMA/CA	—	Carrier Sense Multiple Access/Collision Avoidance
CTC	—	Collection Tree Construction
CTM	—	Capture Threshold Model
CTMA	—	CTM-based packet reception Algorithm
CTS	_	Clear To Send
CW	_	Contention Window
DCF	_	Distributed Coordination Function
DICSA	_	DIstributed and Concurrent link Scheduling Algorithm
DRAND	_	Distributed RANDomized scheduling
DSSS	_	Direct-Sequence Spread Spectrum
DOI	_	Degree Of Irregularity
ECDF	_	Empirical Cumulative Distribution Function
ETX	—	Expected number of Transmissions
FCS	—	Frame Check Sequence
FDMA	_	Frequency Division Multiple Access
Geowindow	_	Geometric-distribution-based contention window adjustment
LPL	—	Low-Power Listening
MAC	_	Medium Access Control
MPDU	_	MAC Protocol Data Unit

NCFSK	_	Non-Coherent Frequency Shit Keying
NCR	_	Neighborhood-aware Contention Resolution
NDLE	_	Neighbor Discovery and Link Estimation
NP	_	Non Polynomial
OQPSK	_	Offset Quadrature Phase-Shift Keying
PDF	_	Probability Density Function
PRR	_	Packet Reception Rate
PSM	_	Primary State Machine
RF	_	Radio Frequency
RIM	_	Radio Irregularity Model
RMSE	_	Root Mean Square Error
RS	_	Reception Slot
RSSI	_	Received Signal Strength Indicator
RSO	_	Reception Slot of One-hop neighbor
RTS	_	Request To Send
RX	_	Reception
SEEDEX	_	SEED EXchange scheduling
SFD	_	Start of Frame Delimiter
SNR	_	Signal-to-Noise Ratio
SINR	_	Signal-to-Interference-plus-Noise Ratio
SINRA	_	SINR-based packet reception Algorithm
SSM	_	Secondary State Machine
TDMA	_	Time Division Multiple Access
ТΧ	_	Transmission
UDG	_	Unit Disk Graph
VDEC	_	Vizing-based Distributed Edge Coloring
VDOI	_	Variance of Degree Of Irregularity
WSN	_	Wireless Sensor Network

LIST OF SYMBOLS

\mathbf{A}	—	Anisotropy matrix
B(x,y)	_	Binomial random variable with x trials and success probability y
B_n	_	Noise bandwidth
$c_{i,j}$	_	Link cost between node i and node j
$C_{tx,rx}$	_	Correlation between transmission power and noise floor heterogeneity
$cost_i$	—	Cost of node i towards the sink
CS_{th}	—	Carrier-sensing threshold
\mathbf{CN}_i	_	Set of the contenders of node i
CW_c	_	Congestion contention window size
CW_N	_	N-th sub-contention window
CW_i	_	Initial contention window size
CW^{δ}	_	Contention window duration in terms of the number of backoff slots
CW_{th}^{δ}	—	Minimum acceptable number of backoff slots in a sub-contention window
d	_	Distance
d_0	_	Reference distance
d_{cs}	_	Carrier-sensing distance
$d_{i,j}$	_	Distance between node i and node j
d_{prop}	_	Propagation range
E_b	_	Energy per bit
E_N^{δ}	_	End of N -th contention window
f_c	_	Carrier frequency
F_n	_	Noise figure
h	_	Number of hops to destination
k	_	Boltzmann constant
K_{θ}	_	Path-loss coefficient at direction θ

$l_{i,j}$	_	The link between node i and node j
L_{packet}	—	Number of bits in a packet
$L_{settling}$	—	Number of settling bits
maxC	—	Maximum number of children per node
$\max N^1$	_	Maximum neighborhood size
$\max N^{1,2}$	_	Maximum one-hop and two-hop neighborhood size
N(x,y)	_	Gaussian random variable with mean \boldsymbol{x} and standard deviation \boldsymbol{y}
N_0	—	Spectral noise density
N_{node}	—	Number of nodes in the network
$\overline{\mathrm{N}^1}$	_	The average number of one-hop neighbors per node
$\overline{\mathrm{N}^2}$	—	The average number of two-hop neighbors per node
\mathbf{N}_i^1	_	The set of the one-hop neighbors of node i
\mathbf{N}_i^2	_	The set of two-hop neighbors of node i
$\mathbf{N}_{i}^{pending}$	_	The set of neighbors from which node i expects to receive response during a time slot reservation round
p	—	Forward link quality
PL(d)	—	Path loss at distance d
$PL(d_0)$	—	Path loss at reference distance d_0
$\Pr(\overline{\text{bit}})$	—	Bit error probability
Pr(packet)	—	Packet reception probability
q	—	Backward link quality
R	—	Transceiver bit rate
$\mathbf{RS}(i)$	—	Set of the reception time slots of node i
$\mathbf{RSO}(i)$	—	Set of the reception time slots of one-hop neighbors of node \boldsymbol{i}
\mathbf{S}	—	The set of the signals currently being received at a node
S_i	—	A signal corresponding to a packet sent by a node
S_N^{δ}	—	Start of N -th contention window
$S_i(t_m, t_n)$	_	A signal that starts at time t_m and finishes at time t_n
$S_i^{CR}(t_m, t_n)$	—	Complete reception of packet i during t_m to t_n
$S_i^{PR}(t_m, t_n)$	—	Partial reception of packet i during t_m to t_n
$SINR_{th}$	—	Threshold SINR value
$SINR_j(S_i)$	—	SINR value corresponding to signal S_i received at node j
$SINR_j(S_i, t)$	_	SINR value corresponding to signal S_i received at node j at time t

T_{packet}	_	Packet transmission duration
T_{packet}^{δ}	_	Packet transmission duration in terms of the number of backoff slots
$\mathbf{TS}(i)$	—	Set of the transmission time slots of node i
$\mathbf{TSO}(i)$	_	Set of the transmission time slots of one-hop neighbors of node \boldsymbol{i}
$\mathbf{TST}(i)$	_	Set of the transmission time slots of two-hop neighbors of node \boldsymbol{i}
W(x,y)	_	Weibull random variable with scale parameter \boldsymbol{x} and shape parameter \boldsymbol{y}
V_i	_	A sample node in the network
V	_	Set of nodes in the network
X_{area}	_	Width of the area
γ	—	Minimum link cost between a node and its neighbors
$\Gamma_{i ightarrow j}$	_	The set of nodes that their transmission time overlap (fully or partially) with the packet reception from node i at node j
δ_i	—	Selected backoff slot by node i
ζ	_	Total propagation, encoding and decoding delays
η	_	Path-loss exponent
heta	_	Degree of a given direction
θ	_	Speed of light
κ_j^t	_	Priority of node j at time slot t
λ	_	Rate parameter of the geometric distribution
$\Lambda\left(c_{j,i},\lambda\right)$	_	The probability of cost broadcast by node j after receiving a cost packet from node i
$\overline{\omega}$	_	Maximum transceiver switching delay
Q	_	Environmental temperature
σ_{ch}	_	Standard deviation of signal power variations caused by multipath channel
σ_{rx}	_	Standard deviation of noise floor heterogeneity
σ_{tx}	_	Standard deviation of transmission power heterogeneity
σ_{WGN}	—	Standard deviation of additive white Gaussian noise
au	—	Synchronization accuracy
υ	_	One-way message delay
$\Upsilon(x)$	_	The distance at which a specific packet reception rate (x) is achieved

$\varphi_{i,j}$	_	A link belonging to set $\mathbf{\Phi}_l^u$
$\mathbf{\Phi}_l^u$	_	Those links between a node and its neighbors that the floor of their ETX cost is in range $[l, u]$
$\Psi_j(S_i)$	_	Reception power corresponding to signal S_i received at node j
$\Psi_j(S_i, t)$	_	Reception power received at node j at time t corresponding to signal S_i
$\bar{\Psi}$	_	Average noise floor
$ar{\Psi}^{adj}_i$	-	Adjusted noise floor of node i considering hardware heterogeneity
$\bar{\Psi}_i^{adj}(t)$	_	Adjusted noise floor of node i at time t
Ω_i	_	Output power corresponding to node i
Ω_i^{adj}	_	Adjusted output power of node i considering hardware heterogeneity
< i, k, o >	_	A time slot reservation entry indicating i as sender, k as receiver, and o as the reserved time slot

LIST OF APPENDICES

APPENDIX	K TITLE	PAGE
А	Eliminating Unimportant Collisions through Propagation	
	Range Confinement	221
В	Publications	227

CHAPTER 1

INTRODUCTION

1.1 Overview

Wireless Sensor Network (WSN)s are currently being used for various applications, ranging from medical monitoring to military surveillance [1, 2]. A WSN is composed of nodes with scarce energy resources, therefore, low-power Radio Frequency (RF) transceivers and microcontrollers are employed in the design of wireless sensor nodes. Meanwhile, wireless transceiver spends most of a node's energy and makes efficient wireless communications a very challenging problem [3].

Since the wireless channel is a broadcast medium, each node's transmission propagates in all directions and affects other nodes based on the distance from the sender. In addition, due to the use of low-power wireless communications, WSNs operate in a distributed manner and employ multi-hop packet forwarding. With respect to these issues, while the packet corresponding to the signal transmitted by a node may be received at the intended receiver, this signal may act as an interfering signal for other ongoing communications. In other words, when two nodes are communicating, usually the signal being received from the sender is overlapped with other interfering signals. Therefore, as each node's transmission may cause interference on other nodes, the term *packet collision* (or simply *collision*) would better reflect interference. Generally, collision is defined as below [4, 5],

Definition 1.1. *Collision.* When at least one signal is present at a node, the arrival of each subsequent signal causes a collision.

Since interference can also be generated by the sources outside the network (e.g., IEEE 802.11 and Bluetooth networks) [6, 7], the term "collision"

only refers to the interference caused by network nodes. Nevertheless, this thesis explicitly employs the term "external interference" for those collisions caused by sources outside the network.

Since WSNs are highly collision-prone, various collision avoidance mechanisms have been proposed to overcome the negative effects of collisions. However, although collisions affect packet reception performance [3, 8, 9], they may not necessarily cause packet loss. Specifically, the capture effect, also called interference tolerance [10], is the ability of a transceiver to receive a signal in the presence of interfering signals as long as the Signal-to-Interference-plus-Noise Ratio (SINR) of the signal being received is above a certain threshold value [4, 11, 12]. The capture effect is supported by most of low-power RF transceivers (e.q., CC1000 [13] and CC2420 [14]) and it has a significant effect on packet reception performance when packets are subject to collision [4, 11, 12, 15–18]. Therefore, as a collision may not cause packet corruption, the literature usually employs definitions that are more specific. For example, the literature on Medium Access Control (MAC) mechanisms normally focuses on those collisions that cause packet corruption. Similarly, in this thesis, while Definition 1.1 is particularly useful for collision analysis and modeling from the physical-layer point of view, related but different definitions are used for the analyses preformed from the MAC-layer perspective.

Most of the applications of WSNs usually employ a large number of nodes (*viz.*, hundreds or even thousands of nodes). Therefore, since empirical experiment with a large number of nodes is very costly and time consuming, researchers rely on simulation for protocol development and evaluation. Accordingly, dealing with collisions in WSNs should be considered from two highly correlated point of views, which are corresponding to the physical layer and MAC layer:

(i) Physical Layer. As WSNs are collision-prone, usually two or more signals arrive and overlap at the physical layer of the nodes. In other words, each signal arriving at the physical layer usually overlaps with other signals with various powers and durations. Therefore, collisions highly affect the performance of wireless networks [19–24]. The *packet reception algorithm (a.k.a., packet reception model)* employed at the physical layer is responsible to model collisions and make decision about the reception of incoming packets. Especially, it is mainly the responsibility of the packet reception algorithm to represent the real behavior of low-power

RF transceivers. Inaccuracy of collision modeling avoids revealing the real efficiency of collision avoidance mechanisms, highly affects the operation and performance of higher-layer protocols, and hinders cross-layer protocol optimizations through the physical layer [9, 25–27]. Accordingly, various interference models and packet reception algorithms have been proposed by the literature (*e.g.*, [19, 20, 28–33]).

As a collision may cause a packet loss, it affects MAC Layer. (ii) the reliability and energy efficiency of transmissions. In addition, when a transmitted packet is not received at its intended receiver, it unnecessarily occupies the channel and results in lower effective Furthermore, as stated earlier, collisions affect the throughput. performance of higher-layer protocols. For example, packet losses during the data-gathering phase of WSNs reduce the number of packets delivered to the sink node, and this directly affects the application for which the network has been deployed. Therefore, many efforts have been made to improve network performance through collision avoidance mechanisms. Specifically, since the MAC layer manages access to the common channel, collision avoidance is mainly addressed at this layer through channel access mechanisms [3, 34–38]. However, it should be noted that a collision avoidance mechanism should not necessarily be implemented at the MAC layer. For example, a module implemented above the MAC layer can improve and manage the operation of a MAC protocol.

1.2 Problem Background

As accurate collision modeling is crucial for the design, development and evaluation of collision avoidance mechanisms, this section, first, studies the challenges of collision modeling. Then, it proceeds with the challenges of providing collision avoidance during the operational phases of WSNs.

1.2.1 Collision Modeling

As stated earlier, collision modeling requires employing a packet reception algorithm at the physical layer to evaluate the incoming signals and model the effects of collisions on packet reception. Meanwhile, a packet reception algorithm relies on an interference model [20, 29, 33] (*e.g.*, SINR, Capture Threshold Model (CTM)) to decide whether an incoming packet should be received and how collisions affect an ongoing reception [19, 28, 30, 31, 39].

There are, in general, two approaches for designing a packet reception algorithm: (i) *packet-level modeling* is computationally efficient but do not accurately reproduce many aspects of collisions with respect to the capture effect; (ii) *physical-level modeling* has high fidelity but is computationally infeasible to be used for long, multi-packet network traces or large-scale networks such as WSNs. Packet-level algorithms typically perform one or two evaluation to determine the effects of collisions on a signal being received [20, 28, 31, 40, 41]. From the simulation point of view, packet-level modeling requires a lightweight algorithm and provides fast simulation. Unfortunately, packet-level algorithms present drawbacks as follows [4, 20, 27, 28, 30, 31, 39]:

- (i) Inaccuracy of Collision Modeling and Packet Reception. When multiple signals collide at a receiver, these algorithms cannot correctly decide which packet should be received. In comparison with a real-world scenario, either these algorithms indicate correct reception for the packets that could not be actually received, or they do not receive the packets that could be actually received. The inaccuracy of these algorithms is mainly due to the incorrect representation of the real behavior of low-power RF transceivers in terms of the capture effect and transceiver synchronization [4, 20, 28, 30, 31]. For example, when a strong signal collides with the beginning of a weaker signal, although it might be possible to receive the weaker signal correctly, these algorithms do not represent any reception. In particular, as the accuracy of these models depends on the factors such as collision intensity, signal arrival times, MAC protocol operation and packet format, they do not provide an accurate solution for collision modeling.
- (ii) Lack of Collision Recovery, Partial Packet Reception, and Collision Detection. Since most of the commonly used RF transceivers support the capture effect, they can switch to a new packet reception after a collision that corrupts the packet currently being received. Therefore, subject to the power of a newly arrived signal, transceivers may recover from a collision. Furthermore, depending on the collision time, some data parts of the corrupted packet may have been correctly received. These received bytes can be delivered by the physical layer to the higher layers [4, 27]. Collision recovery and partial packet reception also allow the MAC layer to perform collision detection. These features are particularly useful for the optimization of higher layers (e.g., [9, 18, 25–27]). However, packet-level algorithms do not provide partial packet reception because these

features depend on accurate modeling of the capture effect, transceiver synchronization modeling, and the SINR values computed during specific fields or bits of the packet. Consequently, packet-level algorithms cannot be used to develop or analyze cross-layer protocol optimization.

On the other hand, physical-level modeling requires SINR calculations at the bit-level; therefore, providing the upper-layer protocols with a high-fidelity estimate of collision impact. Unfortunately, physical-level modeling is very expensive from the computational point of view. It involves a comparison of the signal strength of every possible transmitter at all possible receivers for every bit. Therefore, the overhead of these algorithms scales with the number of bits per packet, the number of packets sent, and the square of the number of nodes in the network. This approach is particularly infeasible in large-scale WSNs with low-power MAC protocols, many of which use extremely long preambles or packet cycling techniques (*e.g.*, [35, 42, 43]). Therefore, new techniques are needed to achieve collision modeling with high accuracy and low overhead.

While collision modeling enables the nodes to make decision about the reception of the incoming signals, the power of the signals received at each node depends on the collision relationship between nodes. Recent studies on low-power wireless communications revealed particular characteristics (e.g., radio irregularity and hardware heterogeneity) that highly affect collision relationship between nodes [44–49]. In other words, in addition to the well-known models of signal propagation (e.g., log-normal shadowing model), these models also affect the signal power level each node receives from other nodes. For example, assume that these models are neglected, and the transmission of node i causes a collision of power x on node j. After considering the radio irregularity and hardware heterogeneity models, the received signal power from node i at node j changes to x', and this change might affect packet reception performance at node j. On the other hand, the accuracy and performance of collision avoidance mechanisms depend on collision relationship between nodes [44, 50–52]. For example, contention-based collision avoidance mechanisms highly rely on the carrier sensing information received from the physical layer. In addition, schedule-based collision avoidance mechanisms rely on collision relationship between nodes for channel access scheduling. Therefore, accurate collision modeling would be meaningless without establishing precise collision relationship between nodes [29]. Although the literature proposes models for establishing precise collision relationship between nodes, unfortunately, investigating the implementation architectures used for implementing these models on simulation platforms indicates the lack of these models. Consequently, for example, the real-world performance of a link-scheduling algorithm (used for collision avoidance during the data-gathering phase) may be highly different than the result obtained by simulation [50, 52]. Therefore, implementing an accurate packet reception algorithm along with the models that affect collision relationship between nodes requires a sophisticated architecture. Using this architecture, the aforementioned algorithms and models can be implemented on a simulation platform such as OMNeT++ [53].

1.2.2 Collision Avoidance

As stated earlier, WSNs are highly collision-prone, therefore, collision avoidance mechanisms are required to improve the performance of these networks. This thesis addresses collision avoidance with respect to the actual operational phases of WSNs: initialization, and data gathering. Therefore, collision avoidance should be investigated according to the particular characteristics of each phase. For each phase, before presenting the importance and challenges of collision avoidance, the operation of that phase is described.

1.2.2.1 Collision Avoidance during the Initialization Phases

The initialization phase has two sub-phases: Neighbor Discovery and Link Estimation (NDLE), and Collection Tree Construction (CTC). Since WSNs operate in a distributed manner, a NDLE protocol should be executed after network deployment to gather neighborhood information and estimate link qualities [54–60]. This information is later used by protocols such as routing and MAC to perform their operation [61, 62]. In addition, since the main observable traffic pattern in WSNs is many-to-one (a.k.a., convergecast) [3, 63–65], it is the responsibility of the CTC phase to establish efficient paths from each node towards the sink [64, 66–69]. Consequently, NDLE and CTC are the essential phases to operationalize a WSN.

During the NDLE phase, nodes should broadcast a fixed number of beacon packets to identify their neighbors and estimate their link qualities [54, 56, 58, 59, 62, 70]. Similarly, CTC is a packet flooding (started from the sink node) in which every node broadcasts its minimum cost towards the sink [64, 67–69]. Consequently, collisions highly affect the accuracy of these phases because they rely on a significant number of broadcast transmissions. During the NDLE phase, for those missing beacon packets caused by collision, nodes cannot distinguish between the packet losses caused by link unreliability and those caused by collisions. Therefore, a node that misses a beacon packet cannot properly estimate its link cost to the node from which the packet has been originated. In addition, collisions affect the number of discovered neighbors. Packet collision during the CTC phase causes cost update failure and increases the cost of the constructed tree, compared with the optimal-cost tree. Particularly, missing a cost packet not only affects the node that has lost the packet, but it also affects the path cost of the nodes that could have used this node as their ancestor. The inaccuracies introduced by the NDLE and CTC phases affect the efficiency of higher-layer protocols. For example, the inaccuracy of neighbor discovery affects the efficiency of scheduling algorithms, because they rely on neighborhood information to assign collision-free time slots to the nodes. In addition, inaccurate estimation of the links prevents the routing protocol to perform efficient packet forwarding. Furthermore, the inaccuracy of the CTC phase results in data transmission over non-optimal paths and causes lower delivery ratio, longer delay and higher energy consumption.

Contention-based channel access (a.k.a.,Carrier Sense Multiple Access (CSMA)) is the only possible way to arbitrate channel access during the NDLE and CTC phases, because: First, as these phases are executed after network deployment, nodes do not have any neighborhood information, therefore, sophisticated channel access mechanisms (e.q., [38, 71]) cannot be employed. Second, the initialization phases should provide adaptive and fast initialization using lightweight protocols with minimum overhead. On the other hand, achieving reliable broadcasting through CSMA is a challenging problem due to the following reasons: First, no contention window adjustment can be applied because collision detection through mutual handshaking or Acknowledgement (ACK) is not possible with broadcast transmissions [72– Second, utilizing multiple unicast transmissions instead of a broadcast 76]. transmission is not feasible because it requires the nodes to be aware of their neighbors, which is not available at the network initialization [77]. In addition, unicast transmissions significantly increase the duration and energy consumption of the initial phases [56]. Unfortunately, although the literature proposes many MAC protocols for improving the reliability of unicast transmissions during the data-gathering phase, no considerable contribution can be found on improving broadcast reliability during the initialization phases [3, 5, 56, 64, 78].

The most straightforward way to improve broadcast reliability is to

broadcast multiple copies of each packet. Although this approach has been used in vehicular networks (e.g., [79, 80]), it cannot be used during the NDLE phase of WSNs, because this phase requires a predetermined number of transmissions. In addition, as this approach multiplies the duration and energy consumption, it is not useful for the CTC phase. Considering the challenges of achieving broadcast reliability, conservative approaches such as extra-large backoff duration and constant beaconing interval have been used to reduce collisions [56, 62, 64]. However, these approaches do not provide collision detection and they are not adaptive to network dynamics. Specifically, due to the influence of various parameters (such as network density, transmission power, path loss, beacon length and transceiver speed) on the number of collisions, it is hard to achieve a trade-off between accuracy and duration. This is even more challenging when no exact network density can be considered for large-scale WSNs with random deployment. For example, the fixed beaconing rate approach either has been used in small-scale networks [61], or it has a very long inter-packet interval. These discussions indicate that CSMA should be improved through adaptive and efficient collision avoidance mechanisms for the broadcast traffic pattern.

1.2.2.2 Collision Avoidance during the Data-Gathering Phase

The fundamental traffic pattern observable in WSNs is packet forwarding towards the sink node [36, 63, 81-83]. A WSN enters this phase after the initialization phases. In order to make accurate and quick decisions, datagathering applications usually require high delivery ratio with minimum end-to-end delay [81-84]. From the channel access perspective, employing contention-based access mechanisms during this phase results in a significant number of collisions, which is the result of traffic direction, multi-hop packet forwarding, and more importantly hidden-node collisions. Since collisions reduce network performance in terms of effective throughput and delivery ratio, scheduling algorithms have been proposed to eliminate the negative effects of collisions on the performance of data-gathering applications [3, 36, 85]. Accordingly, the literature proposes two types of scheduling algorithms: Nodescheduling algorithms assume each node's transmission should be received by all of its neighbors. Therefore, they assign time slots to the nodes to avoid those collisions that may cause a node's transmission to be corrupted at any of its neighbors. In contrast, *link-scheduling algorithms* assume a specific direction for each transmission. In this instance, the collision avoidance strategy is to avoid those collisions that may cause packet corruption at the intended receiver of each packet.

Since link-scheduling algorithms rely on transmission directions, time slot assignment is less constrained and fewer number of time slots can be used for transmission scheduling. Therefore, link-scheduling algorithms provide higher spatial reuse, which results in elevated network throughput [37, 86, 87]. Besides, as the CTC phase establishes an almost static child-parent relationship between nodes, it justifies the benefits of employing link scheduling for improving the performance of data-gathering phase [36, 88, 89]. However, while most of these algorithms are centralized (e.g., [90–93]), others rely on specific assumptions that are not realistic in WSNs (e.g., the requirement to have an interference-free tree topology [94, 95]). In particular, despite significant research on the theoretical aspects of collision avoidance through link scheduling, less attention has been paid to the design of practical scheduling algorithms. Meanwhile, DRAND [38, 61] is a distributed node-scheduling algorithm that does not require any assumption regarding the underlying network. However, considering the convergecast traffic pattern, this algorithm cannot achieve the potential improvements of link scheduling. For example, even if the transmissions of two neighboring nodes to their parents do not cause packet corruption, DRAND prevents concurrent transmission of these nodes. Beside this drawback, as DRAND does not allow one-hop and two-hop neighbors to concurrently apply for time slot reservation, nodes should perform their time slot assignment The lack of concurrency increases the execution duration and sequentially. energy consumption of this algorithm. Based on these discussions, a fast, distributed and applicable link-scheduling algorithm is required to improve packet transmission efficiency during the data-gathering phase.

1.3 Problem Statement

Considering the negative effects of collisions, each node should employ collision avoidance mechanisms to avoid packet corruption at the intended receivers. Although collisions increase the chance of packet corruption at a receiver, the capture effect provides certain conditions under which a packet can be received in the presence of collisions; therefore, accurate collision modeling is required at the physical layer. The previous discussions have revealed the importance and challenges of collision modeling and avoidance from the physical layer (corresponding to packet reception) and MAC layer (corresponding to packet transmission) point of views, respectively. At the physical layer, a sophisticated packet reception algorithm is required to improve the accuracy of collision modeling. At the MAC layer, efficient collision avoidance mechanisms are required to improve the performance of WSNs. This section further elaborates these problems.

1.3.1 First Research Problem: Collision Modeling with High Accuracy and Efficiency

As WSNs are highly collision-prone, a packet reception algorithm is required at the physical layer of the nodes to evaluate the incoming signals and decide about the delivery of the incoming packets to the MAC layer. Unfortunately, the existing packet reception algorithms do not represent accurate collision modeling in terms of decision making about packet reception in the presence of collisions. Specifically, these algorithms do not accurately model the capture effect, and do not provide partial packet reception and collision detection. On the other hand, physical-level packet reception modeling has not been used because of its high complexity and overhead. To overcome these problems the following research question should be addressed:

RESEARCH QUESTION 1.1. How to design and develop a physical-level packet reception algorithm with the following properties: (i) it provides high accuracy in modeling the influence of collisions with respect to the capture effect and signal synchronization; (ii) it is an efficient solution (*i.e.*, number of nodes and packet size do not compromise its accuracy and speed); (iii) it supports partial packet reception and collision detection; (iv) it is independent of the implementation of the higher-layer protocols.

The implementation, evaluation and use of the above-mentioned packet reception algorithm on a simulation platform requires an implementation architecture. Furthermore, accurate collision modeling at the physical layer would be meaningless without establishing precise collision relationship between nodes. Unfortunately, the existing implementation architectures do not support the implementation and evaluation of the above-mentioned packet reception algorithm, and these architectures do not include most of the essential models that affect collision relationship between nodes. Therefore, the following question arises:

RESEARCH QUESTION 1.2. How to design and develop an implementation

architecture through which the aforementioned packet reception algorithm and the existing models that affect collision relationship between nodes can be implemented on a simulation platform?

1.3.2 Second Research Problem: Adaptive and Efficient Collision Avoidance during the Initialization Phases

Contention-based channel access is the only mechanism that can be employed for channel arbitration during the initialization phases of WSNs. However, as contention-based channel access mechanisms do not provide collision avoidance for broadcast transmissions, the accuracy and efficiency of the initialization phases are highly affected by collisions. Therefore, with respect to the considerable influence of the initialization phases on network performance, efficient collision avoidance mechanisms are required. Since the traffic pattern of NDLE and CTC phases are slightly different, the above problem leads to two questions:

RESEARCH QUESTION 2.1. How to adaptively and efficiently improve broadcast reliability through contention-based channel access mechanism during the NDLE phase?

RESEARCH QUESTION 2.2. How to adaptively and efficiently improve broadcast reliability through contention-based channel access mechanism during the CTC phase?

1.3.3 Third Research Problem: Fast and Distributed Link Scheduling for Collision Avoidance during the Data-Gathering Phase

With respect to the convergecast traffic pattern, many scheduling algorithms have been developed for collision avoidance during the data-gathering phase. However, compared with node scheduling, although link scheduling provides higher collision avoidance efficiency for the convergecast traffic pattern, existing link-scheduling algorithms rely on specific assumptions that cannot be satisfied in real-world applications. To overcome this problem the following research question should be addressed:

RESEARCH QUESTION 3.1. How to design and develop a distributed, fast and applicable link-scheduling algorithm for the data-gathering phase?

1.4 Objectives

The main aim of this research is improving collision modeling through a packet reception algorithm, as well as improving network performance through collision avoidance mechanisms. To achieve these aims, the following objectives are defined:

- (i) To analyze collisions and collision modeling algorithms through empirical and simulated experiments.
- (ii) To design and develop a physical-level packet reception algorithm to achieve collision modeling and decision making about packet reception with high accuracy and efficiency.
- (iii) To validate the high accuracy and efficiency of the packet reception algorithm proposed in (ii) through comparing the results of simulated and empirical experiments.
- (iv) To design and develop channel access mechanisms for providing adaptive and efficient collision avoidance during the initialization phases.
- (v) To evaluate the performance of the collision avoidance mechanisms proposed in (iv) through extensive simulation studies.
- (vi) To design and develop a distributed, fast and applicable link-scheduling algorithm for efficient collision avoidance during the data-gathering phase.
- (vii) To evaluate the performance of the link-scheduling algorithm proposed in (vi) through extensive simulation studies.

1.5 Contributions

In order to achieve the aforementioned objectives, the following contributions are presented by this work:

- (i) This research presents the following contributions with respect to collision modeling and analysis:
 - (a) A physical-level packet reception algorithm, called CApture Modeling Algorithm (CAMA), with high accuracy and efficiency. CAMA is designed based on the real characteristics of low-power RF transceivers and it also employs mechanisms for reducing the overhead of high accuracy collision modeling. In addition to accuracy, CAMA also provides partial packet reception and collision detection,

which are useful for cross-layer optimization of higher layers.

- (b) An implementation architecture through which CAMA can be implemented on a simulation platform. This architecture also allows the implementation of the existing models that impact collision relationship between nodes.
- (c) Empirical analysis of collisions with low-power RF transceivers. These studies reveal how collisions affect packet reception, partial packet reception, and collision detection performance. While comparison with empirical results confirms the credibility of CAMA, these evaluations also show the higher accuracy of CAMA against existing packet reception algorithms.
- (d) Sensitivity analysis of collisions, and in particular the capture effect, against various environmental and network parameters. This study exhibits the importance of collision modeling, and shows how environmental and network parameters affect the efficiency of packet reception and collision detection.
- (ii) This research presents the following contributions for achieving collision avoidance and improving the reliability of packet broadcasting during the initialization phases:
 - (a) Contention window adjustment mechanisms for collision avoidance during the NDLE phase. These mechanisms benefit from the collision detection capability of CAMA, and they can provide adaptive collision avoidance with respect to local collision intensity. These mechanisms considerably improve the accuracy of NDLE without violating the energy efficiency requirement of WSNs. Furthermore, since CAMA is the underlying physical layer, the NDLE protocol is enabled to benefit from partially received packets.
 - (b) A mathematical model through which the contention window size can be adjusted to achieve a desired collision avoidance probability during broadcast transmissions. This model can be used for collision analysis and pre-deployment configuration of MAC protocols.
 - (c) The Geometric-distribution-based contention window adjustment (Geowindow) algorithm, which reduces collisions during the CTC phase through contention window size management and transmission prioritization. This algorithm results in significant improvement of CTC accuracy without increasing duration or energy consumption.

- (iii) This research presents the following contribution for collision avoidance during the data-gathering phase:
 - (a) A distributed and concurrent link-scheduling algorithm, called DICSA. DICSA does not require any assumption regarding the underlying network, and achieves fast and flexible time slot assignment. These features translate to the higher performance of data-gathering applications, as well as lower schedule recovery cost in the presence of network dynamics.

1.6 Significance of the Research

Literature review and the experiments presented in this thesis confirm that WSNs are highly collision-prone, and this issue significantly affects the performance of these networks. Therefore, both collision modeling and collision avoidance are essential for protocol development and improving the performance of WSNs. This research addresses collision modeling at the physical layer, because it is responsible for modeling the effects of collisions on packet reception. Collision avoidance is addressed at the MAC layer, because it controls channel access. With respect to the presented contributions, this section highlights the significance of this research:

- (i) The comprehensive empirical measurements presented in this thesis highlight packet reception performance in the presence of collisions. Through comparison with the results of simulated experiments, these studies inform the researchers about the unacceptable accuracy of the existing collision modeling approaches on which all the higher-layer protocol developments are relied.
- (ii) The comprehensive simulation-based sensitivity analyses allow the researchers to consider the effects of environmental and network parameters on collision intensity, collision detection and packet reception performance.
- (iii) As WSNs are highly collision-prone, the proposed packet reception algorithm (*i.e.*, CAMA) is particularly important for protocol development and performance prediction. In addition, this algorithm presents new opportunities to the researchers to employ partial packet reception and collision detection for cross-layer improvement of higher-layer protocols.
- (iv) The proposed implementation architecture can be used to implement

CAMA and the essential models of low-power wireless communications on simulation platforms. This enables the research community to regenerate the real characteristics of low-power wireless communications.

- (v) Collision avoidance during the initialization phases affects the performance of network protocols such as routing and MAC. For example, improving NDLE and CTC accuracy results in higher energy efficiency, higher delivery ratio, and lower delay.
- (vi) The proposed mechanisms for providing broadcast reliability during the initialization phases achieve collision avoidance based on local collision intensity. Therefore, they are very useful for applications that include a large-scale network with random topology.
- (vii) Collision avoidance during the data-gathering phase directly affects network performance. For example, collision avoidance during this phase results in higher energy efficiency, higher network throughput, and lower delay.
- (viii) The proposed link-scheduling algorithm provides fast, distributed and applicable collision avoidance during the data-gathering phase. As most of the WSN applications involve data reporting to a single base station, many applications can be envisaged for this algorithm.

1.7 Scope

The followings clarify the scope of this research:

- (i) This work addresses the collision avoidance problem at the MAC layer, because it controls transceiver operation. However, collision avoidance can also be addressed by network-layer mechanisms (*e.g.*, packet forwarding through less congested paths), physical-layer mechanisms (*e.g.*, rate control), and so forth.
- (ii) This work considers the effects of white Gaussian noise. However, the influence of external interference on collisions has not been considered.
- (iii) This work assumes all the nodes employ a single channel for communications.
- (iv) This work addresses collision avoidance through mechanisms that manage access to a common channel. Therefore, mechanisms such as Frequency Division Multiple Access (FDMA) or Code Division Multiple Access

(CDMA) are out of the scope of this work.

- (v) The empirical validations presented in this thesis employ the two most commonly used low-power RF transceivers, *i.e.*, CC1000 and CC2420. These transceivers are used in sensor nodes such as Mica2, TelosB and MicaZ, which have been widely utilized by the research community. This thesis does not present any validation against other low-power transceivers (such as CC2500 [96] and CC2520 [97]) or the transceivers employed in IEEE 802.11 [75] and 802.15.6 [98] networks.
- (vi) This work does not perform performance evaluation in mobile WSNs, nevertheless,
 - (a) The packet reception algorithm and the architecture proposed in Chapter 4 support node mobility given that the received transmission power during a packet reception is unaffected by mobility.
 - (b) The mechanisms proposed in Chapter 5 can also be employed for collision avoidance in mobile WSNs. However, it should be noted that, depending on the mobility level, mobile WSNs might employ methods such as opportunistic routing instead of packet forwarding through collection tree.
 - (c) The scheduling algorithm proposed in Chapter 6 can support limited mobility. Specifically, it is assumed that node movement, node addition and node removal (or death) are very unlikely. However, this algorithm can be adapted to sporadic changes in network topology.

1.8 Thesis Organization

The remaining of this thesis is organized as follows. Chapter 2 provides the background of this research through studying the collision modeling and collision avoidance approaches. Chapter 3 presents the overall research plan and the performance evaluation platforms of this research. Chapter 4 proposes CAMA and an implementation architecture. In addition, this chapter presents extensive empirical and simulated experiments for analyzing collisions in WSNs. Chapter 5 deals with collision avoidance during the initialization phases of WSNs. First, this chapter proposes mechanisms for improving broadcast reliability during the NDLE phase. Then, it focuses on improving the accuracy of CTC phase through collision avoidance. Through proposing a link-scheduling algorithm, Chapter 6 overcomes the negative effects of collisions during the data-gathering phase. Chapter 7 concludes this research and provides directions for future work.

REFERENCES

- 1. Alemdar, H. and Ersoy, C. Wireless sensor networks for healthcare: A survey. *Computer Networks*, 2010. 54(15): 2688–2710.
- 2. Yick, J., Mukherjee, B. and Ghosal, D. Wireless sensor network survey. *Computer Networks*, 2008. 52(12): 2292–2330.
- Bachir, A., Dohler, M., Watteyne, T. and Leung, K. K. MAC Essentials for Wireless Sensor Networks. *IEEE Communications Surveys* & Tutorials, 2010. 12(2): 222–248.
- Whitehouse, K., Woo, A., Jiang, F., Polastre, J. and Culler, D. Exploiting the Capture Effect for Collision Detection and Recovery. *The Second IEEE Workshop on Embedded Networked Sensors, 2005. EmNetS-II.* Sydney, Australia: IEEE. 2005. 45–52.
- Eisenman, S. and Campbell, A. Structuring contention-based channel access in wireless sensor networks. *Proceedings of the 5th international* conference on Information processing in sensor networks (IPSN '05). Nashville, Tennessee, USA: Ieee. 2006. 226–234.
- Lee, H., Cerpa, A. and Levis, P. Improving wireless simulation through noise modeling. *Proceedings of the 6th international conference on Information processing in sensor networks - IPSN '07.* Cambridge, MA, USA: ACM Press. 2007. 21.
- Rusak, T. and Levis, P. A. Investigating a physically-based signal power model for robust low power wireless link simulation. Proceedings of the 11th international symposium on Modeling, analysis and simulation of wireless and mobile systems - MSWiM '08. Vancouver, British Columbia, Canada: ACM Press. 2008. 37.
- 8. Kumar, S., Raghavan, V. and Deng, J. Medium access control protocols for ad hoc wireless networks: A survey. *Ad Hoc Networks*, 2006. 4(3): 326–358.
- 9. Firner, B., Xu, C., Howard, R. and Zhang, Y. Multiple receiver strategies for minimizing packet loss in dense sensor networks. *Proceedings of the*

11th ACM international symposium on Mobile ad hoc networking and computing - MobiHoc '10. Chicago, Illinois, USA: ACM Press. 2010. 211.

- Kim, J. H. and Lee, J. K. Capture effects of wireless CSMA/CA protocols in Rayleigh and shadow fading channels. *IEEE Transactions* on Vehicular Technology, 1999. 48(4): 1277–1286.
- Son, D., Krishnamachari, B. and Heidemann, J. Experimental study of concurrent transmission in wireless sensor networks. *Proceedings of the* 4th international conference on Embedded networked sensor systems -SenSys '06. Boulder, Colorado, USA: ACM Press. 2006. 237.
- Gezer, C., Buratti, C. and Verdone, R. Capture effect in IEEE 802.15.4 networks: Modelling and experimentation. *IEEE 5th International* Symposium on Wireless Pervasive Computing, ISWPC'10. Mondena, Italy: IEEE. 2010, ii. 204–209.
- 13. Chipcon CC1000. Single Chip Very Low Power RF Transceiver. www.ti.com/lit/ds/symlink/cc1000.pdf, 2014.
- 14. Chipcon CC2420. 2.4 GHz IEEE 802.15.4 / ZigBee-ready RF Transceiver. http://www.ti.com/lit/gpn/cc2420, 2014.
- Abukharis, S., MacKenzie, R. and O'Farrell, T. Throughput and Delay Analysis for a Differentiated p-Persistent CSMA Protocol with the Capture Effect. *Proceedings of the IEEE 73rd Vehicular Technology Conference - VTC Spring.* IEEE. 2011. 1–5.
- Daneshgaran, F., Laddomada, M., Mesiti, F., Mondin, M. and Zanolo, M. Saturation throughput analysis of IEEE 802.11 in the presence of non ideal transmission channel and capture effects. *IEEE Transactions* on Communications, 2008. 56(7): 1178–1188.
- Lee, J., Kim, W., Lee, S.-J., Jo, D., Ryu, J., Kwon, T. and Choi, Y. An experimental study on the capture effect in 802.11a networks. Proceedings of the the second ACM international workshop on Wireless network testbeds, experimental evaluation and characterization - WinTECH '07. Montreal, Quebec, Canada: ACM Press. 2007. 19.
- Lu, J. and Whitehouse, K. Flash Flooding: Exploiting the Capture Effect for Rapid Flooding in Wireless Sensor Networks. *The 28th Conference on Computer Communications (INFOCOM '09)*. Rio de Janeiro, Brazil: IEEE. 2009. 2491–2499.
- 19. Zhang, L. Q., Wang, F., Han, M. K. and Mahajan, R. A general model of

wireless interference. *Proceedings of the 13th annual ACM international conference on Mobile computing and networking - MobiCom '07.* Qubec, Canada: ACM Press. 2007. 171.

- 20. Iyer, A., Rosenberg, C. and Karnik, A. What is the right model for wireless channel interference? *IEEE Transactions on Wireless Communications*, 2009. 8(5): 2662–2671.
- Jain, K., Padhye, J., Padmanabhan, V. and Qiu, L. Impact of interference on multi-hop wireless network performance. Wireless networks, 2005. 11(4): 471–487.
- 22. Blough, D. M., Canali, C., Resta, G. and Santi, P. On the impact of far-away interference on evaluations of wireless multihop networks. *Proceedings of the 12th ACM international conference on Modeling, analysis and simulation of wireless and mobile systems - MSWiM '09.* Tenerife, Canary Islands, Spain: ACM Press. 2009. 90.
- 23. Wang, W., Li, X.-Y., Frieder, O., Wang, Y. and Song, W.-Z. Efficient interference-aware TDMA link scheduling for static wireless networks. *Proceedings of the 12th annual international conference on Mobile computing and networking - MobiCom '06.* Los Angeles, CA, USA: ACM Press. 2006. 262.
- An, M. K., Lam, N. X., Huynh, D. T. and Nguyen, T. N. Minimum latency data aggregation in the physical interference model. *Computer Communications*, 2012. 35(18): 2175–2186.
- Xu, H., Garcia-Luna-Aceves, J. J. and Hamid, R. S. Exploiting the capture effect opportunistically in MANETs. *Proceedings of the Military Communication Conference (MILCOM'10)*. San Jose, CA, USA: IEEE. 2010. 1490–1495.
- 26. Dutta, P., Dawson-Haggerty, S., Chen, Y., Liang, C.-J. M. and Terzis, A. Design and evaluation of a versatile and efficient receiver-initiated link layer for low-power wireless. *Proceedings of the 8th ACM Conference on Embedded Networked Sensor Systems (SenSys '10)*. Switzerland: ACM Press. 2010. 1.
- Jamieson, K. and Balakrishnan, H. PPR: Partial Packet Recovery for Wireless Networks. ACM SIGCOMM Computer Communication Review, 2007. 37(4): 409.
- 28. Chen, Q., Schmidt-Eisenlohr, F., Jiang, D., Torrent-Moreno, M., Delgrossi, L. and Hartenstein, H. Overhaul of IEEE 802.11 modeling

and simulation in ns-2. Proceedings of the 10th ACM Symposium on Modeling, analysis, and simulation of wireless and mobile systems -MSWiM '07. Chania, Crete Island, Greece: ACM Press. 2007. 159.

- 29. Cardieri, P. Modeling Interference in Wireless Ad Hoc Networks. *IEEE Communications Surveys & Tutorials*, 2010. 12(4): 551–572.
- Al-Bado, M., Sengul, C. and Merz, R. What details are needed for wireless simulations? - A study of a site-specific indoor wireless model. *The 31rd Annual IEEE International Conference on Computer Communications (INFOCOM'12)*. Orlando, FL, USA: IEEE. 2012. 289– 297.
- Lee, J., Ryu, J., Lee, S.-J. and Kwon, T. T. Improved modeling of IEEE 802.11a PHY through fine-grained measurements. *Computer Networks*, 2010. 54(4): 641–657.
- 32. Reis, C., Mahajan, R., Rodrig, M., Wetherall, D. and Zahorjan, J. Measurement-based models of delivery and interference in static wireless networks. ACM SIGCOMM Computer Communication Review, 2006. 36(4): 51.
- 33. Gupta, P. and Kumar, P. R. The capacity of wireless networks. *IEEE Transactions on Information Theory*, 2000. 46(2): 388–404.
- Langendoen, K. Medium Access Control in Wireless Sensor Network. In: Medium Access Control in Wireless Networks. Nova Science Publishers, Inc., vol. II. 535–560. 2008.
- 35. Polastre, J., Hill, J. and Culler, D. Versatile low power media access for wireless sensor networks. *Proceedings of the 2nd international conference* on Embedded networked sensor systems (SenSys '04). Baltimore, MD, USA: ACM Press. 2004. 95.
- 36. Incel, O. D., Ghosh, A. and Krishnamachari, B. Scheduling algorithms for tree-based data collection in wireless sensor networks. In: *Theoretical Aspects of Distributed Computing in Sensor Networks*. Springer Berlin Heidelberg. 407–445. 2011.
- Gandham, S., Dawande, M. and Prakash, R. Link scheduling in wireless sensor networks: Distributed edge-coloring revisited. *Journal of Parallel* and Distributed Computing, 2008. 68(8): 1122–1134.
- Rhee, I. and Warrier, A. DRAND: Distributed Randomized TDMA Scheduling for Wireless Ad Hoc Networks. *IEEE Transactions on Mobile Computing*, 2009. 8(10): 1384–1396.

- 39. Hamida, E. B., Chelius, G., Gorce, J. M. and Ben Hamida, E. Impact of the Physical Layer Modeling on the Accuracy and Scalability of Wireless Network Simulation. *Simulation*, 2009. 85(9): 574–588.
- 40. Papanastasiou, S., Mittag, J., Strom, E. G. and Hartenstein, H. Bridging the Gap between Physical Layer Emulation and Network Simulation. *IEEE Wireless Communication and Networking Conference (WCNC)*. Sydney, Australia: IEEE. 2010, vol. 9. 1–6.
- 41. Hamida, E. B., Chelius, G. and Gorce, J.-M. Scalable versus Accurate Physical Layer Modeling in Wireless Network Simulations. *Proceedings* of the 22nd Conference on Principles of Advanced and Distributed Simulation (PADS '08). Washington, DC, USA: IEEE. 2008. 127–134.
- 42. Buettner, M., Yee, G. V., Anderson, E. and Han, R. X-MAC: A short preamble MAC protocol for duty-cycled wireless sensor networks. *Proceedings of the 4th international conference on Embedded networked* sensor systems (SenSys '06). Boulder, Colorado, USA: ACM Press. 2006, May. 307.
- 43. Ye, W., Silva, F. and Heidemann, J. Ultra-low duty cycle MAC with scheduled channel polling. *Proceedings of the 4th international conference* on Embedded networked sensor systems (SenSys '06). Boulder, Colorado, USA: ACM Press. 2006. 321.
- 44. Zhou, G., He, T., Krishnamurthy, S. and Stankovic, J. a. Models and solutions for radio irregularity in wireless sensor networks. ACM Transactions on Sensor Networks, 2006. 2(2): 221–262.
- 45. Zhao, J. and Govindan, R. Understanding packet delivery performance in dense wireless sensor networks. *Proceedings of the 1st International Conference on Embedded Networked Sensor Systems, SenSys '03.* Los Angeles, California, USA: ACM. 2003. 1–13.
- 46. Ganesan, D., Krishnamachari, B., Woo, A., Culler, D., Estrin, D. and Wicker, S. Complex behavior at scale: An experimental study of low-power wireless sensor networks. Technical Report 02-0013. UCLA Computer Science Division. 2002.
- 47. Muetze, T., Stuedi, P., Kuhn, F. and Alonso, G. Understanding Radio Irregularity in Wireless Networks. 5th Annual IEEE Communications Society Conference on Sensor, Mesh and Ad Hoc Communications and Networks, SECON '08. San Francisco, CA, USA: IEEE. 2008. 82–90.
- 48. Ababneh, N. Radio irregularity problem in wireless sensor networks:

New experimental results. *IEEE Sarnoff Symposium, SARNOFF '09.* Princeton, NJ, USA: IEEE. 2009. 1–5.

- Zamalloa, M. Z. and Krishnamachari, B. An analysis of unreliability and asymmetry in low-power wireless links. ACM Transactions on Sensor Networks, 2007. 3(2): 63–81.
- 50. Maheshwari, R., Cao, J. and Das, S. R. Physical Interference Modeling for Transmission Scheduling on Commodity WiFi Hardware. *The 28th Conference on Computer Communications, IEEE INFOCOM '09.* Rio de Janeiro, Brazil: Ieee. 2009. 2661–2665.
- Fu, L., Liew, S. C. and Huang, J. Effective Carrier Sensing in CSMA Networks under Cumulative Interference. *IEEE Transactions on Mobile Computing*, 2013. 12(4): 748–760.
- 52. Maheshwari, R., Jain, S. and Das, S. R. A measurement study of interference modeling and scheduling in low-power wireless networks. *Proceedings of the 6th ACM conference on Embedded network sensor* systems - SenSys '08. Raleigh, NC, USA: ACM Press. 2008. 141.
- 53. OMNeT++. The OMNeT++ Network Simulation Framework. http://www.omnetpp.org, 2014.
- Baccour, N., Koubâa, A., Mottola, L., Zúñiga, M. A., Youssef, H., Boano,
 C. A. and Alves, M. Radio link quality estimation in wireless sensor networks. ACM Transactions on Sensor Networks, 2012. 8(4): 1–33.
- 55. Keshavarzian, A., Uysal-Biyikoglu, E., Herrmann, F. and Manjeshwar,
 A. Energy-efficient link assessment in wireless sensor networks. *IEEE INFOCOM' 04.* IEEE. 2004, vol. 3. 1751–1761.
- 56. Meier, A., Weise, M., Beutel, J. and Thiele, L. NoSE: Efficient initialization of wireless sensor networks. *Proceedings of the 6th ACM* conference on Embedded network sensor systems (SenSys '08). Raleigh, NC, USA: ACM Press. 2008, 285. 397.
- 57. Baccour, N., Ben Jamaa, M., do Rosario, D., Koubaa, A., Youssef, H., Alves, M. and Becker, L. B. A testbed for the evaluation of link quality estimators in wireless sensor networks. ACS/IEEE International Conference on Computer Systems and Applications AICCSA 2010. Hammamet: IEEE. 2010, Section IV. 1–8.
- Wapf, A. and Souryal, M. R. Measuring Indoor Mobile Wireless Link Quality. *IEEE International Conference on Communications*, *ICC '09*. Ieee. 2009. 1–6.

- Boano, C. A., Zuniga, M. A., Voigt, T., Willig, A. and Romer, K. The Triangle Metric: Fast Link Quality Estimation for Mobile Wireless Sensor Networks. *Proceedings of 19th International Conference* on Computer Communications and Networks, ICCCN '10. Zurich, Switzerland: Ieee. 2010. 1–7.
- 60. McGlynn, M. J. and Borbash, S. A. Birthday protocols for low energy deployment and flexible neighbor discovery in ad hoc wireless networks. *Proceedings of the 2nd ACM international symposium on Mobile ad hoc networking & computing - MobiHoc '01.* Long Beach, CA, USA: ACM Press. 2001. 137.
- Warrier, A., Aia, M. and Sichitiu, M. Z-MAC: A Hybrid MAC for Wireless Sensor Networks. *IEEE/ACM Transactions on Networking*, 2008. 16(3): 511–524.
- Couto, D., Aguayo, D., Bicket, J. and Morris, R. A high-throughput path metric for multi-hop wireless routing. Wireless Networks, 2005. 11(4): 419–434.
- Mainwaring, A., Culler, D., Polastre, J., Szewczyk, R. and Anderson,
 J. Wireless sensor networks for habitat monitoring. Proceedings of the 1st ACM international workshop on Wireless sensor networks and applications - WSNA '02. Atlanta, Georgia, USA: ACM Press. 2002. 88.
- Gnawali, O., Fonseca, R., Jamieson, K., Moss, D. and Levis, P. Collection tree protocol. Proceedings of the 7th ACM Conference on Embedded Networked Sensor Systems (SenSys '09). Berkeley, California: ACM Press. 2009. 1.
- 65. Qiu, W., Skafidas, E. and Hao, P. Enhanced tree routing for wireless sensor networks. *Ad Hoc Networks*, 2009. 7(3): 638–650.
- Gnawali, O., Fonseca, R., Jamieson, K., Kazandjieva, M., Moss, D. and Levis, P. CTP: An efficient, robust, and reliable collection tree protocol for wireless sensor networks. *ACM Transactions on Sensor Networks*, 2013. 10(1): 1–49.
- Woo, A., Tong, T. and Culler, D. Taming the underlying challenges of reliable multihop routing in sensor networks. *Proceedings of the 1st international conference on Embedded networked sensor systems SenSys '03.* Los Angeles, California, USA: ACM Press. 2003. 14–27.
- TinyOS. The MultiHopLQI protocol. www.tinyos.net/tinyos-1.x/tos/lib/MultiHopLQI/, 2012.

- Rodrigo Fonseca, Omprakash Gnawali, Kyle Jamieson, Sukun Kim, Philip Levis, A. W. The Collection Tree Protocol (CTP). www.tinyos.net/tinyos-2.x/doc/html/tep123.html, 2007.
- Schoellhammer, T., Greenstein, B. and Estrin, D. Hyper: A routing protocol to support mobile users of sensor networks. Technical report. Los Angeles: Center for Embedded Network Sensing, UC Los Angeles. 2006.
- Song, W.-Z., Huang, R., Shirazi, B. and LaHusen, R. TreeMAC: Localized TDMA MAC protocol for real-time high-data-rate sensor networks. *Pervasive and Mobile Computing*, 2009. 5(6): 750–765.
- 72. Balon, N. and Guo, J. Increasing broadcast reliability in vehicular ad hoc networks. Proceedings of the 3rd international workshop on Vehicular ad hoc networks - VANET '06. Los Angeles, CA, USA: ACM Press. 2006. 104.
- 73. Bharghavan, V., Demers, A., Shenker, S. and Zhang, L. MACAW: a media access protocol for wireless LAN's. SIGCOMM Comput. Commun. Rev., 1994. 24(4): 212–225.
- 74. Kwon, Y., Fang, Y. and Latchman, H. A novel MAC protocol with fast collision resolution for wireless LANs. *The 22nd Annual Joint Conference* of the IEEE Computer and Communications Societies, INFOCOM'03. San Francisco, CA, USA: IEEE. 2003, C. 853–862.
- 75. IEEE Computer Society. IEEE 802.11: Wireless LANs. Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications, 2012.
- Yun, J.-H. and Seo, S.-W. Novel collision detection scheme and its applications for IEEE 802.11 wireless LANs. *Computer Communications*, 2007. 30(6): 1350–1366.
- Halkes, G. and Langendoen, K. Practical Considerations for Wireless Sensor Network Algorithms. Wireless Sensor Network, 2010. 02(06): 441–446.
- 78. Ye, W., Heidemann, J. and Estrin, D. Medium Access Control With Coordinated Adaptive Sleeping for Wireless Sensor Networks. *IEEE/ACM Transactions on Networking*, 2004. 12(3): 493–506.
- 79. Yang, X., Liu, J., Zhao, F. and Vaidya, N. H. A vehicle-to-vehicle communication protocol for cooperative collision warning. *The First Annual International Conference on Mobile and Ubiquitous Systems:*

- Jiang, D., Sengupta, R. and Chrysler, D. Design and analysis of highway safety communication protocol in 5.9 GHZ dedicated short range communication spectrum. *The 57th IEEE Semiannual Vehicular Technology Conference, VTC 2003-Spring.* IEEE. 2003, vol. 4. 2451– 2455.
- Chintalapudi, K., Fu, T., Paek, J., Kothari, N., Rangwala, S., Caffrey, J., Govindan, R., Johnson, E. and Masri, S. Monitoring civil structures with a wireless sensor network. *IEEE Internet Computing*, 2006. 10(2): 26–34.
- Yu, L., Wang, N. and Meng, X. Real-time forest fire detection with wireless sensor networks. *International Conference on Wireless Communications, Networking and Mobile Computing (IWCMC '05).* IEEE. 2005, vol. 2. 1214–1217.
- Szewczyk, R., Mainwaring, A., Polastre, J., Anderson, J. and Culler, D. An analysis of a large scale habitat monitoring application. *Proceedings* of the 2nd international conference on Embedded networked sensor systems - SenSys '04. Baltimore, MD, USA: ACM Press. 2004. 214.
- Guangmeng, G. and Mei, Z. Using MODIS Land Surface Temperature to Evaluate Forest Fire Risk of Northeast China. *IEEE Geoscience and Remote Sensing Letters*, 2004. 1(2): 98–100.
- 85. Ahn, G.-s., Hong, S. G., Miluzzo, E., Campbell, A. T. and Cuomo, F. Funneling-MAC: a localized, sink-oriented MAC for boosting fidelity in sensor networks. *Proceedings of the 4th international conference on Embedded networked sensor systems - SenSys '06.* Boulder, Colorado, USA: ACM Press. 2006. 293.
- 86. Ramanathan, S. A unified framework and algorithm for channel assignment in wireless networks. *Wireless Networks*, 1999. 5(2): 81–94.
- Gronkvist, J. Assignment methods for spatial reuse TDMA. 1st ACM international symposium on Mobile ad hoc networking & computing, ACM MobiHoc'00. Boston, Massachusetts, USA: IEEE. 2000, 1. 119– 124.
- Durmaz Incel, O., Ghosh, A., Krishnamachari, B. and Chintalapudi, K.
 Fast Data Collection in Tree-Based Wireless Sensor Networks. *IEEE Transactions on Mobile Computing*, 2012. 11(1): 86–99.
- 89. Gandham, S., Zhang, Y. and Huang, Q. Distributed time-optimal

scheduling for convergecast in wireless sensor networks. *Computer Networks*, 2008. 52(3): 610–629.

- 90. Choi, H., Wang, J. and Hughes, E. a. Scheduling for information gathering on sensor network. *Wireless Networks*, 2007. 15(1): 127–140.
- 91. Chae, S.-Y., Kang, K. and Cho, Y.-J. A scalable joint routing and scheduling scheme for large-scale wireless sensor networks. Ad Hoc Networks, 2013. 11(1): 427–441.
- 92. Li, Y., Guo, L. and Prasad, S. K. An Energy-Efficient Distributed Algorithm for Minimum-Latency Aggregation Scheduling in Wireless Sensor Networks. 30th International Conference on Distributed Computing Systems (ICDCS'10). Genova: IEEE. 2010. 827–836.
- 93. Tsai, H.-W. and Chen, T.-S. Minimal Time and Conflict-Free Schedule for Convergecast in Wireless Sensor Networks. *IEEE International Conference on Communications (ICC'08)*. Beijing, China: IEEE. 2008. 2808–2812.
- 94. Zhang, Y., Gandham, S. and Huang, Q. Distributed Minimal Time Convergecast Scheduling for Small or Sparse Data Sources. 28th IEEE International Real-Time Systems Symposium (RTSS '07). Washington, DC, USA: IEEE. 2007. 301–310.
- 95. Pan, M.-S. and Tseng, Y.-C. Quick convergecast in ZigBee beaconenabled tree-based wireless sensor networks. *Computer Communications*, 2008. 31(5): 999–1011.
- 96. CC2500. Single Chip Low Cost Low Power RF Transceiver. www.ti.com/product/cc2500, 2014.
- 97. CC2520. Second generation 2.4 GHz ZigBee/IEEE 802.15.4 RF transceiver, 2014.
- IEEE Computer Society. IEEE 802.15: Wireless Personal Area Networks (PANs). Part 15.6: Wireless Body Area Networks, 2012.
- 99. Mica2. Wireless Measurement System. www.xbow.com, 2014.
- 100. MicaZ. Wireless Measurement System. www.xbow.com, 2014.
- 101. TelosB. TelosB Mote Platform. www.xbow.com, 2014.
- 102. TR1000. 916.50 MHz Hybrid Transceiver. http://www.rfm.com/products/data/tr1000.pdf, 2014.

- 103. CC1120. High Performance RF Transceiver for Narrowband Systems. www.ti.com/product/cc1120, 2014.
- 104. IEEE Computer Society. IEEE 802.15: Wireless Personal Area Networks (PANs). Part 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANs), 2012.
- 105. Ganu, S., Ramachandran, K., Gruteser, M., Seskar, I. and Deng, J. Methods for restoring MAC layer fairness in IEEE 802.11 networks with physical layer capture. *Proceedings of the Second International Workshop* on Multi-Hop Ad Hoc Networks: From Theory to Reality - REALMAN '06. Florence, Italy: ACM Press. 2006. 7.
- 106. Chang, H., Misra, V. and Rubenstein, D. A General Model and Analysis of Physical Layer Capture in 802.11 Networks. *Proceedings of 25th IEEE International Conference on Computer Communications, (INFOCOMM* '06). Barcelona, Spain: IEEE. 2006. 1–12.
- 107. Rappaport, T. S. Wireless Communications: Principles and Practice (2nd Edition). Prentice Hall. 2002.
- 108. Zamalloa, M. and Krishnamachari, B. Analyzing the transitional region in low power wireless links. Proceeding fo the First Annual IEEE Communications Society Conference on Sensor and Ad Hoc Communications and Networks - SECON '04. IEEE. 2004. 517–526.
- Srinivasan, K., Dutta, P., Tavakoli, A. and Levis, P. An empirical study of low-power wireless. ACM Transactions on Sensor Networks, 2010. 6(2): 1–49.
- Karl, H. and Willig, A. Protocols and Architectures for Wireless Sensor Networks. Chichester, UK: John Wiley & Sons, Ltd. 2005.
- 111. NS-2. Network Simulator. http://www.isi.edu/nsnam/ns/, 2014.
- 112. Riley, G. The Georgia Tech network simulator. Proceedings of the ACM SIGCOMM workshop on Models, methods and tools for reproducible network research (MoMeTools '03). Karlsruhe, Germany. 2003, August. 5–12.
- 113. GTNetS. The Georgia Tech Network Simulator. www.ece.gatech.edu/research/labs/MANIACS/GTNetS, 2013.
- 114. Son, D. Towards interference-aware protocol design in low-power wireless networks. Ph.D. Thesis. University of Southern California. 2007.
- 115. Maheshwari, R., Jain, S. and Das, S. R. On estimating joint

interference for concurrent packet transmissions in low power wireless networks. Proceedings of the third ACM international workshop on Wireless network testbeds, experimental evaluation and characterization - WiNTECH '08. San Francisco, California, USA: ACM Press. 2008. 89.

- 116. Kochut, A., Vasan, A., Shankar, A. and Agrawala, A. Sniffing out the correct physical layer capture model in 802.11b. *Proceedings of the 12th IEEE International Conference on Network Protocols - ICNP '04.* IEEE. 2004. 252–261.
- 117. Chen, Q., Jiang, D., Taliwal, V. and Delgrossi, L. IEEE 802.11 based vehicular communication simulation design for NS-2. *Proceedings of the* 3rd international workshop on Vehicular ad hoc networks - VANET '06. Los Angeles, CA, USA: ACM Press. 2006. 50.
- 118. Schmidt-eisenlohr, F., Letamendia-murua, J., Torrent-moreno, M. and Hartenstein, H. Bug Fixes on the IEEE 802.11 DCF module of the Network Simulator ns-2.28. Technical report. Department of Computer Science, University of Karlsruhe. 2006.
- 119. GloMoSim. Global Mobile Information Systems Simulation Library. http://pcl.cs.ucla.edu/projects/glomosim/, 2014.
- 120. Castalia. A simulator for Wireless Sensor Networks. http://castalia.research.nicta.com.au/, 2011.
- 121. Köpke, A., Swigulski, M. and Wessel, K. Simulating wireless and mobile networks in OMNeT++ the MiXiM vision. Proceedings of the 1st international conference on Simulation tools and techniques for communications, networks and systems & workshops, Simutools '08. Brussels, Belgium. 2008. 71.
- 122. MiXiM, T. Simulating Wireless and Mobile Networks in OMNeT++. http://mixim.sourceforge.net/, 2014.
- 123. Levis, P., Lee, N., Welsh, M. and Culler, D. TOSSIM: accurate and scalable simulation of entire TinyOS applications. *Proceedings of* the 1st international conference on Embedded networked sensor systems (SenSys'03). Los Angeles, California, USA: ACM. 2003. 126–137.
- 124. TOSSIM. TinyOS Simulator. http://docs.tinyos.net/tinywiki/ index.php/ TOSSIM, 2014.
- 125. Davis, D. H. and Gronemeyer, S. A. Performance of Slotted ALOHA Random Access with Delay Capture and Randomized Time of Arrival. *IEEE Transactions on Communications*, 1980. 28(5): 703–710.

- 126. Arnbak, J. C. and Van Blitterswijk, W. Capacity of Slotted ALOHA in Rayleigh-Fading Channels. *IEEE Journal on Selected Areas in Communications*, 1987. 5(2): 261–269.
- Cheun, K. and Kim, S. Joint delay-power capture in spread-spectrum packet radio networks. *IEEE Transactions on Communications*, 1998. 46(4): 450–453.
- 128. Ware, C., Chicharo, J. and Wysocki, T. Simulation of capture behaviour in IEEE 802.11 radio modems. proceedings of the IEEE 54th Vehicular Technology Conference - VTC Fall '01. Atlantic City, NJ, USA: IEEE. 2001, vol. 3. 1393–1397.
- 129. Hadzi-Velkov, Z. and Spasenovski, B. On the capacity of IEEE 802.11 DCF with capture in multipath-faded channels. *International Journal of Wireless Information Networks*, 2002. 9(3): 191–199.
- Reijers, N., Halkes, G. and Langendoen, K. Link layer measurements in sensor networks. *IEEE International Conference on Mobile Ad-hoc and* Sensor Systems (MASS '04). IEEE. 2004. 224–234.
- 131. Kotz, D., Newport, C., Gray, R. S., Liu, J., Yuan, Y. and Elliott, C. Experimental evaluation of wireless simulation assumptions. *Proceedings of the 7th ACM international symposium on Modeling, analysis and simulation of wireless and mobile systems MSWiM '04.* Venice, Italy: ACM Press. 2004. 78–82.
- 132. Nikookar, H. and Hashemi, H. Statistical modeling of signal amplitude fading of indoor radio propagation channels. *Proceedings of 2nd IEEE International Conference on Universal Personal Communications*. Ottawa, Ont, Canada: IEEE. 1993, vol. 1. 84–88.
- 133. Chen, Y. and Terzis, A. On the implications of the log-normal path loss model. Proceedings of the 9th ACM Conference on Embedded Networked Sensor Systems - SenSys '11. Seattle, Washington, USA: ACM Press. 2011. 26.
- 134. Son, D., Krishnamachari, B. and Heidemann, J. Evaluating the Importance of Concurrent Packet Communication in Wireless Networks. Technical Report April. USC/ISI Technical Report ISI-TR-639. 2007.
- 135. Evans, D., Krasinski, R., Batra, A., Dawkins, M., Hosur, S. and Wang, D. IEEE P802.15 Wireless Personal Area Networks: Coexistence Assurance Document. Technical report. IEEE. 2012.
- 136. Shin, S. Y., Choi, S., Park, H. S. and Kwon, W. H. Packet Error

Rate Analysis of IEEE 802.15.4 Under IEEE 802.11b Interference. In: Wired/Wireless Internet Communications. Springer Berlin Heidelberg. 279–288. 2005.

- 137. IEEE Computer Society. IEEE 802.15: Wireless Personal Area Networks (PANs). Part 15.2: Coexistence of Wireless Personal Area Networks with Other Wireless Devices Operating in Unlicensed Frequency Band, 2003.
- 138. Zhou, G., He, T., Stankovic, J. A. and Abdelzaher, T. RID: radio interference detection in wireless sensor networks. *Proceedings IEEE 24th Annual Joint Conference of the IEEE Computer and Communications Societies, INFOCOM '05.* IEEE. 2005, vol. 2. 891–901.
- 139. Lee, P. W. Q., Seah, W. K. G., Tan, H.-P. and Yao, Z. Wireless sensing without sensors-An experimental study of motion/intrusion detection using RF irregularity. *Measurement Science and Technology*, 2010. 21(12): 124007.
- 140. Biaz, S. Realistic radio range irregularity model and its impact on localization for wireless sensor networks. Proceedings of International Conference on Wireless Communications, Networking and Mobile Computing. IEEE. 2005, vol. 2. 669–673.
- He, T., Huang, C., Blum, B. M., Stankovic, J. a. and Abdelzaher, T. Range-Free Localization Schemes for Large Scale Sensor Networks. *Proceedings of the 9th annual international conference on Mobile computing and networking - MobiCom '03.* San Diego, CA, USA: ACM Press. 2003. 81.
- 142. Cerpa, A., Wong, J. L., Potkonjak, M. and Estrin, D. Temporal properties of low power wireless links. *Proceedings of the 6th ACM* international symposium on Mobile ad hoc networking and computing -MobiHoc '05. Urbana-Champaign, IL, USA: ACM Press. 2005, January. 414.
- Downard, I. T. Simulating Sensor Networks in NS-2. Technical report. Information Technology Division, Naval Research Laboratory. 2004.
- 144. Fall, K. and Varadhan, K. *The NS Manual.* 3. UC Berkeley, LBL, USC/ISI, and Xerox PARC. 2011.
- 145. Gomez, C., Boix, A. and Paradells, J. Impact of LQI-Based Routing Metrics on the Performance of a One-to-One Routing Protocol for IEEE 802.15.4 Multihop Networks. *EURASIP Journal on Wireless Communications and Networking*, 2010. 2010(1): 205.

- 146. Seada, K., Zuniga, M., Helmy, A. and Krishnamachari, B. Energyefficient forwarding strategies for geographic routing in lossy wireless sensor networks. *Proceedings of the 2nd international conference on Embedded networked sensor systems - SenSys '04.* Baltimore, MD, USA: ACM Press. 2004. 108.
- 147. Upadhyayula, S. and Gupta, S. Spanning tree based algorithms for low latency and energy efficient data aggregation enhanced convergecast (DAC) in wireless sensor networks. Ad Hoc Networks, 2007. 5(5): 626– 648.
- 148. Souza, E. D. and Nikolaidis, I. An exploration of aggregation convergecast scheduling. *Ad Hoc Networks*, 2013.
- 149. Xu, X., Li, X. Y., Mao, X., Tang, S. and Wang, S. A Delay-Efficient Algorithm for Data Aggregation in Multihop Wireless Sensor Networks. *IEEE Transactions on Parallel and Distributed Systems*, 2011. 22(1): 163–175.
- Bianchi, G. Performance Analysis of the IEEE 802.11 Distributed Coordination Function. *IEEE Journal on Selected Areas in Communications*, 2000. 18(3): 535–547.
- 151. TinyOS 1.x. http://www.tinyos.net/tinyos-1.x/, 2013.
- 152. TinyOS 2.x. http://www.tinyos.net/tinyos-2.x/, 2013.
- Levis, P., Madden, S., Polastre, J., Szewczyk, R., Whitehouse, K., Woo, A., Gay, D., Hill, J., Welsh, M., Brewer, E. and Culler, D. Tinyos: An operating system for sensor networks. In: *Ambient intelligence*. Springer Verlag, vol. 35. 115–148. 2005.
- 154. Wang, Y., Vuran, M. C. and Goddard, S. Cross-Layer Analysis of the End-to-End Delay Distribution in Wireless Sensor Networks. *IEEE/ACM Transactions on Networking*, 2012. 20(1): 305–318.
- Polastre, J. R. A unifying link abstraction for wireless sensor networks.
 Ph.D. Thesis. University of California, Berkeley, San Diego, California, USA. 2005.
- 156. Borbash, S. A., Ephremides, A. and McGlynn, M. J. An asynchronous neighbor discovery algorithm for wireless sensor networks. Ad Hoc Networks, 2007. 5(7): 998–1016.
- 157. Kohvakka, M., Suhonen, J., Kuorilehto, M., Kaseva, V., Hännikäinen,M. and Hämäläinen, T. D. Energy-efficient neighbor discovery protocol

for mobile wireless sensor networks. Ad Hoc Networks, 2009. 7(1): 24–41.

- 158. Jamieson, K., Balakrishnan, H. and Tay, Y. C. Sift: A MAC Protocol for Event-Driven Wireless Sensor Networks. *Third European Workshop*, *EWSN '06*. Zurich, Switzerland, 2006. 260–275.
- Sharma, G., Ganesh, A. and Key, P. Performance Analysis of Contention Based Medium Access Control Protocols. *IEEE Transactions on Information Theory*, 2009. 55(3): 1665–1682.
- 160. Heidemann, J., Estrin, D. and Ye, W. An energy-efficient MAC protocol for wireless sensor networks. Twenty-First Annual Joint Conference of the IEEE Computer and Communications Societies. Proceedings. (INFOCOMM '02). New York, USA: IEEE. 2002, vol. 3. 1567–1576.
- 161. van Dam, T. and Langendoen, K. An adaptive energy-efficient MAC protocol for wireless sensor networks. Proceedings of the first international conference on Embedded networked sensor systems - SenSys '03. Los Angeles, California, USA: ACM Press. 2003. 171.
- Liu, S., Fan, K.-w. and Sinha, P. CMAC. ACM Transactions on Sensor Networks, 2009. 5(4): 1–34.
- 163. Woo, A. and Culler, D. E. A transmission control scheme for media access in sensor networks. Proceedings of the 7th annual international conference on Mobile computing and networking (MobiCom '01). Rome, Italy: ACM Press. 2001. 221–235.
- 164. Demirkol, I. and Ersoy, C. Energy and delay optimized contention for wireless sensor networks. *Computer Networks*, 2009. 53(12): 2106–2119.
- Wang, J. and Kravets, R. Distributed Optimal Contention Window Control for Elastic Traffic in Single-Cell Wireless LANs. *IEEE/ACM Transactions on Networking*, 2007. 15(6): 1373–1386.
- 166. Gong, H., Liu, M., Mao, Y., Chen, L.-j. and Xie, L. Traffic adaptive MAC protocol for wireless sensor network. *Networking and Mobile Computing*, 2005. 3619: 1134 – 1143.
- 167. Rajendran, V., Obraczka, K. and Garcia-Luna-Aceves, J. J. Energyefficient collision-free medium access control for wireless sensor networks. *Proceedings of the first international conference on Embedded networked sensor systems - SenSys '03.* Los Angeles, California, USA: ACM Press. 2003. 181.
- 168. Krishnamachari, B. and Raghavendra, C. An adaptive energy-efficient

and low-latency MAC for data gathering in wireless sensor networks. Proceedings of the 18th International Parallel and Distributed Processing Symposium (IPDPS'04). IEEE. 2004, C. 224–231.

- 169. Boano, C. A., Voigt, T., Tsiftes, N., Mottola, L., Kay, R. and Z, M. A. Making Sensornet MAC Protocols Robust Against Interference. *Proceedings of the 7th European conference on Wireless Sensor Networks*, *EWSN'10.* Coimbra, Portugal: Springer-Verlag. 2010. 272–288.
- 170. Hauer, J., Willig, A. and Wolisz, A. Mitigating the Effects of RF Interference through RSSI-Based Error Recovery. *Proceedings of the 7th European conference on Wireless Sensor Networks, EWSN'10.* Springer-Verlag Berlin, Heidelberg. 2010, February. 224–239.
- 171. Kumar, R., Paul, A., Ramachandran, U. and Kotz, D. On improving wireless broadcast reliability of sensor networks using erasure codes. *Second International Conference*, MSN 2006. Springer Berlin Heidelberg. 2006. 155–170.
- 172. Lou, W. and Wu, J. Toward Broadcast Reliability in Mobile Ad Hoc Networks with Double Coverage. *IEEE Transactions on Mobile Computing*, 2007. 6(2): 148–163.
- 173. Eugster, P. T., Guerraoui, R., Handurukande, S. B., Kouznetsov, P. and Kermarrec, A.-M. Lightweight probabilistic broadcast. ACM Transactions on Computer Systems, 2003. 21(4): 341–374.
- 174. Fonseca, R., Gnawali, O., Jamieson, K. and Levis, P. Four bit wireless link estimation. Proceedings of the Sixth Workshop on Hot Topics in Networks, HotNets '07. 2007.
- 175. Kim, K.-H. and Shin, K. G. On accurate measurement of link quality in multi-hop wireless mesh networks. *Proceedings of the 12th* annual international conference on Mobile computing and networking -MobiCom '06. Los Angeles, CA, USA: ACM Press. 2006. 38.
- 176. Lal, D., Manjeshwar, A., Herrmann, F., Uysal-Biyikoglu, E. and Keshavarzian, A. Measurement and characterization of link quality metrics in energy constrained wireless sensor networks. *Global Telecommunications Conference, GLOBECOM '03.* IEEE. 2003, vol. 1. 446–452.
- 177. Ergen, S. C. and Varaiya, P. TDMA scheduling algorithms for wireless sensor networks. *Wireless Networks*, 2009. 16(4): 985–997.
- 178. Bao, L. and Garcia-Luna-Aceves, J. J. A new approach to channel

access scheduling for Ad Hoc networks. Proceedings of the 7th annual international conference on Mobile computing and networking - (MobiCom '01). Rome, Italy: ACM Press. 2001. 210–221.

- 179. Tang, L., Sun, Y., Gurewitz, O. and Johnson, D. B. PW-MAC: An energy-efficient predictive-wakeup MAC protocol for wireless sensor networks. *Proceedings of the 30th IEEE International Conference on Computer Communications, INFOCOM'11.* IEEE. 2011. 1305–1313.
- 180. Rozovsky, R. and Kumar, P. R. SEEDEX: A MAC protocol for ad hoc networks. Proceedings of the 2nd ACM international symposium on Mobile ad hoc networking & computing - MobiHoc '01. Long Beach, CA, USA: ACM Press. 2001. 67.
- 181. Bao, L. and Garcia-Luna-Aceves, J. Channel access scheduling in ad hoc networks with unidirectional links. Proceedings of the 5th international workshop on Discrete algorithms and methods for mobile computing and communications - DIALM '01. ACM Press. 2001. 9–18.
- 182. van Hoesel, L., Nieberg, T., Kip, H. and Havinga, P. Advantages of a TDMA based, energy-efficient, self-organizing MAC protocol for WSNs. *IEEE 59th Vehicular Technology Conference. VTC 2004-Spring.* IEEE. 2004, vol. 3. 1598–1602.
- 183. van Hoesel, L. and Havinga, P. A lightweight medium access protocol (LMAC) for wireless sensor networks. 1st International Workshop on Networked Sensing Systems, INSS '04. Tokyo, Japan. 2004. 205–208.
- 184. Nieberg, T., Dulman, S., Havinga, P., van Hoesel, L. and Wu, J. Collaborative algorithms for communication in wireless sensor networks. In: Ambient Intelligence: Impact on Embedded Systems. Springer US. 1–24. 2003.
- 185. Hohlt, B., Doherty, L. and Brewer, E. Flexible power scheduling for sensor networks. *Proceedings of the third international symposium* on Information processing in sensor networks - IPSN'04. Berkeley, California, USA: ACM Press. 2004. 205.
- 186. Chafekar, D., Kumar, V. S. a., Marathe, M. V., Parthasarathy, S. and Srinivasan, A. Approximation Algorithms for Computing Capacity of Wireless Networks with SINR Constraints. *The 27th Conference on Computer Communications*, (INFOCOM'08), 2008: 1166–1174.
- 187. Zhu;, C. and Corson, M. A five-phase reservation protocol (FPRP) for mobile ad hoc networks. *Wirless Networks*, 2001. 7(4): 371–384.

- 188. Rajendran, V., Garcia-Luna-Aceves, J. and Obraczka, K. Energyefficient, application-aware medium access for sensor networks. *IEEE International Conference on Mobile Adhoc and Sensor Systems Conference (MASS'05)*. Washington, DC, USA: IEEE. 2005. 623–630.
- 189. Barroso, A., Roedig, U. and Sreenan, C. μ-MAC: an energy-efficient medium access control for wireless sensor networks. Proceedings of the Second European Workshop on Wireless Sensor Networks, (EWSN 2005). IEEE. 2005. 70–80.
- Lu, G. and Krishnamachari, B. Minimum latency joint scheduling and routing in wireless sensor networks. Ad Hoc Networks, 2007. 5(6): 832– 843.
- 191. Maróti, M., Kusy, B., Simon, G. and Lédeczi, A. The flooding time synchronization protocol. *Proceedings of the 2nd international conference* on Embedded networked sensor systems - SenSys '04. Baltimore, MD, USA: ACM Press. 2004. 39.
- Hu, C. and Hou, J. C. A reactive channel model for expediting wireless network simulation. SIGMETRICS Perform. Eval. Rev., 2005. 33(1): 410.
- 193. Ji, Z., Zhou, J., Takai, M. and Bagrodia, R. Scalable simulation of largescale wireless networks with bounded inaccuracies. Proceedings of the 7th ACM international symposium on Modeling, analysis and simulation of wireless and mobile systems - MSWiM '04. Venice, Italy: ACM Press. 2004. 62.