

FACTORS AFFECTING THE PERFORMANCE OF AD HOC  
ON-DEMAND DISTANCE VECTOR PROTOCOL IN SIMULATED  
MOBILE AD HOC NETWORK SCENARIOS USING TAGUCHI  
APPROACH

TAN JUN BIN

UNIVERSITI TEKNOLOGI MALAYSIA

FACTORS AFFECTING THE PERFORMANCE OF AD HOC  
ON-DEMAND DISTANCE VECTOR PROTOCOL IN SIMULATED MOBILE AD  
HOC NETWORK SCENARIOS USING TAGUCHI APPROACH

TAN JUN BIN

A dissertation submitted in partial fulfilment of the  
requirements for the award of the degree of  
Master of Science (Mathematics)

Faculty of Science  
Universiti Teknologi Malaysia

JANUARY 2014

*To my beloved grandmother, Foo Jit Lan,  
my mother, Choy Pow Ching,  
my father, Tan Guan Kam,  
and my brother, Tan Jun Hua.*

## **ACKNOWLEDGEMENT**

First and foremost, I like to give my deepest gratitude to my supervisor, PM Dr. Robiah Adnan for her consistent encouragement, constructive teachings, valuable comments, and help to make me work independently throughout the length of this study. This thesis would not be done on time without her guidance and support.

A special thanks to Ms Lee Mee Yung as well for her continuous encouragements, understanding and being a good listener. I would like to express my sincere thanks to my beloved parents for their support on further study.

Last but not least, thanks are also due to my friends who supported me throughout the whole years of study together. Finally, I would like to extend my sincere appreciation to all who has helped me in one way or another, but whose name are not mentioned.

## ABSTRACT

The performance of ad hoc on demand vector (AODV) protocol is affected hugely by some common major factors. These factors are terrain, network size, node velocity, pause time, transmission range, traffic load, and packet rates. The main purpose of this study is to analyse the effects of those factors and some selected two-way interactions on the performance measure of drop rates and average end-to-end delay. Taguchi approach was used in this study. Initially,  $L_{16}$  orthogonal array was used to determine the effects of the seven main factors and eight others two-way interactions between selected factors. The final results revealed that terrain, network size, transmission range, and traffic load have significant effects on drop rates. On the other hand, we discovered that terrain, transmission range, traffic load and interaction between node velocity and pause time have significant effects on average end-to-end. Interaction plot for  $L_{16}$  singled out strong interaction between node velocity and pause time for the effect on average end-to-end delay. Furthermore,  $L_8$  orthogonal array was applied to analyse the seven main factors only since most of the interactions effects from  $L_{16}$  were largely insignificant to the response. The most influential factors affecting the drop rates (in descending order) were terrain, transmission range, pause time, network size, packet rates, node velocity, and traffic load. For average end-to-end delay, the most influential factors (in descending order) were transmission range, pause time, terrain, network size, traffic load, packet rates, and node velocity. ANOVA results for  $L_8$  shows that terrain and transmission range have significant effects on drop rates. For average end-to-end delay, terrain, pause time and transmission range have significant effects on the response.

## ABSTRAK

Prestasi protocol *ad hoc on demand vector* (AODV) dipengaruhi oleh pelbagai factor. Faktor-faktor tersebut adalah luas kawasan rangkaian (LKR), saiz rangkaian, masa berhenti seketika (MBS), halaju nod, had jarak penghantaran (HJP), muatan trafik, dan kadar penghantaran data (KPD). Tujuan utama kajian ini adalah untuk menganalisis kesan factor-faktor tersebut dan beberapa interaksi dua hala terpilih terhadap dua metrik prestasi iaitu kadar penurunan dan purata kelewatan data dari nod ke nod (PKNN). Kaedah Taguchi telah digunakan dalam kajian ini. Pada awal eksperimen, tatasusunan ortogon  $L_{16}$  digunakan untuk menentukan kesan daripada tujuh faktor utama dan lapan interaksi dua hala antara faktor yang dipilih. Keputusan mendedahkan bahawa LKR, saiz rangkaian, HJP dan muatan trafik mempunyai kesan yang signifikan terhadap kadar penurunan. Bagi PKNN pula, kami dapati LKR, HJP, muatan trafik dan interaksi antara halaju nod dan MBS mempunyai kesan yang signifikan terhadap respon. Interaksi plot untuk  $L_{16}$  mendapati interaksi antara halaju nod dan MBS mempunyai kesan yang kuat terhadap PKNN. Berikutan dari  $L_{16}$ , tatasusunan ortogon  $L_8$  digunakan untuk menganalisis tujuh faktor utama sahaja sebab kebanyakan interaksi tidak mempunyai kesan yang signifikan terhadap respon. Keputusan mendapati bahawa faktor-faktor yang paling berpengaruh terhadap kadar penurunan adalah LKR, diikuti oleh HJP, MBS, saiz rangkaian, KPD, halaju nod, dan muatan trafik. Untuk PKNN pula, faktor yang paling berpengaruh adalah HJP dan diikuti oleh MBS, LKR, saiz rangkaian, muatan trafik, KPD, dan halaju nod. Keputusan dari ANOVA untuk  $L_8$  menunjukkan bahawa LKR dan HJP mempunyai kesan yang signifikan terhadap kadar penurunan. Untuk PKNN pula, faktor yang signifikan terhadap respon adalah LKR, MBS dan HJP.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENTS</b>	iv
	<b>ABSTRAK</b>	v
	<b>ABSTRACT</b>	vi
	<b>TABLE OF CONTENTS</b>	vii
	<b>LIST OF TABLES</b>	x
	<b>LIST OF FIGURES</b>	xii
	<b>LIST OF SYMBOLS</b>	xiii
	<b>LIST OF ABBREVIATIONS</b>	xv
	<b>LIST OF APPENDICES</b>	xvi
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Background of the Study	1
	1.2 Problem Statement	2
	1.3 Research Objectives	3
	1.4 Limitations of Study	3
	1.5 Scope of the Study	4
	1.6 Significance of the Study	4
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>5</b>
	2.1 Introduction	5
	2.2 Mobile Ad Hoc Network	5
	2.2.1 Characteristics	6
	2.2.2 Applications	7

2.2.3	Issues	8
2.3	Routing	8
2.3.1	Proactive Approach	10
2.3.2	Reactive Approach	10
2.3.3	Hybrid Approach	11
2.4	Ad hoc On-demand Distance Vector Protocol	11
2.4.1	Limitations of AODV	15
2.5	Comparisons between Protocols	16
2.6	Summary	19
<b>3</b>	<b>RESEARCH METHODOLOGY</b>	<b>20</b>
3.1	Introduction	20
3.2	Taguchi Method	20
3.2.1	Fractional Factorial Design	21
3.2.2	Orthogonal Arrays	22
3.2.3	Selection of Orthogonal Array	24
3.2.4	Triangular Table of Interactions	25
3.3	Randomization and Repetition	27
3.4	Signal-to-Noise Ratio	28
3.5	Conversion of S/N Value	30
3.6	Analysis of Average Effects	31
3.7	Analysis of Variance (ANOVA)	32
3.8	Description of the Simulator	33
3.9	Performance Metrics	35
3.10	Experiment Factors	36
3.10.1	Terrain	37
3.10.2	Network Size	37
3.10.3	Node Velocity	38
3.10.4	Pause Time	38
3.10.5	Transmission Range	38
3.10.6	Traffic Load and Packet Rates	40
3.11	Summary	40



<b>4</b>	<b>RESULTS AND DISCUSSIONS</b>	41
4.1	Introduction	41
4.2	L <sub>16</sub> Orthogonal Array	41
4.2.1	Selecting L <sub>16</sub> Array	42
4.2.2	Experimental Data	43
4.2.3	Analysis of Average Effects	47
4.2.4	Interactions Effects	54
4.2.5	ANOVA of Taguchi L <sub>16</sub>	66
4.3	L <sub>8</sub> Orthogonal Array	71
4.3.1	Selecting L <sub>8</sub> Array	71
4.3.2	Experimental Data	72
4.3.3	Analysis of Average Effects	74
4.3.4	Response Graph	77
4.3.5	ANOVA of Taguchi L <sub>8</sub>	78
4.4	Predicted Results with Best Combination	84
4.5	Summary	86
<b>5</b>	<b>CONCLUSION AND RECOMMENDATION</b>	88
5.1	Conclusion	88
5.1.1	Results of L <sub>16</sub> Orthogonal Array	88
5.1.2	Results of L <sub>8</sub> Orthogonal Array	90
5.2	Recommendations	91
	<b>REFERENCES</b>	92
	<b>APPENDIX A</b>	99

## LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Numerical comparison of the three routing protocols	17
3.1	Examples of standard orthogonal arrays	23
3.2	The $L_8$ orthogonal array	23
3.3	Triangular table for two-level factor interactions	26
3.4	$L_4$ orthogonal array with randomized order with repetition	28
3.5	Selected factors and levels	36
4.1	The $L_{16}$ after assigning factors and interactions	43
4.2	Description of experiment 5 using $L_{16}$ array	44
4.3	The raw data of drop rates	45
4.4	The raw data of average end-to-end delay	46
4.5	S/N for experimental data	47
4.6	Main effects and interaction effects for drop rates	51
4.7	Main effects and interaction effects for average end-to-end delay	53
4.8	The $L_{16}$ ANOVA for drop rates	66
4.9	The $L_{16}$ ANOVA for average end-to-end delay	67
4.10	The $L_{16}$ pooled ANOVA for drop rates	69
4.11	The $L_{16}$ ANOVA pooled for average end-to-end delay	70
4.12	The $L_8$ array after assigned factors	72
4.13	The raw data of drop rates	73
4.14	The raw data of average end-to-end delay	73
4.15	S/N for experimental data	74
4.16	$L_8$ response table for drop rates	76
4.17	$L_8$ response table for average end-to-end delay	76
4.18	The $L_8$ ANOVA for drop rates	81
4.19	The $L_8$ ANOVA for average end-to-end delay	81

4.20	The $L_8$ pooled ANOVA for drop rates	83
4.21	The $L_8$ pooled ANOVA for average end-to-end delay	83
4.22	Factors contribution for drop rates	85
4.23	Factors contribution for average end-to-end delay	86

## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Illustration of an ad hoc network	6
2.2	Route finding process in AODV routing protocol	14
3.1	Linear graph for $L_4$ array	27
3.2	Linear graphs for $L_8$ array	27
3.3	Simulator Overview	34
3.4	Illustration for nodes transmission range	39
4.1	The $L_{16}$ main effect response graph for drop rates	51
4.2	The $L_{16}$ main effect response for average end-to-end delay	53
4.3	Interaction plot for drop rates ( $A \times C$ )	54
4.4	Interaction plot for average end-to-end delay ( $A \times C$ )	55
4.5	Interaction plot for drop rates ( $A \times D$ )	56
4.6	Interaction plot for average end-to-end delay ( $A \times D$ )	56
4.7	Interaction plot for drop rates ( $B \times C$ )	57
4.8	Interaction plot for average end-to-end delay ( $B \times C$ )	58
4.9	Interaction plot for drop rates ( $C \times D$ )	59
4.10	Interaction plot for average end-to-end delay ( $C \times D$ )	59
4.11	Interaction plot for drop rates ( $C \times F$ )	60
4.12	Interaction plot for average end-to-end delay ( $C \times F$ )	60
4.13	Interaction plot for drop rates ( $D \times E$ )	61
4.14	Interaction plot for average end-to-end delay ( $D \times E$ )	62
4.15	Interaction plot for drop rates ( $A \times B$ )	63
4.16	Interaction plot for average end-to-end delay ( $A \times B$ )	63
4.17	Interaction plot for drop rates ( $C \times E$ )	64
4.18	Interaction plot for average end-to-end delay ( $C \times E$ )	64
4.19	$L_8$ response graph for drop rates	77
4.20	$L_8$ response graph for average end-to-end delay	78

## LIST OF SYMBOLS

$Df$	- Degrees of freedom
$Df_{TOA}$	- Total degrees of freedom for an orthogonal array
$Df_r$	- Total degrees of freedom for factors and interactions
$Df_A$	- Degrees of freedom for factor $A$
$k_A$	- Number of factor levels for factor $A$
$Df_{(A \times B)}$	- Degrees of freedom for interaction between factor $A$ and $B$
$S/N$	- Signal to Noise ratio
$y_n$	- Response value for $n$ th experiment
$s^2$	- Variance
$\bar{y}$	- Mean
$y_0$	- Target value
$S/N_S$	- Signal to noise ratio for smaller the better
$S/N_L$	- Signal to noise ratio for larger the better
$S/N_T$	- Signal to noise ratio for nominal the best
$N$	- Number of experiments
$\bar{X}_a$	- Average total response for factor $X$ at level $a$
$X_{effect}$	- Average effect for factor $X$
$f$	- Unique flow id serving as an index
$P$	- Fraction of successfully delivered packets
$R_f$	- Count of packets received from flow $f$
$N_f$	- Count of packets transmitted to $f$
$N_p$	- Number of successfully received packets
$i$	- Unique packet identifier
$r_i$	- Time which a packet with unique id $i$ is received
$s_i$	- Time which a packet with unique id $i$ is sent
$d$	- Distance between two nodes
$r$	- Radius transmission range

$F$	-	Fisher ratio
$Sig$	-	Significance value
$F - ratio$	-	Fisher ratio
$CF$	-	Correlation factor
$SS_T$	-	Total sum of squares
$SS_X$	-	Sum of square for factor $X$
$SS_e$	-	Sum of square for error
$V_X$	-	Variance for factor $X$
$V_e$	-	Variance for error
$SS'_X$	-	Pure sum of square for factor $X$
$P_X$	-	Percentage of total variation for factor $X$
$P_e$	-	Percentage of total variation for error
$y_{predicted}$	-	Predicted response value

## LIST OF ABBREVIATIONS

LAN	-	Local Area Network
MANET	-	Mobile Ad Hoc Network
ISP	-	Internet Service Provider
DSDV	-	Destination Sequenced Distance Vector
AODV	-	Ad hoc On-demand Distance Vector
DSR	-	Dynamic Source Routing
TORA	-	Temporary Ordered Routing Algorithms
PDF	-	Packet Delivery Fraction
PAN	-	Personal Area Networking
RREQ	-	Route Request
RREP	-	Route Reply
FUFD	-	Full Factorial Design
FRFD	-	Fractional Factorial Design
MSD	-	Mean Square Deviation
STB	-	Smaller the better
LTB	-	Larger the better
NTB	-	Nominal the best
$MSD_{STB}$	-	Mean square deviation for smaller the better
$MSD_{LTB}$	-	Mean square deviation for larger the better
$MSD_{NTB}$	-	Mean square deviation for nominal the best
ANOVA	-	Analysis of variance
NS2	-	Network Simulator 2
OTcl	-	Object Tool Command Language
NAM	-	Network Animator
$NPD$	-	Number of packets dropped

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	An example of a simulation generated by NAM	99



## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Background of the Study**

Communication is defined by the exchange of information between two or more mediums. In terms of computing, communication is data transfer between computing devices using a conductor for the linkage in between. Since the first wireless communication device invented by Bell and Tainter in the year 1880, wireless communication between mobile users has become more popular over the years up until now. This is due to the contribution of current technological advancements which have made wireless communication possible on every laptop, mobile phones and even some non-computing devices. These devices usually utilize wireless modem or wireless LAN (Local Area Network) as backbone support.

In next generation of wireless communication, there will be a need for a survivable, efficient, dynamic communication for emergency situations, and even disaster relief efforts. Such network is conceived as applications of Mobile ad hoc networks (MANET) where in Latin, ad hoc means “for this purpose only”. MANET is a wireless network that transmits from nodes to nodes and these nodes are referring to mobile platforms such as mobile phones with built-in wireless connector and laptop, the network is going on without the use of infrastructure such as the cables and the base station. MANET is able to operate on a rough terrain or a spontaneous setup as long as there are nodes present in the range. However, in order to gain access to the internet, one of the nodes must be connected via cable or wireless to an internet service provider (ISP).

MANET is a collection of wireless mobile nodes forming a temporary network. The nodes in a wireless network can move around constantly. Therefore the network topology can change dynamically and unpredictably. For this reason, some protocols must be employed in the system so that any changes in routing will be reflected on the routing algorithm and thus topology can be restructured to repair or update routes.

There had been many studies carried out to design, compare or to improve the MANET protocol algorithm, for example like Destination Sequenced Distance Vector (DSDV), Ad hoc On-demand Distance Vector (AODV), Dynamic Source Routing (DSR), and Temporary Ordered Routing Algorithms (TORA) [1][2]. However in this dissertation, our aims are to determine and analyse the effects of several factors on the performance of AODV protocol. AODV protocol is chosen because it is one of the reactive protocols that generally use high mobility nodes. Prior to this study, Sarahintu [32] has analysed the DSR protocol.

## **1.2 Problem Statement**

Many researchers have analysed on the performance of certain protocols as well as comparing among the protocols [2] [3]. From past studies, some protocols are found to excel over other protocols in certain scenarios. Therefore, before selecting which protocol to be employed, it has to be tested for its stability and reliability over a certain network configuration and scenario. For AODV protocol, its performance can be analysed by a set of performance metrics such as the packet delivery fraction (PDF) or drop rates, routing overhead and average end-to-end delay [1] [4].

Besides that, there are also some factors that need to be examined such as the terrain, network size, node velocity, transmission range, pause time, and packet rates [5]. These factors are some of the important elements that should be considered in designing specific scenarios in order to examine AODV performance.

The main problem in this study is to determine the effect of each factor mentioned above on the performance of AODV. Hence, we utilize Taguchi's method to examine the effect of factors as well as interactions between some factors correspond to drop rates and average end-to-end delay. This study is able to identify the influential factors that contribute to the performance of AODV protocol. Furthermore, Taguchi approach is also able to rank those factors according to their difference coefficients. In addition of above statement, this study also helped in determining if each factor has significant effect on the performance metrics.

### **1.3 Research Objectives**

The objectives of this research are outlined as follows:

- a. To analyse different parameter settings on AODV performance using Taguchi approach.
- b. To rank the factors that affect AODC performance.
- c. To determine the interaction effects of some factors on AODV performance.
- d. To determine the factors that significantly affect AODV performance.
- e. To predict the performance of AODV based on the obtained optimum settings.

### **1.4 Limitations of Study**

This study was limited on the analysis of factors with two factor levels and the types of analysis only include the  $L_{16}$  orthogonal array which limited to selections of fifteen factors and  $L_8$  orthogonal array which focused on selections of seven factors.

## **1.5 Scope of the Study**

This research focused on the analysis of AODV protocol performance in MANET using the simulation program instead of using real experiments. The simulation setting was based on a group of mobile nodes forming an ad hoc network within a compound relative to a conference hall with sparse distribution and small workload [6]. In terms of nodes mobility, it was assumed that the nodes are moving according to mean speed of walking pedestrian in a commercial area [8][9] and each mobile node had a transmission range limited within 20 meters [10][11].

## **1.6 Significance of the Study**

Results of this study will be helpful for those routing engineers in structuring a new reactive protocol or improving the existing formulation of AODV protocol. By acquiring the knowledge on the significance factors, the engineers will know which parameter should be given higher priority compared to the others and the priority could be ranked accordingly for all the predominance factors. This would help minimizing their workloads and significantly help in time saving.

## REFERENCES

1. Bobade, N. P., and Mhala, N. N. Performance Evaluation of AODV and DSR On-demand Routing Protocol with Varying MANET Size. *International Journal of Wireless & Mobile Networks (IJWMN)* Vol. 4, No. 1, February 2012.
2. Gupta A. K., Sadawarti H., Verma A. K., et al. Performance analysis of AODV, DSR & TORA Routing Protocols. *International Journal of Engineering and Technology*, Vol. 2, No. 2, April 2010.
3. Ali S., and Ali A. *Performance Analysis of AODV, DSR and OLSR in MANET*. Department of Electrical Engineering with emphasis on Telecommunication Blekinge Institute of Technology, Sweden 2009.
4. Gupta S. K., and Saket R. K. Performance Metric Comparison of AODV and DSDV Routing Protocols in MANETs using NS-2. *International Journal of Research and Reviews in Applied Sciences*, Vol. 7, No. 3, June 2011.
5. Biradar S. R. et al. Performance Evaluation and Comparison of AODV and AOMDV. *International Journal on Computer Science and Engineering*, Vol. 2, No. 2, 2010, 373-377.
6. Sarahintu M., and Lee M. H. Performance Evaluation on Mobile Ad Hoc Networks with Dynamics Source Routing Protocol. *Prosiding Simposium Kebangsaan Sains Matematik Ke-14*. June 2006, 517-523.
7. Johnson D. B., and Maltz D. A. *Dynamic Source Routing in Ad Hoc Wireless Networks*. In: Imelinski, T and Korth, H. ed. *Mobile Computing* Norwell, Mass.: Kluwer Academic Publisher. 151-181; 1998.

8. Lam, Willian H. K. and Cheung Chung-yu. *Pedestrian speed/flow relationships for walking facilities in Hong Kong*. Transportation Engineering, 2000. 126(4): 343-349.
9. Young S. B. *Evaluation of pedestrian walking speeds in airport terminals*. Transportation Research Record, 1999. 1674, 20-26.
10. Perkins C. *Ad Hoc Networking*. Upper Saddle River, N. J.: Addison-Wesley, 2001.
11. Deng, Han Y. S., Po-Ning Chen, and Varshney P. K. Optimum Transmission Range for Wireless Ad Hoc Networks. *Proceedings of Wireless Communication and Networking (WCNC04)*. March 21-25, 2004. Atlanta, Georgia: IEEE. 2004. 2, 1024-1029.
12. Cordeiro C. M., and Agrawal D. P. *Mobile Ad Hoc Networking*. OBR Research Centre for Distributed and Mobile Computing, ECECS University of Cincinnati, Cincinnati, USA.
13. Kumar M. and Mishra R. An Overview of MANET: History, Challenges and Applications. *Indian Journal of Computer Science and Engineering (IJCSE)*, 2012.
14. Goyal P., Parmar V., and Rishi R. MANET: Vulnerabilities, Challenges, Attacks, Application. *IJCEM International Journal of Computational Engineering & Management*, Vol. 11, January 2011.
15. Taneja K. and Patel R. B. Mobile Ad hoc Networks: Challenges and Future. *Proceedings of National Conference on Challenges & Opportunities in Information Technology (COIT-2007)*, March 23, 2007.
16. Ross R. J. *Taguchi Techniques for Quality Engineering*. 2<sup>nd</sup> ed. New York: McGraw-Hill, Inc. 1996.
17. Rama R. S. and Padmanabhan. G. Application of Taguchi methods and ANOVA in optimization of Process Parameters for Metal Removal Rate in Electrochemical Machining of Al/5%SiC Composites, *International*

*Journal of Engineering Research and Application (IJERA)*, Vol. 2, Issue 3, May-Jun 2012, pp. 192-197.

18. Roy R. K. *Design of Experiment Using the Taguchi Approach: 16 step to product and process improvement*. Toronto, Canada: John Wiley & Sons, Inc. 2001
19. Dehnad K. *Quality Control, robust design, and the Taguchi method*. Pacific Grove, California: Wadsworth & Brooks/Cole Advanced Books & Software, 1989.
20. Bagchi T. P. *Taguchi Methods Explained Practical Steps to Robust Design*. New Delhi: Prentice Hall of India, 1993.
21. Peace G. S. *Taguchi Methods: a Hands-on Approach*. Reading, Mass.: Addison-Wesley Publishing Company, 1993.
22. Roy R. K. *A primer on the Taguchi Method*. New York: Van Nostrand Reinhold, 1990.
23. Taguchi, G. *System of Experimental Design: Engineering Methods to Optimize Quality and Minimize Costs*, UNIPUB/Kraus International Publications, 1987.
24. Kacker, R. N. and Tsui, K. L. Interaction graphs: graphical aids for the planning experiments, *J. Qual. Technol.* 22(1), 1-4, 1990.
25. Krishnaiah, K., and Shahabudeen, P. *Applied Design of Experiments and Taguchi Methods*. New Delhi: Asoke K. Ghosh, PHI Learning Private Limited, 2012.
26. Hunter, J. S. Statistical Design Applied to Product Design, *Journal of Quality Technology*, 17(4). Pp. 210-221, 1985.
27. Ryan, N. E. *Taguchi Methods and QFD: Hows and Whys for Management*, ASI Press, Michigan, 1988.
28. Issariyakul, T., Hossain, E. *Introduction to Network Simulator NS2*, Springer Science+Business Media, 2009.

29. Wech, B. B. *Practical Programming in Tcl and Tk*. 2<sup>nd</sup> ed. Upper Saddle River, NJ: Prentice Hall. 1997.
30. Network Simulator 2, at <http://www.isi.edu/nsnam/ns/>, Accessed on 4-5-13.
31. Sarahintu, M., Lee, M. H., and Mohamed, H. *The optimization of network parameters of dynamic source routing protocol for ad hoc network using Taguchi method*. Technical Report, 2007. Lt/M Bil.01/2007.
32. Sarahintu, M. *Factors affecting the performance of dynamic source routing protocol in mobile ad hoc networks using Taguchi approach*. Master thesis, Universiti Teknologi Malaysia, Faculty of Science, 2008.
33. Ankenman, B. *Design of Experiments with Two-level and Four-level Factors*, Department of Industrial Engineering and Management Sciences Northwestern University, Evanston, IL 60208, 1999.
34. Box, G. E. P., Hunter, W. G., and Hunter, J. S. *Statistics for Experimenters*. John Wiley, New York, NY. 1978
35. Totaro, M. W. and Perkins, D. D. Using statistical design of experiments for analysing mobile ad hoc networks. *Proceedings of 8<sup>th</sup> ACM international symposium on Modelling, analysis and simulation of wireless and mobile systems*. October 10-13, 2005. Montreal, Quebec: ACM. 2005. 156-168.
36. Maltz, D. A, Broch, J., Jetcheva, J., and Johnson, D. B. The Effects of On-Demand Behaviour in Routing Protocols for Multi-hop Wireless Ad Hoc Networks. *IEEE Journal on Selected Areas of Communications*, 1999. 17(8): 1439-1453.
37. Broch, J., Maltz, D. A., Johnson, D. B., Hu, Y. C., and Jetcheva, J. A Performance Comparison of Multi-Hop Wireless Ad Hoc Network Routing Protocols. *Proceedings of the 4<sup>th</sup> Annual ACM/IEEE International Conference on Mobile Computing and Networking*. October 1998. Dallas, TX: ACM/IEEE. 1998. 85-97.
38. Rastogi, R., Thaniasaru, I., and Chandra, S. Design Implications of Walking Speed for Pedestrian Facilities. *J. Transp. Eng.*, 137(10), 687-696. 2011.



39. Das, S. R., Perkins, C. E., and Royer, E. M. Performance comparison of two On-Demand Routing Protocols for Ad Hoc Networks. *Proceedings of the IEEE Conference on Computer Communications (INFOCOM)*. March 2000. Tel Aviv, Israel: IEEE. 2000. 3-12.
40. Kawatra, N. and Kumar, V. Effect of Pause Time and Nodes Mobility Speed on AODV and DSR in MANET. *International Journal of Scientific and Engineering Research*, Vol. 3, Issue 10, October 2012.
41. Jacobson, A. *Metrics in Ad Hoc Networks*. Master Thesis. Lulea University of Technology Sweden; 2000.
42. Naserian, M., Tepe, K. E., Tarique, M. Routing overhead analysis for reactive routing protocols in wireless ad hoc networks. *Wireless and Mobile Computing, Networking and Communications, 2005. (WiMob'2005), IEEE International Conference*. August 22-24, 2005. Montreal, Canada: IEEE. 2005. 3, 87-92.
43. Pucha, H., Das, S. M., and Hu, Y-C. The performance impact of traffic patterns on routing protocols in mobile ad hoc networks. *Proceedings of the 7<sup>th</sup> ACM international symposium on Modelling, Analysis and Simulation of Wireless and Mobile systems*. October 04-06, 2004. Venice, Italy: ACM. 2004. 211-219.
44. Gorantala, K. *Routing Protocols in Mobile Ad-hoc Networks*, Master's Thesis in Computing Science, Umea University, June 15, 2006.
45. Cisco. Cisco Internetworking. *Cisco Press*, 2002.
46. Royer, E. M. and Toh, C-K. A review of current routing protocols for ad hoc mobile wireless networks. *IEEE Personal Communications*, 1999, 7(4): 45-46.
47. Gupta, M. and Kaushik, S. Performance Comparison Study of AODV, OLSR and TORA Routing Protocols for MANETS. *International Journal of Computational Engineering Research*, 2011.

48. Perkins, C. E. and Royer, E. M. *Ad-hoc On-demand Distance Vector Routing*. Technical report, Sun Micro Systems Laboratories, Advanced Development Group, USA.
49. Ramachandran, K. AODV-st. Technical report, University of California, Santa Barbara, USA. <http://www.cs.ucsb.edu/krishna/aodv-st/> (last visited 11-05-2013).
50. Ning, P. and Sun, K. *How to misuse AODV: A case study of insider attacks against mobile ad-hoc routing protocols*. Technical report, Comput. Sci. Dept., North Carolina State University, Raleigh, NC, USA, 2003.
51. Shrivastva, D., Rajput, S. S., and Kumar, H. MANET protocols analysis with varying pause time simulation and speed. *International Journal of Advanced Research in Computer Engineering and Technology*, Volume 1, Issue 8, October 2012.
52. Bingham, D. R. and Sitter, R. R. Design issues in fractional factorial split-plot experiments. *Journal of Quality Technology* 33, 2-15, 2001.
53. Ranjan, P. *Factorial and fractional factorial designs with randomization restrictions- A projective geometric approach*. Ph.D thesis, Department of Statistics and Actuarial Science, Simon Fraser University, 2007.
54. Bansal, M. and Barua, G. *Performance comparison of two on-demand routing protocols for mobile ad hoc networks*. Department of Computer Science and Engineering, Indian Institute of Technology, Guwahati.
55. Bansal, M. and Barua, G. *Performance of TCP over IEEE 802.11 based ad hoc networks*. Department of Computer Science and Engineering, Indian Institute of Technology, Guwahati.
56. Perkins, D. D., Hughes, H. D., and Owen, C. B. *Factors affecting the performance of ad hoc networks*. Department of Computer Science and Engineering, Michigan State University, 2002.
57. Sarahintu, M. and Tuah, N. *Determining the effects of factors affecting the performance of dynamic source routing protocol using factorial design*.

Technical report. Institute of research, Development and Commercialization, Universiti Teknologi MARA, 2010.

58. Perkins, D. D., Hughes, H. D., and Owen, C. B. Factors affecting the performance of ad-hoc networks. *IEEE Computer*, 2002, pp. 2048-2052.
59. Hines, W. G. S., Pragmatics of Pooling in ANOVA Tables. *The American Statistician*, Vol. 50, No. 2, pp. 127-139, May 1996