

COMPACT AND MULTIBAND METAMATERIAL HAIRPIN-LINE BANDPASS
FILTERS

MUHAMMAD AKRAM BIN MOHD SOBRI

A project report submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Engineering (Electronic and Telecommunication)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

JANUARY 2018

To my parents, for their endless love and support

ACKNOWLEDGEMENT

This report could not be done without the help and support by various individuals. I could not thank them enough. Nevertheless, I would like to express my gratitude for them here.

First and foremost, I would like to express my most sincere gratitude to my supervisor, Dr Mohd Fairus Bin Mohd Yusoff for his guidance, support and encouragement. His vast experience and deep knowledge of the subject proved to be immense help to me. Without his endless support and motivation, this report would not have been the same as presented here. The topic of Compact and Multiband Metamaterial Hairpin-line Bandpass Filters will not be accomplish without his help and guidance.

My sincere appreciation also extends to all the staff in Wireless Communication Centre (WCC) who have provided assistance at various occasions. A lot of thanks to them especially to Muhammad Lokman Samingan, student master and others staff that they have spent much time and effort to check my progress and gave many opinions regarding to the main project of this report.

I would like to take this opportunity to express my most sincere gratitude to my friends for giving me comments and lots of support to finish this report. Last but not least, to my beloved family who has always been there to encourage, comfort and give their fullest support when I most needed them.

ABSTRACT

In RF and microwave field, the bandpass filters are very important in communication systems. Bandpass filters are used as frequency selective devices in many RF and microwave applications such as transmitter and receiver. In recent years, a new type of artificial materials called as metamaterials have attracted the attention of many researchers. Metamaterials have a wide range of potential uses in communication areas such as optical and RF design. The metamaterial is a material engineered to have an electromagnetic property that is not found in nature. Thanks to the presence of these properties many researchers have using the metamaterial to produce the high performance and compact devices. The rapid development of microwave and millimeter wave in communication systems greatly stimulates the demand for high-performance bandpass filters with compact dimensions, low insertion loss, high attenuation in the stopband, low cost and multiband responses. In this project, the compact and multiband metamaterial hairpin bandpass filters have been proposed to reduce the size of the filter and to provide a multiband filter with less complex structure. The proposed bandpass filters were designed by using the complementary split ring resonator (CSRR) structure. The compact size was achieved with size reduction of 10% from the conventional hairpin filter. For the proposed multiband bandpass filter, two-band frequency responses were obtained at 3.5 and 5.5 GHz. Moreover, both of them have an insertion loss less than 1 dB and high attenuation at stopband.

ABSTRAK

Dalam bidang RF dan gelombang mikro, penapis laluan jalur sangat penting dalam sistem komunikasi. Penapis laluan jalur digunakan sebagai alat pemilih kekerapan dalam banyak aplikasi RF dan gelombang mikro seperti pemancar dan penerima. Dalam beberapa tahun kebelakangan ini, sejenis bahan buatan baru yang dipanggil sebagai bahan metamaterial telah menarik perhatian ramai penyelidik. Bahan metamaterial mempunyai pelbagai potensi penggunaan dalam bidang komunikasi seperti reka bentuk optik dan RF. Bahan metamaterial adalah bahan kejuruteraan yang mempunyai sifat elektromagnetik yang tidak terdapat dalam alam semula jadi. Terima kasih kepada kehadiran sifat-sifat ini ramai penyelidik telah menggunakan metamaterial untuk menghasilkan prestasi tinggi dan peranti padat. Perkembangan pesat gelombang mikro dan gelombang milimeter dalam sistem komunikasi sangat merangsang permintaan untuk penapis bandpass berprestasi tinggi dengan dimensi padat, kehilangan sisipan yang rendah, pengecilan yang tinggi di perhentian, kos rendah dan pelbagai jalur tindak balas. Dalam projek ini, penapis laluan jalur padat dan pelbagai jalur metamaterial telah dicadangkan untuk mengurangkan saiz penapis dan menyediakan penapis pelbagai jalur dengan struktur yang kurang kompleks. Penapis laluan jalur yang dicadangkan telah direka dengan menggunakan struktur resonator cincin berpisah (CSRR). Saiz padat dicapai dengan pengurangan saiz sebanyak 10% dari penapis rambut konvensional. Untuk penapisan bandpass pelbagai jalur yang dicadangkan, respons kekerapan dua jalur diperoleh pada 3.5 dan 5.5 GHz. Lebih-lebih lagi, kedua-duanya mempunyai kehilangan penyisipan kurang dari 1 dB dan pengecilan tinggi pada hentian.

TABLE OF CONTENTS

| CHAPTER | TITLE | PAGE |
|----------|------------------------------|------|
| | DECLARATION | ii |
| | DEDICATION | iii |
| | ACKNOWLEDGEMENT | iv |
| | ABSTRACT | v |
| | ABSTRAK | vi |
| | TABLE OF CONTENTS | vii |
| | LIST OF TABLES | x |
| | LIST OF FIGURES | xi |
| | LIST OF ABBREVIATIONS | xiv |
| | LIST OF SYMBOLS | xv |
| 1 | INTRODUCTION | 1 |
| | 1.1 Research Background | 1 |
| | 1.2 Problem Statement | 3 |
| | 1.3 Objectives | 4 |
| | 1.4 Scope of The Work | 4 |
| | 1.5 Chapter Outline | 4 |
| 2 | LITERATURE REVIEW | 6 |
| | 2.1 Introduction | 6 |
| | 2.2 Filter | 6 |
| | 2.2.1 Basic Types of Filter | 6 |
| | 2.2.1.1 Low-Pass Filter | 7 |
| | 2.2.1.2 High-Pass Filter | 7 |
| | 2.2.1.3 Band-Pass Filter | 8 |

| | | | |
|----------|---------|---|-----------|
| | 2.2.1.4 | Band-Stop Filter | 9 |
| 2.3 | | Metamaterial Transmission Lines | 9 |
| 2.4 | | Implementation of Metamaterial Transmission Lines | 11 |
| | 2.4.1 | CL- Loaded Approach | 11 |
| | 2.4.2 | Resonant-Type Approach | 12 |
| 2.5 | | Gap Analysis of Bandpass Filter Designs | 15 |
| | 2.5.1 | Miniaturized ultra-wideband bandpass filter based on CRLH-TL unit cell | 15 |
| | 2.5.2 | New design of ultra-wideband bandpass filter using interdigitated coupled lines CRLH-TL structure | 16 |
| | 2.5.3 | Compact CSRRs-loaded UWB Bandpass filter with Improved Selectivity | 17 |
| | 2.5.4 | C-band parallel coupled bandpass filter with harmonic suppression using open stub and CSRRs | 18 |
| | 2.5.5 | Spurious response suppression in hairpin filter using CSRR merged in the filter structure | 19 |
| | 2.5.6 | A multiband bandpass filter using interdigital and step-impedance techniques for 4G, WiMAX and WLAN systems | 20 |
| 2.6 | | Chapter Summary | 22 |
| 3 | | RESEARCH METHODOLOGY | 23 |
| | 3.1 | Introduction | 23 |
| | 3.2 | Design Flow | 23 |
| | 3.3 | Filters Design Procedures | 25 |
| | 3.3.1 | Unit Cell of CSRR Design | 26 |
| | 3.3.2 | Compact Metamaterial Hairpin-Line Bandpass Filter Design | 29 |
| | 3.3.3 | Multiband Metamaterial Hairpin-Line Bandpass Filter Design | 33 |

| | | |
|----------|--|-----------|
| 3.4 | Simulation | 37 |
| 3.5 | Gantt Chart | 37 |
| 3.6 | Chapter Summary | 39 |
| 4 | RESULTS AND DISCUSSION | 40 |
| 4.1 | Introduction | 40 |
| 4.2 | Simulation Results | 40 |
| 4.2.1 | Unit Cell CSRR | 40 |
| 4.2.2 | Compact Metamaterial Hairpin-Line Bandpass Filter | 41 |
| 4.2.3 | Multiband Metamaterial Hairpin-Line Bandpass Filter | 44 |
| 4.3 | Chapter Summary | 46 |
| 5 | CONCLUSION | 47 |
| 5.1 | Research Outcomes | 47 |
| 5.2 | Future Works | 48 |
| | REFERENCES | 49 |

LIST OF TABLES

| TABLE NO. | TITLE | PAGE |
|------------------|--|-------------|
| 3.1 | Dimensions of unit cell CSRR | 29 |
| 3.2 | Design specification of compact metamaterial hairpin-line bandpass filter | 29 |
| 3.3 | Element values for Chebyshev lowpass prototype filters [1] | 31 |
| 3.4 | Dimensions of CSRR at 2.7 GHz | 33 |
| 3.5 | Design specification of compact metamaterial hairpin-line bandpass filter | 34 |
| 3.6 | Dimensions of CSRR at 2.7 GHz | 37 |
| 3.7 | Gantt chart | 38 |
| 4.1 | Size of the conventional hairpin bandpass filter and the compact metamaterial hairpin bandpass filter at 2.2 GHz | 44 |
| 4.2 | Center frequency and bandwidth of multiband metamaterial hairpin bandpass filter and conventional wideband hairpin bandpass filter | 46 |

LIST OF FIGURES

| FIGURE NO. | TITLE | PAGE |
|------------|--|------|
| 2.1 | Frequency response and circuit prototype of low-pass filter | 7 |
| 2.2 | Frequency response and circuit prototype of high-pass filter | 8 |
| 2.3 | Frequency response and circuit prototype of band-pass filter | 8 |
| 2.4 | Frequency response and circuit prototype of band-stop filter | 9 |
| 2.5 | Microstrip CRLH transmission line implemented by means of shunt connected grounded stubs and interdigital capacitors [2]. | 12 |
| 2.6 | Lumped element equivalent T-circuit model of the unit cell of CL-loaded metamaterial transmission lines [2] | 12 |
| 2.7 | Typical unit cell and relevant dimensions of a CPW metamaterial transmission line [3] | 13 |
| 2.8 | Unit cell of CSRR-based metamaterial transmission lines [3] | 14 |
| 2.9 | The lumped element equivalent circuit model of the unit cell of CSRR [3] | 14 |
| 2.10 | Frequency responses of unit cells of CSRR and SRR [3]. | 15 |
| 2.11 | (a) Layout of the microstrip interdigital coupled line, (b) Layout of the proposed LPF, (c) Layout of the proposed UWB filter and (d) Simulated and measured s-parameters of the proposed UWB filter [4] | 16 |
| 2.12 | (a) The proposed UWB filter using interdigitated coupled lines CRLH-TL structure and (b) Simulated and Measured result of UWB filter [5] | 17 |
| 2.13 | (a) Geometry of the CSRR-loaded filter: a) Top layer, b) bottom layer, c) CSRR configuration, and (b) Simulation results of the proposed UWB bandpass filter [6] | 18 |

| | | |
|------|--|----|
| 2.14 | (a) Configuration of the filter with stubs embedding and CSRRs etched in ground plane below the center of microstrip feed lines and (b) Insertion loss of the proposed C-band bandpass filters [7] | 19 |
| 2.15 | (a) The purposed filter structure to improve rejection response of the filter and (b) Comparison the simulation results between simulated bandpass hairpin filter integrated with three CSRR (solid line) and conventional bandpass hairpin filter (dotted line) [8] | 20 |
| 2.16 | (a)Layout and (b) Simulated results of the proposed multiband BPF. | 21 |
| 3.1 | Flowchart | 25 |
| 3.2 | Unit cell of CSRRs with a series gap (a) and without series gap (b) | 26 |
| 3.3 | Geometry transmission line | 27 |
| 3.4 | Split ring resonator (SRR) calculator | 28 |
| 3.5 | Compact metamaterial hairpin-line bandpass filter | 30 |
| 3.6 | Hairpin resonator [2] | 31 |
| 3.7 | Geometry of hairpin-line structure at frequency 2.4 GHz | 32 |
| 3.8 | Geometry of CSRR structure at frequency 2.7 GHz | 33 |
| 3.9 | Multiband metamaterial hairpin-line bandpass filter | 35 |
| 3.10 | Geometry of hairpin-line structure at frequency 5 GHz | 36 |
| 3.11 | Geometry of CSRR structure at frequency 2.7 GHz | 36 |
| 4.1 | Simulation results of unit cell CSRR | 41 |
| 4.2 | Simulation results of comparison between conventional hairpin bandpass filter at 2.4 GHz and compact metamaterial hairpin bandpass filter | 42 |
| 4.3 | Simulation results of comparison between conventional hairpin bandpass filter and compact metamaterial hairpin bandpass filter at 2.2 GHz | 43 |
| 4.4 | Figure 4.4 Geometry of the conventional hairpin bandpass filter and the compact metamaterial hairpin bandpass filter at 2.2 GHz | 44 |

| | | |
|-----|--|----|
| 4.5 | Simulation results of comparison between multiband meta-material hairpin bandpass filter and conventional wideband hairpin bandpass filter | 45 |
|-----|--|----|

LIST OF ABBREVIATIONS

| | | |
|-------|---|---|
| RF | - | Radio Frequency |
| CSRR | - | Complementary Split Ring Resonator |
| SRR | - | Split Ring Resonator |
| CPW | - | Coplanar Waveguide |
| BPF | - | Bandpass Filter |
| CST | - | Computer Simulation Technology |
| DGS | - | Defected Ground Structure |
| UWB | - | Ultra Wideband |
| LPF | - | Low Pass Filter |
| SSRR | - | Symmetrical Split Ring Resonator |
| CRLH | - | Composite Right/Left Handed |
| TL | - | Transmission Line |
| LH | - | Left Handed |
| RH | - | Right Handed |
| WLAN | - | Wireless Local Access Network |
| WiMAX | - | Worldwide Interoperability for Microwave Access |
| FBW | - | Fractional Bandwidth |

LIST OF SYMBOLS

| | | |
|---------------|---|--------------|
| λ | - | wavelength |
| δ | - | conductivity |
| μ | - | permeability |
| ε | - | permittivity |

CHAPTER 1

INTRODUCTION

1.1 Research Background

A bandpass filter (BPF) is a two-port network used to control the frequency response at a certain point in an RF or microwave system by providing transmission at frequencies within the passband of the filter and attenuation in the stopband of the filter [9]. Band-pass filters are used as frequency selective devices in many RF and microwave applications such as transmitters and receivers [10–12]. The advance of telecommunication system has enhanced the need for more sophisticated devices in order to support the variety of the applications. In order to meet the consumers need, some designing factors of microwave filters such as compactness, steepness, low cost, lightweight, small size, good performance, and low loss are important parameters that are desirable to have for enhanced system performance and to reduce the fabrication cost [1].

The implementation of the microstrip band-pass filters has various topologies such as end-coupled, parallel-coupled, hairpin-line, interdigital and combline filters. This project represents the design of a hairpin-line band-pass filter. The hairpin-line band-pass filter is one of the most popular microstrip filter configurations used for the compact structure. This design is easy to fabricate because it has open-circuited ends that require no grounding. This design is obtained by folding the resonators of parallel-coupled into a “U” shape. This configuration will reduce the length of the parallel-coupled band-pass filter.

In recent years, a new type of artificial materials called as metamaterials have

attracted the attention of many researchers. The presence of such material with effective negative permittivity (ϵ) and negative permeability (μ) was theoretically investigated by a Russian scientist Veselago in [13]. The metamaterial is a material engineered to have an electromagnetic property that is not found in nature [3]. That means, in the normal material, they have positive permittivity and permeability. For metamaterial, they can produce negative permittivity or negative permeability or negative index of refraction. Metamaterials derive their properties not from the properties of the base materials, but from their newly designed structures. In RF and microwave engineering, in order to obtain properties not present in the conventional material, the transmission line is loaded with reactive elements and it called metamaterial transmission lines. Metamaterial transmission line is an artificial line consisting of a host line such as microstrip and coplanar waveguide (CPW) loaded with reactive elements such as inductances, capacitance or resonator [14]. Thanks to the presence of these reactive elements in the line we have more degree of freedom for design as compared to conventional lines so it means that we have more design flexibility so that we can make device design based on dispersion and impedance engineering. The example of an application for wireless communication by using metamaterial transmission line is filter [4–8] and sensor [15–17]. There are two ways for the implementation of metamaterial transmission lines. First, the CL-loaded approach, where the host line is loaded with series capacitances and shunt inductances. Second, the resonant-type approach, where the line is loaded with electrically small resonators, such as split ring resonator (SRR) and complementary split ring resonator (CSRR) [18]. SRR and CSRR are the most widely used planar structure for exhibiting left-handed property. At resonance, these resonators exhibit sharp stopband and are smaller in size compared to the wavelength, hence known as sub-wavelength resonators.

This project is about designing of compact and multiband metamaterial hairpin-line bandpass filters by using CSRR structure. By applying this technique, the proposed filter can reduce size more than the conventional hairpin filter. Moreover, a structure for design multiband filter is not complex and provide high attenuation at stopband.

1.2 Problem Statement

With the rapid development of microwave and millimeter wave communication systems, it greatly stimulates the demand for high-performance microwave filters with compact dimensions, low insertion loss, high attenuation in stopband and low cost. Miniaturization of microwave filters is one of the fundamental requirements in communication systems. In order to reduce cost and enhance system performance, the small-size and high-performance filters are always necessary. Usually, the size of microwave filter is large at low frequency. Therefore, many researchers have been proposed to reduce the filter size by using a parallel-coupled resonator, hairpin-line resonator, interdigital resonator and combline resonator. However, the size of planar filters with parallel-coupled resonators, hairpin resonators, interdigital resonators or combline resonators design is obviously still too large to accept the demand for modern communication and electronic systems. To solve this problem, the metamaterial is used to reduce more size and improve the performance of the filter. In this project, a compact metamaterial hairpin-line bandpass filter by using CSRR structure has been proposed.

In addition, with the rapid evolution of multiband and multiservice communication systems, filters with a multiband response are in high demand. In the field of advanced multiband wireless systems, filters with the two-through seven-band operation for RF devices have become indispensable. The challenges to circuit designers designing a multi-band bandpass filter are to achieve a compact size and low insertion loss simultaneously. The previous works are usually too many components inside have caused large circuit size and structure design very complex. Besides of the ability to support various wireless communication applications, also need to satisfy the specifications of a bandpass filter which are size reduction, high stability, high selectivity simultaneously. In this project, a multiband metamaterial hairpin-line bandpass filter by using CSRR structure has been proposed

1.3 Objectives

The following objectives of this project are;

1. To design a unit cell of CSRR at frequency 2.4 GHz.
2. To design a compact metamaterial hairpin-line bandpass filter by using CSRR structure.
3. To design a multiband metamaterial hairpin-line bandpass filter by using CSRR structure.

1.4 Scope of The Work

The scope of this project is to design and simulate of compact and multiband metamaterial hairpin-line bandpass filter by using CSRR structure. The proposed bandpass filter using Rogers RT6006 as a substrate of BPF with a thickness (h) of 1.27 mm, a relative permittivity (ϵ_r) of 6.15 and a loss tangent δ of 0.025. Other material use is copper with the thickness of 0.035 mm as transmission line and ground plane. The proposed of compact bandpass filter needs to operate at operating frequency 2.2 GHz with the fractional bandwidth of 20%, while for the proposed of multiband bandpass filter needs to operate at operating frequency 3.3 and 5.5 GHz with the fractional bandwidth of 40% and 20%. Bandpass filter design, simulation and optimize process using the Computer System Technologies (CST) simulator. The performances of bandpass filter are determined by analysis of S-parameter.

1.5 Chapter Outline

This report consists five chapters, which provide information and the concept of designing for compact and multiband metamaterial hairpin-line bandpass filters by using CSRR structure. Chapter 1 gives a brief introduction to the research background, problem statement, objectives of project and scope of the work was done.

Chapter 2 describes some review of works previous researcher about compact and multiband bandpass filter, metamaterial transmission line, and metamaterial bandpass filter. Chapter 3 describes the methodology, the procedures of design, simulation, and analysis of the proposed bandpass filter have been discussed in details. Chapter 4 shows the simulation results of the conventional hairpin-line bandpass filter, the proposed compact bandpass filter, and the proposed bandpass filter. The comparison simulation results between conventional hairpin-line filter and metamaterial hairpin-line filter have been discussed in chapter 4. Chapter 5 gives a brief conclusion for this project and the problems encountered have been explained in this chapter.

REFERENCES

1. Hong, J.-S. G. and Lancaster, M. J. *Microstrip filters for RF/microwave applications*. vol. 167. John Wiley & Sons. 2004.
2. Caloz, C. and Itoh, T. Transmission line approach of left-handed (LH) materials and microstrip implementation of an artificial LH transmission line. *IEEE Transactions on Antennas and Propagation*, 2004. 52(5): 1159–1166.
3. Naqui, J., Zamora, G., Paredes, F., Bonache, J. and Martín, F. Metamaterial transmission lines for wireless communications, sensing and RFID. *Microwave Symposium (MMS), 2014 14th Mediterranean*. IEEE. 2014. 1–6.
4. Alburaikan, A., Aqeeli, M., Huang, X. and Hu, Z. Miniaturized ultra-wideband bandpass filter based on CRLH-TL unit cell. *Microwave Conference (EuMC), 2014 44th European*. IEEE. 2014. 540–543.
5. Bu, Q., Ding, J. and Guo, C. J. New design of ultra-wideband bandpass filter using interdigitated coupled lines CRLH-TL structure. *Antennas, Propagation & EM Theory (ISAPE), 2012 10th International Symposium on*. IEEE. 2012. 486–489.
6. Naghar, A., Alejos, A. V., Aghzout, O., Falcone, F. and Sánchez, M. G. Compact CSRRs-loaded UWB Bandpass filter with Improved Selectivity.
7. Naghar, A., Alejos, A. V., Aghzout, O., Falcone, F. and Sanchez, M. G. C-band parallel coupled bandpass filter with harmonic suppression using open stub and CSRRs. *Antennas and Propagation (EuCAP), 2015 9th European Conference on*. IEEE. 2015. 1–2.
8. Afkhami, A. and Tayarani, M. Spurious response suppression in hairpin filter using CSRR merged in the filter structure. *Progress In Electromagnetics Research C*, 2009. 11: 137–146.

9. Pozar, D. *Microwave Engineering, Fourth Edition Wiley E-Text Reg Card*. John Wiley & Sons, Incorporated. 2013. ISBN 9781118631430. URL <https://books.google.com.my/books?id=N9W-kQEACAAJ>.
10. Hasan, M. N., Gu, Q. J. and Liu, X. Reconfigurable blocker-tolerant RF front-end filter with tunable notch for active cancellation of transmitter leakage in FDD receivers. *Circuits and Systems (ISCAS), 2016 IEEE International Symposium on*. IEEE. 2016. 1782–1785.
11. Hasan, M. N., Gu, Q. J. and Liu, X. Tunable blocker-tolerant RF front-end filter with dual adaptive notches for reconfigurable receivers. *Microwave Symposium (IMS), 2016 IEEE MTT-S International*. IEEE. 2016. 1–4.
12. Addou, M. A., Hijazi, R., Gómez-García, R., Barelaud, B., Jarry, B. and Lintignat, J. Two-branch channelized N-path filter for reconfigurable receiver. *Electronics, Circuits and Systems (ICECS), 2016 IEEE International Conference on*. IEEE. 2016. 484–487.
13. Veselago, V. Electrodynamics of substances with simultaneously negative electrical and magnetic permeabilities. *Physics-Uspekhi*, 1968. 10(4): 504–509.
14. Aznar, F., Gil, M., Siso, G., Bonache, J. and Martin, F. SRR-and CSRR-based metamaterial transmission lines: modeling and comparison. *Signal Integrity and High-Speed Interconnects, 2009. IMWS 2009. IEEE MTT-S International Microwave Workshop Series on*. IEEE. 2009. 49–52.
15. Ekmekci, E. and Turhan-Sayan, G. Metamaterial sensor applications based on broadside-coupled SRR and V-Shaped resonator structures. *Antennas and Propagation (APSURSI), 2011 IEEE International Symposium on*. IEEE. 2011. 1170–1172.
16. Mandel, C., Kubina, B., Schüßler, M. and Jakoby, R. Passive chipless wireless sensor for two-dimensional displacement measurement. *Microwave Conference (EuMC), 2011 41st European*. IEEE. 2011. 79–82.
17. Puentes, M., Weiß, C., Schüßler, M. and Jakoby, R. Sensor array based on split ring resonators for analysis of organic tissues. *Microwave Symposium Digest (MTT), 2011 IEEE MTT-S International*. IEEE. 2011. 1–4.

18. Gil, M., Bonache, J., Selga, J., García-García, J. and Martín, F. Broadband resonant-type metamaterial transmission lines. *IEEE Microwave and Wireless Components Letters*, 2007. 17(2): 97–99.
19. Kinayman, N. and Aksun, M. *Modern microwave circuits*. Artech House. 2005.
20. Aznar, F., Gil, M., Bonache, J. and Martin, F. Modelling metamaterial transmission lines: a review and recent developments. *Opto-Electronics Review*, 2008. 16(3): 226–236.
21. Martín, F. Metamaterials for wireless communications, radiofrequency identification, and sensors. *ISRN Electronics*, 2012. 2012.
22. Syahral, M. and Munir, A. Development of multiple elements of SRR-based Bandpass Filter. *Telecommunication Systems Services and Applications (TSSA), 2016 10th International Conference on*. IEEE. 2016. 1–4.
23. Rathore, V., Awasthi, S. and Biswas, A. Design of compact dual-band bandpass filter using frequency transformation and its implementation with Split Ring Resonator Dual-band bandpass filter using SRR. *Microwave Conference (EuMC), 2014 44th European*. IEEE. 2014. 949–952.
24. Garcia-Garcia, J., Martín, F., Falcone, F., Bonache, J., Baena, J. D., Gil, I., Amat, E., Lopetegi, T., Laso, M. A., Iturmendi, J. A. M. *et al.* Microwave filters with improved stopband based on sub-wavelength resonators. *IEEE Transactions on Microwave theory and techniques*, 2005. 53(6): 1997–2006.
25. Wu, B., Li, B., Su, T. and Liang, C.-H. Study on transmission characteristic of split ring resonator defected ground structure. *Progress In Electromagnetics Research*, 2006. 50: 710–714.
26. Ketkuntod, P., Chomtong, P., Meesomklin, S. and Akkaraekthalin, P. A multiband bandpass filter using interdigital and step-impedance techniques for 4G, WiMAX and WLAN systems. *Electrical Engineering/Electronics, Computer, Telecommunications and Information Technology (ECTI-CON), 2015 12th International Conference on*. IEEE. 2015. 1–4.
27. Chomtong, P., Akkaraekthalin, P. and Vivek, V. A Wideband Monopole with Built-in Interdigital Capacitor for Size Reduction and Capacitive Feed for

Improved Response. *iEECON*, 2013.

28. Meesomklin, S., Chomtong, P., Akkaraekthalin, P. and Vivek, V. A compact multi-band BPF using tri-section with interdigital capacitor hairpin resonator for GSM WiMAX and WLAN systems. *EECON 35*, 2012: 667–670.
29. Xu, F., Liu, X., Guo, H., Wang, Y. and Mao, L. A compact dual-mode BPF base on interdigital structure. *Microwave and Millimeter Wave Technology (ICMMT), 2010 International Conference on*. IEEE. 2010. 1595–1597.