

A NEW VISCOELASTIC DAMPER FOR SEISMIC PROTECTION OF STEEL  
BUILDING FRAME

FARNOUD RAHIMI MANSOUR

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Doctor of Philosophy (Civil Engineering)

Faculty of Civil Engineering  
Universiti Teknologi Malaysia

NOVEMBER 2017

This thesis is dedicated to the memory of my father who supported me a lot and passed away during my PhD studies. He is always in my heart and I miss him every day. I know that he would be very proud to see me complete my doctoral degree. I also would like to dedicate the thesis to my beloved mother and wonderful wife for their endless love, faith, support, and encouragement. I also dedicate this work to my brother and my wife's parents who have walked alongside me during doctoral degree.

## ACKNOWLEDGEMENT

I would like to express my sincere gratitude to my supervisors, Dr. Suhaimi Abu Bakar and Dr. Mohammadreza Vafaei for their supports and generous guidance which made it possible for me to work on a topic that was of great interest to me. It was a pleasure working with them. I am highly indebted and thoroughly grateful to Mr. Or Tan Teng and Doshin Rubber Products (M) Sdn Bhd, for providing the materials to facilitate my research. I would also like to thank Dr. Sophia C.Alih, Dr. Patrick Tiong, Prof. Dr. Azlan Bin Adnan, Dr. Jem Rongong, and Mr. Mohd Zamri Ramli for their assistance. I would also like to express my deepest gratitude to the Universiti Teknologi Malaysia (UTM) for letting me fulfill my dream and providing the necessary facilities and materials. Especially thanks to the staff of UTM's structural laboratory for their assistance. I would like to finally thank my lovely wife, my family and friends for their patience, support and encouragement. I was not able to complete my PhD thesis without them.

## ABSTRACT

Viscoelastic dampers (VEDs) are widely used to protect structures against earthquake. Conventional VEDs are generally installed within a diagonal brace configuration which provides a stiff structural system and reduces their effectiveness. In addition, the aforementioned configuration is not suitable for retrofitting purpose and violates architectural requirements. In this study, a new type of viscoelastic damper is proposed in order to improve the seismic performance of steel structures and to overcome the drawbacks of the conventional VEDs. In order to evaluate the performance of the proposed VED, dynamic responses of a 3-story scaled down steel frame equipped with the proposed VED were obtained experimentally and numerically under harmonic excitations. In this stage, ABAQUS software was used to establish a detailed finite element analysis. The results obtained were compared with a frame equipped with the conventional VED as well as a moment resisting frame and braced frames. The effects of the size of viscoelastic layer on its dynamic characteristics were also investigated. In addition, a nonlinear time history analysis of a 10-story full scale steel frame was performed using SAP2000 software to demonstrate the effectiveness of the proposed VED for tall buildings. The results of this study showed that the frames equipped with dampers performed better than the braced frames in terms of reduction in the maximum displacement, acceleration and base shear responses of the 3-story moment resisting frame. Compared to the conventional VED, the proposed VED was more effective in reducing displacements, while it was slightly less effective in reduction of accelerations and base shears. It was also found that smaller thickness of the viscoelastic layer decreased displacement responses, however, it increased acceleration and base shear responses. The larger cross-section area of the viscoelastic layer resulted in smaller displacement responses, but larger acceleration and base shear responses. Thus, analysis of the 10-story frame showed that the effectiveness of VEDs for reducing maximum displacement and acceleration responses were strongly dependent on the characteristics of earthquake records. The proposed VED was more effective in reducing responses of the lower floors. Based on the results obtained, the maximum base shear response of the frame equipped with the conventional VED was smaller than the frame equipped with the proposed VED and larger than the bare frame regardless of the characteristics of earthquake records. The results showed that the viscoelastic dampers have more advantage in preventing the formation of plastic hinges in the frames even under severe earthquake. In addition, compared to the conventional VED, the proposed VED resulted in less damage to the structural members due to less plastic hinge formation. Therefore, the implementation of the proposed VED can overcome the deficiency of the VED in seismic protection of structures.

## ABSTRAK

Peredam visco-elastik (VED) digunakan secara meluas untuk melindungi struktur terhadap gempa bumi. VED konvensional umumnya dipasang di antara konfigurasi perambat pepenjur yang menghasilkan sistem struktur yang kukuh dan mengurangkan keberkesannya. Di samping itu, konfigurasi ini adalah tidak sesuai untuk tujuan pengubahsuaian dan boleh melanggar keperluan seni bina. Dalam kajian ini, peredam visco-elastik jenis terbaru dicadangkan bagi meningkatkan prestasi seismik struktur keluli dan mengatasi kelemahan VED konvensional. Bagi menilai prestasi VED yang dicadangkan, gerak balas dinamik bagi kerangka keluli 3 tingkat yang dilengkapi dengan VED yang dicadangkan telah diperolehi daripada eksperimen dan kiraan berangka di bawah pengujian harmonik. Pada tahap ini, perisian ABAQUS telah digunakan untuk menjalankan analisis unsur terhingga secara terperinci. Hasil yang diperolehi dibandingkan dengan kerangka yang dilengkapi dengan VED konvensional sepertimana kerangka penahan momen dan kerangka dirembat. Kesan saiz bagi lapisan visco-elastik terhadap ciri-ciri dinamik turut disiasat. Di samping itu, analisis sejarah masa tak linear bagi kerangka keluli 10 tingkat berskala penuh dijalankan menggunakan perisian SAP2000 bagi menunjukkan keberkesanan VED yang dicadangkan untuk bangunan tinggi. Dapatan kajian menunjukkan bahawa kerangka yang dilengkapi dengan peredam adalah lebih baik berbanding kerangka dirembat dari segi pengurangan anjakan maksimum, pecutan dan gerak balas ricih asas untuk kerangka penahan momen tiga tingkat. Berbanding dengan VED konvensional, VED yang dicadangkan adalah lebih berkesan dalam mengurangkan anjakan, namun ia kurang berkesan dalam pengurangan pecutan dan ricih asas. Kajian juga menunjukkan ketebalan yang lebih kecil bagi lapisan visco-elastik mengurangkan gerak balas anjakan, walau bagaimanapun, ia boleh meningkatkan pecutan dan gerak balas ricih asas. Keluasan keratan lintang yang lebih besar bagi lapisan visco-elastik boleh menghasilkan gerak balas anjakan yang lebih kecil, namun pecutan dan gerak balas asas ricih adalah lebih besar. Oleh itu, analisis kerangka 10 tingkat menunjukkan bahawa keberkesanan VED dalam pengurangan anjakan maksimum dan gerak balas pecutan adalah amat bergantung kepada ciri-ciri rekod gempa bumi. VED yang dicadangkan adalah lebih berkesan dalam pengurangan gerak balas bagi tingkat bangunan yang lebih rendah. Berdasarkan keputusan yang diperolehi, gerak balas ricih asas maksimum bagi kerangka yang dilengkapi dengan VED konvensional adalah lebih kecil berbanding kerangka dilengkapi dengan VED yang dicadangkan dan lebih besar berbanding kerangka penahan momen tanpa mengambil kira ciri-ciri rekod gempa bumi. Keputusan juga menunjukkan bahawa peredam visco-elastik mempunyai kebaikan dalam menghalang pembentukan engsel plastik dalam kerangka walaupun di bawah gempa bumi yang teruk. Di samping itu, berbanding dengan VED konvensional, VED yang dicadangkan boleh mengurangkan kerosakan kepada anggota struktur disebabkan pembentukan engsel plastik yang lebih sedikit. Oleh itu, pelaksanaan VED yang dicadangkan dapat mengatasi kekurangan VED konvensional dalam perlindungan seismik struktur.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENT</b>	iv
	<b>ABSTRACT</b>	v
	<b>ABSTRAK</b>	vi
	<b>TABLE OF CONTENTS</b>	vii
	<b>LIST OF TABLES</b>	xv
	<b>LIST OF FIGURES</b>	xviii
	<b>LIST OF ABBREVIATIONS</b>	xxxvi
	<b>LIST OF SYMBOLS</b>	xxxviii
	<b>LIST OF APPENDICES</b>	xl
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Background	1
	1.2 Problem statement	5
	1.3 Objective of the research	6
	1.4 Scope of the research	7
	1.5 Outline of the research	8
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>10</b>
	2.1 Introduction	10
	2.2 Nature of earthquake	11
	2.3 Nature of seismic force	11

2.4	Seismic design of structures	14
2.5	Innovative seismic design	15
2.5.1	Metallic dampers (MDs)	18
2.5.2	Friction dampers (FDs)	20
2.5.3	Viscous fluid dampers (VFDs)	22
2.5.4	Tuned mass dampers (TMDs)	24
2.5.5	Tuned liquid dampers (TLDs)	25
2.6	Viscoelastic dampers (VEDs)	28
2.6.1	Available type of viscoelastic (VE) material	33
2.6.2	Installation configurations of VEDs	35
2.7	Installation of VEDs in building structures	42
2.8	Effectiveness of VEDs	44
2.9	VEDs for retrofitting purpose	50
2.10	Mechanical properties of VEDs	53
2.11	Analytical modeling of VEDs	57
2.12	Scaling and similitude techniques	61
<b>3</b>	<b>RESEARCH METHODOLOGY</b>	<b>64</b>
3.1	Introduction	64
3.2	Experimental works	69
3.2.1	Design of the bare frame	71
3.2.2	Dynamic characteristics of the bare frame	72
3.2.3	Design of the viscoelastic dampers	72
3.2.3.1	Description of the conventional viscoelastic damper	74
3.2.3.2	Description of the proposed viscoelastic damper	76
3.2.4	Construction of experimentally tested frames	78
3.2.4.1	Details of the structural members' connections	80
3.2.4.2	Details of the base connections to the shaking table	82

3.2.4.3 Details of the viscoelastic dampers' connections to the structural members	82
3.2.5 Test equipments and test setup	83
3.2.6 Experimental tests	85
3.2.6.1 Free vibration tests	86
3.2.6.2 Harmonic excitation tests	87
3.2.7 Mechanical properties of materials	87
3.2.7.1 Tensile properties of steel and viscoelastic material	88
3.2.7.2 Shear properties of viscoelastic material	90
3.3 Numerical studies	92
3.3.1 Finite element modeling and analysis of the scaled down frame	94
3.3.1.1 Finite element modeling of the scaled down frame	94
3.3.1.2 Finite element modeling of the viscoelastic damper	96
a) Hyperelasticity properties	97
b) Viscoelasticity properties	98
3.3.1.3 Verification of finite element models	99
3.3.1.4 Finite element analysis of the scaled down frame model	100
3.3.2 Effect of dimensions of viscoelastic layer on performance of the proposed viscoelastic damper	102
3.3.3 Proposed simplified model for simulation of viscoelastic dampers	103
3.3.4 Performance of the proposed viscoelastic damper in multi-storey steel structures under seismic excitations	104
3.3.4.1 Design of the multi-storey moment resisting model frame	105
3.3.4.2 Selection of earthquake records	106



	3.3.4.3 Effectiveness of the proposed viscoelastic damper on seismic responses of multi-storey steel structures	109
<b>4</b>	<b>EXPERIMENTAL RESULTS AND DISCUSSION</b>	<b>112</b>
	4.1 Introduction	112
	4.2 Materials test results	113
	4.2.1 Tensile test results	113
	4.2.1.1 Tensile test results of steel material	113
	4.2.1.2 Tensile test results of viscoelastic material	116
	4.2.2 Shear test results	117
	4.2.2.1 Static shear test results of viscoelastic material	118
	4.2.2.2 Dynamic shear test results of viscoelastic material	120
	4.3 Experimental test results of the tested frames	135
	4.3.1 Free vibration test results of the tested frames	136
	4.3.1.1 Natural frequency	136
	4.3.1.2 Modal damping ratio	138
	4.3.2 Force vibration test results of the tested frames	139
	4.3.2.1 Comparison of bare frame with braced frames	140
	4.3.2.2 Comparison between dynamic responses of chevron braced frame and frame with the proposed viscoelastic damper	146
	4.3.2.3 Comparison between dynamic responses of diagonally braced frame and frame with the conventional viscoelastic damper	150
	4.3.2.4 Effectiveness of the viscoelastic dampers	154
<b>5</b>	<b>NUMERICAL RESULTS AND DISCUSSION</b>	<b>161</b>
	5.1 Introduction	161
	5.2 Validation of finite element (FE) models	162

5.2.1 Validation of FE model of 3-story bare frame	162
5.2.2 Validation of FE model of viscoelastic damper	167
5.3 Effect of the proposed viscoelastic damper on response of the scaled down frame under harmonic excitation	173
5.3.1 Dynamic responses of the frames at resonance frequencies with various loading magnitudes	175
5.3.1.1 Comparison between dynamic responses of bare frame and braced frames	179
5.3.1.2 Comparison between dynamic responses of chevron braced frame and frame with the proposed viscoelastic damper	184
5.3.1.3 Comparison between dynamic responses of diagonally braced frame and frame with the conventional viscoelastic damper	189
5.3.1.4 Comparison between dynamic responses of all analyzed frames	194
5.3.2 Dynamic responses of the frames under loading frequencies of 80 % to 120 % of the frames' resonance frequency with the magnitude of 0.05g	199
5.3.2.1 Comparison between dynamic responses of bare frame and braced frames	199
5.3.2.2 Comparison between dynamic responses of chevron braced frame and frame with the proposed viscoelastic damper	204
5.3.2.3 Comparison between dynamic responses of diagonally braced frame and frame with the conventional viscoelastic damper	209
5.3.2.4 Efficiency of the proposed viscoelastic damper compared to the conventional viscoelastic damper	213
5.3.3 Effect of change in the size of the viscoelastic layer on the performance of the proposed viscoelastic damper	215

5.3.3.1 Effect of change in the thickness of the viscoelastic layer	218
5.3.3.2 Effect of change in the area of the viscoelastic layer	210
5.3.4 Seismic performance of multi-storey structures equipped with the proposed viscoelastic damper	220
5.3.4.1 Validation of SAP2000 software	221
5.3.4.2 Proposed simplified model for viscoelastic damper	224
5.3.4.3 Analysis of the multi-storey model frame without added dampers	227
5.3.4.4 Time history analysis of the multi-storey frame with and without added viscoelastic damper	230
5.3.4.5 Seismic performance of the frames under peak ground acceleration of 0.1g	231
a) Maximum displacement responses for earthquake records in low A/V group	232
b) Maximum displacement responses for earthquake records in medium A/V group	235
c) Maximum displacement responses for earthquake records in high A/V group	240
d) Maximum acceleration responses for earthquake records in low A/V group	244
e) Maximum acceleration responses for earthquake records in medium A/V group	248
f) Maximum acceleration responses for earthquake records in high A/V group	251
g) Maximum base shear responses of the frames for different group of records	254

5.3.4.6	Seismic performance of the frames under peak ground acceleration of 0.3 g	257
a)	Maximum displacement responses for earthquake records in low A/V group	257
b)	Maximum displacement responses for earthquake records in medium A/V group	261
c)	Maximum displacement responses for earthquake records in high A/V group	265
d)	Maximum acceleration responses for earthquake records in low A/V group	269
e)	Maximum acceleration responses for earthquake records in medium A/V group	272
f)	Maximum acceleration responses for earthquake records in high A/V group	276
g)	Maximum base shear responses of the frames for different group of records	279
<b>6</b>	<b>CONCLUSION</b>	<b>290</b>
	6.1 Introduction	290
	6.2 Research findings	290
	6.2.1 Experimentally obtained findings for the effectiveness of the proposed damper in reducing responses of a scaled down frame	291
	6.2.2 Numerical results regarding effectiveness of the proposed damper in reducing dynamic responses of the scaled down frame	292
	6.2.2.1 Results of excitations at resonance frequency of the frames with different amplitudes	293

6.2.2.2 Results of excitations with the constant amplitude and different ranges of frequencies	294
6.2.3 Results obtained for change in the dimensions of the viscoelastic layer and its effects on the dynamic performance of the proposed viscoelastic damper	294
6.2.3.1 Effects of change in the thickness of VE layer on the dynamic responses	295
6.2.3.2 Effect of changes in area of VE layer	296
6.2.4 Development of the simplified FE model of viscoelastic damper for the analysis of multi-storey structures	296
6.2.5 Results of effectiveness of the proposed damper in reducing dynamic responses of multi-storey structures	297
6.3 Contribution to the body of knowledge	299
6.4 Recommendation for future works	299
<b>REFERENCES</b>	<b>300</b>
Appendices A-C	311-318

## LIST OF TABLES

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
3.1	Dimensions of specimens for tensile test	89
3.2	Dimensions of the viscoelastic layer used for the proposed damper	102
3.3	Selected earthquake records	108
4.1	Yield and ultimate stress and strain obtained for the three specimens	114
4.2	Experimental natural frequencies for the tested frames	138
4.3	Displacement responses of the tested frames at different floors under their natural frequency	159
4.4	Acceleration responses of the tested frames at different floors under their natural frequency	159
4.5	Percentage of changes in displacement responses of the tested frames compared to the bare frame at different floors under their natural frequency	160
4.6	Percentage of changes in acceleration responses of the tested frames compared to the bare frame at different floors under their resonance frequency	160
5.1	Comparison of the first three modal frequency of numerical analysis and experimental tests	163
5.2	Experimentally and numerically obtained results for stiffness and energy absorption of the viscoelastic damper	173

5.3	Maximum displacement responses of the 10-story bare frame and frames with the VEDs under low group excitations (PGA=0.1 g)	283
5.4	Maximum displacement responses of the 10-story bare frame and frames with the VEDs under low group excitations (PGA=0.3 g)	283
5.5	Maximum displacement responses of the 10-story bare frame and frames with the VEDs under medium group excitations (PGA=0.1 g)	284
5.6	Maximum displacement responses of the 10-story bare frame and frames with the VEDs under medium group excitations (PGA=0.3 g)	284
5.7	Maximum displacement responses of the 10-story bare frame and frames with the VEDs under high group excitations (PGA=0.1 g)	285
5.8	Maximum displacement responses of the 10-story bare frame and frames with the VEDs under high group excitations (PGA=0.3 g)	285
5.9	Maximum acceleration responses of the 10-story bare frame and frames with the VEDs under low group excitations (PGA=0.1 g)	286
5.10	Maximum acceleration responses of the 10-story bare frame and frames with the VEDs under low group excitations (PGA=0.3 g)	286
5.11	Maximum acceleration responses of the 10-story bare frame and frames with the VEDs under medium group excitations (PGA=0.1 g)	287
5.12	Maximum acceleration responses of the 10-story bare frame and frames with the VEDs under medium group excitations (PGA=0.3 g)	287
5.13	Maximum acceleration responses of the 10-story bare frame and frames with the VEDs under high group excitations (PGA=0.1 g)	288

5.14	Maximum acceleration responses of the 10-story bare frame and frames with the VEDs under high group excitations (PGA=0.3 g)	288
5.15	Average of maximum base shear responses of the 10-story bare frame and frames with the viscoelastic dampers under various excitations	289



## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Structural failure around the world due to earthquake	2
1.2	Example of typical passive energy dissipating devices based on Soong T.T.et al,1997	4
2.1	Different kinds of faults and their relative relationships of motion	11
2.2	Induced inertia force when a building experiences acceleration at its base	12
2.3	Simplification of how inertia forces on a building are expresses	13
2.4	Typical types of metallic dampers	19
2.5	H-BRB damper	20
2.6	Examples of friction devices	22
2.7	Viscous fluid damper	23
2.8	Viscous damping wall system	23
2.9	Tuned mass damper used for Taipei 101 skyscraper	25
2.10	Tuned liquid damper	26
2.11	Tuned liquid column damper	27
2.12	Typical structural viscoelastic damper	28
2.13	Details of visco-plastic device	30
2.14	Viscoelastic coupling damper (VCD) concept	31
2.15	Developed viscoelastic damper by Chen et al. [20]	33
2.16	The proposed beam-to-column connection by Banisheikholeslami et al. [54]	36

2.17	Installation configurations of VE dampers	37
2.18	Configurations of toggle-brace-damper (TBD) system	39
2.19	One-story frame using scissors-jack damper	40
2.20	Seesaw system configuration	41
2.21	Energy dissipation scheme of seesaw system	41
2.22	VEDs used in the World Trade Center Buildings in New York City	43
2.23	VEDs used in the Columbia Sea First building	44
2.24	Schematic diagram of the self-centering bridge piers	50
2.25	Force-displacement hysteresis curve of a VED	55
2.26	Typical analytical models for viscoelastic dampers	58
2.27	Generalized analytical models for viscoelastic dampers	61
3.1	Research methodology flowchart	68
3.2	Details of the experimentally tested frames	71
3.3	Configuration of the conventional viscoelastic damper used in the study	75
3.4	Dimensions of the conventional viscoelastic damper used in the study	76
3.5	Configuration of the proposed viscoelastic damper used in the study	77
3.6	Details of the proposed viscoelastic damper used in the study	78
3.7	Constructed frames for the experimental tests	80
3.8	Details of the structural members' connections	81
3.9	Base connections of the frames to the shaking table	82
3.10	Details of the viscoelastic dampers' connections to the structural members	83
3.11	Data loggers and accelerometers	84
3.12	Schematic test setup	85
3.13	Geometry of specimens for tensile test	88
3.14	Universal Testing Machine set up for the viscoelastic material	90
3.15	Tested specimen for shear test	91

3.16	Shear test setup	92
3.17	True plastic stress and strain properties used for steel material	95
3.18	Finite element modeling of the 3-story scaled-down bare frame	96
3.19	Finite element model of the conventional viscoelastic damper	97
3.20	Finite element models of the scaled down frames	101
3.21	Proposed simplified model for viscoelastic dampers	104
3.22	Details of the 10-story four-bay 2D frame used in the numerical studies	105
3.23	Analyzed 10-story frames	110
4.1	Tested steel specimens after fracture	114
4.2	Stress-strain graph of a tested steel specimen	115
4.3	Tested viscoelastic material specimens after fracture	116
4.4	Elongation-stress relationship of the three tested viscoelastic specimens	117
4.5	Static shear test	118
4.6	Force-deformation behavior of the viscoelastic damper (static test)	119
4.7	Stress-strain behavior of the viscoelastic damper (static test)	120
4.8	Force-displacement hysteresis loops of the viscoelastic damper for 5 % strain under different frequencies	123
4.9	Force-displacement hysteresis loops of the viscoelastic damper for 20 % strain under different frequencies	125
4.10	Force-displacement hysteresis loops of the viscoelastic damper for 50 % strain under different frequencies	127
4.11	Force-displacement hysteresis loops of the viscoelastic damper for frequency excitation of 0.1 Hz with different strains	128

4.12	Force-deformation hysteresis loops of the viscoelastic damper for frequency excitation of 1 Hz with different strains	128
4.13	Force-displacement hysteresis loops of the viscoelastic damper for frequency excitation of 5 Hz with different strains	129
4.14	Force-displacement hysteresis loops of the viscoelastic damper for strain amplitude of 5 % with different frequencies	129
4.15	Force-displacement hysteresis loops of the viscoelastic damper for strain amplitude of 20 % with different frequencies	130
4.16	Force-displacement hysteresis loops of the viscoelastic damper for strain amplitude of 50 % with different frequencies	130
4.17	10 <sup>th</sup> cycle load-deformation of the viscoelastic damper under 50% strain and frequency of 0.1 Hz	131
4.18	Shear storage modulus ( $G'$ ) of VE material under different frequencies and strains at room temperature of 24 °C	132
4.19	Shear loss modulus ( $G''$ ) of VE material under different frequencies and strains at room temperature of 24 °C	133
4.20	Loss factor ( $\eta$ ) of VE material under different frequencies and strains at room temperature of 24 °C	133
4.21	Energy dissipation ( $W$ ) of VE material under different frequencies and strains at room temperature of 24 °C	134
4.22	Fourier analysis results obtained from measured response acceleration at third floor of the tested frames	137
4.23	Displacement response of the bare frame under free vibration test	139
4.24	Displacement responses obtained at the first floor	141
4.25	Acceleration responses obtained at the first floor	142
4.26	Displacement responses obtained at the second floor	143

4.27	Displacement responses obtained at the third floor	144
4.28	Acceleration responses obtained at the second floor	145
4.29	Acceleration responses obtained at the third floor	145
4.30	Displacement responses obtained at the first floor	147
4.31	Displacement responses obtained at the second floor	147
4.32	Displacement responses obtained at the third floor	148
4.33	Acceleration responses obtained at the first floor	148
4.34	Acceleration responses obtained at the second floor	149
4.35	Acceleration responses obtained at the third floor	149
4.36	Displacement responses obtained at the first floor	151
4.37	Displacement responses obtained at the second floor	151
4.38	Displacement responses obtained at the third floor	152
4.39	Acceleration responses obtained at the first floor	152
4.40	Acceleration responses obtained at the second floor	153
4.41	Acceleration responses obtained at the third floor	153
4.42	Percentage of changes in displacement of the first floor of the frames with reference to the bare frame	155
4.43	Percentage of changes in displacement of the second floor of the frames with reference to the bare frame	155
4.44	Percentage of changes in displacement of the third floor of the frames with reference to the bare frame	156
4.45	Percentage of changes in acceleration of the first floor of the frames with reference to the bare frame	157
4.46	Percentage of changes in acceleration of the second floor of the frames with reference to the bare frame	157
4.47	Percentage of changes in acceleration of the third floor of the frames with reference to the bare frame	158
5.1	FE model and the first three mode shapes of the 3-story scaled-down bare frame	163
5.2	Experimentally and numerically obtained responses for displacement of the 3-story scaled-down bare frame at the first floor	164

5.3	Experimentally and numerically obtained responses for displacement of the 3-story scaled-down bare frame at the second floor	165
5.4	Experimentally and numerically obtained responses for displacement of the 3-story scaled-down bare frame at the third floor	165
5.5	Experimentally and numerically obtained responses for acceleration of the 3-story scaled-down bare frame at the first floor	166
5.6	Experimentally and numerically obtained responses for acceleration of the 3-story scaled-down bare frame at the second floor	166
5.7	Experimentally and numerically obtained responses for acceleration of the 3-story scaled-down bare frame at the third floor	167
5.8	Finite element model of the viscoelastic damper	168
5.9	Deformed shape of the FE model of the viscoelastic damper under shear	168
5.10	Experimentally and numerically obtained load-displacement results for the damper under 20 % shear strain (static test)	169
5.11	Experimentally and numerically obtained responses of the viscoelastic damper under 50 % strain and frequency of 0.1 Hz	170
5.12	Experimentally and numerically obtained responses of the viscoelastic damper under 50 % strain and frequency of 0.2 Hz	171
5.13	Experimentally and numerically obtained responses of the viscoelastic damper under 50 % strain and frequency of 1 Hz	171
5.14	Experimentally and numerically obtained responses of the viscoelastic damper under 50 % strain and frequency of 2.5 Hz	172

5.15	Experimentally and numerically obtained responses of the viscoelastic damper under 50 % strain and frequency of 5 Hz	172
5.16	Finite element modeling of the 3-story scaled-down analyzed frames	175
5.17	Maximum deformation of the analyzed frames for excitation frequency tuned to their resonance frequency and the magnitude of 0.05 g	178
5.18	Maximum displacement responses obtained for the 3-story scaled-down bare frame and the braced frames at the first floor	180
5.19	Maximum displacement responses obtained for the 3-story scaled-down bare frame and the braced frames at the second floor	181
5.20	Maximum displacement responses obtained for the 3-story scaled-down bare frame and the braced frames at the third floor	181
5.21	Maximum acceleration responses obtained for the 3-story scaled-down bare frame and the braced frames at the first floor	182
5.22	Maximum acceleration responses obtained for the 3-story scaled-down bare frame and the braced frames at the second floor	182
5.23	Maximum acceleration responses obtained for the 3-story scaled-down bare frame and the braced frames at the third floor	183
5.24	Maximum base shear responses obtained for the 3-story scaled-down bare frame and the braced frames	183
5.25	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the first floor	185

5.26	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the second floor	186
5.27	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the third floor	186
5.28	Maximum acceleration responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the first floor	187
5.29	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the second floor	187
5.30	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the third floor	188
5.31	Maximum base shear responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED	188
5.32	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the first floor	190
5.33	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the second floor	191
5.34	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the third floor	191
5.35	Maximum acceleration responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the first floor	192
5.36	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the second floor	192



5.37	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the third floor	193
5.38	Maximum base shear responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED	193
5.39	Maximum displacement ratios obtained for the 3-story scaled-down frames at the first floor	195
5.40	Maximum displacement ratios obtained for the 3-story scaled-down frames at the second floor	196
5.41	Maximum displacement ratios obtained for the 3-story scaled-down frames at the third floor	196
5.42	Maximum acceleration ratios obtained for the 3-story scaled-down frames at the first floor	197
5.43	Maximum displacement ratios obtained for the 3-story scaled-down frames at the second floor	197
5.44	Maximum displacement ratios obtained for the 3-story scaled-down frames at the third floor	198
5.45	Maximum base shear ratios obtained for the 3-story scaled-down frames	198
5.46	Maximum displacement responses obtained for the 3-story scaled-down bare frame and the braced frames at the first floor	201
5.47	Maximum displacement responses obtained for the 3-story scaled-down bare frame and the braced frames at the second floor	201
5.48	Maximum displacement responses obtained for the 3-story scaled-down bare frame and the braced frames at the third floor	202
5.49	Maximum acceleration responses obtained for the 3-story scaled-down bare frame and the braced frames at the first floor	202

5.50	Maximum acceleration responses obtained for the 3-story scaled-down bare frame and the braced frames at the second floor	203
5.51	Maximum acceleration responses obtained for the 3-story scaled-down bare frame and the braced frames at the third floor	203
5.52	Maximum base shear responses obtained for the 3-story scaled-down bare frame and the braced frames	204
5.53	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the first floor	205
5.54	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the second floor	206
5.55	Maximum displacement responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the third floor	206
5.56	Maximum acceleration responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the first floor	207
5.57	Maximum acceleration responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the second floor	207
5.58	Maximum acceleration responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED at the third floor	208
5.59	Maximum base shear responses obtained for the 3-story scaled-down chevron braced frame and frame with the proposed VED	208
5.60	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the first floor	210

5.61	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the second floor	210
5.62	Maximum displacement responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the third floor	211
5.63	Maximum acceleration responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the first floor	211
5.64	Maximum acceleration responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the second floor	212
5.65	Maximum acceleration responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED at the third floor	212
5.66	Maximum base shear responses obtained for the 3-story scaled-down diagonally braced frame and frame with the conventional VED	213
5.67	Reduction in the dynamic responses when the proposed and conventional viscoelastic dampers are added to the 3-story scaled-down braced systems	214
5.68	Effect of change in the thickness of the VE layer on displacement responses	216
5.69	Effect of change in the thickness of the VE layer on acceleration responses	217
5.70	Effect of change in the thickness of the VE layer on base shear responses	217
5.71	Effect of change in the area of the VE layer on displacement responses	219
5.72	Effect of change in the area of the VE layer on acceleration responses	219
5.73	Effect of change in the area of the VE layer on base shear responses	220

5.74	Displacement responses of the 3-story scaled-down bare frame at the first floor obtained from experimental test and numerical analysis	222
5.75	Displacement responses of the 3-story scaled-down bare frame at the second floor obtained from experimental test and numerical analysis	223
5.76	Displacement responses of the 3-story scaled-down bare frame at the third floor obtained from experimental test and numerical analysis	223
5.77	Comparison of force-displacement responses of the conventional VED obtained by SAP2000 and ABAQUS for 50 % strain and loading frequency of 0.1 Hz	225
5.78	Comparison of force-displacement responses of the conventional VED obtained by SAP2000 and ABAQUS for 50 % strain and loading frequency of 0.2 Hz	225
5.79	Comparison of force-displacement responses of the conventional VED obtained by SAP2000 and ABAQUS for 50 % strain and loading frequency of 1 Hz	226
5.80	Comparison of force-displacement responses of the conventional VED obtained by SAP2000 and ABAQUS for 50 % strain and loading frequency of 2.5 Hz	226
5.81	Comparison of force-displacement responses of the conventional VED obtained by SAP2000 and ABAQUS for 50 % strain and loading frequency of 5 Hz	227
5.82	Stress contour based on the equivalent static analysis	228
5.83	Axial force diagram	229
5.84	Moment diagram	229
5.85	Schematic view of force-displacement relationship used in nonlinear analysis together with different stages of damages	230
5.86	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 1 record (PGA=0.1 g)	232

5.87	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 2 record (PGA=0.1 g)	233
5.88	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 3 record (PGA=0.1 g)	233
5.89	Average of maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in low group (PGA=0.1 g)	234
5.90	Deformed shape of the analyzed frames for low 1 record (PGA=0.1 g)	235
5.91	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 1 record (PGA=0.1 g)	236
5.92	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 2 record (PGA=0.1 g)	237
5.93	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 3 record (PGA=0.1 g)	237
5.94	Average of maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in medium group (PGA=0.1 g)	239
5.95	Deformed shape of the analyzed frames for medium 1 record (PGA=0.1g)	240
5.96	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 1 record (PGA=0.1g)	241
5.97	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 2 record (PGA=0.1g)	242

5.98	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 3 record (PGA=0.1g)	242
5.99	Average of maximum displacement responses of the 10-story full-scale bare frame and frames with the conventional and proposed VEDs when excited by records in high group (PGA=0.1 g)	243
5.100	Deformed shape of the analyzed frames for high 1 record (PGA=0.1 g)	244
5.101	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 1 record (PGA=0.1 g)	245
5.102	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 2 record (PGA=0.1 g)	246
5.103	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 3 record (PGA=0.1 g)	246
5.104	Average of maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in low group (PGA=0.1 g)	248
5.105	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 1 record (PGA=0.1 g)	249
5.106	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 2 record (PGA=0.1 g)	250
5.107	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 3 record (PGA=0.1 g)	250

5.108	Average of maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in medium group (PGA=0.1 g)	251
5.109	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 1 record (PGA=0.1g)	252
5.110	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 2 record (PGA=0.1g)	252
5.111	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 3 record (PGA=0.1g)	253
5.112	Average of maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in high group (PGA=0.1 g)	254
5.113	Average of maximum base shear responses of the 10-story bare frame and frames with the conventional and proposed VEDs for low A/V group (PGA=0.1g)	255
5.114	Average of maximum base shear responses of the 10-story bare frame and frames with the conventional and proposed VEDs for medium A/V group (PGA=0.1g)	256
5.115	Average of maximum base shear responses of the 10-story bare frame and frames with the conventional and proposed VEDs for high A/V group (PGA=0.1g)	256
5.116	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 1 record (PGA=0.3 g)	258
5.117	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 2 record (PGA=0.3 g)	258

5.118	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 3 record (PGA=0.3 g)	259
5.119	Average of maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in low group (PGA=0.3 g)	260
5.120	Deformed shape of the analyzed frames for low 1 record (PGA=0.3 g)	261
5.121	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 1 record (PGA=0.3 g)	262
5.122	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 2 record (PGA=0.3 g)	262
5.123	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 3 record (PGA=0.3 g)	263
5.124	Average of maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in medium group (PGA=0.3 g)	264
5.125	Deformed shape of the analyzed frames for medium 1 record (PGA=0.3g)	265
5.126	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 1 record (PGA=0.3g)	266
5.127	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 2 record (PGA=0.3g)	267
5.128	Maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 3 record (PGA=0.3g)	267



5.129	Average of maximum displacement responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in high group (PGA=0.3 g)	268
5.130	Deformed shape of the analyzed frames for high1 record (PGA=0.3 g)	269
5.131	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 1 record (PGA=0.3 g)	270
5.132	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 2 record (PGA=0.3 g)	271
5.133	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by low 3 record (PGA=0.3 g)	271
5.134	Average of maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in low group (PGA=0.3 g)	272
5.135	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 1 record (PGA=0.3 g)	273
5.136	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 2 record (PGA=0.3 g)	274
5.137	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by medium 3 record (PGA=0.3 g)	274
5.138	Average of maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in medium group (PGA=0.3 g)	276

5.139	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 1 record (PGA=0.3g)	277
5.140	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 2 record (PGA=0.3g)	277
5.141	Maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by high 3 record (PGA=0.3g)	278
5.142	Average of maximum acceleration responses of the 10-story bare frame and frames with the conventional and proposed VEDs when excited by records in high group (PGA=0.3 g)	279
5.143	Average of maximum base shear responses of the 10-story bare frame and frames with the conventional and proposed VEDs for low A/V group (PGA=0.3g)	280
5.144	Average of maximum base shear responses of the 10-story bare frame and frames with the conventional and proposed VEDs for medium A/V group (PGA=0.3g)	281
5.145	Average of maximum base shear responses of the 10-story bare frame and frames with the conventional and proposed VEDs for high A/V group (PGA=0.3g)	281

## LIST OF ABBREVIATIONS

VE	-	Viscoelastic
MDs	-	Metallic Dampers
FDs	-	Friction Dampers
VEDs	-	Viscoelastic Dampers
VED	-	Viscoelastic Damper
VFDs	-	Viscous Fluid Dampers
TMDs	-	Tuned Mass Dampers
TLDs	-	Tuned Liquid Dampers
ADAS	-	Added Damping and Stiffness
BRB	-	Buckling-Restrained Brace
H-BRB	-	Hybrid-Buckling-Restrained Brace
VF	-	Viscous Fluid
PTMD	-	Pounding Tuned Mass Damper
TLCD	-	Tuned Liquid Column Damper
VPD	-	Visco-Plastic Damper
VCD	-	Viscoelastic Coupling Damper
MRPRA	-	Malaysian Rubber Producers' Research Association
UHDNR	-	Ultra-High Damping Natural Rubber
TBD	-	Toggle-Braced-Damper
RC	-	Reinforced Concrete
HMD	-	Hybrid Mass Damper
SMM	-	Standard Maxwell Model
SKM	-	Standard Kelvin Model
FDM	-	Fractional Derivatives Model
MPL	-	Modified Power Law

GEB	-	Global Energy Bound
LVDT	-	Linear Variable Differential Transformer
FE	-	Finite Element
PGA	-	Peak Ground Acceleration
AISC	-	American Institute of Steel Construction
FEMA	-	Federal Emergency Management Agency
ASTM	-	American Society for Testing and Materials
CVED	-	Conventional Viscoelastic Damper
PVED	-	Proposed Viscoelastic Damper

## LIST OF SYMBOLS

$T_g$	-	Glass transition temperature
$\delta$	-	Phase angle
$\Delta t$	-	Time interval
$N$	-	Number of time steps
$G'$	-	Shear storage modulus
$G''$	-	Shear loss modulus
$\eta$	-	Loss factor
$u_{\max}$	-	Maximum displacement
$T$	-	Ambient temperature
$f$	-	Excitation frequency
$e$	-	Natural logarithm
$K_d$	-	Damper stiffness
$K$	-	Spring stiffness
$C$	-	Dashpot damping
$E$	-	Young's modulus
$\nu$	-	Poisson's ratio
$R$	-	Response reduction ratio
$g$	-	Gravity
$\eta_{(\text{damper-brace})}$	-	Viscoelastic damper assembly loss factor
$K_{\text{brace}}$	-	Brace stiffness
$K_{\text{damper}}$	-	Viscoelastic damper stiffness
$\eta_{\text{damper}}$	-	Viscoelastic damper loss factor
$K_{(\text{damper-brace})}$	-	Viscoelastic damper assembly stiffness
$\xi$	-	Required damping ratio
$K_i$	-	$i$ th story stiffness

$n$	-	Number of viscoelastic layer
$A$	-	Area of viscoelastic layer
$h$	-	Thickness of viscoelastic layer
$\theta$	-	Angle of viscoelastic damper
$\varepsilon$	-	True strain
$\sigma$	-	True stress
$\varepsilon$	-	Nominal strain
$\sigma_0$	-	Nominal stress
$E^*$	-	Complex Young's modulus
$E'$	-	Shear Young's modulus
$A/V$	-	Peak ground acceleration to velocity
$W$	-	Energy dissipation per cycle
$F_1$	-	Force at maximum displacement
$F_2$	-	Force at zero displacement
$u_i$	-	Displacement amplitude of the peak at time $i$
$u_{(i+nj)}$	-	Displacement amplitude of the peak $n$ periods away

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	Design of the scaled viscoelastic damper	311
B	Amount of induced moment due to partial break in the continuity of the beam	313
C	Frequency obtained by the used accelerometers for six different excitations	314
D	Natural frequency and damping ratio of the constructed frames	315
E	Prony series coefficients	316
F	Design of the real size damper	317

## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Background**

An earthquake is the perceptible shaking of the surface of the Earth, resulted by the sudden release of energy in the Earth's crust that creates seismic waves. They are among the most feared natural hazards which cause devastating consequences every year due to destruction of buildings and other structures. For example, the Bam (Iran) earthquake of magnitude 6.6, happened on Dec. 26, 2003, led to enormous loss of life and property. More than 27000 people died, eighty-five to ninety percent of buildings and infrastructures were either damaged or destroyed, and left an estimated 100000 people homeless. Even more recently, the April 2015 Nepal earthquake killed more than 8800 people and injured more than 23000. Hundreds of thousands of people were made homeless with entire villages flattened. It also destroyed century-old buildings at the UNESCO World Heritage sites.

Seismic events usually caused damages in structures that have not been properly designed for earthquake or are constructed prior to the formulation of seismic design guidelines. The seismic performances of these buildings are often unsatisfactory. They often have inadequate lateral strength, stiffness and inadequate



ductility. Figure 1.1 shows some of the structural failure around the world due to earthquake. Widespread damage from the 1929 Murchison and 1931 Hawke's Bay earthquakes had a profound effect on public perceptions of the hazard posed by earthquakes. Attention was focused on weaknesses in building construction, especially poor building standards and lack of any provision for earthquake-resistant design. This led to formulation of seismic design guidelines which was incorporated into the building codes. The current building codes (i.e., ASCE, Eurocode 8) recommend that earthquake loading must be considered in design in addition to the gravity load for constructing a structure in a seismically active zone. In addition, the buildings constructed prior the current seismic design codes also require retrofitting or upgrading to be protected from earthquakes.



New Zealand earthquake (2011)



Iran earthquake (Bam 2003)



Nepal earthquake (2015)




Japan earthquake (2011)

**Figure 1.1** Structural failure around the world due to earthquake [1, 2]

Nowadays, due to construction of tall and super tall buildings demand for safe and economical seismic design has increased. Therefore, protecting structures together with their occupants and contents from destructive natural hazards such as earthquakes have become a constant challenging task for civil engineers. In general, there are two fundamental approaches in seismic design of building structures; to increase structural capacity (conventional approach) or to decrease seismic demand (innovative approach). Conventional seismic design relies on strategies that increase the strength, stiffness and ductility of a building to control earthquake induced motions. According to the conventional approach, structures should not collapse under a major earthquake, even if the building itself is severely damaged. Therefore, conventional seismic design is not appropriate for structures such as hospital and fire station which must remain functional after earthquake to continue their serviceability. Moreover, this approach does not provide an appropriate safety margin for the design of tall building structures.

To overcome the shortcomings inherent in the philosophy of the conventional seismic design, a number of innovative approaches have been introduced in recent years [3, 4]. These approaches rely on dissipating the seismic energy through improving dynamic characteristics of structures. Therefore, vibration induced by dynamic loads is controlled and the amount of seismic force transmitted to the structure is reduced. The modern approach of seismic design can be classified into two groups including systems that increase the natural period of the structures and those that increase their damping ratio. The latter aims to increase the damping level of structure and reduce their seismic demand by adding some supplemental devices known as dampers. Usage of supplemental damping devices for dissipating seismic induced energy of buildings has gained increasing interest in the past few decades. Variety of energy dissipation systems have been developed and investigated while new types of dampers is under development. Example of typical energy dissipating devices are shown in Figure 1.2. These control system devices can act in passive, active and semi-active method or a combination of them. Active and semi-active control systems are evolution of passive control technologies to improve the effectiveness and efficiency of vibration control devices. In such systems, controlling forces are applied to the damper through external source powers like actuator(s) based on the feedback

from sensors that measure the excitation and/or the response of the structure. The major drawback of these systems is that the power source which is essential to activate the dampers might be disrupted during seismic events. In addition, instruments of active or semi-active systems such as actuators, sensors or computer are very costly and a relatively short service life is still a problem for these instruments [5].



**Figure 1.2** Example of typical passive energy dissipating devices based on Soong T.T. et al, 1997 [6]

Because passively controlled devices do not require an external power source for operation and utilize the motion of the structure to develop the control forces, the implementation of this type of devices has outdistanced significantly the implementation of others [7]. In this study, a novel viscoelastic damper is proposed to improve the seismic performance of structures and to overcome the drawbacks of the conventional viscoelastic damper. The proposed damper consists of a single layer viscoelastic material sandwiched between two steel plates. The damper is placed in the mid-span of a beam and connects to two braces that form an inverted V shape. The effectiveness of the proposed viscoelastic damper was evaluated experimentally and numerically. The proposed viscoelastic damper shares the advantages of a variety of existing dampers and can dissipate input energy under all levels of vibrations. The

main advantage of this new damper is that it does not occupy the span of entire frames. Therefore, from architectural point of view such configuration is preferable especially when it comes to seismic retrofit via viscoelastic (VE) damper.

## 1.2 Problem statement

The use of passive energy dissipation devices has become very popular in recent years. The performance of these devices in reducing the seismic response of buildings was extensively investigated experimentally as well as numerically and their effectiveness were widely proven. Currently, viscoelastic dampers are widely used in many countries as energy dissipation devices to reduce earthquake-induced vibrations in new and existing buildings. Viscoelastic dampers do not only have the advantages of easier installation as well as manufacturing, good durability and low cost, but also they have high energy dissipation capacity. Conventionally, viscoelastic dampers are generally installed within a diagonal brace configuration for structures such as buildings. The application of the devices in the traditional configuration, however, could present some disadvantages, particularly when they are applied in building retrofits. In fact, even if in new structures the columns are designed to bear the additional axial forces induced by the dampers, in existent buildings these forces can create an untimely failure of the columns that are connected to the VE dampers [8]. In addition, the aforementioned configuration provides a stiff structural system which may lead to lower shear deformation in VE material, thus lowering their efficiency and energy dissipation. Excluding these matters, the application of this type of retrofitting often interferes with architectural requirements such as open space and unobstructed view as the configuration occupies entire bays in frames [8]. In recent years, several new configurations have been developed including the toggle-brace and the scissor-jack dissipation system [9, 10]. However, analysis and detailing of these configurations are so complex. In this research, a novel viscoelastic damper is proposed in order to improve the seismic performance of steel structures and to overcome the drawbacks of the conventional VEDs. The proposed VED can be used

in design of new structures or retrofitting of existing structures. The configuration of the proposed VED results in magnifying the displacement of the damper and increases its efficiency. In addition, using the proposed VED results in less axial forces applied to the column and is preferred for retrofitting purpose. In this research, damper induced column axial forces are addressed quantitatively by degree of plastic hinge formation and are fully explained later. On the other hand, the configuration is preferred from architectural point of view as it does not occupy the span of entire frames in contrast to the conventional VED.

### **1.3 Objective of the research**

The main aim of this project is to develop a novel viscoelastic damper for seismic retrofit of steel structures. Specific objectives are:

- i) To study dynamic behavior of frame with and without the conventional viscoelastic damper.
- ii) To propose a new type of viscoelastic damper considering drawbacks of the conventional viscoelastic dampers.
- iii) To investigate experimentally and numerically the efficiency of the proposed viscoelastic damper installed inside a scaled down steel structure.
- iv) To determine numerically the effect of different viscoelastic layer dimensions on the performance of the proposed viscoelastic damper.
- v) To propose a simplified numerical model for the viscoelastic dampers in structural analysis of multi-storey structures.

- vi) To evaluate numerically the seismic performance of the proposed viscoelastic damper in multi-storey structures by using the proposed simplified model.

#### **1.4 Scope of the research**

This research is intended to propose a novel viscoelastic device to improve seismic performance of structures and to overcome the deficiency of the conventional viscoelastic damper. Effectiveness of the proposed damper is evaluated through comparing responses of a 3-story scaled down bare frame to a frame with and without the conventional and proposed viscoelastic damper. Both experimental and numerical approaches are employed for this purpose. In addition, seismic performance of the damper is investigated by nonlinear time history analysis of full-scale 10-story frame. The main response parameters that are studied in this research are displacement and acceleration through the height of the building. The scope of this investigation is as follow:

- Conventional viscoelastic damper uses two layers of viscoelastic material with the size of 60 mm×20 mm×5 mm.
- In this research, the effect of changes in the dimensions of viscoelastic layer on performance of the proposed viscoelastic damper are only investigated.
- In this study, different sizes of viscoelastic layers are employed for the proposed viscoelastic damper. The size of viscoelastic layers includes 900 mm<sup>2</sup> (30 mm×30 mm), 2500 mm<sup>2</sup> (50 mm×50 mm) and 4900 mm<sup>2</sup> (70 mm×70 mm) in area with thickness of 3 mm, 5 mm and 7 mm.
- The mechanical properties of viscoelastic material are tested at various frequencies ranged from 0.1 Hz to 5 Hz and strains of 5 %, 20 % and 50 %.
- The effect of temperature on the properties of viscoelastic material are not considered in this research.
- Performance of the damper installed at the first level of a 3-story steel frame with scale of 1:3 is investigated experimentally under harmonic excitation only.

- Due to limitation of harmonic shaking table, responses of the fully damped frame is studied numerically using ABAQUS software.
- Excitation frequency included 20 % below and above the frame's resonance frequency.
- Response of a 10-story building equipped with the proposed damper was studied numerically using SAP2000 software.

### **1.5 Outline of the research**

This research is subdivided into six chapters. The chapters are organized as follow:

- i. Chapter 1 presents an introduction and background of the study as well as objectives and scope of the research, and explains problem statement and motivation of this research.
- ii. Chapter 2 presents a literature review on technical background of issues related to the viscoelastic dampers. In addition, nature of seismic loads and an overview of several supplemental damping devices are explained.
- iii. Chapter 3 describes research methodology to attain the objectives of this study. In this chapter, both experimental and numerical approach are discussed in details.
- iv. Chapter 4 presents the results obtained experimentally for performance evaluation of the proposed viscoelastic damper. The results of mechanical properties of materials used for experimental tests are also displayed in this chapter.

- v. Chapter 5 presents the results obtained by numerical studies for performance evaluation of the proposed viscoelastic damper. In addition, effect of the viscoelastic layer sizes on the performance of the proposed viscoelastic damper is investigated in this chapter. Finally, a simplified model is proposed for analysis of high rise buildings.
  
- vi. Chapter 6 summarizes the results and presents a final conclusion along with recommendations for future work.



## REFERENCES

1. Manafpour, A. *Bam earthquake, Iran: Lessons on the seismic behaviour of building structures*. in *14th World Conference on Earthquake Engineering, Beijing, China*. 2008.
2. Lohani, T.N., et al., *Challenges after earthquakes: lessons learnt from the 2015 nepal earthquake*. 2017.
3. Zhang, B.-L., Q.-L. Han, and X.-M. Zhang, *Recent advances in vibration control of offshore platforms*. *Nonlinear Dynamics*, 2017: p. 1-17.
4. Soong, T.T. and M.C. Constantinou, *Passive and active structural vibration control in civil engineering*. Vol. 345. 2014: Springer.
5. Tan, X., *Vibration control of structures with viscoelastic dampers*. 1998, The Hong Kong Polytechnic University.
6. Marko, J., D. Thambiratnam, and N. Perera, *Influence of damping systems on building structures subject to seismic effects*. *Engineering Structures*, 2004. 26(13): p. 1939-1956.
7. Ji, X., et al., *Damping identification of a full- scale passively controlled five-story steel building structure*. *Earthquake Engineering & Structural Dynamics*, 2013. 42(2): p. 277-295.
8. Passoni, C., et al. *Existing structures connected with dampers: state of the art and future developments*. in *2ECEES: 2nd European Conference on Earthquake Engineering and Seismology, Istanbul, Turkey, 24-29 August 2014*. 2014. EAEE (European Association of Earthquake Engineering).
9. Şigaher, A.N. and M.C. Constantinou, *Scissor-jack-damper energy dissipation system*. *Earthquake Spectra*, 2003. 19(1): p. 133-158.

10. Hwang, J.-S., Y.-N. Huang, and Y.-H. Hung, *Analytical and experimental study of toggle-brace-damper systems*. Journal of structural engineering, 2005. 131(7): p. 1035-1043.
11. Park, S., *Analytical modeling of viscoelastic dampers for structural and vibration control*. International Journal of Solids and Structures, 2001. 38(44): p. 8065-8092.
12. Xu, X.Q., *Effectiveness of dampers in response of structures to near-fault earthquakes*. 2006, Concordia University.
13. Ansal, A., *Perspectives on European earthquake engineering and seismology*. Vol. 1. 2014: Springer.
14. Symans, M., et al., *Energy dissipation systems for seismic applications: current practice and recent developments*. Journal of structural engineering, 2008. 134(1): p. 3-21.
15. Symans, M.D. and M.C. Constantinou, *Semi-active control systems for seismic protection of structures: a state-of-the-art review*. Engineering structures, 1999. 21(6): p. 469-487.
16. Soong, T. and B. Spencer, *Supplemental energy dissipation: state-of-the-art and state-of-the-practice*. Engineering structures, 2002. 24(3): p. 243-259.
17. Spencer Jr, B. and S. Nagarajaiah, *State of the art of structural control*. Journal of structural engineering, 2003. 129(7): p. 845-856.
18. Constantinou, M. and M. Symans, *Seismic response of structures with supplemental damping*. The Structural Design of Tall Buildings, 1993. 2(2): p. 77-92.
19. Whittaker, A. and M. Constantinou, *Seismic Energy Dissipation Systems for Buildings*, in *Earthquake Engineering: From Engineering Seismology to Performance-Based Engineering*. 2004, CRC Press.
20. Chen, Y.F., J. Liu, and Y. Shi, *Retrofitting of a seismically deficient building*. Journal of Structural Integrity and Maintenance, 2016. 1(3): p. 107-113.
21. Huang, M., *Application of Vibration Damping Technology in High Rise Building*. Open Construction and Building Technology Journal, 2015. 9: p. 131-134.
22. Chopra, A.K., *Dynamics of structures*. Vol. 3. 1995: Prentice Hall New Jersey.
23. Chang, K., et al., *Seismic response of a 2/5 scale steel structure with added viscoelastic dampers*. NCEER Rep, 1991. 91: p. 0012.

24. Kasai, K., Y. Fu, and A. Watanabe, *Passive control systems for seismic damage mitigation*. Journal of Structural Engineering, 1998. 124(5): p. 501-512.
25. Brady, P.A., *Experimental and Analytical Investigation of the Dynamic Response of Lightly Reinforced Concrete Frames and Viscoelastic Dampers*. 2004, University of Illinois at Urbana-Champaign.
26. Kim, D.H., et al., *Wind- induced vibration control of tall buildings using hybrid buckling- restrained braces*. The Structural Design of Tall and Special Buildings, 2014. 23(7): p. 549-562.
27. Ibrahim, Y.E.-H., *A new visco-plastic device for seismic protection of structures*. 2005, Virginia Tech.
28. Lee, D.-G., S.-I. Hong, and J.-K. Kim, *Analysis of a Building Structure with Added Viscoelastic Dampers*. Journal of the Earthquake Engineering Society of Korea, 1998. 2(3): p. 27-35.
29. Muresan, C.I., E.H. Dulf, and O. Prodan, *A fractional order controller for seismic mitigation of structures equipped with viscoelastic mass dampers*. Journal of Vibration and Control, 2016. 22(8): p. 1980-1992.
30. Villaverde, R., *Reduction seismic response with heavily- damped vibration absorbers*. Earthquake Engineering & Structural Dynamics, 1985. 13(1): p. 33-42.
31. Kaynia, A.M., J.M. Biggs, and D. Veneziano, *Seismic effectiveness of tuned mass dampers*. Journal of the Structural Division, 1981. 107(8): p. 1465-1484.
32. Sladek, J.R. and R.E. Klingner, *Effect of tuned-mass dampers on seismic response*. Journal of structural engineering, 1983. 109(8): p. 2004-2009.
33. Zhang, P., et al., *Seismic control of power transmission tower using pounding TMD*. Journal of Engineering Mechanics, 2012. 139(10): p. 1395-1406.
34. Tian, L., et al., *Vibration Control of a Power Transmission Tower with Pounding Tuned Mass Damper under Multi-Component Seismic Excitations*. Applied Sciences, 2017. 7(5): p. 477.
35. Wakahara, T., T. Ohyama, and K. Fujii, *Suppression of wind-induced vibration of a tall building using tuned liquid damper*. Journal of Wind Engineering and Industrial Aerodynamics, 1992. 43(1-3): p. 1895-1906.
36. Fujino, Y., et al., *Tuned liquid damper (TLD) for suppressing horizontal motion of structures*. Journal of Engineering Mechanics, 1992. 118(10): p. 2017-2030.

37. Ashasi-Sorkhabi, A., et al., *Experimental investigations of tuned liquid damper-structure interactions in resonance considering multiple parameters*. Journal of Sound and Vibration, 2017. 388: p. 141-153.
38. Xu, Y., B. Samali, and K. Kwok, *Control of along-wind response of structures by mass and liquid dampers*. Journal of Engineering Mechanics, 1992. 118(1): p. 20-39.
39. Samali, B., et al. *Effectiveness of optimised tuned liquid column dampers in controlling vibration of tall buildings subject to strong ground motions*. in *Proc. 2nd International Conf. on Highrise Buildings*. 1992.
40. Xu, Z.-D., D.-X. Wang, and C.-F. Shi, *Model, tests and application design for viscoelastic dampers*. Journal of Vibration and Control, 2011. 17(9): p. 1359-1370.
41. Samali, B. and K. Kwok, *Use of viscoelastic dampers in reducing wind-and earthquake-induced motion of building structures*. Engineering Structures, 1995. 17(9): p. 639-654.
42. Nielsen, E.J., et al. *Viscoelastic damper overview for seismic and wind applications*. in *1996 Symposium on Smart Structures and Materials*. 1996. International Society for Optics and Photonics.
43. Shen, K. and T. Soong, *Modeling of viscoelastic dampers for structural applications*. Journal of Engineering Mechanics, 1995. 121(6): p. 694-701.
44. Sabetahd, R., K. Jafarzade, and Y.M.A. Lotfollahi, *Performance evaluation of visco-elastic dampers in near-fault earthquakes using nonlinear time-history analysis*. 2011.
45. Charney, F.A. and Y.E. Ibrahim. *New visco-plastic passive energy device*. in *Proc. of 13th World Conference on Earthquake Engineering*. 2004.
46. Ibrahim, Y.E., J. Marshall, and F.A. Charney, *A visco-plastic device for seismic protection of structures*. Journal of Constructional Steel Research, 2007. 63(11): p. 1515-1528.
47. Christopoulos, C. and M. Montgomery, *Viscoelastic coupling dampers (VCDs) for enhanced wind and seismic performance of high-rise buildings*. Earthquake Engineering & Structural Dynamics, 2013. 42(15): p. 2217-2233.
48. Montgomery, M. and C. Christopoulos, *Experimental validation of viscoelastic coupling dampers for enhanced dynamic performance of high-rise buildings*. Journal of Structural Engineering, 2014. 141(5): p. 04014145.

49. Pant, D.R., M. Montgomery, and C. Christopoulos, *Analytical Study on the Dynamic Properties of Viscoelastically Coupled Shear Walls in High-Rise Buildings*. Journal of Engineering Mechanics, 2017. 143(8): p. 04017047.
50. Schaefer, R.J., *Mechanical properties of rubber*. Harris' Shock and Vibration Handbook, Sixth edition, A. Piersol, T. Paez (Eds), McGraw-Hill Companies Inc, 2010: p. 33.1-33.18.
51. Yokota, H., et al., *Structural control for seismic load using viscoelastic dampers*. Proc., 10WCEE, 1992.
52. Lee, K., et al., *Non-linear rate-dependent hysteresis model for structural dampers made from ultra-high damping natural rubber*. Journal of Rubber Research, 2004. 7(2): p. 79-103.
53. Constantinou, M.C., et al., *Toggle-brace-damper seismic energy dissipation systems*. Journal of Structural Engineering, 2001. 127(2): p. 105-112.
54. Banisheikholeslami, A., F. Behnamfar, and M. Ghandil, *A beam-to-column connection with visco-elastic and hysteretic dampers for seismic damage control*. Journal of Constructional Steel Research, 2016. 117: p. 185-195.
55. Tezcan, S.S. and O. Uluca, *Reduction of earthquake response of plane frame buildings by viscoelastic dampers*. Engineering Structures, 2003. 25(14): p. 1755-1761.
56. Min, K.-W., J. Kim, and S.-H. Lee, *Vibration tests of 5-storey steel frame with viscoelastic dampers*. Engineering Structures, 2004. 26(6): p. 831-839.
57. Mortezaei, A. and S.M. Zahrai, *Seismic response of reinforced concrete building with viscoelastic damper under near field earthquake*. Asian Journal of Civil Engineering, 2009. 9(3): p. 347-359.
58. Mazza, F. and A. Vulcano, *Control of the earthquake and wind dynamic response of steel- framed buildings by using additional braces and/or viscoelastic dampers*. Earthquake Engineering & Structural Dynamics, 2011. 40(2): p. 155-174.
59. Ribakov, Y. and A.M. Reinhorn, *Design of amplified structural damping using optimal considerations*. Journal of Structural Engineering, 2003. 129(10): p. 1422-1427.
60. Charney, F. and R. McNamara. *Use of damped mode shapes in visualizing the efficiency of an auxiliary damped 39-story office building*. in *Seventh US National Conference on Earthquake Engineering (7NCEE)*. 2002.

61. Constantinou, M.C., *Testing and modeling of an improved damper configuration for stiff structural systems*. 1997, State University of New York Buffalo.
62. Bo, L. and L. Xingwen, *Seismic design of structure with improved toggle-brace-damper system*.
63. Constantinou, M.C., *Highly effective seismic energy dissipation apparatus*. 2002, Google Patents.
64. Kang, J.D. and H. Tagawa, *Seismic response of steel structures with seesaw systems using viscoelastic dampers*. *Earthquake Engineering & Structural Dynamics*, 2013. 42(5): p. 779-794.
65. Park, K.-S., H.-M. Koh, and D. Hahm, *Integrated optimum design of viscoelastically damped structural systems*. *Engineering Structures*, 2004. 26(5): p. 581-591.
66. Chang, K., M. Lai, and E. Nielsen. *Seismic response of viscoelastically damped structure under strong earthquake ground motions*. in *Earthquake Engineering: Proceedings of the Tenth World Conference on Earthquake Engineering, 19-24 July, 1992, Madrid, Spain*. 1992. CRC Press.
67. Xu, Z.-D., C. Xu, and J. Hu, *Equivalent fractional Kelvin model and experimental study on viscoelastic damper*. *Journal of Vibration and Control*, 2015. 21(13): p. 2536-2552.
68. Xu, Z.-D. and C.-F. Shi. *Energy Dissipation Analysis on Real Application by using ViscoElastic Dampers*. in *14th World Conference on Earthquake Engineering*. 2008.
69. Shen, K., et al., *Seismic behaviour of reinforced concrete frame with added viscoelastic dampers*. *Engineering Structures*, 1995. 17(5): p. 372-380.
70. Mahmoodi, P. and C.J. Keel. *Performance of viscoelastic structural dampers for the Columbia Center Building*. in *Building Motion in Wind*:. 1986. ASCE.
71. Keel, C.J. and P. Mahmoodi. *Design of viscoelastic dampers for Columbia Center Building*. in *Building Motion in Wind*:. 1986. ASCE.
72. Cho, K.-P., et al., *Viscoelastic damping for wind-excited motion of a five-story building frame*. *Journal of Wind Engineering and Industrial Aerodynamics*, 1998. 77: p. 269-281.
73. Lin, R., et al., *An experimental study on seismic behaviour of viscoelastically damped structures*. *Engineering Structures*, 1991. 13(1): p. 75-84.

74. Aiken, I.D. and J.M. Kelly, *Earthquake simulator testing and analytical studies of two energy-absorbing systems for multistory structures*. 1990, University of California, Berkeley.
75. Chang, K., et al., *Seismic behavior and design guidelines for steel frame structures with added viscoelastic dampers*. 1993: National Center for Earthquake Engineering Research.
76. Chang, K., et al., *Effect of ambient temperature on viscoelastically damped structure*. *Journal of Structural Engineering*, 1992. 118(7): p. 1955-1973.
77. Chang, K., et al., *Seismic behavior of steel frame with added viscoelastic dampers*. *Journal of structural engineering*, 1995. 121(10): p. 1418-1426.
78. Xu, Z.-D., *Earthquake mitigation study on viscoelastic dampers for reinforced concrete structures*. *Journal of Vibration and Control*, 2007. 13(1): p. 29-43.
79. Vijay, U., P.K. Rajkumar, and P. Ravichandran, *Seismic response control of RC structure using viscoelastic dampers*. *Indian Journal of Science and Technology*, 2015. 8(28).
80. Aye, S. and D.K.M. Aung, *Comparative Study on Seismic Response of RC Structure Using Viscous Dampers and Viscoelastic Dampers*. 2014, IJSETR.
81. Lavanya, K. and K. Manjunatha, *Comparative study on seismic effects of fluid viscous and viscoelastic dampers in rc building*. 2016.
82. Guo, A. and H. Gao, *Seismic Behavior of Posttensioned Concrete Bridge Piers with External Viscoelastic Dampers*. *Shock and Vibration*, 2016. 2016.
83. MUNSHI, J.A. *Seismic rehabilitation of non-ductile reinforced concrete gravity frame*. in *Proceedings of Twelfth World Conference Earthquake Engineering*. 2000.
84. Munshi, J. and K. Kasai. *Seismic retrofit of moment resisting frame with viscoelastic dampers*. in *IABSE Symp*. 1995.
85. Kanitkar, R., et al., *Seismic retrofit of a steel moment frame structure using viscoelastic dampers*. *J. of Earthquake Technology*, 1998. 354: p. 207-219.
86. Xu, Z.-D., T. Ge, and Y.-X. Liao, *Chao Xu*. *Journal of Computational and Nonlinear Dynamics* November, 2016. 11: p. 061019-1.
87. Oh, S.-T., *Seismic behavior of a 2/5-scale steel structure with added viscoelastic dampers*. *Dissertation Abstracts International(USA)*, 1992. 53(5): p. 176.

88. Lai, M., et al. *Viscoelastic damper: a damper with linear or nonlinear material*. in *Eleventh World Conference on Earthquake Engineering*. 1996.
89. Chang, K., Y. Lin, and M. Lai, *Seismic analysis and design of structures with viscoelastic dampers*. ISET Journal of Earthquake Technology, 1998: p. 143-166.
90. Lewandowski, R. and Z. Pawlak, *Dynamic analysis of frames with viscoelastic dampers modelled by rheological models with fractional derivatives*. Journal of sound and Vibration, 2011. 330(5): p. 923-936.
91. Lewandowski, R., A. Bartkowiak, and H. Maciejewski, *Dynamic analysis of frames with viscoelastic dampers: a comparison of damper models*. Structural Engineering and Mechanics, 2012. 41(1): p. 113-137.
92. Koh, C.G. and J.M. Kelly, *Application of fractional derivatives to seismic analysis of base-isolated models*. Earthquake engineering & structural dynamics, 1990. 19(2): p. 229-241.
93. Makris, N. and M. Constantinou, *Fractional-derivative Maxwell model for viscous dampers*. Journal of Structural Engineering, 1991. 117(9): p. 2708-2724.
94. Bagley, R.L., *Power law and fractional calculus model of viscoelasticity*. AIAA journal, 1989. 27(10): p. 1412-1417.
95. Viot, P., et al., *Scale effects on the response of composite structures under impact loading*. Engineering Fracture Mechanics, 2008. 75(9): p. 2725-2736.
96. Kittirungsi, B., *A Scaling Methodology for Dynamic Systems: Quantification of Approximate Similitude and Use in Multiobjective Design*. 2008.
97. Rastogi, G., K. Moin, and S. Abbas, *Dimensional analysis and development of similitude rules for dynamic structural models*. Int J Emerg Technol Adv Eng, 2015. 5: p. 68-72.
98. Buckingham, E., *On physically similar systems; illustrations of the use of dimensional equations*. Physical review, 1914. 4(4): p. 345.
99. Engineers, A.S.o.C., *Minimum design loads for buildings and other structures*. Vol. 7. 1994: Amer Society of Civil Engineers.
100. Standard, A., *Standard Specification for Carbon Structural Steel*. 2008, A36/A36M-08, West Conshohocken, USA.



101. Chang, K., Y. Lin, and M. Lai. *Seismic design of structures with added viscoelastic dampers*. in *Proceedings of the 11th World Conference on Earthquake Engineering*. 1996.
102. Zhang, R.-H. and T. Soong, *Seismic design of viscoelastic dampers for structural applications*. *Journal of Structural Engineering*, 1992. 118(5): p. 1375-1392.
103. Phares, B., et al., *Investigation of High-Strength Bolt-Tightening Verification Techniques*. 2016.
104. Committee, R., *Specification for structural joints using ASTM A325 or A490 Bolts*. AISC Inc., Chicago, Illinois, USA, 2004.
105. Standard, A., *E8," Standard Test Methods for Tension Testing of Metallic Materials*. Annual book of ASTM standards, 2004. 3: p. 57-72.
106. Committee, A., *Standard test methods for vulcanized rubber and thermoplastic rubbers and thermoplastic elastomers-Tension [D 412-98]*. New York: American National Standards Institute, 1998.
107. Systèmes, D., *Abaqus 6.14–Analysis Users’s Guide: Volume IV: Elements*. Providence, Rhode Island, 2013.
108. Rijnen, M., et al., *A numerical and experimental study on viscoelastic damping of a 3D structure*. *Journal of Sound and Vibration*, 2015. 349: p. 80-98.
109. Freitas, F.A.C.d., *A theoretical and experimental technique to measure fracture properties in viscoelastic solids*. 2007.
110. Karki, P., *Computational and experimental characterization of bituminous composites based on experimentally determined properties of constituents*. 2010.
111. Berkeley, C., *CSI Analysis Reference Manual for SAP2000*. Computers and Structures, Inc., Berkeley, California, 2007.
112. Construction, A.I.o.S. *Supplement to the Load and Resistance Factor Design Specification for Structural Steel Buildings*. 1989. AISC.
113. Tso, W., T. Zhu, and A. Heidebrecht, *Engineering implication of ground motion A/V ratio*. *Soil Dynamics and Earthquake Engineering*, 1992. 11(3): p. 133-144.
114. Hakansson, P., *Finite Element Modeling of a Rubber Block Exposed to Shock Loading*. Report TFHF-5087, Lund University, Department of Mechanics and Materials, Sweden, 2000.

115. Dall'Asta, A. and L. Ragni, *Experimental tests and analytical model of high damping rubber dissipating devices*. Engineering Structures, 2006. 28(13): p. 1874-1884.
116. Martínez Rodríguez, M., *Analysis of structural damping*. 2006.
117. FEMA, F., *356: Pre Standard and Commentary for the Seismic Rehabilitation of Buildings*. 2000. Federal Emergency Management Agency: Washington, DC, USA.