Boise State University ScholarWorks

2018 Graduate Student Showcase

Conferences

4-26-2018

Semi-Arid Ecosystem Plant Functional Type and LAI from Small Footprint Waveform Lidar

Nayani Ilangakoon Boise State University

Nancy F. Glenn Boise State University

Lucas Spaete

Boise State University

Hamid Dashti Boise State University

Andrew Poley
Boise State University



Semi-arid Ecosystem Plant Functional Type and LAI from Small Footprint Waveform Lidar

Nayani Ilangakoon, Nancy F. Glenn, Lucas Spaete, Hamid Dashti, Andrew Poley Department of Geosciences, Boise State University, Boise, ID, USA https://bcal.boisestate.edu/

INTRODUCTION

- In this study we use variables derived from full waveform lidar to demonstrate their capacity to differentiate key plant functional types (PFTs) including aspen (AS), Douglas fir (DF), juniper (JP), bitterbrush (BT), sagebrush (SG), bare ground (GD); and leaf area index (LAI) in a heterogeneous tree-shrub, co-dominant, semi-arid ecosystem.
- Our results provide a solution to difficulties in deriving shrub and LAI estimates from discrete return lidar in semi-arid ecosystems, in which returns are often too low to characterize the vegetation.
- By imputing our results, we can assess landscape-wide ecosystem structure, state, habitat suitability as well constrain uncertainties in vegetation dynamic models.

FULL WAVEFORM LIDAR

Full waveform lidar emits an amplified laser beam and digitizes the backscattered energy as a near continuous waveform with a high vertical resolution ($^{\sim}1$ ns = 15 cm). The resultant 3D wave contains properties of both the emitted wave and the target (Fig. 1). These waveform properties can be used to infer biophysical properties of vegetation.




Figure 1. Discrete return lidar point cloud from a juniper tree (left). Full waveform lidar representation of the same juniper tree (right).

METHODS

Vegetation was classified into PFTs and the LAI was derived by first geolocating the waveforms and then approximating the backscattered full waveform signals. We implemented a sum of Gaussian approximation and frequency domain deconvolution techniques to extract the variables from waveform signals (Fig. 2). An ensemble random forest algorithm was applied to the derived variables at 1 m and 10 m spatial scales to differentiate the dominant PFTs in the study site (Fig. 3).




Figure 2. Variable derivation from the lidar waveforms.


Waveform Variables Validation Random Training samples base classifiers Majority

Figure 3. Ensemble random forest for PFT classification.


Figure 4. Distribution of rise time and standard deviation of cumulative lidar energy at 90th percentile of PFTs.

1. Associations of waveform derived percent energy, rise time, pulse width, backscatter cross section and deconvolved target profiles separate PFTs of trees and shrubs from each other and from bare ground (Fig. 4).

RESULTS



2. Lidar variables that relate to the target structure (pulse width, energy distribution, and rise time) dominate the variables that relate to radiometric properties (backscatter cross section) (Fig. 4, 5a, and 5b).







Figure 5. a) Distribution of height above ground of selected PFTs. b) Distribution of pulse width and backscatter cross section of PFTs.

3. Inclusion of height above ground improves tree PFT separation, however shrub PFTs and ground were confused (Fig. 5a). Shrub-ground confusion can be eliminated using percent energy (Fig. 4), pulse with and backscatter cross section (Fig. 5 b)



4. Resulted in a high overall PFT accuracy (@1 m, 80%; @10m, 89% accuracy) (Fig.

Figure 6. PFT classification map of a lidar flight line

5. Gap fraction derived from the waveform backscatter cross section shows a strong negative correlation with plot scale shrub LAI (Fig. 7).




Figure 7. Correlation of waveform derived plot scale gap fraction and field observed LAI

References

- Hancock, S., Armston, J., Li, Z., Gaulton, R., Lewis, P., Disney, M., Gaston, K. J. (2015). Waveform lidar over vegetation: An evaluation of inversion methods for estimating return energy. Remote Sensing of Environment, 164, 208–224.
- Heinzel, J., & Koch, B. (2011). Exploring full waveform LiDAR parameters for tree species classification. International Journal of Applied Earth Observation and Geoinformation, 13(1), 152-
- Wagner, W., Hollaus, M., Briese, C., & Ducic, V. (2008). 3D vegetation mapping using small-footprint full-waveform airborne laser scanners. *International Journal of Remote Sensing*, 29(5), 1433–1452.
- Fieber, K. D., Davenport, I. J., Ferryman, J. M., Gurney, R. J., Walker, J. P., & Hacker, J. M. (2013). Analysis of full waveform LiDAR data for classification of an orange orchard scene. ISPRS Journal of Photogrammetry and Remote Sensing, 82, 63–82.