

UDK 53.086

The Fractal Nature Materials Microstructure Influence on Electrochemical Energy Sources

V.V. Mitić^{1,2}, Lj. Kocić¹, V. Paunović¹, F. Bastic^{1*)}, D. Sirmić¹¹University of Niš, Faculty of Electronic Engineering, Aleksandra Medvedeva 14, 18000 Niš, Serbia²Institute of Technical Sciences of SASA, Knez Mihailova 35, 11000 Belgrade, Serbia

Abstract:

With increasing of the world energy crisis, research for new, renewable and alternative energy sources are in growth. The focus is on research areas, sometimes of minor importance and applications, where the different synthesis methods and microstructure properties optimization, performed significant improvement of output materials' and components' electro-physical properties, which is important for higher energy efficiency and in the electricity production (batteries and battery systems, fuel cells and hydrogen energy) contribution. Also, the storage tanks capacity improvement, for the energy produced on such way, which is one of the most important development issues in the energy sphere, represents a very promising research and application area. Having in mind, the results achieved in the electrochemical energy sources field, especially electrolyte development, these energy sources, materials fractal nature optimization analysis contribution, have been investigated. Based on materials fractal structure research field, particularly electronic materials, we have performed microstructure influence parameters research in electrochemistry area. We have investigated the H_2O_3 concentration influence (from 0.01wt% to 1wt%) and sintering temperature (from 1320°C to 1380°C), as consolidation parameters, and thus, also open the electrochemical function fractalization door and in the basic thermodynamic parameters the fractal correction introduced. The fractal dimension dependence on additive concentration is also investigated.

Keywords: *Electrochemistry, Battery systems, Microstructure, Thermodynamic parameters, Fractals, Fractal dimension.*

1. Introduction

Today, we confront with our entire civilization future development high energy deficit, a good reason the worldwide scientific research are looking for new energy solutions. Many, new and alternative energy sources studies, which have been done in a previous couple of centuries, and the scientific and technological development have less importance in exploitation, up today. Nowadays, just opposite, many new energy sources development projects are focused just on some results and phenomena which have been a subject of previous investigations, as it was mentioned above, and while the time have been, somehow "aside". So the research fields in energy area are actually very rich and full of challenges [1,

*) **Corresponding author:** filip.bastic@gmail.com

2].




Fig. 1. Global new energy sources R&D circle design of PEM (Proton Exchange Membrane) fuel cell materials and processes.

Because of this scientific paper subject, we will give short electrochemistry main points knowledge review. Electrochemistry, as the chemical reactions studies science, which takes place at the interface of the electrode (solid metal or semiconductor) and the electrolyte, i.e. an ionic conductors, involved as electrical charge between the electrodes and the electrolyte movement is the area of our interest in research, too (Fig.1) [3]. It means, practically examines the interaction between electrical energy and chemical changes. The catalysis, or especially electrocatalysis, as a part of electrochemistry, practically considering the chemical reaction rate increasing processes with one or more reactants with the additional substances presence, known as the catalyst [4]. It is also including, all of the electrochemical reaction, such as reactions at the surface of an insertion electrode and at the surface of permeation cells. Mixed-ionic-electronic conducting oxides have an increasing role in the electrocatalyst [5]. Typical examples are the electrodes in solid oxide fuel cells, SOFC, and the membrane that separates oxygen from the air. Mixed Ionic Electronic Conductor, MIEC, are solid semiconductors and metals that conduct both ionic and electronic defects [6]. Also, we can mention as example a cell for oxygen permeation (Fig. 2). The driving force is an oxygen partial pressure difference on the two separation membrane sides; The membrane is a MIEC, which allows the oxygen permeation in the form of ions O^{2-} being accompanied by an electronic (electron/hole) current for maintaining charge neutrality. It is, either, the MIEC which also catalyses the cathodic and anodic reactions (Fig. 2a), or, thin layers that are added on top of the MIEC, in order to catalyze these reactions, (Fig. 2b). As these layers must be permeable, they are either also MIECs or porous.




Fig. 2. a) Oxygen MIEC permeation membrane that is also the electro-catalyst, b) oxygen MIEC permeation membrane with two thin MIEC electro-catalysts coating (also MIECs).

In that sense, we will take in consideration some of equations, which are electro-physically characterize, many of previous mentioned processes, as the Gibbs free energy equation, the Gibbs free energy (ΔG), the cell potential (E° cell) and the equilibrium constants (K) connection equation and the Butler-Volmer equation (describes the electrical current, related to electrodes, potential dependence).

Also, we would like to remind on some newest results from our experimental and theoretical research in the area of microstructure fractalization and the electro-physical properties, which have been resulted based on that. This is very significant for electrolyte bulk, too.

2. Experimental procedure

The samples of Ho_2O_3 doped BaTiO_3 were prepared by conventional solid state reaction. Reagent grade BaTiO_3 powder (Murata) with Ba and Ti ratio of 1,005 and Ho_2O_3 powders (Fluka chemika) were used as starting materials. The content of additive oxides ranged from 0.01wt% to 1wt% Ho_2O_3 . Starting powders were balls, milled in ethyl alcohol for 24 hours using polypropylene bottle and zirconia balls. After drying at 200°C for several hours, the powders were pressed into 7mm disk diameter and 3mm thickness under 120 MPa. The compacts were sintered from 1320°C to 1380°C in air for four hours. Sintered samples were further exposed to the standard preparation procedure, such as cleaning of refractory sand, then partly silvering using silver-palladium paste, to which the solder is performed for further samples measurement, testing and characterization, and further electrophysical testing on the lifecycle and moist heat with appropriate equipment and chambers.

The electron microscope further analysis these previously tested samples, have been also applied; the necessary preparation procedures were completed, the samples were covered with a gold thin layer, using the sputter process. Thus prepared samples were exposed to analysis in the electron microscope (JEOL JSM-5300), where the microstructure analysis were performed under different magnifications [7, 8]. SEM micrographs of Ho_2O_3 doped BaTiO_3 with different dopant concentration and different sintering temperatures are shown in Fig. 3.




Fig. 3. SEM micrographs of Ho_2O_3 doped BaTiO_3 sintered at 1320°C with a) 0.01wt% Ho_2O_3 , b) 0.1wt% Ho_2O_3 , c) 1wt% Ho_2O_3 and sintered at 1380°C with d) 0.01wt% Ho_2O_3 , e) 0.1wt% Ho_2O_3 , f) 1wt% Ho_2O_3 .

3. Results and Discussion

Based on SEM analysed samples, we noticed, for 0.1wt% of $\text{Ho}_2\text{O}_3/\text{BaTiO}_3$, the size of the grains was up to $50\mu\text{m}$, but by increasing the dopant concentration to 1wt% the average grain size was from $4\mu\text{m}$ to $10\mu\text{m}$. Also, the spiral concentric grain growth, for the samples sintered with 0.1wt% of Ho_2O_3 , disappeared when the concentration increased up to 1wt% of dopant.

For Ho_2O_3 doped BaTiO_3 -ceramics, sintered at 1320°C , density varies from 80% of theoretical density (TD) for high doped samples (1.0wt% of dopant), to 93% TD for samples doped with 0.01wt% Ho_2O_3 [9].

In previous papers [8, 11, 12, 19, 20] the stress was set on fractal nature of perovskite ceramics structure. It was interesting here to estimate fractal dimensions DH_f of BaTiO_3 -ceramics specimens with different Ho_2O_3 percentage (0.01wt% - 1wt%) and compare obtained results. Fig. 4 (middle) shows the surface reconstruction of the SEM (a) from Fig. 3, and its Fourier transform indicating pretty high fractal dimension of such a reconstructed surface. Three sets of BaTiO_3 -ceramics specimens were prepared with 0.01wt% , 0.1wt% and 1wt% Ho_2O_3 and shot on SEM with magnifications of 3500, 5000, 7500, 10000 and 15000 each. The box-counting algorithm then applied to reveal fractal dimension of such SEM photos. The results are given in Tab. I.

Tab. I. Fractal dimension (by box-counting) of BaTiO_3 -ceramics with different additive concentrations and different magnifications

Additive	Fractal dimension calculated by box-counting technique				
0.01wt%	1.7549	1.7697	1.8102	1.7282	1.8076
0.1wt%	1.7890	1.7570	1.7633	1.7534	1.8228
1wt%	1.7903	1.7694	1.7894	1.8264	1.8515

The data of each set then are approximated by a cubic spline function which are represented by Fig. 5.




Fig. 4. Left: The square sample of the SEM (a) from Fig. 3. Middle: Surface reconstruction based on gray levels distribution. Right: Fourier transform of the surface data.

The latest materials fractal nature and structure research, which involves the necessary fractal correction to the corresponding basic thermodynamic parameters and associated physical-mathematical apparatus, can introduce significant new results within the research which rebuilt the thermodynamic fundamental process principles in the material world. Above all, it is bringing, in functional connectivity, Hausdorff fractal dimension, which enables the order recognition, reconstruction and prognosing the materials microstructural constituents shape and bringing them out of the chaotic and asymmetric shapes in a controlled and regulated, on the one hand, with the thermodynamic system fractalized entropy, on the other hand.




Fig. 5. Fractal dimension DH_f of three specimens from Fig. 3, vs. magnification rate. The concentration of additives are indicated.

Because the intergranular contacts inside the $BaTiO_3$ -ceramics materials, we may understand, now, the intergranular capacities real nature, and use it as a phenomena explanation of capacities fair high amount realized with barium-titanate ceramics and ceramics based on the other perovskite materials. This phenomena are stressed in a set of recent papers [10-18], in the form of a correction factor α that we added as a multiplicative constant for relative permittivity ϵ_r of the ceramics material under consideration. In this manner, instead of ϵ_r in all formulas we set $\alpha \epsilon_r$, with a hypotheses that the real number α compensates increasing capacity that comes from the intergranular contacts fractal nature. One way is to estimate the value of α to lead it out from the outline fractal dimension or the ceramics grains surface. In the meantime this idea was more elaborated to get its final form. Since the fractal dimension DH_f of a typical grain's surface is just slightly above surface's topological dimension, $D_T = 2$, the difference $DH_f - D_T = DH_f - 2$, is thereby supposed to be responsible for affection to a part of ferroelectric phenomena in barium-titanate ceramics that can not be explain by purely grain surfaces Euclidean geometry [19]. But, since the measured fractal dimension differs throughout the ceramics material, it is suitable to introduce a normalized surface fractality parameter α_s

$$\alpha_s = \frac{1}{\max\{DH_f\} - \min\{DH_f\}} (DH_f - \min\{DH_f\}) \tag{1}$$

which ensures the unit range $0 < \alpha_s < 1$.

But, $BaTiO_3$ -ceramics is also a porous material that corresponds to a lacunar fractal models. It brings in a new phenomenon. Namely, solidification of porous and “spongy” materials increases overall fractal dimension from (theoretically) 2 to full solid 3. In other words, fractal dimension DH_p of a porous material ranges $2 < DH_p < 3$. It causes another correction factor, “ α -pores”,

$$\alpha_p = D_T - DH_p \tag{2}$$

where D_T is dimension of the space and DH_p is corresponding fractal dimension of a porous configuration. Therefore, $0 < \alpha_p < 1$. Due to their geometric root, the dimensionless quantities α_s and α_p will be called geometric fractality factors.

Further, we are aware of the existence of the third (dimensionless) factor α_M carrying over the influence of disorder movement of ferroelectric particles that is factor of fractal movements.

As it is known, there is a moving “cloud” of moving particles in semiconductors (and metals as well) consists of electrons in atoms with large atomic numbers, nucleons in heavy atomic nuclei, and gases consisting of quasi particles with half-integral spin. This is called Fermi gas and obeys Fermi-Dirac statistics. The classic theory of Fermi gas assumes that (i) the interactions between the electrons are irrelevant and can be ignored; (ii) the electrons move in a constant potential and we can ignore everything about the structure of the material; (iii) The crystal comprises a fixed background of N identical positively charge nuclei and N electrons, which can move freely inside the crystal without seeing any of the nuclei (monovalent case); and (vi) Coulomb interactions are negligible because the system is neutral overall.

Now, real Fermi gas dynamics impose necessity of fractal movements factor α_M inclusion, that makes third factor, next to geometric ones α_s and α_p . Since Fermi gas particles have dynamics similar to 3D Brownian one, α_M should be derivate of Hausdorff fractal dimension DH_M of a Brownian 3D space-filling curve. It is obvious that $1 \leq DH_M \leq 3$. The lower limit, $\min DH_M = 1$, is imposed by continuity of trajectory of a particle. The upper limit $\max DH_M = 3$, in turn is the maximum of trajectory complexity in 3D space. It is reasonable to normalize quantity α_M , by taking

$$\alpha_M = \frac{1}{\max\{DH_M\} - \min\{DH_M\}} (DH_M - \min\{DH_M\}) \quad (3)$$

which ensures $0 < \alpha_M < 1$.

In this way, three independent dimensionless fractality factors α_s , α_p and α_M are introduced. These are real numbers from the open interval (0, 1).

Now, our hypothesis is that working temperature of BaTiO₃-ceramics must be influenced by these three fractality factors, making correction of „theoretic” temperature T , to get the new “real” temperature T_r , which is temperature actually lower than T which is affected by the material inner fractality, and thereby $T_r = T - \Delta T$. Obviously, $T_r \leq T$ with equality if no fractal structure of S, P or M type is present. Now, by setting $\alpha = \frac{T_r}{T} = 1 - \frac{\Delta T}{T}$, one has $T_r = \alpha T$, where, α depends on all three alpha-components α_s , α_p and α_M given by (1), (2) and (3), so,

$$\alpha = \Phi(\alpha_s, \alpha_p, \alpha_M) \quad (4)$$

Now by the Curie-Weiss law, the relative permittivity will be given by

$$\varepsilon_r = \frac{C_c}{T_r - T_C} = \frac{C_c}{\alpha T - T_C} = \frac{C_c}{\Phi(\alpha_s, \alpha_p, \alpha_M) T - T_C}$$

where C_c is the Curie constant $C_c = 1.7 \times 10^6$ K. This is the natural way to show how the dielectric constant incorporates the influence of fractal nature of the ceramics materials. In

this way, capacity is slightly bigger than it will be if the fractal nature of BaTiO₃-ceramics is neglected [20].

We underline that the function Φ is unknown by now, but a good approximation would be a linear combination of α_S, α_P , and α_M ,

$$\alpha = \Phi(\alpha_S, \alpha_P, \alpha_M) = \omega_1 \alpha_S + \omega_2 \alpha_P + \omega_3 \alpha_M, \quad (5)$$

where $\omega_1, \omega_2, \omega_3 \geq 0$, $\omega_1 + \omega_2 + \omega_3 = 1$, are so called barycentric coefficients. The identity (5) ensures boundedness of the function Φ (and so of \square as well), i.e.,

$$\min(\alpha_S, \alpha_P, \alpha_M) \leq \Phi(\alpha_S, \alpha_P, \alpha_M) \leq \max(\alpha_S, \alpha_P, \alpha_M)$$

After the fractal correction, the Gibbs free energy equation, the Gibbs free energy, the cell potential and the equilibrium constants connection equation and the Butler-Volmer equation will have the following form:

Gibbs free energy equation:

$$G(p, T) = U + pV - T_r S$$

or

$$G(p, T) = H - T_r S \quad (6)$$

ΔG , E_{cell}° and K connection equation:

$$\Delta G^\circ = -RT_r \ln K = -nFE_{\text{cell}}^\circ \quad (7)$$

Butler-Volmer equation:

$$I = A \cdot j_0 \cdot \left\{ \exp \left[\frac{\alpha_a n F}{RT_r} (E - E_{eq}) \right] - \exp \left[-\frac{\alpha_c n F}{RT_r} (E - E_{eq}) \right] \right\}$$

or

$$j = j_0 \cdot \left\{ \exp \left[\frac{\alpha_a n F \eta}{RT_r} \right] - \exp \left[-\frac{\alpha_c n F \eta}{RT_r} \right] \right\} \quad (8)$$

where is:

- T_r – real temperature, and it holds $T_r = \alpha T$,
- α - correction function;
- α_S - a normalized surface fractality correction factor;
- α_P – porosity correction factor;
- α_M - factor reflecting fractal dynamics.

In this way, global phenomenological parameters, processes and equations, as a results at the science development level, transformed into modern thermodynamics, physicochemical and mathematical apparatus, that provides new scientific research area in the direction of more precise control of particles and processes within the deeper nanoscale microstructure level, which opens the further components and integrated systems miniaturization frontiers, especially in the electrochemistry energy sources area. This extension towards the electrochemistry field, practically continuing to justify opening the new research and scientific areas nominated by terminology “Fractal Microelectronics”.

4. Conclusions

On the base of the batteries, fuel cells and hydrogen usage area analysis results, it is evidently that the civilization in energy field facing with different challenges.

Our experimental-research and theoretical work is a part of extended investigations in the materials structures analysis area, in the fractal nature domain, what is important for more precise contact surface in energy storage area and in materials consolidation for battery systems.

BaTiO₃-ceramics with Ho₂O₃ additive, has larger importance in new energy sources and technologies application field. Our results confirm microstructure constituents shapes, grains and pores, reconstruction possibilities as also Brownian motion particles application, as a particular part of the fractal nature, by long term scientific results and knowledge on the electronic materials fractal analysis. The Tab. 1 and Fig.s 4 give plenty of information about fractal nature of doped BaTiO₃ ceramics. Especially illustrative is Fig. 5, showing that addition of Ho₂O₃ increases fractal dimension, as it is expected and it was also mentioned in some earlier papers [15, 16, 17]. Also, higher magnification reveals more complex structure caused by additives, so the dimension increases with magnification.

These investigations have original contribution in the basic thermodynamic parameters area (by introducing the α fractal correction function, having as the arguments three correction parameters α_s (representing grains' surface fractality), α_p (fractality of pores) and α_M (Brownian motion), as electrochemistry area functions, especially from the energy storage aspects and creating new approach towards intergranular capacity. This is very capital for the new and alternative energy sources, as the new frontiers establishing towards electronic components and systems miniaturization and also higher level integration area, what is in the new experimental-theoretical approach frame and in direction to new theoretical model [Mitić-Kocić], which could consider as a future fractal electronics, and specifically in this paper in electrochemistry area.

Acknowledgements

This research is a part of the project „Directed synthesis, structure and properties of multifunctional materials“ (172057). The authors gratefully acknowledge the financial support of Serbian Ministry of Education, Science and Technological Development for this work.

5. References

1. F. Bastić, The Fractal Nature Materials Microstructure Influence on the Battery Systems and Fuel Cells Energy Efficiency and Capacity Increasing, Ms Thesis, Faculty of Electronic Engineering, University of Niš, Serbia, 2014.
2. HORIZON 2020 – WORK PROGRAMME 2014-2015, Secure, clean and efficient energy, EC, 2014.
3. Roop L. Mahajan, Interdisciplinary Research & Innovation (IDRI) for a Sustainable Energy Future, American Ceramic Society, EMA Meeting, Plenary talk, Orlando, USA, 2011.
4. Katsaounis, S. Brosda, C.G. Vayenas: Encyclopedia of Electrochemistry, A.J. Bard, M. Stratmann Eds., Vol. 5 Electrochemical Engineering, D.D. Macdonald, P. Schmuki Eds., Swiley-VCH Verlag GmbH & Co. KgaA, Weinheim, 2007 pp. 23-86.

5. Riess: Mixed-Ionic-Electronic Conducting Oxides for Electrocatalysis, *Ceramics Materials in Energy Systems for Sustainable Development*, 2008, pp. 297-306.
6. Riess, *Electrochemistry of Mixed Ionic-Electronic Conductors*, in: *CRC Handbook of Solid State Electrochemistry*, P.J. Gellings, H.J.M. Bouwmeester, eds. CRC Press, Inc. 1997, pp. 223-268.
7. V.V. Mitić, *Structure and Electrical Properties of BaTiO₃-Ceramics*, Monography, Zadužbina Andrejević, Belgrade, Yugoslavia, 2001.
8. V. V. Mitić, Lj. Kocić, Fractal nature structure, grains and pores, reconstruction analysis method and application in advance designed microstructure properties prognosis function, Patent, Application number 2015/0152, Intellectual Property Office, Serbia, 2015.
9. S. Janković, V. V. Mitić, Lj. Kocić, V. Paunović, M. Miljković, Statistical analysis of the influence of temperature on microstructure contact surfaces on BaTiO₃ -ceramics doped with Ho₂O₃, *Science of sintering*, Vol. 46, pp. 345-352, 2014.
10. V. V. Mitić, Lj. M. Kocić, I. Mitrović, M. M. Ristić, *Models of BaTiO₃ Ceramics Grains Contact Surfaces*, The 4th IUMRS International Conference in Asia OVTA Makuhari, Chiba, Japan 1997.
11. V. V. Mitić, Lj. M. Kocić, M. Miljković, I. Petković, *Fractals and BaTiO₃-Ceramics Microstructure Analysis*, *Mikrochim. Acta [Suppl.]* (1998) 15, Springer-Verlag, pp. 365-369.
12. P. Petković, V.V. Mitić, Lj. M. Kocić, *Contribution to BaTiO₃-Ceramics Structure Analysis by Using Fractals*, *Folia Anatomica*, (1998) 26, Suppl. 1, pp. 67-69.
13. V. V. Mitić, Lj. M. Kocić, I. Mitrović, *A Model for Calculating Contact Surfaces of BaTiO₃-Ceramics*, *Science of Sintering*, Vol. 30 (1), pp. 97-104, 1998.
14. V.V. Mitić, Lj. M. Kocić, I. Z. Mitrović, *Fractals and BaTiO₃-Ceramics Intergranular Impedance*, Gordon Research Conference: Ceramics, Solid State Studies in Ceramics, Kimball Union Academy, Meriden, New Hampshire, (1999) August 1-6.
15. V. V. Mitić, V. B. Pavlović, Lj. M. Kocić, V. Paunović, D. Mancić, *Application of the Intergranular Impedance Model in Correlating Microstructure and Electrical Properties of Doped BaTiO₃*, *Science of Sintering*, (Vol. 41, No. 3 Page 247-256), 2009.
16. V. V. Mitić, V. Paunović, D. Mancić, Lj. M. Kocić, Lj. Živković, V. B. Pavlović, *Dielectric Properties of BaTiO₃ Doped with Er₂O₃ and Zb₂O₃ Based on Intergranular Contacts Model*, *Advances in Electroceramic Materials*, Vol. 204 (Eds: K. M., Nair, D., Suvorov, R. W. Schwarty, R. Guo), Wiley, 2009, pp. 137-144.
17. J. Purenović, V.V. Mitić, L. M. Kocić, V.B. Pavlović, V. Paunović, and M. Purenović, *Electrical Properties and Microstructure Fractal Analysis of Magnesium-Modified Aluminium-Silicate Ceramics*. *Science of Sintering* (2011) 43 (2): 193-204.
18. V. V. Mitić, V. B. Pavlović, V. Paunović, M. Miljković, J. Nedin, and M. Dukić, *The Influence of Consolidation Parameters on Grain Contact Surfaces BaTiO₃-Ceramics*, in *Advances and Applications in Electroceramics II: Ceramic Transactions*, Volume 235 (eds K. M. Nair and S. Priya), 2012 John Wiley & Sons, Inc., Hoboken, NJ, USA.
19. V. V. Mitić, Lj. Kocić, V. Paunović, V. Pavlović, *Fractal Corrections of BaTiO₃-ceramic Sintering Parameters*, *Sci. Sinter.* 46 (2014) 149-156.
20. V. V. Mitić, V. Paunović, Lj. Kocić, *Dielectric Properties of BaTiO₃ Ceramics and Curie-Weiss and Modified Curie-Weiss Affected by Fractal Morphology*, in: *Advanced Processing and Manufacturing Technologies for Nanostructured and Multifunctional Materials* (T. Ohji, M. Singh and S. Mathur eds.), *Ceramic Engineering and Science Proceedings*, Vol. 35 (6) 2014, pp. 123-133.

Садржај: Са порастом енергетске кризе у свету, развијена су истраживања за нове, обновљиве и алтернативне изворе енергије. Фокус је на истраживању у областима, некада мањег значаја и примене, где се различитим методама синтезе, као и оптимизацијом микроструктурних својстава, врши значајно побољшање излазних електрофизичких својстава материјала и компонента, од значаја за већу енергетску ефикасност и принос у производњи електричне енергије (батерије и батеријски системи, гориве ћелије, као и хидрогенски извори). Такође, побољшање капацитета резервоара за складиштење тако произведене енергије, који је један од најзначајнијих развојних проблема у енергетској сфери, представља изузетно подручје за перспективна истраживања и примене. Имајући у виду постигнуте резултате у области електрохемијских извора енергије, посебно развоја електролита, истраживали смо допринос анализе фракталне природе материјала у оптимизацији ових енергетских извора. На бази истраживања из области фракталне структуре материјала, посебно електронских материјала, извели смо истраживања утицајних параметара микроструктуре у области електрохемије. Испитивали смо утицај концентрације H_2O_3 (од 0.01wt% до 1wt%) и температуре синтеровања (од 1320°C до 1380°C), као консолидационих параметара и тиме отворили врата фрактализацији електрохемијских функција и увели фракталну корекцију код основних термодинамичких параметара. Испитивана је зависност фракталне димензије узорака од концентрације адитива.

Кључне речи: електрохемија, батеријски системи, микроструктура, термодинамички параметри, фрактали, фрактална димензија.
