



Unmanned Airborne Vehicles (UAVs) for monitoring small streams and optimizing river maintenance

UAV-borne observations of water level, surface velocity and discharge

Bandini, Filippo; Luthi, Beat; Smith, Ole; Klint Jensen, Inger; Jiang, Liguang; Pheiffer Sunding, Tanya; Bauer-Gottwein, Peter

Publication date:
2019

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Bandini, F., Luthi, B., Smith, O., Klint Jensen, I., Jiang, L., Pheiffer Sunding, T., & Bauer-Gottwein, P. (2019). Unmanned Airborne Vehicles (UAVs) for monitoring small streams and optimizing river maintenance: UAV-borne observations of water level, surface velocity and discharge . Abstract from MOXXI 2019 International Conference, New York, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Unmanned Airborne Vehicles (UAVs) for monitoring small streams and optimizing river maintenance

UAV-borne observations of water level, surface velocity and discharge

Filippo Bandini¹, Beat Lüthi², Ole Smith³, Inger Klint Jensen³, Liguang Jiang¹, Tanya Pheiffer Sunding¹, Peter-Bauer Gottwein¹

(1) DTU Environment, Bygningstorvet Bygning 115, Kgs. Lyngby 2800, Denmark;

(2) Photrack AG, Ankerstrasse 16A, Zürich 8004, Switzerland;(3) Orbicon A/S, Linnés Allé 2, Taastrup 2630, Denmark

Monitoring and maintenance of Danish streams cost approx. 20-30 million USD per year. Watercourse regulations prescribe that each municipality is obliged to ensure specific cross section shape or conveyance. For this reason, ca. 20000 km of public rivers in DK must be surveyed with in-situ measurements of bathymetry and discharge every 3-10 years. These costly surveys are conducted manually and are essential for targeting river maintenance, i.e. river vegetation cutting and bottom clean-up. Maintenance operations are also detrimental to the river ecological status but are necessary to avoid floods.

In this context, more efficient methods are required to monitor rivers and optimize river maintenance. Unmanned Aerial Vehicles (UAVs) can provide high spatial resolution and dense temporal coverage data, in quick turn-around time, with waypoint-based automatic flights. To retrieve accurate UAV flight positions and angles, UAVs are generally equipped with accurate Global Position System (GPS) receivers and Inertial Measurement Units (IMUs).

A UAV, equipped with an accurate differential-GPS system and a lightweight radar chip, can monitor water level (i.e. water surface elevation above mean sea level) by subtracting the range between the UAV and the water surface (measured by the radar) from the altitude of the UAV above the geoid (measured by the GPS). Surface velocity can be estimated with Surface Structure Image Velocimetry (SSIV), a variant of image cross-correlation techniques, applied to video frames retrieved from the on-board video camera. By observing the displacements between particles, such as leaves or foam, visible on the water surface, or by observing ripples generated by water turbulence, these cross-correlation techniques can predict water surface velocity. Surface velocity observations can be used to estimate discharge by following standard EN ISO 748:2007, and by combining it with the water depth profile and a roughness coefficient.

UAV-water level observations of a stretch of Åmose Å (Denmark) are shown in the figure below. UAV-observations (in meters above mean sea level (mamsl)) showed an accuracy of ca. 3 cm when compared to in-situ Real Time Kinematic (RTK) GPS observations. These UAV observations represent a new dataset for hydrology: river water level profiles with high spatial resolution (ca. 0.5 m). River water slope is an informative dataset to understand how rivers are affected by vegetation growth and river maintenance. Indeed, water level measurements were used to calibrate a hydrodynamic model and estimate spatially distributed Manning numbers, which have a controlling influence on channel conveyance.

