

3D mapping of the Earth's trapped radiation particles using ASC: from the inner zone to the magnetosphere

Herceg, Matija; Jørgensen, John; Jørgensen, Peter S.; Denver, Troelz

Publication date: 2019

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA):

Herceg, M., Jørgensen, J., Jørgensen, P. S., & Denver, T. (2019). 3D mapping of the Earth's trapped radiation particles using ASC: from the inner zone to the magnetosphere. Poster session presented at The General Assembly 2019 of the European Geosciences Union (EGU), Vienna, Austria.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- · You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



3D mapping of the Earth's trapped radiation particles using µASC: from the inner zone to the magnetosphere

EGU2019-17883

Introduction

As a pioneer of the fully autonomous star trackers, the micro Advanced Stellar Compass (DTU Space) has been operating successfully on numerous satellite missions ranging from Low Earth Orbiters (e.g. ESA's Swarm) to Deep Space missions (e.g. NASA's Juno), accurately providing absolute attitude reference. Besides its primary function of attitude determination, the µASC is also capable of detecting and monitoring the population of the Earth's high energy particles.

The particles with energies high enough (>20MeV) to pass the heavy shielded optics, will leave a temporary trace on the CCD sensor. The signature of these high energy particles is eliminated in flight by the instrument software ensuring full performance even during the most intense CMEs.



Mapping the rate of the penetrating particles on the CCD sensor enables the monitoring of the high energy particle flux. We present compilation of detected particle flux, its global maps and radial variation from 400 to 10000 km altitude. We further present a view of the dynamic part of the flux, from injection sources such as CMEs, which gives a detailed profiling of the direction, injection time scales and relaxation times.

micro Advanced Stellar Compass µASC

- Designed and produced by the Measurement and Instrumentation (DTU)
- One of the most successful star tracker worldwide
- Autonomously calculates attitude based on all bright stars in the CHUs
- Absolute accuracy of < 1 arc second
- Operating on many satellite missions without a single failure

DTU Space µASC





Matija Herceg¹, John L. Jørgensen¹, Peter S. Jørgensen¹, Troelz Denver¹

¹DTU Space, Measurement & Instrumentation Systems, Technical University of Denmark, Copenhagen, Denmark

- Silicon carbide structure and metal CHU





