

Technical University of Denmark



## Hydrostratigrafisk zonerings til grundvandsmodellering baseret på resistivitets- og borehulsdata, eksempel fra norsminde

**Marker, Pernille Aabye**

*Published in:*  
Vintermøde om Jord- og Grundvandsforurening

*Publication date:*  
2014

*Document Version*  
Også kaldet Forlagets PDF

[Link back to DTU Orbit](#)

*Citation (APA):*  
Marker, P. A. (2014). Hydrostratigrafisk zonerings til grundvandsmodellering baseret på resistivitets- og borehulsdata, eksempel fra norsminde. I Vintermøde om Jord- og Grundvandsforurening (s. 77-77). Vingsted: ATV Jord og Grundvand.

## DTU Library

Technical Information Center of Denmark

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# **HYDROSTRATIGRAFISK ZONERING TIL GRUNDEVANDSMODELLERING BASERET PÅ RESISTIVITETS- OG BOREHULSDATA, EKSEMPEL FRA NORSMINDE**

Ph.d.-studerende Pernille Aabye Marker  
Institut for Vand og Miljøteknologi, Danmarks Tekniske Universitet  
paam@env.dtu.dk

Regional hydrological models are important tools in water resources management. Model prediction uncertainty is primarily due to structural (geological) non-uniqueness which makes sampling of the structural model space necessary to estimate prediction uncertainties. Today geological input to hydrological models is made by geologists, who use cognitive approaches based on geophysical surveys and borehole observations to construct one-truth geological models. Good spatial coverage along with high resolution make airborne time-domain electromagnetic (AEM) data valuable for the hydrostratigraphical input to hydrological models. Geological structures and heterogeneity, which spatially scarce borehole lithology data may overlook, are well resolved in AEM surveys. Due to the discrepancy between hydrological and geophysical parameter spaces the challenge is to translate the electrical resistivity distribution into hydrogeological properties. The translation between hydrological and geophysical parameter space varies spatially and between sites, making a fixed translation insufficient.

This study presents a semi-automatic sequential hydrogeophysical inversion method for the integration of AEM and borehole data into regional groundwater models in sedimentary areas, where sand/clay distribution govern groundwater flow. The coupling between hydrological and geophysical parameters is managed using a translator function with spatially variable parameters followed by a 3D zonation. Observed borehole lithologies are represented as clay fractions. The translator function translates the electrical resistivities obtained in a preceding geophysical inversion into clay fractions and is calibrated with observed clay fraction data from boreholes. Principal components are computed for the translated clay fractions and geophysical resistivities. Zonation is carried out by k-means clustering on the principal components. The hydraulic parameters of the zones are determined in a hydrological model calibration using head and discharge observations. The method was applied to field data collected at a Danish field site. The dataset includes interpreted borehole observations and AEM flight path coverage. A classical geological model is available for comparison.

Our results show that a competitive hydrological model can be constructed from the AEM dataset using the automatic procedure outlined above. Alternative zonations using various clustering settings, comprising the number of clusters and clustering variables, were evaluated with respect to the performance of the associated hydrological model, and by comparison with the classical geological model.