

University of Dundee

DOCTOR OF PHILOSOPHY

Utilisation of remote sensing for the study of debris-covered glaciers: development and testing of techniques on Miage Glacier, Italian Alps

Foster, Lesley A.

Award date: 2010

Awarding institution: University of Dundee

Link to publication

#### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
  You may freely distribute the URL identifying the publication in the public portal

#### Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# DOCTOR OF PHILOSOPHY

Utilisation of remote sensing for the study of debris-covered glaciers: development and testing of techniques on Miage Glacier, Italian Alps

Lesley A. Foster

# 2010

University of Dundee

Conditions for Use and Duplication

Copyright of this work belongs to the author unless otherwise identified in the body of the thesis. It is permitted to use and duplicate this work only for personal and non-commercial research, study or criticism/review. You must obtain prior written consent from the author for any other use. Any quotation from this thesis must be acknowledged using the normal academic conventions. It is not permitted to supply the whole or part of this thesis to any other person or to post the same on any website or other online location without the prior written consent of the author. Contact the Discovery team (discovery@dundee.ac.uk) with any queries about the use or acknowledgement of this work.

# **CONTENTS**

	Page
CONTENTS	i
LIST OF TABLES	viii
LIST OF FIGURES	xi
LIST OF EQUATIONS	xviii
TERMINOLOGY	xix
ACKNOWLEDGEMENTS	xxiii
DECLARATION	xxiv
ABSTRACT	XXV
CHAPTER 1: INTRODUCTION	1
1.1. Background	1
1.2. Aims and objectives	5
1.3. Thesis synopsis	8
<u>CHAPTER 2: APPLICATION OF REMOTE SENSING TO THE STUDY AND MONITORING OF</u> DEBRIS-COVERED GLACIERS: A LITERATURE REVIEW	10
2.1. Introduction	10
2.2. Debris-covered glaciers	10
2.2.1. Development of debris cover and lateral debris movement	13
2.3. Impact of debris cover on glacial surface processes	14
2.3.1. Thermal Properties of a debris layer	14
2.3.1.1. Thermal conductivity (K)	15
2.3.1.2. Thermal resistance (Tr)	16
2.3.1.3. Thermal diffusivity (Tdf)	16

2.3.1.4. Specific heat capacity (c)	17
2.3.1.5. Conductive heat flux (COND)	18
2.3.2. Factors which affect the thermal properties of a debris layer	18
2.3.2.1. Sediment texture (grain size)	19
2.3.2.2. Sediment lithology (composition)	19
2.3.2.3. Debris moisture content	20
2.3.3. Ablation rates on debris-covered glaciers	21
2.4. Thermal remote sensing	22
2.4.1. Thermal infrared energy	23
2.4.2. Interaction of thermal infrared energy with the atmosphere	24
2.5. Previous applications of satellite imagery: 'clean' glacial monitoring	25
2.5.1. GLIMS	25
2.5.2. Surface albedo	26
2.5.3. Glacier motion	27
2.5.4. Changes in glacial extent and elevation	28
2.6. Previous applications of satellite imagery: debris-covered glacier monitoring	29
2.6.1. Glacier boundary and debris mapping	29
2.6.2. Digital elevation models (DEM's), generation, and surface change estimation	32
2.6.3. Surface velocity measurements	33
2.7. Lithology mapping using remote sensing	34
2.8. Debris thickness estimations from satellite imagery	36
2.8.1. Surface energy balance	36
2.8.2. Short wave radiation (SWR)	38
2.8.3. Long wave radiation (LWR)	39
2.8.4. Sensible (SHF) and latent heat fluxes (LHF)	39
2.8.4.1. Eddy covariance method	40
2.8.4.2. Profile methods	41
2.8.5. Calculating melt rates (modelling)	45
2.8.6. Previous application to debris-covered glaciers	46

2.8.6.1. Surface temperature	46
2.8.6.2. Surface layer (in)stability in turbulent fluxes	49
2.8.6.3. Thermal properties of debris layer	49
2.8.6.4. Distributed modelling	51
2.9. Key research questions	52
2.10. Summary	54
CHAPTER 3: STUDY SITE	56
3.1. Introduction	56
3.2. Site description	56
3.3. Study site selection	59
CHAPTER 4: METHODOLOGY	60
4.1. Methodology/research design	60
4.2. Field data collection	62
4.2.1. Meteorological data – automatic weather station (AWS)	63
4.2.1.1. Longwave radiation (LWR) and Shortwave radiation (SWR)	65
4.2.1.2. Air temperature data (HMP45C sensors)	65
4.2.2. Surface temperature data	66
4.2.3. Debris thickness measurements	68
4.2.4. Ablation measurements	71
4.2.5. Relationship of air temperature to surface temperature measurements	71
4.2.6. Rock lithologies	73
4.3. Remotely sensed data and image pre-processing	75
4.3.1. ASTER DEM	77
4.3.2. Orthophoto DEM	79
4.3.2.1. Slope and Aspect	80
4.4. Summary	81

CHAPTER 5: EXTRACTING DEBRIS THICKNESS FROM THERMAL BAND IMAGERY	83
5.1. Introduction	83
5.2. Methodology	85
5.3. Validation of ASTER with field observations	86
5.3.1. Surface thermistor temperatures vs. ASTER temperatures	86
5.3.2. Spatial variability of surface temperatures	87
5.3.3. Analysis of the effects of different microenvironments on thermistor temperature	91
5.3.3.1. Rock underside	94
5.3.3.2. Comparison of rock type	96
5.3.3.3. Shading	97
5.3.3.4. Varied depths	99
5.4. Surface temperature-debris thickness relationship	100
5.4.1. Surface data from thermistors	100
5.4.2. Debris thickness variability	102
5.5. Estimating debris thickness with ASTER imagery	107
5.5.1. Empirical method	107
5.5.1.1. Debris temperature relationship	107
5.6. Energy balance modelling	111
5.6.1. Energy balance modelling: application	112
5.7. Extracting debris thickness values through an energy balance model	116
5.7.1. Application of the model	116
5.7.2. Testing transferability of air and surface temperature relationship	124
5.7.2.1. Application to different days with similar weather conditions	124
5.7.2.2. Application to different locations on the glacier surface	126
5.8. Debris thickness maps derived from 2005 ASTER thermal imagery	127
5.9. Evaluation of calculated debris thickness	130
5.9.1. Visual comparison	130
5.9.2. Numerical comparison	131

5.9.2.1. Field data – 2005 stake data

iv

5.9.2.2. Field data – 2006/2007 transect data	134
5.9.2.3. Supraglacial debris load	135
5.9.2.4. Comparison of Mihalcea et al., (2008) thickness estimates	136
5.10. Sensitivity analysis	139
5.10.1. Conductivity	139
5.10.2. Surface roughness value $(z_0)$	140
5.10.3. Emissivity	141
5.10.4. Slope and aspect	143
5.10.5. Application of variable LWR values	145
5.11. Comparison with 2004 debris thickness map – from ASTER	149
5.12. Testing of Mihalcea et al., (2008)	154
5.13. Summary	157
CHAPTER 6: CHANGES IN DEBRIS COVER EXTENT OVER TIME	160
6.1. Introduction	160
6.2. Remotely sensed data	162
6.2.1. Landsat imagery	162
6.2.2. ASTER imagery	163
6.3. Methodology	163
6.3.1. Manual delineation	163
6.3.2. Semi-automatic methods	164
6.4. Method testing and development	165
6.4.1. Manual digitising	165
6.4.1.1. Sporadic debris problems and its treatment	166
6.4.2. Semi automatic method	167
6.4.2.1. Method problems	170
6.5. Debris extent results	175
6.5.1. Manual digitising: precision analysis	176
6.6. Analysis of results	

6.6.1. Glacier snout	178
6.6.2. Middle reaches	179
6.6.3. Upper reaches	180
6.7. Discussion of results	182
6.8. Summary	183

CHAPTER 7: MONITORING SURFACE ELEVATION CHANGES AND VELOCITY AS A MEANS	185
DF ASSESSING THE MASS BALANCE STATUS OF DEBRIS-COVERED GLACIERS	

7.1. Introduction	185
7.2. Elevation data	187
7.2.1. Error analysis	187
7.2.1.1. Geographical accuracy	187
7.2.1.2. Vertical accuracy	190
7.2.1.3. Elevation differences related to slope and aspect	194
7.3. Extracting elevation changes	196
7.4. Surface elevation changes	196
7.4.1. Discussion of results	201
7.5. Surface Velocity	201
7.6. Summary	204
CHAPTER 8: MAPPING OF LITHOLOGY USING REMOTLEY SENSED DATA; DEVELOPMENT AND TESING USING ASTER IMAGERY	206
8.1. Introduction	206
8.2. Methodology	208
8.2.1. Rock unit spectral reflectance	208
8.2.2. Cluster analysis	210
8.2.3. Supervised classification	211
8.2.4. Validation data	213
8.2.5. Unsupervised classification	214

214

8.3. Results

8.3.1. Rock samples	214
8.3.2. Cluster analysis results	218
8.3.3. Supervised classification results	221
8.3.4. Comparison to field data	224
8.3.4.1. 2007 and 2009 field data	224
8.3.4.2. Field photographs	226
8.3.5. Unsupervised classification results	227
8.4. Implications	229
8.5. Summary	232
CHAPTER 9: DISCUSSION	234
9.1. Introduction	234
9.2. What was known prior to this study?	234
9.3. What is known now the study has been completed?	235
9.4. Applicability of findings in both a Glaciological and remote sensing perspective	239
9.4.1. Glaciological	239
9.4.2. Remote sensing	241
9.5. Future work	242
9.6. Summary	247
CHAPTER 10: CONCLUSION	248
10.1. Concluding Comments	251
<u>BIBLIOGRAPHY</u>	252
APPENDIX	263

### LIST OF TABLES

	Page
TABLE 2.1: Thermal conductivities of a variety of materials <sup>1</sup> Gupta (2003), <sup>2</sup> Oke (1987).	15
TABLE 2.2: Example thermal diffusivities <sup>2</sup> Drury (1993), <sup>2</sup> Oke (1987).	17
TABLE 2.3: Example Specific heat capacities <sup>1</sup> Gupta (2003), <sup>2</sup> Oke (1987).	18
TABLE 2.4: a) Published albedo values for different surfaces, <sup>1</sup> Knap et al., (1999), <sup>2</sup> Jumikis (1977), b)Variation of albedo with differences in debris cover (Brock et al., 2000).	20
TABLE 2.5: Comparison of ablation rates on clean and debris covered ice on the Columbia glacier, NorthCascades, Washington (Pelto, 2000).	21
TABLE 2.6: Critical and effective thicknesses, <sup>1</sup> Mattson (2000), <sup>2</sup> Popovnin and Rozova (2002), <sup>3</sup> Mattson et al., (1993), <sup>4</sup> Kayastha et al., (2000) <sup>5</sup> Kirkbride and Dugmore (2003), <sup>6</sup> Driedger (1981, cited in Kirkbride and Dugmore, 2003), <sup>7</sup> Brock et al., (2000).	21
TABLE 2.7: Aerodynamic roughness lengths on both clean and debris-covered glaciers.	44
TABLE 4.1: Meteorological Instrument specifications.	62
TABLE 4.2: Meteorological station details.       Image: Comparison of the station of the state	63
TABLE 4.3: Details of thermistor probe positioning and duration of sampling period.	66
TABLE 4.4: Location of debris thickness measurements in 2005, 2006, and 2007.	70
TABLE 4.5: Satellite data used ( <sup>1</sup> Aster-web NASA, 2008; <sup>2</sup> Lang and Welch, 1999; <sup>3</sup> Land Process Distributed         Active Archive Centre, 2008).	75
TABLE 4.6: Wavebands of the Landsat MS, TM and $ETM^+$ and the ASTER sensor bands.	76
TABLE 5.1: Summary of surface temperatures for all spatial scales, a) 2 m and 5 m small scale transects, b)large scale 20 m transects.	90
TABLE 5.2: Example temperature values from the upper and underside of a rock at 10:40 (time of ASTER imageacquisition)	96
TABLE 5.3: Example temperature values from rocks with different albedo (one a dark schist, the other a lightergranite) at 10:40 (time of ASTER image acquisition)	96
TABLE 5.4: Correlation coefficients of debris thickness vs. surface temperature at different times.	100
TABLE 5.5: Sill values for each of the transects in the lower, middle and upper reaches.	103
TABLE 5.6: Mean flux values over a 24 hour period (01/08/05).	113
TABLE 5.7: Air temperature values generated from surface temperature using both regression coefficients froma single day's data between 08:00-10:00 and 10 days data between 08:00-10:00.	125

TABLE 5.8: Differences of estimates from measured thicknesses (at each of the stake locations in 2005) for each133of the four images.

TABLE 5.9: Average debris thickness for transect area and ASTER debris thickness estimate for the same135transect (ASTER thickness estimate for entire transect calculated using surface temperature extracted from the<br/>mid point of each transect), where: 1 = Energy balance method ( $T_a$  equation 08:00-10:00)  $z_o$  0.002 m, 2 =<br/>Energy balance method  $z_o$  0.003 m ( $T_a$  equation 08:00-10:00), 3 = empirical linear approach, 4 = empirical<br/>quadratic approach a) 2006, all transects 5 m spacing, b) 2007, upper transect 5 m and lower transect 20 m<br/>spacing.

TABLE 5.10: Total supraglacial debris load, adjusted for assumed void space (average glacier value of 38%136applied)

TABLE 5.11: Impact of different thermal conductivity values on debris thickness estimates, using the maximum,139minimum and average thermal conductivity values recorded at the 25 stake locations in 2005,  $z_o$  of 0.001m used.Average debris thickness and standard deviation results generated from all debris thickness estimates from everyASTER pixel, along with debris thickness estimates at the weather station site (known debris thickness of 0.16m).

TABLE 5.12: Average thickness estimates, and standard deviations from all ASTER pixels, and debris thickness 140 estimates with varying  $z_o$  values, conductivity 0.96  $Wm^{-1} K^{-1}$ .

TABLE 5.13: Impact of different emissivity values on surface temperatures (10:40 01/08/05) and resulting debris 142 thickness estimates at the AWS (measured depth 0.16 m) using the energy balance model (air temperature measured),  $z_o$  0.001 m, conductivity 0.96 Wm<sup>-1</sup> K<sup>-1</sup>.

TABLE 5.14: Impact of including slope and aspect in the debris thickness estimation model, using a  $z_o$  of 0.001143m. Firstly, with an average value for both slope and aspect for the entire glacier, secondly with an individual<br/>slope and aspect value for each pixel, with mean debris thickness values generated using debris thickness<br/>estimates from all ASTER pixels on the glacier. Also comparison of results using slope and aspect to the<br/>measured value at the AWS, with the slope and aspect value extracted for the corresponding pixel to the AWS<br/>(slope 4°, aspect 123°), actual debris thickness at the AWS 0.16 m.143

TABLE 5.15: Total supraglacial debris load, adjusted for assumed void space (average glacier value of 38%144applied)

TABLE 5.16: Total supraglacial debris load, adjusted for assumed void space (average glacier value of 38%148applied)

TABLE 5.17: Total supraglacial debris load, adjusted for assumed void space (average glacier value of 38%152applied)

TABLE 6.1: Precision uncertainty in manual digitising, with the maximum and minimum errors being the largest177and smallest distance between any of the digitised lines at random sample locations (25 locations in total),precision uncertainty is also related to actual pixel size to identify the maximum uncertainty in terms of the

number of pixels,

(2000), <sup>2</sup>Oke (1987), <sup>3</sup> Hunt (1989).

TABLE 6.2: Debris covered area from manually delineated extents and semi-automatic method.	175
TABLE 7.1: Average errors experienced at 30 sample points between each DEM a) flat ground, b) steep terrain.	191
TABLE 8.1: Number of training sites and total number of pixels wihtin these training sites for each rock unit, and slope class.	213
TABLE 8.2: Classified rock samples collected in 2007.	215
TABLE 8.3: Percentage of sites appear in the same group regardless of using ASTER wavebands only or all wavelengths available.	220
TABLE 8.4: a) Confusion matrix and accuracy of supervised classification, b) producer's and user's accuracies.	222
TABLE 8.5: 2007 and 2009 field samples of rock type against classification rock type for the corresponding pixel, if a sample point was located on the boundary of two rock types both rock types are identified.	225
TABLE 8.6: Rock types present at each field photograph site compared to rock type identified by the supervisedclassification.	226
TABLE 8.7: 2007 Field samples of rock type against unsupervised classification rock type for the corresponding pixel, if a sample point was located on the boundary of two/three rock types all rock types are identified.	228
TABLE 8.8: Emissivity, true kinetic temperature and radiant temperature of 5 materials at 300 K and 27 °C(Jensen, 2000).	229
TABLE 8.9: Example emissivity values for rock types found on the Miage Glacier (columns 1 and 2), and effect         on surface temperature retrieval and calculated debris thickness values using the energy balance model, <sup>1</sup> Jensen	231

Х

### LIST OF FIGURES

	Page
FIGURE 2.1: Exposure of a medial moraine in the ablation zone, $AD = ice$ -debris interface, $AE = moraine$ crest,	12
$B = ice \ core, \ AC = level \ of \ nearby \ glacier \ not \ affected \ by \ differential \ ablation \ (Kirkbride, 1995).$	
FIGURE 2.2: Cycle of ridge and trough development.	13
FIGURE 2.3: Relationship between debris cover thickness and ablation (Mattson et al., 1993).	22
FIGURE 2.4: Absorption, emission, transmission, and reflection of thermal infrared energy from an object.	23
FIGURE 2.5: Diurnal surface temperature variations of both bare rock and debris lying on ice (Taschner and Ranzi, 2002).	31
FIGURE 2.6: Reflectance curves for three rock families showing spectral similarities of reflectance and absorption features, a) limestones, b) sandstones, c) shales(Prost, 1994).	35
FIGURE 2.7: Stability functions against the Richardson number, showing the flow regimes that occur at different Richardson number values(Oke, 1987).	42
FIGURE 2.8: Vertical temperature profiles within a debris layer on Ngozumpa Glacier, Nepal (Nicholson and Benn 2006).	48
FIGURE 3.1: Map showing the location of the Miage glacier within the Mont Blanc Massif – the Western Alps (Deline, 2005).	57
FIGURE 3.2: Map of the Miage glacier showing its physical characteristics (Thomson et al., 2000).	58
FIGURE 4.1: Lower Weather Station (LWS) in 2005.	64
FIGURE 4.2: Location of weather stations in 2005, 2006, and 2007, with inset's showing detail of slight location variation in the upper and lower locations between years (ASTER 2000, VNIR 1).	64
FIGURE 4.3: Correction applied to air temperature data; example of 01/08/05.	65
FIGURE 4.4a-d: Location of two thermistor probes at four site locations a) 2007 with one sensor on the top of the rock and the other on the bottom, b) 2007 one sensor on a lighter granite the rock and another on a darker schist, c) one sensor in slight shade one in direct sun, d) one on thicker and the other on thinner debris layer near exposed ice.	67
FIGURE 4.5: Surface temperature stake locations in 2005 (ASTER 2000, VNIR1).	67
FIGURE 4.6: Location of surface thermistors during 2007 field campaign (ASTER 2000, VNIR 1).	68
FIGURE 4.7: Debris thickness measurement locations in 2005, 2006, and 2007, with zoomed in detail of 2007 transect in the upper reaches of the glacier (ASTER 2000, VNIR 1).	70
FIGURE 4.8: Air and surface temperature measuring equipment and set up.	72

FIGURE 4.9: Portable air and surface temperature measurements (03/09/07) (ASTER 2000, VNIR 1).	72
FIGURE 4.10: Location of rock sample collection points.	73
FIGURE 4.11: Field sketch showing rock type distribution in 2007.	74
FIGURE 4.12: Rock lithology observations 2009.	74
FIGURE 4.13: Generation of DEM through stereo image collection (ERSDAC, 2005).	78
FIGURE 4.14: 1991 orthophoto DEM of the Miage Glacier and surrounding landscape.	80
FIGURE 4.15: a) slope and b) slope aspect for each pixel in the DEM.	81
FIGURE 5.1: ASTER surface temperatures vs. thermistor surface temperatures (01/08/05 10:40) at 21 sample points and corresponding ASTER pixels, 1:1 relationship line plotted.	87
FIGURE 5.2: Surface temperature values with comparison between daily 10:40 temperatures and average values for the sample period a) 2m spacing glacier transect ( $20/06/07 - 21/06/07$ ), b) 5m spacing glacier transect ( $22/06/07 - 17/07/07$ ), c) 20 m spacing glacier transect ( $31/08/07 - 04/09/07$ ), d) Average surface temperature during the night ( $00:00-06:00$ ) – of the 5m across and down glacier transect.	89
FIGURE 5.3: Relationship between the surface energy exchange and the diurnal cycle of surface temperature (Oke, 1987).	92
FIGURE 5.4: Characteristic diurnal pattern of surface temperature – average temperatures calculated from the entire 2005 data season ( $06/06/05 - 08/09/05$ ), recorded at the LWS.	92
FIGURE 5.5: Diurnal $T_s$ and SWR $\downarrow 01/08/05$ showing fluctuations between 07:30-20:00 at LWS site.	93
FIGURE 5.6: Diurnal cycles of temperature at different depths (0cm, 6cm, 12, cm), from a sensor profile located at the LWS, where total debris thickness was 20 cm.	94
FIGURE 5.7: a) location of thermistors b) Average diurnal temperature variability between $31/08/07-04/09/07$ of a thermistor sensor placed on the top of a rock and another placed on the underside, clast thickness ~0.02 m (Thermistor located 100 m from the LWS).	95
FIGURE 5.8: a) Tiny_Tag 13_14 at the AWS site, b) 'typical' diurnal temperature variations (31/08/07-04/09/07) between thermistors on different rocks, one a dark schist, the other a lighter granite.	97
FIGURE 5.9: Diurnal temperature variations between a thermistor paced in a shaded location and the other in an open location, a) thermistor location, b) average hourly surface temperatures (31/08/07-04/09/07).	98
FIGURE 5.10: Average daily temperature variations between thermistors on debris thicknesses 0.4 m and 0.05 m a) Location of thermistors, b) Average hourly surface temperatures for the sampling period (31/08/07-04/09/07).	99
FIGURE 5.11: Surface temperature(from surface thermistors) vs. debris thickness at a) 10:40 01/08/05 (time of ASTER image acquisition) in 2005 (stake locations – over entire glacier) and b) 10:40 31/08/07 (debris transect locations middle glacier), c) Average surface temperature between 06:00-12:00 01/08/05, d) Average surface temperatu	101

xii

FIGURE 5.12: Photographs of the upper transect a) 2006, b) 2007 arm 1, c) 2007arm 3, showing transect was	104
taken along the top of steep sided moraine, d) 2007arm 4, taken up towards the top of a steep ice cliff, e) 2007	
arm 2, transect from the top of the steep moraine into the trough area. Red marking show transect direction.	
FIGURE 5.13: Photos of the middle transect a) arm 1, across glacier, showing transect was taken over a moraine, b) arm 2, across glacier, also across a moraine, c) arm 3, down glacier d) arm 4, up glacier, along a steep moraine also showing large number of large boulders on the top of the moraine. Red lines show transect direction.	105
FIGURE 5.14: Photographs of the lower transect, a) arm 1, across glacier, showing samples were taken across a moraine, b) arm 2, c) arm 3, up glacier, showing transect was taken along the top of a moraine, d) arm 4. Transect direction shown by red lines.	106
FIGURE 5.15: Thermistor temperatures plotted against debris thickness, a) linear line of fit applied 01/08/05 at 10:40 (thermistor temperatures), b) linear line of fit applied 01/08/05 at 10:40 (ASTER temperatures), c) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermistor temperatures), d) Quadratic line of fit applied 01/08/05 at 10:40(thermist	108
FIGURE 5.16: Plots of debris thicknesses against ASTER pixel temperature obtained for both linear and quadratic regression equations, with linear extension to the quadratic plot for shallow debris depths.	109
FIGURE 5.17: Plotted results of different surface energy fluxes at 10 minute intervals, with $\partial$ STOR calculated hourly 01/08/05 measured at the LWS.	113

FIGURE 5.18: Melt rate in water equivalent units as a result of COND at hourly timescales on the 01/08/05. 114

115

FIGURE 5.19: Average hourly summer daytime fluxes 2005 (June-September) measured at the LWS.

FIGURE 5.20: Estimated debris thickness from the energy balance model at the AWS stie on 01/08/05 ( $z_0 = 0.001$  117 m) for the time period when the assumption of a linear downward temperature profile in the debris is likely to be met (08:00-16:30). Point thickness measured at the AWS site is 0.16 m.

FIGURE 5.21: Debris thickness estimates and actual thicknesses at different sites, using a fixed air temperature **118** value (measured at the LWS), and measured thermistor surface temperatures.

FIGURE 5.22: *a)* Mean hourly temperature lapse rates between the upper and lower AWS 23/06/07, *b)* Mean daily **120** cycles of hourly temperature lapse rates between the upper and lower AWS for 2006 (LR06) and 2007 (LR07) seasons (Brock et al., in press), *c)* Mean daily cycle of air and surface temperature for the 2005 ablation season, with air temperature measured at 3 heights: 0.5 m, 1 m, and 2 m, surface temperature recorded using surface thermistors (Brock et al., in press) Plot of air vs. surface temperature 01/08/05 to determine correlation of the two variables, *a)* air temperature vs. CNR1 estimated surface temperature, *b)* air temperature vs. surface thermistor ground temperature.

FIGURE 5.23: *Plot of air vs. surface temperature 01/08/05 to determine relationship between the two variables,* **121** *air temperature vs. CNR1 estimated surface temperature.* 

FIGURE 5.24: Surface temperature (CNR1) vs. Air temperature at 2 m 01/08/05, 2 hourly intervals.	122
FIGURE 5.25: Mean wind speeds recorded at the AWS showing a lull in the early morning on both the 601/08/05,	123
and using average values for the summer 2005 period.	
FIGURE 5.26: Regression plot of air and surface temperature relationship between 08:00-10:00, 01/08/05, CRN1 data relationship.	124
FIGURE 5.27: Regression plot of air and surface temperature relationship between 08:00-10:00 on 10 days with similar weather conditions to 01/08/05, both air and surface temperature measured at the LWS.	125
FIGURE 5.28: 2m air temperature vs. surface temperature on two different days, 31/08/07 (11:19-12:16) and 03/09/07 (11:30-13:50), with different surface materials highlighted.	127
FIGURE 5.29: Estimated debris thickness for the entire debris covered portion of the glacier using a) linear empirical approach, b) quadratic empirical relationship, c) energy balance model approach $z_o$ of 0.002 m applied, and $T_a$ equation from 01/08/05 08:00-10:00, d) energy balance model approach $z_o$ of 0.003 m applied, and $T_a$ equation from 01/08/05 08:00-10:00.	128
FIGURE 5.30: Impact of $z_{o}$ , wind speed and temperature gradient on calculated SHF values.	129
FIGURE 5.31: Field map of measured thicknesses in 1997 (unpublished map cited in Diolaiuti et al., 2006).	131
FIGURE 5.32: Comparison of thickness estimates obtained using an energy balance approach $z_0 0.002$ , air temperature regression equation 01/08/05 08:00-10:00, b) energy balance approach $z_0 0.003$ , air temperature regression equation 01/08/05 08:00-10:00, c) a empirical linear approach with different equations for each 100 m elevation band (starting at 1700-1800, up to 2400 – 2500 m) (Mihalcea et al., 2008) $T_s$ from 01/08/05 ASTER image.	138
FIGURE 5.33: CRN1 T <sub>s</sub> values with different emissivity values applied.	142
FIGURE 5.34: Debris thickness estimates when a) when different aspect/slope values are used for each pixel, b) average slope and aspect values are used in the model – both obtained from an orthophoto DEM, with a $z_o$ of 0.001 m.	144
FIGURE 5.35: a) Calculated LWR values, b) debris thickness when LWR is calculated for each ASTER pixel $z_o$ 0.016 m, c) debris thickness when LWR is calculated for each ASTER pixel $z_o$ 0.03 m, d) debris thickness when calculated SWR from each pixels slope and aspect is used with the calculated LWR values, $z_o$ of 0.016 m used.	147
FIGURE 5.36: Surface temperatures in a) 29/07/04, b) 01/08/05 from corresponding AST08 images.	150
FIGURE 4.37: 27/07/04 Debris thickness with air temperature calculated using $08:00-10:00$ equation, a) $z_o 0.002$ m, b) $z_o 0.003$ m.	151
FIGURE 5.38: Differences between debris thickness estimates in 2005 and 2004, a) $z_o 0.002 \text{ m b}$ $z_o 0.003 \text{ m}$ .	151
FIGURE 5.39: Debris thickness maps using the empirical approach of Mihalcea et al., (2008) a) 2005, b) 2004.	155
FIGURE 6.1: Identification of debris areas showing clear difference between dark debris-covered areas, blue-grey	164

(ice) and white (snow) non-debris covered areas, b) manually digitised areas of debris cover, shown in green (ASTER false colour composite image R:1, G:2, B:3N 14/08/04).

FIGURE 6.2: Field photographs illustrating debris-free areas in the upper reaches of the glacier and also the<br/>problem of snow cover at the upper limit of debris cover, a) Tributary Glacier de Mont Blanc, July 2007, b) upper<br/>limit of debris cover on the Miage June 2005, c) upper limit of debris cover on the Miage June 2006, d) upper limit<br/>of debris cover on the Miage June 2007.166

FIGURE 6.3: Processing steps completed for debris extent identification on Landsat TM 10/09/90 image, a)168TM4/TM5 band ratio, with glacier areas white, b) TM4/TM5 band ratio image with threshold of 2 applied,<br/>glaciers white, c) IHS image of TM band 3,4,and 5, d) IHS channel 2 (hue image) with threshold of 126 applied,<br/>therefore, all vegetation removed, e) Slope image showing areas  $<24^{\circ}$  (white), f) debris extent (white).

FIGURE 6.4: Processing steps completed for debris extent identification on ASTER 14/08/04 image , a)169VNIR3/SWIR4 band ratio, with glacier areas white, b) VNIR3/SWIR4 band ratio image with threshold of 2applied, glaciers white, c) IHS image of TM band 3,4, and 5, d) IHS channel 2 (hue image) with threshold of 126applied, therefore, all vegetation removed, e) Slope image showing areas <24° (white), f) debris extent (white).</td>

FIGURE 6.5: Photograph showing steepness of medial moraines, Miage Glacier. 170

FIGURE 6.6: 1991 Orthophoto DEM slope map showing high lateral slope angles of the medial moraines.171FIGURE 6.7: Application of different slope angles to the orthophoto DEM (step 5 of semi-automatic.172classification), a) orthophoto with slopes  $>24^{\circ}$  removed, b) debris extent map with slopes  $>24^{\circ}$  excluded applied to172ASTER 2004, c) orthophoto with slopes  $>30^{\circ}$  removed, d) debris extent map with slopes  $>30^{\circ}$  removed applied toASTER 2004, e) orthophoto with slopes  $>45^{\circ}$  removed, f) debris extent map with slopes  $>45^{\circ}$  removed applied toASTER 2004.ASTER 2004.

FIGURE 6.8: ASTER DEM a) slope image with all slopes  $>24^{\circ}$  removed, b) debris extent image with ASTER DEM 174 slope image applied (slopes  $>24^{\circ}$  removed) to semi-automatic method, c) slope image with all slopes  $>30^{\circ}$ removed, d) debris extent image with ASTER DEM slope image applied (slopes  $>30^{\circ}$  removed) to semi-automatic method, e) slope image with all slopes  $>50^{\circ}$  removed, f) debris extent image with ASTER DEM slope image applied (slopes  $>50^{\circ}$  Removed) to semi-automatic method.

FIGURE 6.9: *a)* 1975satellite image highlighting problems of both corase spatial resolution and snow, *b)* 2006 **175** ASTER image showing issues of snow and cloud cover which obsure the glacier.

FIGURE 6.10: Debris extent variations, a) manual method 10/09/90, b) semi-automatic method 10/09/90, c) **176** manual method 14/08/04, d) semi-automatic method 14/08/04.

FIGURE 6.11: Precision analysis of manually digitised debris extents, a) Landsat TM 10/09/90, b) ASTER 177 14/08/04

FIGURE 6.12: Precision error sources in manual digitising, due to fuzzy boundaries between debris and clean ice.178FIGURE 6.13: Lower reaches a) 2004 debris extent from Paul et al., (2004) method, b) 2004 debris cover179

manually delineated (green debris cover), c) completely covered glacier snout (looking down glacier) June 2006,d) completely covered glacier snout (looking up valley towards the glacier) August 2007.

FIGURE 6.14: Middle reaches a) 2004 Debris cover of middle reaches using Paul et al. (2004) method, b) 2004180debris cover manually delineated, c) completely covered medial moraine June 2006 (1), d) completely coveredareas away from the medial moraine June 2006 (3), e) bare ice on exposed cliff faces August 2007 (2).

FIGURE 6.15: Upper reaches a) 2004 Debris cover from upper reaches using Paul et al., (2004) method b) debris **181** cover manually delineated (green = debris, yellow = bare ice), c) bare rock between tributary glaciers – glacier de Mont Blanc 2005 (1), d)-e) 1990 and 2004 Satellite images showing area of bare rock on the slopes of the glacier de Mont Blanc appears to look debris covered (area circled in red), f) medial moraines – debris covered August 2007 (2).

FIGURE 6.16: Debris cover development of the Miage Glacier between 1770-1940, Key: 1 – Clean ice, 2 –182discontinuous debris cover, 3 – continuous debris cover, 4 – medial moraine, 5 – local rock-avalanche deposit(Deline, 2005).

FIGURE 7.1: Location of 2005 stakes and 2007 GPS base station on a) 2000 ASTER image, b) 2006 ASTER189image showing geolocational error on 2006 image, c) 2006 (newly georeferenced) images showing removal of<br/>geolocation errors from the 2006 ASTER images.189

FIGURE 7.2: Locations of sample points on flat ground and steep terrain. 190

FIGURE 7.3: Location of sample points and error values found at each site 2005-2006, showing increase in error **193** where snow, cloud, or shadow from the clouds is present, a) flat terrain, b) steep terrain.

FIGURE 7.4: Analysis of the impact of slope/aspect on elevation errors a) 2000-2004 aspect, b) 2004-2005, 2005-2006 aspect, c) 2000-2004 slope, d) 2004-2005, 2005-2006 aspect.

FIGURE 7.5: Area of interest a) 2000 and 2004 areas, b) 2005, showing areas where data was excluded due to **196** obvious distortions in the 3B band which resulted due to the presence of cloud and snow.

FIGURE 7.6: Surface elevation changes a) between 2000-2004 (with annual rates also displayed), b) between 197 2004-2005.

FIGURE 7.7: Surface elevation changes with all data above 2150 m excluded, and linear regression applied a) **198** 2000-2004, b) 2004-2005.

FIGURE 7.8: Surface elevation changes a) all glacier 2000-2004 annual rates, b) all suitable glacier area 2004-2005, c) all data up to 2150 m 2000-2004 annual rates, d) all data up to 2150 m 2004-2005 (all negative changes shown in red, all positive in green.

FIGURE 7.9: Surface velocities between 2004-2005. The Miage Glacier outline is shown to illustrate areas of zero velocity on the valley sides. 202

FIGURE 8.1: Rock samples spectral signatures a) little variation between the top and bottom (site 1c), b) clear 209 variation on each side of the rock (site 10e).

FIGURE 8.2: Map of geological units in surface debris on Miage glacier (Deline, 2002), Where L0 Rusted debris,	212
L1 Mount Blanc granite (L1a Coarse grained, L1b medium grained, L1c granite with feldspars), L2 Micro	
granite, L3 Gneiss, L4 Schists (L4a Chloroschists, L4b Black crystal schists, L4c Ochreous schists, L4d whist	
schists) L5 Ardoisier schist, L6 Quartzites, L7 Amphibolite, L8 tectonic breccias.	
FIGURE 8.3: Training sites identified from the 2007 field map of the location of major rock types ( $R:2$ , $G:3$ , $B:4$ ).	213
FIGURE 8.4: a) sample of schist collected at site 12D, b) spectral response of sample 12D.	216
FIGURE 8.5: a) sample of gneiss collected at site 14C, b) spectral response of sample 14C.	216
FIGURE 8.6: a) sample of rusted debris collected at site 10B, b) spectral response of sample 10B.	217
FIGURE 8.7: a) sample of slate collected at site 11A, b) spectral response of sample 11A.	217
FIGURE 8.8: a) sample of granite collected at site 7A, b) spectral response of sample 7A.	217
FIGURE 8.9: <i>a)</i> sample of tectonic breccia collected at site 7C, <i>b</i> ) spectral response of sample 7C.	218
FIGURE 8.10: 'Cut' dendrogram output for all collected rock samples, where each colour represents a new class identified manually, a) using their spectral response at all wavelengths of the spectroradiometer, b) ASTER bands 1-9.	219
FIGURE 8.11: Supervised classification outputs with the slope class removed.	222
FIGURE 8.12: Photograph of lower transect area in 2006 showing presence of schist and gneiss (along with other rock types), with corresponding extract from classified image suggesting schist dominates the same region.	226

227

FIGURE 8.13: Unsupervised classification of rock type distribution.

### **LIST OF EQUATIONS**

xviii

EQUATION 2.1: Thermal conductivity (K)	15
EQUATION 2.2: Thermal resistance (Tr)	16
EQUATION 2.3: Thermal diffusivity (Tdf)	17
EQUATION 2.4: Conductive heat flux (COND)	18
EQUATION 2.5: Semi-automatic debris-covered glacier boundary mapping on Landsat TM data	30
EQUATION 2.6: Semi-automatic debris-covered glacier boundary mapping on ASTER data	30
EQUATION 2.7: Surface energy balance of a glacier	37
EQUATION 2.8: Surface energy balance of a debris-covered glacier	37
EQUATION 2.9-2.13:SWR	38
EQUATION 2.14-2.16: <i>LWR</i>	39
EQUATION 2.17: SHF	41
EQUATION 2.18-2.19: Bulk Richardson number	43
EQUATION 2.20: Energy from precipitation	45
EQUATION 2.21: Change in heat store	45
EQUATION 2.22: Calculating melt	46
EQUATION 2.23-2.26: Nakawo and Young (1981) energy balance equation	47
EQUATION 2.27-2.29: Nicholson and Benn (2006) LHF and SHF calculation	50
EQUATION 5.1: Linear regression equation for calculating debris thickness	110
EQUATION 5.2: Quadratic regression equation for calculating debris thickness	110
EQUATION 5.3: Simplified energy balance model for debris-covered glaciers	112
EQUATION 5.4: Equation to estimate debris thickness	117
EQUATION 5.5: Air temperature regression equation using radiative temperature	121
EQUATION 5.6: 08:00 - 10:00 air temperature regression equation using radiative temperature (01/08/05)	123
EQUATION 5.7-5.14: Mihalcea et al., (2008) regression equations to estimate debris thickness from surface	137
temperature data, each equation applicable at 100 m elevation bands	
EQUATION 5.15: Estimating upwelling LWR	146

Page

#### **TERMINOLOGY**

#### A

A = Dimensionless transfer coefficient

*A*' = Aspect of the slope (degrees)

Ab = Ablation (m)

Ac = Linear coefficient

 $\partial T_t$  = Average rate of temperature change (K s<sup>-1</sup>)

 $\partial t$ 

 $\alpha$  = Stability correction constant

\* $\alpha$  = Surface albedo

\* $\alpha_m$  = Mean albedo of the snowpack

 $\partial STOR$  = change in heat store (W m<sup>-2</sup> or M J m<sup>-2</sup>)

ASTER = Advanced Spacebourne Thermal Emission and Reflectance radiometer

AVP = Air vapour pressure (kPa)

AWS = automatic weather station

#### <u>B</u>

 $\beta$  = Coefficient of heat transfer (4.89 J m<sup>-3</sup> deg<sup>-1</sup>)

#### <u>C</u>

c = Specific heat capacity of air at constant pressure (1.0 J kg<sup>-1</sup> deg<sup>-1</sup>)

 $COND = Conductive heat flux (W m^{-2})$ 

 $C_{pw}$  = Specific heat capacity of water (4200 J kg<sup>-1</sup> deg<sup>-1</sup>)

 $c_t$  = density of material (Kg m<sup>-3</sup>)

#### D

d = Debris thickness (m)

D = Bulk exchange/transfer coefficient (J m<sup>-3</sup> K<sup>-1</sup>)

 $D_f$  = Diffuse fraction of total incoming shortwave radiation (Wm<sup>-2</sup>)

#### E

 $\varepsilon^* =$  Effective emissivity of the sky

 $e_a$  = Vapour pressure in the air (Pa)

*ep* = empirical constant (stability correction constant)

 $e_s$  = Vapour pressure at debris surface (Pa)

 $\varepsilon_0$  = Clear sky emissivity (8.733 x 10<sup>-3</sup> Ta 0.788)

#### F

F =Radiation heat flux (Wm<sup>-2</sup>)

#### G

g = Acceleration due to gravity (9.8 m<sup>-1</sup> s<sup>-2</sup>)

G =Global radiation flux (W m<sup>-2</sup>)

#### K

k = von Karmans constant (0.40; Oke 1987)

kc = Constant depending upon cloud type (0.26 = mean value for altostratus, altocumulus, stratocumulus, stratus, and cumulus)

K = Thermal conductivity (Wm<sup>-1</sup> K<sup>-1</sup>)

#### L

L = Monin-Obukhov stability length scale

 $L_e$  = Latent heat of evaporation of water (2.49 x 10<sup>6</sup> J kg<sup>-1</sup>)

 $L_i$  = latent heat fusion of ice (3.34 10<sup>5</sup> J Kg<sup>-1</sup>)

LHF = Latent heat flux (W m<sup>-2</sup>)

LPDAAC = Land Processes Distributed Active Archive Centre

 $LWR\downarrow$  = Incoming long wave radiation (W m<sup>-2</sup>)

 $LWR\uparrow$  = Out going long wave radiation (W m<sup>-2</sup>)

LWR = Longwave radiation flux (W  $m^{-2}$ )

LWS = Lower weather station

#### M

M = Total radiance from the surface of a material W m<sup>-2</sup>

*MELT* = Sub-tephra ice melt rate over unit of time (mm w.e. per hour)

#### N

n = Cloud cover (value ranging 0.0-1.0, where 1 complete cloud cover, 0 no cloud cover)

#### <u>P</u>

P =Air pressure at the site (Pa)

 $\rho_a = \text{Air density (kg m}^{-3})$ 

 $\rho o$  = Density of the air at standard sea-level pressure (1.29 kgm<sup>-3</sup>)

*PRE* = Energy from precipitation

 $\rho w$  = Density of water (1000 kg/m<sup>-3</sup>)

 $\rho t$  = Density of a material (Kg m<sup>-3</sup>)

#### R

 $r = \text{Rainfall rate (mm hr}^{-1})$ 

R = Thermal resistance (K m<sup>2</sup> W<sup>-1</sup>)

Rb =Richardson number

RH = Relative humidity (%)

#### <u>S</u>

SA = Solar azimuth (degrees)

SHF = Sensible heat flux (W m<sup>-2</sup>)

Shl = Stake height in the first month (m)

Sh2 = Stake height in the second month (m)

- $\sigma$  = Stefan-Boltzmann constant 5.6697 x 10<sup>-8</sup> Wm<sup>-2</sup> K<sup>-4</sup>
- $SWR\downarrow$  = Incoming short wave radiation (W m<sup>-2</sup>)
- $SWR\uparrow$  = Out going short wave radiation (W m<sup>-2</sup>)
- SWR =Radiation flux (W m<sup>-2</sup>)
- *SWR*'*n* = Equivalent radiation received by a surface (Wm<sup>-2</sup>)
- SWR  $\downarrow$  *dif* = Diffuse component of incoming shortwave radiation (Wm<sup>-2</sup>)
- $SWR \downarrow dir =$  Direct component of incoming shortwave radiation (Wm<sup>-2</sup>)
- $SWR_f = Diffuse fraction of total incoming shortwave radiation (Wm<sup>-2</sup>)$
- SWR' = Incoming shortwave radiation measured in a horizontal plane  $(Wm^{-2})$

#### <u>T</u>

T = Absolute temperature (K)

 $T_{a(K)}$  = Absolute air temperature (K)

 $T_a = \text{Air temperature (°C)}$ 

- Td = Temperature difference (°C)
- Tdf = Thermal diffusivity (m<sup>2</sup> s<sup>-1</sup> x10<sup>-6</sup>)

 $T_{di}$  = Temperature at debris-ice interface (°C)

```
T_i = Ice temperature (°C)
```

Tr = Thermal resistance (m<sup>2</sup> deg W<sup>-1</sup>)

 $T_r$  = Temperature of rainfall (°C)

 $T_s$  = Surface temperature (°C)

 $T_z$  = Air temperature (K) at height z (m)

#### <u>U</u>

```
u = Wind speed (m s^{-1})
```

 $u_z$  = Mean wind speed at height z (M<sup>s-1</sup>)

UWS = Upper weather station

#### W

 $\lambda_m$  = Wavelength of maximum spectral radiant exitance (µm)

#### Z

 $z_a =$  Measurement height (m)

 $z_o =$  Aerodynamic roughness length (m)

 $z_t$  = Roughness length for temperature (m)

Z' = Angle of slope from the horizontal (degrees)

Z = Angle of sun above horizon (degrees)

# **ACKNOWLEDGEMENTS**

First and foremost I would like to thank Dr Mark Cutler and Dr Ben Brock of the University of Dundee for all their help and support during the completion of this project.

Secondly I would like to thank Professor Claudio Smiraglia, Dr Gugliemina Diolaiuti, Dr Claudia Mihalcea and others from the University of Milan, Department of Earth Sciences for their help during the duration of my fieldwork and provision of orthophoto DEMs and field data from 2005.

I would also like to thank Dr Adrian Luckman of Swansea University, for his help in the generation of a surface velocity map of the Miage glacier.

Also I would like to thank all the undergraduate students who have helped in the collection of field data for my project in the 2006, 2007, 2008 and 2009 field campaigns.

Finally, thank you to all those who have provided continuous support during the completion of this project.

# **DECLARATION**

I declare that all of the work within this thesis is my own, also unless stated:

- All references cited have been consulted.
- The work of which the thesis is a record has been completed by myself.
- It has not been previously accepted for a higher degree.

Signed:....

## ABSTRACT

#### <u>Utilisation of remote sensing for the study of debris-covered glaciers: development and testing of</u> <u>techniques on Miage Glacier, Italian Alps</u>

An increase in the number of debris-covered glaciers and expansion of debris cover across many glaciers has been documented in many of the world's major glacierised mountain ranges over the last 100 years. Debris cover has a profound impact on glacier mass balance with thick layers insulating the underlying ice and dramatically reducing ablation, while thin or patchy cover accelerates ablation through albedo reduction. Few debris-covered glaciers have been studied in comparison with 'clean' glaciers and their response to climatic change is uncertain. Remote sensing, integrated with field data, offers a powerful but as yet unrealised tool for studying and monitoring changes in debris-covered glaciers. Hence, this thesis focuses on two key aims: i) to test the utility of visible/near infrared satellite sensors, such as TERRA ASTER, for studying debris-covered glaciers; ii) to develop techniques to fully exploit the capability of these satellite sensors to extract useful information, and monitor changes over time.

Research was focused on four interrelated studies at the Miage Glacier, in the Italian Alps. First, a new method of extracting debris-thickness patterns from ASTER thermal-band imagery was developed, based on a physical energy-balance model for a debris surface. The method was found to be more accurate than previous empirical approaches, when compared with field thickness measurements, and has the potential advantage of transferability to other sites. The high spatial variability of 2 m air temperature, which does not conform to a standard lapse rate, presents a difficulty for this approach and was identified as an important area for future research. Secondly, ASTER and Landsat TM data are used to map debris-cover extent and its change over time using several different methods. A number of problems were encountered in mapping debris extent including cloud cover and snow confusion, spatial resolution, and identifying the boundary between continuous and sporadic debris. Analysis of two images in late summer 1990 and 2004 revealed only a small up glacier increase in debris cover has occurred, confirming other work's conclusions that the debris cover on Miage Glacier increased to its present extent prior to the 1990s.

A third area of research used ASTER DEMs to monitor surface elevation changes of the Miage Glacier over time to update previous studies. Surface velocities on the glacier tongue were also calculated between 2004-2005 using feature-tracking of ASTER orthorectified visible band imagery and ASTER DEMs. However, ASTER DEMs were found to be rather poor for both applications due to large elevation errors in topographically rough parts of the glacier, which prevented a full analysis and comparison of results to previous surface elevation and velocity studies. Finally, the lithological units of the debris cover were mapped, based on the spectral differences of different rock types in the debris layer, providing information both on the location and concentration of different rock types on the surface. Therefore, the identification in the variation in emissivity throughout the glacier surface can be identified, which in turn has an impact upon calculated surface temperatures and ablation respectively.

Overall, this research presents a significant contribution to understanding the impact of a debris layer on an alpine glacier, which is an area of key interest and current focus of many present glaciological studies. Since future glacial monitoring will increasingly have to consider supraglacial debris cover as a common occurrence, due to climate warming impacts of glacial retreat and permafrost melting. This contribution is achieved through the successful application of methods which utilise ASTER data to estimate debris thickness and debris extent, and the lithological mapping of debris cover. Therefore, the potential for incorporating these remote sensing techniques for debris-covered glaciers into current global glacier monitoring programs has been highlighted. However the utility of ASTER derived DEMs for surface elevation change analysis and surface velocity estimations in a study site of steep and varied terrain has been identified as questionable, due to issues of ASTER DEM accuracy in these regions.

xxvi