

Permeation, antifouling and desalination performance of TiO₂ nanotube incorporated PSf/CS blend membranes.

ABSTRACT

Polysulfone (PSf) and chitosan (CS) blend membranes were prepared by incorporating titanium dioxide nanotubes (TiO₂NT) in different compositions. The proper blending of PSf and CS in the PSf/CS/TiO₂ membranes was confirmed by ATR-IR spectroscopy. The influence of nanotubes on morphology of membranes was investigated by Field Emission Scanning Electron Microscopy (FESEM). The effect of nanotubes on hydrophilicity of the membranes was studied by water swelling and contact angle measurements. The distribution of TiO₂NT on the membrane surface was determined by Transmission Electron Microscope (TEM) analysis. The permeation property of PSf/CS/TiO₂NT membranes was carried out by measuring the time dependent pure water flux (PWF). Bovine serum albumin (BSA) protein rejection studies were performed to know the antifouling properties. The rheological percolation threshold of PSf/CS/TiO₂NT solutions was measured by viscosity studies. The nanotubes incorporated PSf/CS membranes showed enhanced permeation and antifouling properties compared to PSf/CS and nascent PSf ultrafiltration membranes. Membranes prepared well above rheological percolation threshold showed drastic reduction in pore size and acted as nanofiltration (NF) membranes.

Keyword: NF membrane; BSA; Antifouling; Chitosan