

Technical University of Denmark



Partitioning of hydrophobic organic chemicals between silicone polymers and LDPE

Gilbert, D.; Witt, G.; Smedes, F.; Mayer, Philipp

Published in:
Science Across Bridges, Borders and Boundaries

Publication date:
2014

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Gilbert, D., Witt, G., Smedes, F., & Mayer, P. (2014). Partitioning of hydrophobic organic chemicals between silicone polymers and LDPE. In Science Across Bridges, Borders and Boundaries: Programme Book Basel, Switzerland: SETAC-Europe.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

TH052 Partitioning of hydrophobic organic chemicals between silicone polymers and LDPE D. Gilbert, Aarhus University Science and Technology Faculty / Department of Environmental Sciences; G. Witt, HAW Hamburg / Department of Environmental Engineering; F. Smedes, DELTARES / RECETOX; P. Mayer, Technical University of Denmark / Department of Environmental Engineering. Hydrophobic organic chemicals (HOCs) are widely distributed in the environment. To monitor their occurrence and fate, and to determine their toxic potential, several methods exploit HOC partitioning using polymer-based passive sampling and dosing. A wide range of polymeric materials is available, and especially different silicone materials are often preferred for HOCs offering great flexibility in application formats. Differences between polymeric partitioning phases can be determined on the basis of polymer-polymer partitioning coefficients. Simple co-exposure experiments were thus conducted with a wide range of silicone materials and one low density polyethylene. The obtained polymer-polymer partition coefficients (1) revealed differences in the partitioning of HOCs between polymers, (2) indicated the presence of fillers in some polymers, (3) indicated differences in chemical structure of some silicone polymers and (4) allowed to determine the contribution of partitioning differences between polymers to the total variability in published polymer-water partition coefficients. Finally, we present strategies on how polymer-polymer partition coefficients can be applied for correction of differences between passive sampling and dosing materials, and for the determination of polymer-specific partition coefficients.