

Chapman University Chapman University Digital Commons

Mathematics, Physics, and Computer Science
Faculty Articles and Research

Science and Technology Faculty Articles and
Research

8-2018

Partially-Ordered Multi-Type Algebras, Display Calculi and the Category of Weakening Relations

Peter Jipsen

Chapman University, jipsen@chapman.edu

Fei Liang

University of Delft

M. Andrew Moshier

Chapman University, moshier@chapman.edu

Apostolos Tzimoulis

University of Delft

Follow this and additional works at: https://digitalcommons.chapman.edu/scs_articles

 Part of the [Algebra Commons](#)

Recommended Citation

Jipsen, P., Liang, F., Moshier, M. A., Tzimoulis, A. (2017) Partially-ordered multi-type algebras, display calculi and the category of weakening relations. Proceedings of LATD 2018.

This Article is brought to you for free and open access by the Science and Technology Faculty Articles and Research at Chapman University Digital Commons. It has been accepted for inclusion in Mathematics, Physics, and Computer Science Faculty Articles and Research by an authorized administrator of Chapman University Digital Commons. For more information, please contact laughtin@chapman.edu.

Partially-Ordered Multi-Type Algebras, Display Calculi and the Category of Weakening Relations

Comments

This paper was presented at the [Logic, Algebra and Truth Degrees conference](#) in August 2018.

Partially-ordered multi-type algebras, display calculi and the category of weakening relations

Peter Jipsen^{*1}, Fei Liang², M. Andrew Moshier¹ and Apostolos Tzimoulis²

¹ Chapman University, California, USA

jipsen@chapman.edu

moshier@chapman.edu

² University of Delft, The Netherlands

f.liang@tudelft.nl

apostolos@tzimoulis.eu

We define partially-ordered multi-type algebras and use them as algebraic semantics for multi-type display calculi that have recently been developed for several logics, including dynamic epistemic logic [7], linear logic [10], lattice logic [11], bilattice logic [9] and semi-De Morgan logic [8].

Multi-type algebras, also called many-sorted or heterogeneous algebras [1] have been studied in the setting of universal algebra and they have applications, e.g., as abstract data types in computer science [2] and in algebraic logic [4].

A multi-type algebra is of the form $\mathbb{A} = ((A_\tau)_{\tau \in \mathcal{T}}, \mathcal{F})$ where each $f \in \mathcal{F}$ is a function $f : A_{\tau_1} \times \cdots \times A_{\tau_n} \rightarrow A_\tau$ for some $\tau_1, \dots, \tau_n, \tau \in \mathcal{T}$. The set of types \mathcal{T} and the sequences $\tau_1, \dots, \tau_n, \tau$ for each operation $f \in \mathcal{F}$ determine the signature Σ of the algebra. A partially-ordered multi-type algebra (pom-algebra for short) replaces the carrier sets A_τ by partially-ordered sets (A_τ, \leq_τ) and insists that the operations are order-preserving or order-reversing in each argument. This is recorded in the signature Σ by a sequence $\varepsilon \in \{1, \partial\}^n$ for each n -ary operation f such that $A_{\tau_i}^{\varepsilon_i} = A_{\tau_i}$ for $\varepsilon_i = 1$ if f is order-preserving in the i th coordinate, and $A_{\tau_i}^{\varepsilon_i} = A_{\tau_i}^\partial$, the dual poset, otherwise. Pom-algebras are a generalization of partially ordered (un)type algebras. Varieties and quasivarieties of partially ordered algebras have been studied by Pigozzi in [12], and these universal algebraic concepts extend smoothly to pom-algebras of a given signature.

In the setting of this talk we mostly consider pom-algebras in which each carrier set has lattice operations \vee_τ, \wedge_τ defined on it. In this case \leq_τ is assumed to be the lattice order and such algebras are called lattice-ordered multi-type algebras, or ℓm -algebras. An important insight of multi-type display calculi is that certain unitype lattice-ordered algebras can be recast as ℓm -algebras where each of the carriers support simpler algebraic structure. The decomposition of lattice-ordered unitype algebras into simpler loosely connected components can lead to the definition of uniform decision procedures, in the form of display calculi, for the equational theory or even the universal theory of the original untyped algebras. In some cases the unitype algebras satisfy identities that cannot be captured by display calculus rules, but for their pom-algebra counterparts this difficulty is resolved since the carriers of each type satisfy simpler identities.

Examples and results

Every lattice decomposes as a pom-algebra of a join-semilattice and a (disjoint) meet-semilattice, with the connection given by an inverse pair of order-isomorphisms. The decision procedure given by the display calculus of this variety of pom-algebras is Whitmann's solution of the word problem for free lattices, originally due to Skolem (see [3]).

A semi-De Morgan lattice (not necessarily distributive) decomposes as a lattice and a De Morgan lattice, connected by two unary order-preserving maps as in [8]. The display calculus for semi-De Morgan lattices interleaves Whitmann's solution for lattices with a similar algorithm for De Morgan lattices.

A linear logic algebra with exponentials decomposes into a residuated lattice and a Heyting algebra connected with two adjunctions. Again this leads to a display calculus for linear logic.

The concept of *residuated frame* from [6] is extended to ℓ m-algebras and provides multi-type frame semantics for display calculi. This allows many of the techniques for residuated frames to be applied in the more general setting of ℓ m-algebras.

Display calculi use sequents of the form $s \leq_{\tau} t$ as ingredients for the rules of the calculus, with both terms s, t having the same result type τ . However if $t = f(t_1, \dots, t_n)$ one can also consider a new sequent symbol $s \leq_{\tau}^f (t_1, \dots, t_n)$. In this case \leq_{τ}^f is a relation from A_{τ} to $A_{\tau_1}^{\varepsilon_1} \times \dots \times A_{\tau_n}^{\varepsilon_n}$. Similarly the top-level operation symbol of the left-hand term of a sequent can be used to define a new sequent symbol. From this point of view sequent separator symbols are morphisms in the category of posets, similar to the adjunctions that map between carrier posets in pom-algebras.

For posets $\mathbb{P} = (P, \leq^{\mathbb{P}})$ and $\mathbb{Q} = (Q, \leq^{\mathbb{Q}})$ a binary relation $R \subseteq P \times Q$ is a *weakening relation* if $\leq^{\mathbb{P}} \circ R \circ \leq^{\mathbb{Q}} \subseteq R$. The class of posets with with weakening relations as morphisms forms a category $\overline{\text{Pos}}$ that contains the category Pos of posets with order-preserving maps. We characterize the display calculus morphisms as weakening relations in the category $\overline{\text{Pos}}$.

References

- [1] Birkhoff G., Lipson J. D. (1970) Heterogeneous Algebras, *Journal of Combinatorial Theory*, **8**, 115–133
- [2] Burmeister P. (2002) Lecture Notes on Universal Algebra Many-Sorted Partial Algebras, <http://www.mathematik.tu-darmstadt.de/Math-Net/Lehrveranstaltungen/Lehrmaterial/SS2002/AllgemeineAlgebra/download/LNPartAlg.pdf>
- [3] Burris, S. (1995), Polynomial time uniform word problems. *Mathematical Logic Quarterly*, 41: 173–182
- [4] Caleiro C., Goncalves R. (2007) On the Algebraization of Many-Sorted Logics. In: Fiadeiro J.L., Schobbens P.Y. (eds) *Recent Trends in Algebraic Development Techniques*. WADT 2006. *Lecture Notes in Computer Science*, vol 4409. Springer, Berlin, Heidelberg

~

- [5] Frittella S., Greco G., Kurz A., Palmigiano A., Sikimić V. (2016) Multi-type sequent calculi, <https://arxiv.org/abs/1609.05343>
- [6] Galatos N., Jipsen P. (2013) Residuated frames with applications to decidability, Transactions of the American Mathematical Society **365**(3) 1219-1249
- [7] Greco G., Kurz A., Palmigiano A. (2013) Dynamic epistemic logic displayed. In: Grossi D., Roy O., Huang H. (eds) Logic, Rationality, and Interaction. LORI 2013. Lecture Notes in Computer Science, vol 8196. Springer, Berlin, Heidelberg
- [8] Greco G., Liang F., Moshier M.A., Palmigiano A. (2017) Multi-type display calculus for semi De Morgan logic. In: Kennedy J., de Queiroz R. (eds) Logic, Language, Information, and Computation. WoLLIC 2017. Lecture Notes in Computer Science, vol 10388. Springer, Berlin, Heidelberg
- [9] Greco G., Liang F., Palmigiano A., Rivieccio U. (2017) Bilattice logic properly displayed, <https://arxiv.org/abs/1709.02167>
- [10] Greco G. and Palmigiano A. Linear logic properly displayed, <https://arxiv.org/abs/1611.04181>
- [11] Greco G. and Palmigiano A. Lattice logic properly displayed, <https://arxiv.org/abs/1612.05930>
- [12] Pigozzi D. (2004) Partially ordered varieties and quasivarieties, https://orion.math.iastate.edu/dpigozzi/notes/santiago_notes.pdf