

Old Dominion University ODU Digital Commons

Mechanical & Aerospace Engineering Faculty
Publications

Mechanical & Aerospace Engineering

8-2018

Editorial for the Special Issue on Micro/Nano- Chip Electrokinetics, Volume II

Xiangchun Xuan

Shizhi Qian

Old Dominion University, sqian@odu.edu

Follow this and additional works at: https://digitalcommons.odu.edu/mae_fac_pubs

 Part of the [Nanoscience and Nanotechnology Commons](#)

Repository Citation

Xuan, Xiangchun and Qian, Shizhi, "Editorial for the Special Issue on Micro/Nano-Chip Electrokinetics, Volume II" (2018).
Mechanical & Aerospace Engineering Faculty Publications. 68.
https://digitalcommons.odu.edu/mae_fac_pubs/68

Original Publication Citation

Xuan, X. C., & Qian, S. Z. (2018). Editorial for the special issue on Micro/Nano-Chip Electrokinetics, Volume II. *Micromachines*, 9(8).
doi:10.3390/mi9080383

This Editorial is brought to you for free and open access by the Mechanical & Aerospace Engineering at ODU Digital Commons. It has been accepted for inclusion in Mechanical & Aerospace Engineering Faculty Publications by an authorized administrator of ODU Digital Commons. For more information, please contact digitalcommons@odu.edu.

Editorial

Editorial for the Special Issue on Micro/Nano-Chip Electrokinetics, Volume II

Xiangchun Xuan ^{1,*}  and Shizhi Qian ²¹ Department of Mechanical Engineering, Clemson University, Clemson, SC 29634, USA² Department of Mechanical and Aerospace Engineering, Old Dominion University, Norfolk, VA 23529, USA; SQian@odu.edu

* Correspondence: xcxuan@clemson.edu

Received: 25 July 2018; Accepted: 30 July 2018; Published: 2 August 2018



There has been a rapidly increasing interest in the use of micro/nanofluidics to develop various point-of-care technologies for global health [1,2]. Electrokinetics is often the method of choice in these micro/nano-chips for an accurate transport and manipulation of fluids and samples [3,4]. This special issue in *Micromachines* is the continuation of our successful first volume on Micro/Nano-Chip Electrokinetics [5]. It consists of 22 contributions, which cover multiple aspects of electrokinetics related phenomena for various chemical and biological applications. We divide these papers into three primary categories and summarize them briefly below.

1. Linear Electrokinetic Phenomena (Seven Papers)

Fluid electroosmosis and particle electrophoresis are linear electrokinetic phenomena, and are proportional and parallel to the applied electric field [3,4]. Electroosmotic flow in micro/nanochannels can be significantly affected by the fluid rheological properties in addition to the wall properties. Guo and Qi [6] obtained an analytical solution of the electroosmotic peristaltic flow of viscoelastic fluids through a cylindrical microchannel using the fractional Jeffrey's constitutive model. Choi et al. [7] carried out a finite element analysis of the electroosmotic flow of power-law fluids in a rectangular microchannel with asymmetric wall zeta potentials. They later [8] reported an approximate analytical solution to a similar flow in a slit microchannel. Mei et al. [9] studied the electroosmotic flow of a linear Phan–Thien–Tanner fluid in a nanoslit by solving numerically the nonlinear Poisson–Nernst–Planck equations. Matías et al. [10] presented a perturbation analysis of Joule heating effects on electroosmotic flow in a microcapillary tube filled with immiscible Newtonian and power-law fluids. Lu et al. [11] used a molecular dynamics simulation to study the electroosmotic flow in rough nanochannels, with particular attention to the fluid–solid interactions. Lim et al. [12] developed a technique to fabricate microchannels with black silicon nanostructures for a controllable suppression of electroosmotic flow.

2. Nonlinear Electrokinetic Phenomena (Eight Papers)

Nonlinear electrokinetic phenomena occur because of the action of electric field on an electrically induced dipole (i.e., dielectrophoresis or DEP) or free charge (e.g., induced charge electrokinetic phenomena and electrothermal flow). Akshay et al. [13] demonstrated significantly enhanced particle focusing and enrichment by the use of three-dimensional reservoir-based dielectrophoresis (rDEP) at the reservoir–microchannel junction. Zhao et al. [14] used a volumetric polarization and integration method to investigate the mechanisms for their observed tumbling motion of pearl chains and alignment of ellipsoidal particles. Both phenomena were found to be governed by the particle–particle interactions under DEP. Ji et al. [15] reported a direct numerical simulation of similar dielectrophoretic interactions between deformable particles. Liu et al. [16] proposed a method of bipolar field-effect control of direct current electroosmosis for multifunctional sample handling. Later, Tao et al. [17] used a similar idea to design nanofluidic ion diodes for field-effect control of ion current. Hu et al. [18]

utilized the stirring fluid motion of induced charge electroosmotic flow over a floating gate electrode to improve the binding efficiency of microfluidic heterogeneous immunoassays. Ren et al. [19] explored the feasibility of using alternating current electric field-induced nonlinear electroosmosis next to sharp dielectric corners for on-chip mixing. Liu et al. [20] studied the electrode cooling effect on the travelling wave electrothermal flow in rotating electric fields.

3. Other Electric-Field-Mediated Phenomena (Seven Papers)

Song et al. [21] reported a numerical study of the electric-magnetic regulation of the heat convection between an electrolyte solution and microchannel walls for potential applications to microelectronics cooling. Shen et al. [22] demonstrated the use of optimized electrical driving waveforms to reduce the fringe phenomena in electrophoretic display. Zhang et al. [23] reported an on-chip impedance sensor that is capable of detecting both rigid particles and soft droplets/bubbles in hydraulic oil in an inductive and a capacitive mode, respectively. Yazdanshenas et al. [24] developed a microfluidic Kelvin water dropper that can generate high-voltage electricity through water dripping and also used their device to replace the high-voltage power supply in electrowetting. Hu et al. [25] demonstrated a microfluidic mixer design that utilizes amplified Marangoni chaotic advection induced by alternating current electrowetting of a metal droplet. Ahmed and Kim [26] presented a numerical parametric study of electroosmotic micro-mixers with heterogeneously charged surface patches on channel walls. In another study, Chen et al. [27] proposed and numerically verified the use of embedded asymmetric electrode arrays on microchannel walls to generate vortices for mixing enhancement.

We would like to express our sincere thanks to all of the contributors to this Special Issue. We also appreciate the time and efforts from all the reviewers, without which this Special issue would not be possible.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Jung, W.E.; Han, J.; Choi, J.W.; Ahn, C.H. Point-of-care testing (POCT) diagnostic systems using microfluidic lab-on-a-chip technologies. *Microelectron. Eng.* **2015**, *132*, 46–57. [[CrossRef](#)]
2. Fernandes, A.C.; Gernaey, K.V.; Kruhne, U. Connecting worlds—A view on microfluidics for a wider application. *Biotechnol. Adv.* **2018**, *36*, 1341–1366. [[CrossRef](#)] [[PubMed](#)]
3. Li, D. *Electrokinetics in Microfluidics*; Elsevier Academic Press: Burlington, MA, USA, 2004.
4. Chang, H.C.; Yeo, L.Y. *Electrokinetically Driven Microfluidics and Nanofluidics*; Cambridge University Press: New York, NY, USA, 2010.
5. Xuan, X.; Qian, S. Editorial for the special issue on micro/nano-chip electrokinetics. *Micromachines* **2017**, *8*, 145. [[CrossRef](#)]
6. Guo, X.; Qi, H. Analytical solution of electro-osmotic peristalsis of fractional jeffreys fluid in a micro-channel. *Micromachines* **2017**, *8*, 341. [[CrossRef](#)]
7. Choi, W.; Yun, S.; Choi, D.S. Electroosmotic flows of power-law fluids with asymmetric electrochemical boundary conditions in a rectangular microchannel. *Micromachines* **2017**, *8*, 165. [[CrossRef](#)]
8. Choi, W.; Yun, S.; Choi, D.S. Approximate solution for electroosmotic flow of power-law fluids in a planar microchannel with asymmetric electrochemical boundary conditions. *Micromachines* **2018**, *9*, 265. [[CrossRef](#)]
9. Mei, L.; Zhang, H.; Meng, H.; Qian, S. Electroosmotic Flow of Viscoelastic Fluid in A Nanoslit. *Micromachines* **2018**, *9*, 155. [[CrossRef](#)]
10. Matías, A.; Méndez, F.; Bautista, O. Interfacial electric effects on a non-isothermal electroosmotic flow in a microcapillary tube filled by two immiscible fluids. *Micromachines* **2017**, *8*, 232. [[CrossRef](#)]
11. Lu, P.; Liu, X.; Zhang, C. Electroosmotic flow in a rough nanochannel with surface roughness characterized by fractal cantor. *Micromachines* **2017**, *8*, 190. [[CrossRef](#)]
12. Lim, A.E.; Lim, C.Y.; Lam, Y.C.; Taboryski, R. Electroosmotic flow in microchannel with black silicon nanostructures. *Micromachines* **2018**, *9*, 229. [[CrossRef](#)]

13. Kale, A.; Patel, S.; Xuan, X. Three-dimensional reservoir-based dielectrophoresis (rDEP) for enhanced particle enrichment. *Micromachines* **2018**, *9*, 123. [[CrossRef](#)]
14. Zhao, Y.; Brcka, J.; Faguet, J.; Zhang, G. Elucidating the mechanisms of two unique phenomena governed by particle-particle interaction under DEP: Tumbling motion of pearl chains and alignment of ellipsoidal particles. *Micromachines* **2018**, *9*, 279. [[CrossRef](#)]
15. Ji, X.; Xu, L.; Zhou, T.; Shi, L.; Deng, Y.; Li, J. Numerical investigation of DC dielectrophoretic deformable particle-particle interactions and assembly. *Micromachines* **2018**, *9*, 260. [[CrossRef](#)]
16. Liu, W.; Wu, Q.; Ren, Y.; Cui, P.; Yao, B.; Li, Y.; Hui, M.; Jiang, T.; Bai, L. On the bipolar DC flow field-effect-transistor for multifunctional sample handling in microfluidics: A theoretical analysis under the debye-huckel limit. *Micromachines* **2018**, *9*, 82. [[CrossRef](#)]
17. Tao, Y.; Liu, W.; Ren, Y.; Hu, Y.; Li, G.; Ma, G.; Wu, Q. On developing field-effect-tunable nanofluidic ion diodes with bipolar, induced-charge electrokinetics. *Micromachines* **2018**, *9*, 179. [[CrossRef](#)]
18. Hu, Q.; Ren, Y.; Liu, W.; Tao, Y.; Jiang, H. Simulation analysis of improving microfluidic heterogeneous immunoassay using induced charge electroosmosis on a floating gate. *Micromachines* **2017**, *8*, 212. [[CrossRef](#)]
19. Ren, Y.; Liu, W.; Tao, Y.; Hui, M.; Wu, Q. On AC-field-induced nonlinear electroosmosis next to the sharp corner-field-singularity of leaky dielectric blocks and its application in on-chip micro-mixing. *Micromachines* **2018**, *9*, 102. [[CrossRef](#)]
20. Liu, W.; Ren, Y.; Tao, Y.; Chen, X.; Wu, Q. Electrode cooling effect on out-of-phase electrothermal streaming in rotating electric fields. *Micromachines* **2017**, *8*, 327. [[CrossRef](#)]
21. Song, M.; Chi, X.; Wang, Y.; Ma, Y. Electromagnetic regulation of electrolyte solution heat convection in microchannels. *Micromachines* **2018**, *9*, 262. [[CrossRef](#)]
22. Shen, S.; Gong, Y.; Jin, M.; Yan, Z.; Xu, C.; Yi, Z.; Zhou, G.; Shui, L. Improving electrophoretic particle motion control in electrophoretic displays by eliminating the fringing effect via driving waveform design. *Micromachines* **2018**, *9*, 143. [[CrossRef](#)]
23. Zhang, H.; Zeng, L.; Teng, H.; Zhang, X. A novel on-chip impedance sensor for the detection of particle contamination in hydraulic oil. *Micromachines* **2017**, *8*, 249. [[CrossRef](#)]
24. Yazdanshenas, E.; Tang, Q.; Zhang, X. Electrowetting using a microfluidic kelvin water dropper. *Micromachines* **2018**, *9*, 92. [[CrossRef](#)]
25. Hu, Q.; Ren, Y.; Liu, W.; Chen, X.; Tao, Y.; Jiang, H. Fluid flow and mixing induced by AC continuous electrowetting of liquid metal droplet. *Micromachines* **2017**, *8*, 119. [[CrossRef](#)]
26. Ahmed, F.; Kim, K.Y. Parametric study of an electroosmotic micromixer with heterogeneous charged surface patches. *Micromachines* **2017**, *8*, 199. [[CrossRef](#)]
27. Chen, L.; Deng, Y.; Zhou, T.; Pan, H.; Liu, Z. A novel electroosmotic micromixer with asymmetric lateral structures and DC electrode arrays. *Micromachines* **2017**, *8*, 105. [[CrossRef](#)]

