

Proceedings of the Society for Computation in Linguistics

Volume 2

Article 31

2019

Empty Categories Help Parse the Overt

Weiwei Sun

Peking University, ws@pku.edu.cn

Follow this and additional works at: <https://scholarworks.umass.edu/scil>



Part of the [Computational Linguistics Commons](#)

Recommended Citation

Sun, Weiwei (2019) "Empty Categories Help Parse the Overt," *Proceedings of the Society for Computation in Linguistics*: Vol. 2 , Article 31.

DOI: <https://doi.org/10.7275/s40b-cr80>

Available at: <https://scholarworks.umass.edu/scil/vol2/iss1/31>

This Extended Abstract is brought to you for free and open access by ScholarWorks@UMass Amherst. It has been accepted for inclusion in Proceedings of the Society for Computation in Linguistics by an authorized editor of ScholarWorks@UMass Amherst. For more information, please contact scholarworks@library.umass.edu.

Empty Categories Help Parse the Overt

Weiwei Sun

Institute of Computer Science and Technology
The MOE Key Laboratory of Computational Linguistics
Center for Chinese Linguistics
Peking University
ws@pku.edu.cn

Abstract

This paper is concerned with whether deep syntactic information can help surface parsing, with a particular focus on empty categories. We consider data-driven dependency parsing with both linear and neural disambiguation models. We find that the information about empty categories is helpful to reduce the approximation error in a structured prediction based parsing model, but increases the search space for inference and accordingly the estimation error. To deal with structure-based overfitting, we propose to integrate disambiguation models with and without empty elements. Experiments on English and Chinese TreeBanks indicate that incorporating empty elements consistently improves surface parsing.

1 Introduction

In the last two decades, there was an increasing interest in producing rich syntactic annotations that are not limited to surface analysis. Such analysis, e.g. deep dependency structures (King et al., 2003), is usually coupled with grammars under deep formalisms, e.g. Combinatory Categorical Grammar, Head-driven Phrase-Structure Grammar and Lexical-Functional Grammar. Although deep grammar formalisms allow information beyond local construction to be constructed, it is still not clear whether such additional information is helpful for surface syntactic analysis. This is partly because analysis grounded on different grammar formalisms, e.g. HPSG and CFG, are not directly comparable.

In the Government and Binding (GB; Chomsky (1981)) theory, empty category is a key concept bridging S-Structure and D-Structure, due to its possible contribution to trace *movements*. Following the linguistic insights underlying GB, a traditional dependency analysis can be augmented with

empty elements, viz. covert elements (Xue and Yang, 2013). The new representation provides a considerable amount of deep syntactic information, while keeping intact all dependencies of overt words. In this paper, we arguably call dependencies among overt words only surface analysis. See Figure 1 for an English example. Integrating both overt and covert elements in one unified representation provides an effective yet light-weight way to achieve deeper language understanding beyond surface syntax.

This paper studies graph-based parsing models for this new representation with a particular focus on the impact of information about the covert on parsing the overt. The major advantage of the graph-based approach to dependency parsing is that its constrained factorization enables the design of polynomial time algorithms for decoding, especially for projective structures. Following GB, an empty element can only be a dependent. Furthermore, the number and distribution of empty elements in one sentence are highly constrained. These properties make polynomial time decoding for joint empty element detection and dependency parsing still plausible. To exemplify our idea, we extend McDonald and Pereira (2006)’s second-order and Koo and Collins (2010)’s third-order models for the new problem.

The influence of incorporating empty elements is twofold. On the one hand, the extra information enriches the structural information of the outputs, which is important to reduce the approximation error in a structured prediction problem. On the other hand, predicting empty elements increases the search space for decoding, and thus increases the difficulty of parameter estimation for disambiguation. To evaluate the impact of empty categories, we implement different parsing models based on global linear and neural models, and conduct experiments on English Penn TreeBank

which represents a small substructure of \mathbf{y} ; for example, \mathbf{y} might be factored into the set of its component dependencies. The parts are evaluated using a *local* scoring function SCOREPART. The factorization thus establishes implicit independence restrictions between parts, which can be exploited to efficiently solve the combinatorial optimization problem involved in the search for the highest-scoring dependency analysis.

Now consider dependency parsing with empty category detection. We also formulate the issue as an optimization problem. Assume that we are given a sentence x with n normal words. We use an index set $\mathcal{I}_o = \{(i, j) | i, j \in \{1, \dots, n\}\}$ to denote all possible overt dependency edges, and use $\mathcal{I}_c = \{(i, \phi_j) | i, j \in \{1, \dots, n\}\}$ to denote all possible covert dependency edges. ϕ_j denotes an empty node that precede the j th word. Then a dependency parse with empty nodes can be represented as a vector:

$$\mathbf{z} = \{z(i, j) : (i, j) \in \mathcal{I}_o \cup \mathcal{I}_c\}.$$

Let \mathcal{Z} denote the set of all possible \mathbf{z} , and PART(\mathbf{z}) denote the factors in the dependency tree, including edges (and edge siblings in the second-order model). Then parsing with ECD can be defined as a search for the highest-scored $\mathbf{z}^*(x)$ in all compatible analyses, just like parsing without empty elements:

$$\begin{aligned} \mathbf{z}^*(x) &= \arg \max_{\mathbf{z} \in \mathcal{Z}(x)} \text{SCORE}(x, \mathbf{z}) \\ &= \arg \max_{\mathbf{z} \in \mathcal{Z}(x)} \sum_{p \in \text{PART}(\mathbf{z})} \text{SCOREPART}(x, p) \end{aligned}$$

The choice of factorization involves a tradeoff between complexity and expressiveness, and thus design of factorizations that are both expressive and efficiently parsable is of critical importance for practical parsing applications. A number of dynamic programming (DP) algorithms have been designed for first- (Eisner, 1996), second- (McDonald and Pereira, 2006; Carreras, 2007) and third- (Koo and Collins, 2010) factorization. In Zhang et al. (2017), we introduced the basic design of the above algorithms and their extensions to include detection of empty categories.

3 Experiments

We conduct experiments on both English and Chinese treebanks. In particular, PTB and CTB are used. Because PTB and CTB are phrase-structure

Table 1: UAS_o of different individual models on test data. The upper and bottom blocks present results obtained by sibling and tri-sibling models respectively.

| Algo | English | Chinese |
|------|---------------|---------------|
| 1 | 91.73 | 89.16 |
| 3 | 91.70 (−0.03) | 89.20 (+0.04) |
| 4 | 91.72 (−0.01) | 89.28 (+0.12) |
| 2 | 92.23 | 90.00 |
| 5 | 92.41 (+0.18) | 89.82 (−0.18) |

treebanks, we need to convert them into dependency annotations. To do so, we use the tool provided by Stanford CoreNLP to process PTB, and the tool provided by Xue and Yang (2013) to process CTB 5.0. We use gold-standard POS to derive features for disambiguation. We use standard training, validation, and test splits to facilitate comparisons. Accuracy is measured with unlabeled attachment score for all overt words (UAS_o): the percentage of overt words with the correct head. We are also concerned with the prediction accuracy for empty elements. To evaluate performance on empty nodes, we consider the correctness of empty edges. We report the percentage of empty words in right slot with correct head. The i -th slot in the sentence means that the position immediately after the i -th concrete word. So if we have a sentence with length n , we get $n + 1$ slots.

Table 1 lists the accuracy of individual models coupled with different decoding algorithms on the test sets. We focus on the prediction for overt words only. Models coupled with Algorithm 1, 3 and 4 are second-order models, while with 2 and 5 third-order ones. When we take into account empty categories, more information is available. The empirical results suggest that deep linguistic information does not necessarily help surface analysis.

We can see from the definition of the extended algorithms that the search space for decoding is significantly increased. This results in a side effect for practical parsing. Given the limit of available annotations for training, searching for more complicated structures in a larger space is harmful to the generalization ability in structured prediction (Sun, 2014). Incorporating empty elements significantly increases the difficulty for parameter estimation, and therefore it is harder to find a good disambiguation model. To control structure-based overfitting, we propose to combine the two score functions learned from models with and without

Table 2: UAS_o of different joint decoding models on test data. “CM” and “DD” are short for joint decoders based on chart merging and dual decomposition respectively. The upper and bottom blocks present results obtained by sibling and tri-sibling models respectively. All improvements are statistically significant.

| | Algo | English | Chinese |
|----|------|---------------|---------------|
| CM | 1+3 | 91.94 (+0.21) | 89.53 (+0.37) |
| | 1+4 | 91.88 (+0.15) | 89.44 (+0.28) |
| DD | 1+3 | 91.96 (+0.23) | 89.53 (+0.37) |
| | 1+4 | 91.94 (+0.21) | 89.53 (+0.37) |
| CM | 2+5 | 92.60 (+0.37) | 90.35 (+0.35) |
| DD | 2+5 | 92.71 (+0.48) | 90.38 (+0.38) |

empty elements.

We evaluate two joint decoders: chart merging and dual decomposition. Table 2 lists the accuracy of different joint decoding models on the test sets. We can see that the joint decoding framework is effective to deal with structure-based overfitting. This time, the accuracy of analysis for overt words is consistently improved across a wide range of conditions. Especially, the third-order model is improved more. We use the Hypothesis Tests method (Berg-Kirkpatrick et al., 2012) to evaluate the improvements. When the p -value is set to 0.05, all improvements in Figure 2 is statistically significant.

Table 3: UAS_o of different neural parsing models on test data. Results are obtained by sibling models. The joint decoder is CM.

| Algo | English | Chinese |
|------|---------|---------|
| 1 | 93.59 | 90.70 |
| 3 | 93.49 | 90.45 |
| 1+3 | 93.96 | 92.00 |

We also evaluate the impact of empty categories as well as joint decoding on neural dependency parsing. Table 3 summarizes the results. Due to the complexity of third-order parsing model as well as its marginal improvement, we only report results obtained by second-order parsing. Without structure regularization, i.e. joint decoding in our case, incorporating information about empty category cannot improve surface parsing. In fact, the parsing accuracy decreases slightly. When the model for parsing without empty elements is incorporated, empty category always improves surface parsing. The improvement is statistically significant.

References

- Taylor Berg-Kirkpatrick, David Burkett, and Dan Klein. 2012. An empirical investigation of statistical significance in NLP. In *Proceedings of the 2012 Joint Conference on EMNLP and CoNLL*.
- Xavier Carreras. 2007. Experiments with a higher-order projective dependency parser. In *In Proc. EMNLP-CoNLL*.
- Yufei Chen, Yuanyuan Zhao, Weiwei Sun, and Xiaojun Wan. 2018. Pre- and in-parsing models for neural empty category detection. In *Proceedings of the ACL*. <http://aclweb.org/anthology/P18-1250>.
- Noam Chomsky. 1981. *Lectures on Government and Binding*. Foris Publications, Dordrecht.
- Jason M. Eisner. 1996. Three new probabilistic models for dependency parsing: an exploration. In *Proceedings of the 16th conference on Computational linguistics - Volume 1*, pages 340–345.
- Tracy Holloway King, Richard Crouch, Stefan Riezler, Mary Dalrymple, and Ronald M. Kaplan. 2003. The PARC 700 dependency bank. In *Proceedings of the 4th International Workshop on Linguistically Interpreted Corpora (LINC-03)*, pages 1–8.
- Terry Koo and Michael Collins. 2010. Efficient third-order dependency parsers. In *Proceedings of ACL*. Association for Computational Linguistics, Uppsala, Sweden, pages 1–11.
- Mitchell P. Marcus, Mary Ann Marcinkiewicz, and Beatrice Santorini. 1993. Building a large annotated corpus of english: the Penn treebank. *Comput. Linguist.* 19(2):313–330.
- Ryan McDonald and Fernando Pereira. 2006. Online learning of approximate dependency parsing algorithms. In *Proceedings of EACL-2006*, volume 6, pages 81–88.
- Xu Sun. 2014. Structure regularization for structured prediction. In *Advances in Neural Information Processing Systems 27*, pages 2402–2410.
- Naiwen Xue, Fei Xia, Fu-dong Chiou, and Marta Palmer. 2005. The Penn Chinese treebank: Phrase structure annotation of a large corpus. *Natural Language Engineering* 11:207–238.
- Nianwen Xue and Yaqin Yang. 2013. Dependency-based empty category detection via phrase structure trees. In *Proceedings of NAACL-2013*. Atlanta, Georgia, pages 1051–1060.
- Xun Zhang, Weiwei Sun, and Xiaojun Wan. 2017. The covert helps parse the overt. In *Proceedings of the CoNLL*, pages 343–353. <http://aclweb.org/anthology/K17-1035>.