

ASSESSMENT OF TRAFFIC CONGESTION IN THE CENTRAL AREAS OF KIMBERLEY CITY

D.K. DAS¹ & M.S.M. KEETSE²

SURT RESEARCH GROUP

¹CENTRAL UNIVERSITY OF TECHNOLOGY, FREE STATE

²SOL PLAATJE MUNICIPALITY, KIMBERLEY, SOUTH AFRICA

Abstract

Traffic congestion is a challenge leading to undesirable consequences in most of the cities of the world. Many large and medium cities of South Africa, specifically the central business districts (CBD) are facing this challenge and are severely affected by this mobility problem. One such city, Kimberley, because of its unique physical, spatial, road network, economic characteristics and requirement of the mobility of heavy vehicles in addition to the normal city traffic faces typical traffic congestion challenges in its CBD area, particularly during the peak hours, which warranted this investigation. So, the objective of this paper is to assess the degree of traffic congestion (Level of Service (LOS)) in the roads of CBD area and explores a possible mechanism to ease the problem. A survey research methodology and application of relevant empirical models were employed to assess the level of traffic congestion and observe possible solutions to ease the traffic conduct this investigation. Findings revealed that there is appreciable level of traffic congestion in some of the roads of the CBD area of the Kimberley City, specifically during the peak hours, which needs strategic intervention. A reengineering solution, such as, traffic diversion from the congested roads to the underutilised or least congested roads could assist in easing the traffic congestion, increase in speed and reduction in travel time resulting into optimal utilisation of all the roads in the CBD area of the city.

Keywords: Traffic congestion; Level of Service; Central Business District; Peak hours; Diversion of Traffic

1. INTRODUCTION

Traffic congestion has become a disturbing problem in many cities all over the world. It results a range of undesirable consequences, which include negative economic impacts and environmental pollution (Rao and Rao, 2012; Sorensen et al, 2008; Wang, Gao, Xu, Sun, 2014). Many of the South African cities are not away from this challenge. Specifically, the central business districts (CBD) of many large and medium cities of the country are severely affected by this mobility problem. For, instance the Kimberley City in the Northern Cape Province, because of its unique physical, spatial, road network, economic characteristics and requirement of mobility of heavy vehicles in addition to the normal city traffic faces typical traffic congestion challenges in its CBD area, particularly during the peak hours.

So, it is essential to assess the level of traffic congestion and the influence of the imperative solutions, which could assist in evolving strategies to meet the challenges. The objective of this paper is to assess the degree of traffic congestion (Level of Service (LOS)) in the roads of CBD area and to proffer a possible mechanism to ease the problem in the roads of CBD area. The study was conducted by using a survey research methodology and application of relevant empirical models for assessing traffic congestion and to derive a mechanism to ease the traffic congestion challenges. Statistical traffic data were used for this purpose and the Kimberley City was considered as the case study. The study revealed that there is appreciable level of traffic congestion in three important roads (particularly roads, which are carrying heavy vehicles) in the CBD area of the Kimberley City, specifically during the peak hours. It is also seen that LOS in a number of roads are within the permissible limits, and can carry additional traffic without creating much congestion. So, diversion of about 21% – 27% of the total traffic from the heavily congested roads to the underutilised or lesser congested roads will result into higher LOS (lower congestion), increase in speed by 7km/h to 10km/h from the current speed levels, and decrease in travel time by 15% to 20% and vice versa.

2. LITERATURE REVIEW

There is no single definition of traffic congestion and the problem can be interpreted in different ways, although in general it is a situation in which demand for road space exceeds the supply (ECMT, 2007; Lascano Kezic, Durango-Cohen, 2012; Talukdar, 2013). Traffic congestion occur when traffic is delayed due to the presence of excess number of vehicles on the same portion of the road way at a particular time resulting into slower than the normal or "free flow" speeds (Department of transportation U.S., 2005, p. 1; Link et al. 1999, p. 9). There shall be long queues of vehicles, which move in constant start and stop basis because the number vehicles trying to use the road exceeds the design capacity of the road. Consequently, it results into delay in traffic movement and the traveller cannot move in a desirable manner (ECMT, 1999; Goodwin 2004; Levinson et al., 1997; Lomax, 1990; Lomax, Turner and Schunk, 1997; Taylor, 2003). Thus, traffic congestion can be described in two ways; (1) the high vehicle concentration moving at low flow speed, and (2) the number of vehicles on the road is close to or exceeds the maximum capacity of the road causing an imbalance between travel demand and transport system supply (Hon, 2005, p. 24; Talukdar, 2013). Congestion is generally categorised into recurrent, non-recurrent congestion and pre-congestion state (Brownfield et al, 2003). Recurrent congestion occurs mainly when there are too many vehicles at the same time, consequently reducing traffic speed and increasing commuting time, which may relate to rapid growth in population, urbanization and growth in car ownership and use. It occurs typically during peak hours but can also occur off peak hours.

However, non-recurrent congestion is associated with random conditions or special and unique conditions, including traffic incidents (ranging from disabled vehicles to major crashes), work zones which slow traffic down, weather and special events. Pre congestion state occurs where free-flow conditions breakdown but full congestion has not yet occurred (Banjo, 1984; Brownfield et al, 2003; Chakwizira, 2007; HCM, 2000).

According to the Department of transportation, United States (2005, pp.1-2), there are generally seven reasons of traffic congestion. These seven reasons are generally grouped into three broad categories, such as, traffic influencing events, traffic demand and physical road features. Traffic incidents, work zones and weather are the traffic influencing events. Traffic incidents include vehicular crashes, breakdowns, debris in travel lanes, events that occur on the shoulder or roadside, etc. A construction activity on the roadway is the example of a work zone. Reduced visibility, bright sunlight on the horizon, presence of fog or smoke, wet, snowy or icy road way are the examples of poor weather. Traffic demand includes fluctuations in normal traffic, such as day to day variability in demand and special events. Physical highway features include road way physical and geometrical characteristics, poor traffic control devices and physical bottlenecks (capacity) of the road (Talukdar, 2013).

A wide number of indicators have been developed to measure traffic congestion (Dijker, Piet, Bovy, and Vermijs, 1998; Grant-Muller, 2005). However, literature suggests that only a small number form the basis for regular monitoring of the road network and more concrete indicators are needed to measure congestion at a practical level (Grant-Muller & Laird, 2006). One of the major indicators, which mostly favoured is the total amount of delay encountered calculated across all traffic from the difference between the actual speed encountered and free flow speed (Dft, 2000, 2000b; Dodgson, Young, and van der Veer, 2002). This leads to the measurement of average delay by a vehicle travelling per kilometre. It was believed to be advantageous in providing a better picture of how changing traffic levels and different policy packages can affect time lost to congestion, although delays are measured purely in terms of vehicle journey time and no allowances are made for differences in occupancy rates, values of time, or for additional factors, such as additional operating or environmental impacts that congestion can generate. Similarly, simple measures relating to speed are also used to indicate congestion, particularly for a motorway environment (Grant-Muller, 2005). These indicators include mean journey times, variability of journey times, throughput (total number of vehicles per time interval that pass a point on the carriageway), queue lengths, speed differential between lanes and delay per hour/day (Graham and Glaister, 2004; Grant-Muller, 2005; Grant-Muller & Laird 2006; Noland and Polak, 2002). Besides, the congestion reference flow (a quantified measure of congestion for a link -junction must be considered separately) and the level of service (LOS) are other basic congestion measures applied widely in some countries like USA and Scotland, (Highways Agency, 1997; State-wide Planning Scenario Synthesis, 2005).

The concentration of trip destinations in a small area – particularly central area of the cities poses the challenge of providing large transportation capacity in limited physical space, while preserving the historical, political, cultural, economic and environmental heritage/values of the areas. It has been observed that there are larger share of trips to the city centres (with a defined and preeminent central area) in cities. As such, the total number of trips grows exponentially with the city size. Simultaneously, city centres are characteristically areas of high concentration of activities, and space is scarce. Therefore, there exists a dichotomy of high demand for transportation capacity in a geographic environment where space is limited (Lascano Kezic, Durango-Cohen, 2012).

The various approaches to address the problems of congestion in urban areas particularly in the city centers fall in three broad categories: supply management, land use management and transportation demand management. Supply management includes all measures taken to increase the number of people and trips served by the transportation system in order to accommodate as much demand as possible. This includes added capacity for vehicles as well as transit, bicycles, pedestrians, and multi-mode facilities (Gao and Song, 2000; Yang and Bell, 1998; Zanjirani Farahani et al., 2013; Meyer, 2003) and traffic signal timing optimization (Ceylan and Bell, 2004; Stevanovic et al., 2013). However, according to critics of this method, majority of the traffic jams are caused by accidents and events – not because of lack of capacity (STPP, 2001), so adding capacity to alleviate the problems becomes controversial on account of induced demand argument and the environmental and health effects of additional travel and land consumption (Gifford, 2005). Besides, supply management methods do little to mitigate congestion caused by non-recurring incidents. Land-use management describes the use of growth management, planning, and zoning to promote local density to encourage transit. Transit oriented development and high-density land use are both examples of this type of management. Critics of the land use management measures cite two major challenges that increased congestion is created by high-density development, and it takes long time to change land-use patterns and behaviors; they also doubt regarding the connection and causality between the two (Taylor, 2002). Transportation demand management (TDM) is a strategy of instituting largely financial incentives and disincentives to encourage motorists to use alternate routes, times and modes, or to defer trips entirely in order to reduce the demand for traffic facilities. TDM arises out of a desire to consider alternatives to “supply-side” measures because of the negative community effects of induced demand. The measures include: congestion pricing, park-and-ride lots, high-occupancy-vehicle lanes, high-occupancy-toll lanes, employer commute option programs, telecommuting, alternative work schedules, and traffic calming measures. Of all the measures, congestion pricing tends to be both most effective and politically legitimate as a funding source (Gifford, 2005); however, due to the cost it places on drivers, it is one of the hardest methods to implement (Bass, 2008).

Efficient vehicle routing, punctuality of routes and diversion of vehicles are also considered as other options to alleviate traffic congestion particularly in the congested urban areas. However, the problem of vehicle routing lies at the heart of the distribution management and the conditions vary from one setting to other; and the objectives and constraints encountered in practice are highly variable. Although, some research has been done in this area, the focus is limited to a number of prototype problems, and the literature on vehicle routing – segregation of vehicular traffic (modal split), optimal traffic assignment on different alternative roads and reengineering of the traffic system at the local level, and their impact on the road network – congestion and travel time under the effect of combination of the parameters is scarce (Cordeau, Laporte, Savelsbergh, Vigo, 2007).

Overall, the studies and practices, which deal with the traffic congestion mitigation, include increasing of road infrastructure supply or decreasing of travel demand, or both. Current studies have however demonstrated that increasing the size of infrastructure could be only part of the answer (OECD, 2013), as many measures are intrinsically interactive, which may need to be addressed jointly. With increased growth of traffic flow, it is crucial to develop cost-efficient policies, which would alleviate traffic congestion and address negative externalities in terms of environmental impact and cost to the economy (Watling, Milne, Clark, 2012).

3. THE STUDY AREA

Kimberley City of South Africa was considered as the study area for this study. It is the capital city of the Northern Cape Province of the country and is situated on the latitude 28.7419°S and longitude 24.7719° E. It is primarily known for its diamond mining activities. However, in recent years the economic functions of the city are changing because of the reduced mining activities. The city has a combined urban population of more than 225000 (Census, 2011). It has a total of 48 suburbs, which includes districts and townships and has a designated CBD. The city is connected to various major cities of the country, such as, Johannesburg, Pretoria, Cape Town, and Bloemfontein by national roads. It is also found that the city is about on an average of 800 km from some of the major cities in South Africa, i.e. Cape Town, Polokwane, Nelspruit and the town of Springbok. Apparently the city is the central point of the country from the road network point of view.

The CBD performs important urban functions of the city. It provides facilities for both commercial and administrative activities. Spatially, it is bounded by Quinn Street in the East, Cecil Sussman/Quinn Street in the North, Cecil Sussman/Bultfontein road in the west, and Lennox Street in the South, and is considered as the primary focused study area of the investigation.

The arterial roads, which generally influence the traffic movement in the CBD area, are Long, Barkly, Bishop, Carter, Schnidtsdrif, Memorial and Transvaal Streets. As mentioned above these roads in an around the CBD area are under heavy pressure because of the combined movement of heavy vehicles in and out of the city and normal inter and intra city traffic resulting to inefficient traffic movement. Thus, it was felt pertinent to choose the CBD area of the city as the study area for this investigation.

4. RESEARCH METHODOLOGY

Survey was conducted to collect traffic data (Average Daily Traffic and Speed) at the study area level. Besides statistical data such was collected from authentic organisations. The level of services (LOS) or degrees of traffic congestion were measured by using the most relevant empirical models. LOS for different roads was measured by using volume capacity ratio (V/C) ratio in terms of Passenger Car Units (PCU) both for normal hours and peak hour of day. The reason for which LOS for normal hours and peak hours in different roads are measured are to observe the traffic congestions scenarios separately during normal hours and peak hours of the day and to find the possibility and the quantum of the traffic, which can be diverted or rerouted from the heavily congested roads to the less congested roads at different periods of the day. While calculating the LOS the following models (equations (Eq.)) were employed. They are:

$$\text{LOS (normal hours)} = V/C \dots\dots\dots \text{Eq. (1)}$$

Where, V=Average hourly volume of traffic =Annual Average Daily traffic / Total number of hours in the day experiencing traffic flow.

$$\text{LOS (peak hours)} = V_p/C \dots\dots\dots \text{Eq. (2)}$$

Where, V_p = Average peak hourly volume of traffic = Total peak hour traffic / Total number of peak hours in the day.

C= Capacity of the roads the capacity, estimated to be 1,100 vehicles per hour per lane for arterial roads (Type II and III equivalent to U3-minor arterial roads and U4 roads in South African cities) (TRB, 1994, Appendix B-Traffic Level of Service Calculation Methods, B 6-7; TRH26, COTO, 2012:22). The capacity was estimated based on a saturation flow rate of 1,900 vehicles per lane per hour (TRB, 1994, Appendix B-Traffic Level of Service Calculation Methods, B 6-7) and on the assumption that major roads would receive 60% of the green time and roads perpendicular to the major roads would receive 40% of the green time.

Besides, Percent Traffic Diversion model was employed along with LOS in order to examine the traffic congestion scenario, percentage of traffic that can be rerouted or diverted, consequent increase in speed and reduction in travel time.

Percent Traffic Diversion (P) (Kadiall, 2008) is calculated by using the model given as below.

$$P = 100 / (1 + tR^6) \dots\dots\dots \text{Eq. (3)}$$

tR = Travel time ratio = Time on new system/ Time on old system

Statistical traffic (volume and speed) data for different roads in and around the CBD area of the city from secondary sources, such as, Sol Plaatje Municipality were used for this purpose.

5. FINDINGS AND DISCUSSION

5.1 Traffic congestion scenario in terms of Level of Service (LOS) in different roads of the CBD area of the city

The LOS in the different roads of the CBD area of the Kimberley City is presented in Table 1. It is evaluated for the traffic movement both to the city and from the city. From Table 1, it is revealed that at the current scenario during normal hours, for the traffic moving towards the city, Transvaal road (influenced by Pniel road) has a LOS F (V/C= 1.04) and is highly congested, whereas another road– the Long Street is almost running to its capacity (V/C = 0.93 LOS E) and is a cause of concern. All other roads, such as, Barkly (V/C= 0.16), Bishop (V/C= 0.55), Carter (V/C= 0.37), Schnidtsdrift (V/C= 0.35), Barkly section 2 (impacting Transvaal) (V/C= 0.41), and Memorial Streets (V/C= 0.22) have LOS levels A (V/C = between 0 and 0.5), and as a result experience no congestion problems. Bishop Street, which carries a significant quantum of heavy vehicles is observed to be on the threshold (currently LOS A) although does not experience much congestion now, has the possibility to move to the higher level of congestion (LOS B) in future. Similarly, during peak hours two of the roads – Long Street (Vp/C =1.24) and Transvaal road (Vp/C =1.39) have LOS F (Vp/C > 1.0) and are highly congested. Bishop Street is experiencing LOS C (Vp/C =0.73). All other roads have LOS A and are observed to be not experiencing much congestion even during peak hours. However, the higher values of Vp/C ratio show that there is a possibility of these roads to move to the next level of congestion in future. Therefore, traffic congestion alleviation interventions are necessary in at least two roads, such as Long Street, Transvaal road, although Bishop Street also needs careful attention.

Table 1: LOS in different roads of CBD area Kimberley

Roads	No of lanes	Average hourly Volume (in PCU V)	Peak Hourly Volume (in PCU Vp)	Capacity (C) of two lane arterial roads	V/C	LOS (Normal hours)	V _p /C	LOS (Peak hours)
Long	2	2611.9	3482.5	2800	0.93	E	1.24	F
Barkly	2	449.3	599.0	2800	0.16	A	0.21	A
Bishop	2	1531.5	2042	2800	0.55	A	0.73	C
Carter	2	1028.1	1370.8	2800	0.37	A	0.49	A
Schnidtsdrift	2	977.5	1303.4	2800	0.35	A	0.47	A
Barkly section 2 (impacting Transvaal)	2	1134.7	1512.9	2800	0.41	A	0.54	A
Memorial	2	607.6	810.1	2800	0.22	A	0.29	A
Transvaal (influenced by Pniel)	2	2926.8	3902.3	2800	1.04	F	1.39	F

5.2. Percent of traffic diversion and future scenarios of LOS, change in travel time and speed

Table 2 presents the future scenario of LOS and associated variables like change in travel time, improvement in speed and requirement of traffic diversion. The traffic scenarios for both to the city and from the city show similar trends. However, the results revealed that if a minimum of 21% of traffic from Long Street and 27% of traffic from Transvaal road are diverted to other roads, the LOS level of these two roads will change to level E from level F during peak hours, and to level C (from level E for Long Street and F for Transvaal road) during normal hours, thereby easing the severe traffic congestion level. Consequently, increase in travel speed of 7 Km/h in Transvaal road and 10 Km/h in Long Street can be experienced. Also, reduction in the travel time can range from 15% to 20% in Transvaal road and Long Street respectively. On the other hand, although, the current LOS levels do not warrant diversion of traffic from all other roads, any such intervention will create LOS levels of A in these roads. However, as these roads have very lower level of congestion (higher level of service (LOS) ranging between A and C); they are seemed to be underutilised both during normal and peak hour. This scenario would allow diversion of traffic from severely congested roads to the roads that are underutilized resulting into optimal level of service in most of the roads in the CBD area of Kimberley city.

Table 2: Travel time reduction, percent traffic diversion and consequent LOS in different roads of CBD area (to City), Kimberley

Roads	Average Speed increase from current actual speed in Km/ h	Travel time ratio = Time in New system/ Time in old system	Minimum % vehicle needs diversion 100-100/(1+ t_R^6)	Average hourly Volume (in PCU V)	Peak Hourly Volume (in PCU V_p)	Capacity (C) of two lane arterial roads in PCU	V/C	LOS Normal hour	Vp/C	LOS Peak hour
Long	10 (40)	0.8	21	2063.4	2751.2	2800	0.74	C	0.98	E
Barkly	10 (50)	0.83	25	336.9	449.3	2800	0.12	A	0.16	A
Bishop	10 (40)	0.8	21	1209.9	1613.2	2800	0.43	A	0.57	A
Carter	10 (50)	0.83	25	771.1	1028.1	2800	0.27	A	0.36	A
Schmidtsdrift	10 (50)	0.83	25	733.2	977.5	2800	0.26	A	0.34	A
Barkly section 2 impacting Transvaal	10 (50)	0.83	25	851.0	1134.7	2800	0.30	A	0.40	A
Memorial	10 (50)	0.83	25	455.7	607.6	2800	0.16	A	0.21	A
Transvaal influenced by Priel	7 (43)	0.85	27	2107.2	2809.7	2800	0.75	C	1.00	E

Note: The numbers in parenthesis in column 2 represent the current average speed of the roads

6. CONCLUSION AND FURTHER RESEARCH

Traffic congestion is observed to be a challenge in the Kimberley City particularly in some of the roads in the CBD area, which warranted this investigation.

Empirical analyses were conducted to assess the LOS (congestion scenarios) and to observe scenarios of improvement in travel time, improvement in speed and improvement in LOS in different roads in the CBD areas of the city under a traffic congestion reduction intervention like traffic diversion or rerouting.

The investigation also revealed that two of the roads (Transvaal road and Long Street) in the CBD area of the Kimberley City are severely congested during both normal and peak hours, while one road (Bishop) can become a cause of concern during peak hours. However, Percent Traffic Diversion based on travel time ratio and change in speed, shows that with a reasonable level of diversion of traffic from congested roads to the roads with lesser congestion can improve LOS, increase speed and reduce travel time in the roads of the CBD area of the city and vice versa, allowing roads to be optimally utilised.

The investigation has a few limitations. The analyses were carried out by application of two empirical models, such as, LOS and Percent Traffic Diversion. However, further, analyses, such as, Segment delay, Travel time index, Traffic transmission index, and Lane mile duration index as relevant with the use of a larger data set could provide further insight to the traffic congestion problem in the CBD area, which is the further scope of this investigation.

Despite the limitations, this study revealed that some of the roads in the CBD area of the Kimberley City are severely congested both during normal and peak hours. However, reengineering policy interventions like traffic diversion from highly congested roads to lesser congested/ underutilized roads will ease the traffic congestion problem as well as will improve on travel time and speed, which could result optimal utilisation of all the roads in the CBD area of the city.

7. REFERENCES

Banjo, G. A. (1984), 'Towards a New Framework for Urban Transport Planning in Third World Cities', Proc. Australian Road Research Board Conference, Vol. 12(1).

Bass, P. (2008), 'Traffic Literature Review: Congestion and Quality of Intersections', Hamline Midway Coalition. www.cura.umn.edu/search/index.php.

Brownfield, J. Graham, A. Eveleigh, H. Ward, H. Robertson, S. Allsop, R. (2003b), 'Congestion and accident risk', Road Safety Research Report No. 44, Department for Transport, DfT.<http://www.dft.gov.uk>.

Ceylan, H., Bell, M.G.H, (2004), 'Traffic signal timing optimization based on genetic algorithm approach, including drivers' routing', Transportation Research Part B, Vol. 38 (4), pp. 329–342.

Chakwizira, J. (2007), 'The question of road traffic congestion and decongestion in the greater Johannesburg area: some perspective', Proceedings of the 26th Southern African Transport Conference (SATC 2007), ISBN Number: 1-920-01702-X Pretoria, South Africa.

Cordeau, J., Laporte, G., Savelsbergh Martin W.P., Vigo, D. (2007), 'Vehicle Routing Chapter 6 C', In Barnhart and G. Laporte (Eds.), Handbook in OR & MS, Vol. 14, DOI: 10.1016/S0927-0507(06)14006-2.

Department of Transportation, U.S. (2005), 'Traffic congestion and reliability: Trends and advanced strategies for congestion mitigation', Office of Operations, Texas Transportation Institute, Federal Highway Administration.

Department for Transport. (2000), 'Tackling Congestion and pollution: the Government's first report', <http://www.dft.gov.uk>.

Department for Transport. (2000b), 'A measure of Road Traffic congestion in England' <http://www.dft.gov.uk>.

Dijker, T., Piet, H.L., Bovy, R., and Vermijs, G.M.M. (1998), 'Car following under non-congested and Congested conditions', Transportation Research Record, Vol. (1644), pp. 20-28.

Dodgson, J., Young, J., and van der Veer J. (2002), 'Paying for Road Use, Technical 61 Report, A report to the Commission for Integrated Transport', National Economic Research Associates (NERA), London, February. <http://www.cfit.gov.uk/docs/2002/pfru/research/pdf/pfru-tech.pdf>.

European Conference of Ministers of Transport, (ECMT). (1999), 'Report of the Hundred and Tenth Round Table on Transport Economics held in Paris on 12 - 13" March 1998 on The following topic: Traffic Congestion in Europe, Paris: Economic Research Centre, European Conference of Ministers of Transport.

European Conference of Ministers of Transport, (ECMT). (2007), 'Managing urban traffic congestion- summary document', Transport Research Centre, European Conference of Ministers of Transport.

Gao, Z.Y., Song, Y.F. (2002), 'A reserve capacity model of optimal signal control with user-equilibrium route choice', Transportation Research Part B, Vol. (36), pp. 313–323.

Gifford, J. L. (2005), 'Congestion and its Discontents, In D.M. Levinson and K.J. Krizek, Access to Destinations, (Eds), pp.39 – 62, Amsterdam: Elsevier Ltd.

Graham, D.J., and Glaister, S. (2004), 'Road traffic demand elasticity estimates - a review', Transport Reviews, Vol. 24(3), pp. 261–274.

Goodwin, P.B. (2004), 'The Economic Costs of Road Traffic Congestion. Discussion paper, Rail Freight Group, Transport Studies Unit, University College London. <http://eprints.ucl.ac.uk/archive/00001259/>.

Grant-Muller, S. (2005). 'Assessment Methodology report', Project deliverable-Report 203754_MM_003.

Grant-Muller, S., & Laird, J. (2006), 'Costs of congestion: literature based Review of methodologies and analytical Approaches', Scottish Executive Social Research Institute for Transport Studies, University of Leeds.

HCM. (2000). 'Highway Capacity Manual', Transportation Research Board, ISBN-13:978-0309067461.

Highways Agency, Scottish Office development department, The Welsh Office, The department of the Environment for Northern Ireland. (1997), 'Design manual for Roads and Bridges, Traffic Flow Ranges for Use in the Assessment of New Rural Roads', DMRB, Vol. (5), Section1, Part 3. <http://www.highways.gov.uk/>.

Hon, M. L. (2005), 'Evaluation of traffic congestion relieving options with using cost-benefit analysis: case study of Central-Wan Chai', unpublished MSc. Thesis, The University of Hong Kong.

Kadiali, L.R. (2008), 'Traffic Engineering and Transportation Planning', New Delhi, Khana Publishers, ISBN 9788174092205.

Lascano Kezic., Marcelo, E., Durango-Cohen, P. L. (2012), 'The transportation systems of Buenos Aires, Chicago and Sao Paulo: City centres, infrastructure and policy analysis', Transportation Research Part A, Vol. (46), pp.102–122.

Levinson, H.S., Lomax, T.J. & Turner, S. (1997), 'Traffic Congestion - Past - Present- Future' In Rahim, F. (Ray) Benekohal (ed.), Traffic Congestion and Traffic Safety in the 21st Century: Challenges, Innovations, and Opportunities: Proceedings of the Conference, Chicago, Illinois, June 8-11, 1997, New York: American Society of Civil Engineers.

Link, H., Dodgson, J.S., Maibach, M. & Herry, M. (1999), 'The Costs of Road Infrastructure and Congestion in Europe', Heidelberg: Physica-Verlag.

Lomax, T.J. (1990), 'Estimating transportation corridor mobility', Transportation Research Record: Journal of the Transportation Research Board, Vol. 1280, pp. 82-91.

Lomax, S.T.T., Turner, S., Shunk, G., Levinson, H.S., Pra, R.H., Bay, P.N., Douglas, G.B. (1997), 'Quantifying congestion', NCHRP Final Report 398.

- Washington, D.C.: Transportation Research Board, Volume (1), pp. 108
- Meyer, M. (2003), 'Synthesis. Presentation at Traffic Congestion: Issues and Options', June 26 – 27, at University of California at Los Angeles.
- Noland, R.B., and Polak, J.W. (2002), 'Travel time variability: a review of theoretical and empirical issues', *Transport Reviews*, Vol. 22(1), pp. 39-54.
- Organization for Economic Cooperation and Development (OECD). (2013), 'Better use of infrastructures to reduce environmental and congestion costs, In OECD Economic Surveys: Belgium 2013. OECD Publishing, Paris, pp. 11–13.
- Rao, A. M., Rao, K. R. (2012), 'Measuring Urban Traffic Congestion – A Review', *International Journal for Traffic and Transport Engineering*, Vol. 22(4) pp.286–305 DOI: [h_p://dx.doi.org/10.7708/ij_e.2012.2\(4\).01](http://dx.doi.org/10.7708/ij_e.2012.2(4).01).
- Sorensen, P., Wachs, M., Min Endy Y., Kofner, A., Ecola, L., Hanson, M., Yoh, A., Light, T., and Griffin, J. (2008), 'Reducing Traffic Congestion in Los Angeles in Moving Los Angeles: Short- Term Policy Options for Improving Transportation', MG-748-JAT/METRO/MCLA (available at <http://www.rand.org/pubs/monographs/MG748/>), 716 pp., ISBN: 978-0-8330-4555-3.
- Stevanovic, A., Stevanovic, J., Kergaye, C. (2013), 'Optimization of traffic signal timings based on surrogate measures of safety', *Transportation Research Part C*, Vol. (32), pp. 159–178.
- Surface Transportation Policy Project (STTP). (2001), 'Easing the Burden: A Companion Analysis of the Texas Transportation Congestion Study'.
- Talukdar, M. H. (2013), 'Framework for Traffic Congestion Management', *Economia, Seria Management*, Vo, 16(1), pp. 54-64.
- Taylor, B. (2002), 'Rethinking Traffic Congestion', *Access*, Vol. (21), pp. 8-16.
- TRB. (1994), 'Transportation Research Board, Highway Capacity Manual, Special Report', 209, Washington, D.C., pp. 11-4.
- TRH26, COTO. (2012), 'South African Road Classification and Access Management Manual', The South African National Roads Agency Limited, South Africa, Pretoria.
- Wang, G., Gao, Z., Xu, M., Sun, H. (2014), 'Joint link-based credit charging and road capacity improvement in continuous network design problem', *Transportation Research Part A*, Vol. (67), pp. 1–14.
- Watling, D., Milne, D., Clark, S. (2012), 'Network impacts of a road capacity reduction: Empirical analysis and model predictions' *Transportation Research Part A*, Vol. (46) pp. 167–189.

Yang, H., Bell, M.G.H. (1998), 'Models and algorithms for road network design: a review and some new developments', *Transportation Review*, Vol.18 (3) pp. 257–278.

Zanjirani Farahani, R., Miandoabchi, E.Z., Szeto, W.Y., Rashidi, H. (2013). 'A review of urban transportation network design problems', *European Journal of Operation Research*, Vol. 229 (2) pp. 281–302.