

Serbian Ceramic Society Conference ADVANCED CERAMICS AND APPLICATION V New Frontiers in Multifunctional Material Science and Processing

Serbian Ceramic Society
Institute of Technical Sciences of SASA
Institute for Testing of Materials
Institute of Chemistry Technology and Metallurgy
Institute for Technology of Nuclear and Other Raw Mineral Materials
School of Electrical Engineering and Computer Science of Applied Studies

PROGRAM AND THE BOOK OF ABSTRACTS

SERBIAN CERAMIC SOCIETY CONFERENCE ADVANCED CERAMICS AND APPLICATION V

New Frontiers in Multifunctional Material Science and Processing

Serbian Ceramic Society
Institute of Technical Science of SASA
Institute for Testing of Materials
Institute of Chemistry Technology and Metallurgy
Institute for Technology of Nuclear and Other Raw Mineral Materials
School of Electrical Engineering and Computer Science of Applied Studies

PROGRAM AND THE BOOK OF ABSTRACTS

Book title: Serbian Ceramic Society Conference - ADVANCED CERAMICS AND APPLICATION V: Program and the Book of Abstracts

Publisher:

Serbian Ceramic Society

Editors:

Prof.dr Vojislav Mitić Dr Lidija Mančić Dr Nina Obradović

Technical Editors: Dr Lidija Mančić Dr Nina Obradović Adriana Peleš

Printing:

Serbian Ceramic Society

Circulation:

140 copies

CIP - Каталогизација у публикацији - Народна библиотека Србије, Београд

666.3/.7(048) 66.017/.018(048)

SERBIAN Ceramic Society Conference - Advanced Ceramics and Application (5; 2016; Beograd)

Advanced Ceramics and Application: new frontiers in multifunctional material science and processing: program and the book of abstracts / V Serbian Ceramic Society Conference, Belgrade, 21-23. September 2016.; [organized by] Serbian Ceramic Society ... [et al.]; [editors Vojislav Mitić, Lidija Mančić, Nina Obradović]. - Belgrade: Serbian Ceramic Society, 2016 (Belgrade: Serbian Academy of Sciences and Arts). - 82 str.; 30 cm

Tiraž 140.

ISBN 978-86-915627-4-8

- 1. Serbian Ceramic Society (Beograd)
- а) Керамика Апстракти b) Наука о материјалима Апстракти c) Наноматеријали Апстракти

COBISS.SR-ID 225924876

P8

Influence of alternations in ultra-centrifugal milling parameters on the coal ash quality for the construction composites design

Anja Terzić¹, Lato Pezo², Ljubiša Andrić³, Ljiljana Miličić¹, Zagorka Radojević¹

¹Institute for Materials Testing, Belgrade, Serbia

²Institute of General and Physical Chemistry, University of Belgrade, Belgrade, Serbia

³Institute for Technology of Nuclear and Other Raw Mineral Materials, Belgrade, Serbia

The coal ash mechano-chemical treatment conducted by means of the high energy mill was optimized using mathematical and statistical tools. The merits of the alternations in ash processing schemes with a referral regarding the improvement of its reactivity were highlighted. This will eventually lead to higher volume utilization of the fly ash as a cement replacement in concrete design. In order to obtain the most favorable output, the impact of the sets of processing parameters (number of rotor revolutions, current intensity, activation period, circumferential rotor speed, mill capacity) on the on the product's quality factors (grain size distribution, average grain size, micronization level, agglomeration tendency, specific surface area) was assessed via Response surface method, Standard score analysis and Principal component analysis. Quality parameters in an extensive range of processing parameters were accurately predicted with developed models. The calculated r² values were in the range of 0.84-0.99. The optimal ash sample, characterized by 0.93 Standard Score, was produced using a set of processing parameters appropriate to experimental sequence with applied 120 µm sieve mesh. The microstructural characteristics were assessed using image-processing values and histogram plots of the activated fly ash SEM images. Multiple comparison tests revealed that the optimal variations in the activation parameters could improve the technology of cement replacement material production and its transfer into an economically attractive sustainable solution which is a new step in the design of high-volume fly ash based composites.

P9

Fractal tools in terrorist and financial crime prevention

D. Đurđević¹, M. Stevanović¹, V.V. Mitić^{2,3}, Lj. Kocić²
¹Academy of National Security, Belgrade, Serbia
²Faculty of Electronic Engineering, University of Nis, Serbia
³Institute of Technical Sciences of SANU, Belgrade, Serbia

Information society imposes globalization and universality of values. In these circumstances, terrorism, institutional political violence which targets trying to achieve the morbid fear of provoking a spectacular way, inappropriately given conditions, becomes a real threat not only to the nations but also to politics on the global level. In 1996, the International Monetary Fund estimated that 2–5% of the worldwide global economy involved laundered money. Today, intelligence activities in preventing and combatting terrorism include financial investigations and money laundering for the purpose of financing terrorism, resulting in broadening of the

scope of data to the level which makes it impossible for human logical evaluation. Technologies development that enables increasing capacity of speed and the amount of data processing has enabled defining, analysing and exploring more and more models. This led to the idea of computer experiments and simulations trying to get to more complex planning and forecasting for the purpose of countering terrorism and "dirty" money transaction, as highly dangerous, complex and variable phenomena. This presentation aims at quotation the wide spectrum of mathematically founded fractal concepts suited togenerate computer models of anti-terrorist activities. In this sense, the logistic behind the items connected with detecting and recognizing degree of terroristic threat by comparing fractal structure of people's faces, fast search through the databases of faces and fingerprints. The speed of searching processes is of vital importancewhich promotes the crucial importance of compression and data reduction with preservation of regularity. Especially important are analytic forecasting of missing visual data and forms, to supplement the empirical evidences and records. All these operations are possible with higher degree of knowledge utilization and adaptation of virtual reality in the fight against terrorism and different forms of money laundering. The results indicate that the achievements implementation of the concept of fractals depends on substantial prior knowledge, environmental influences, subsystem integration, decentralization and synchronization, and allows us to come up with similar high information technology models, but not necessarily to enable identification of the authentic features of the various anomalies that result in objectively asocial consequences. In this sense, we conclude that the application of information technology in the fight against terrorism, based on the concept of fractals has its place in the arsenalof anti-terroristic prevention.

P10

Effects of SA surface treatment on the properties of CaCO₃ used as filler in construction composites

Dragan Radulović¹, Anja Terzić², Ljubiša Andrić¹, Milan Petrov¹
¹Institute for Technology of Nuclear and Other Raw Mineral Materials, Belgrade, Serbia
²Institute for Materials Testing, Belgrade, Serbia

Calcium carbonate (CaCO₃) is mineral filler that has been most extensively used in the construction composites as well as in the polymer industry. Coarse CaCO₃ grains can be easily incorporated into the composite material, but the smaller-sized particles tend to agglomerate due to the enhanced particle-to-particle interactions, which leads to serious performance problems. The most efficient way of surpassing this problem is to enhance the final composite properties by surface treatment of the filler with a surfactant. Following such procedure a water-repellent construction composites are obtained (i.e. reparation mortars, mortars for the exterior works, thin coatings for concrete walls, etc.). The stearic acid is a universal and economical surfactant which is often used to improve CaCO₃ hydrophobic properties. This study investigates and subsequently compares the surface and mechanical properties of untreated ground calcium carbonate powder and treated powder with stearic acid using a dry process coating system. The CaCO₃ powder (grain size class: -200 + 63 μm) was pulverized in a laboratory Retsch-ZM-1 mill with a 250 μm mesh size sieve and a peripheral comminuting path. The surface of CaCO₃ powder is