EFFECT OF SWEET POTATO PECTIN ON MULTILAYER EMULSION STABILITY

NURUL HAZIRAH BT HAMIDON

A thesis submitted in fulfilment of the requirements for the award of the degree of Master of Philosophy

Faculty of Chemical and Energy Engineering Universiti Teknologi Malaysia

MAY 2018

To my beloved parents, family and friends.

ACKNOWLEDGEMENT

Alhamdulillah to Allah SWT for His guidance and love that gave me strength to complete my study. I would like to express my sincerest gratitude to my beloved supervisor, Dr. Dayang Norulfairuz Abang Zaidel. Thank you for giving me guidance and advices throughout my Master journey and for being a great role model to me. I would always be thankful for having her as my supervisor.

I am also utterly thankful to my helpful lab assistant, Mr Nur Muhammad El-Qarny. He has been a great help for me especially during my lab work. Thank you so much for the wonderful assistance. I would also like to convey my gratitude to my cheerful lab mates; Nurul Hidayah Ismail, Nor Fadzilah Abu Bakar, Nor Azizah Mohammad, and Nabilah Abdul Samad. Thank you for being a great friend and for helping me in my study. Also to my lovely friend, Nurazrina Mohd Azman, thank you my friend for the support during this whole journey.

To my family, especially my parents, Zaiton Bakar and Hamidon Zaini, thank you for loving me and for always having my back. Last but not least, to my role model in the family, my oldest sister, Nurul Nadiah Hamidon, thank you for always attending to my inquiries and help me with my research. I am grateful to all that have directly or indirectly helped me to complete this thesis.

ABSTRACT

Sweet potato (*Ipomoea batatas*) is a good alternative source of pectin which has the potential for stabilization of emulsion. This study aimed to optimize the extraction of pectin from sweet potato peels, and to investigate the effect of sweet potato pectin on multilayer emulsion stability. Response surface methodology was employed to optimize pectin extraction from sweet potato peels using citric acid. The factors included in the experimental design were temperature (60 - 100 °C), time (40 -100 min) and pH (1 -2). The yield of pectin was calculated on the basis of the sweet potato cell wall material. The degree of esterification (DE) of the pectin was analyzed using Fourier transform infrared spectroscopy. The extracted sweet potato pectin was incorporated in oil-in-water emulsion after homogenization using microfluidizer producing whey protein isolate-pectin multilayer emulsion. The effects of environmental conditions on the multilayer emulsion were studied by subjecting the emulsions to various conditions namely: 0 - 1.2 wt % pectin, pH 3 - 7and 0 - 400 mM salt solution. The emulsion stability was characterized by determination of particle size, zeta-potential and creaming index (CI). The optimum conditions to extract the maximum yield of pectin of 65.8% were at extraction temperature 76°C, time 64 min and pH 1.2. The pectin was categorized as highmethoxyl pectin with DE of 58.5%. Decreasing of zeta-potential (+2.38 to -14.8 mV) showed the adsorption of pectin layer around the emulsion droplets. CI was the lowest (3.64%) at the highest pectin concentration (1.2 wt%) which showed great stability against creaming. Multilayer emulsion showed better stability at high pectin concentration and wide range of salt concentration compared to primary emulsion. Pectin addition largely improved the stability of emulsion especially at pH 4 and 5. Multilayer emulsion prepared using sweet potato pectin can be utilized to produce food emulsion with good stability against environmental pressure (pH and salt content) and can be further applied for controlled release of active ingredients in functional food and beverages.

ABSTRAK

Ubi keledek (Ipomoea batatas) adalah sumber alternatif bagi pektin yang berpotensi untuk menstabilkan emulsi. Kajian ini bertujuan untuk mengoptimumkan pengekstrakan pektin dari kulit ubi keledek dan mengkaji kesan pektin pada kestabilan emulsi dwi-lapis. Metodologi tindak balas permukaan digunakan untuk mengoptimumkan pengekstrakan pektin dari kulit ubi keledek menggunakan asid sitrik. Faktor yang termasuk dalam reka bentuk eksperimen adalah suhu (60 - 100 °C), masa (40 - 100 min) dan pH (1 - 2). Hasil pektin dihitung berdasarkan bahan dinding sel ubi keledek. Darjah pengesteran (DE) pektin dianalisa menggunakan spektroskopi inframerah transformasi Fourier. Pektin ubi keledek yang telah diekstrak dimasukkan ke dalam emulsi minyak dalam air selepas proses penghomogenan menggunakan mikropembendalir untuk menghasilkan emulsi dwilapis protein dadih susu terasing-pektin. Kesan persekitaran terhadap emulsi dwilapis telah dikaji dengan mengubah emulsi kepada pelbagai keadaan: 0 - 1.2 % berat pektin, pH 3 - 7 dan larutan garam 0 - 400 mM. Kestabilan emulsi dicirikan berdasarkan penentuan saiz zarah, potensi zeta dan pengukuran indeks pengkriman (CI). Keadaan optimum untuk mengekstrak hasil pektin yang maksimum iaitu 65.8% adalah pada suhu 76 °C, masa 64 minit dan pH 1.2. Pektin dikategorikan sebagai pektin metoksil tinggi dengan DE sebanyak 58.5%. Pengurangan potensi zeta (+2.38 hingga -14.8 mV) menunjukkan penjerapan lapisan pektin di sekitar titisan emulsi. CI adalah terendah (3.64%) pada kepekatan pektin yang tertinggi (1.2% berat) yang mana menunjukkan kestabilan yang baik terhadap pengkriman. Emulsi dwi-lapis lebih stabil pada kepekatan pektin tinggi dan pada julat kepekatan garam yang lebih luas berbanding emulsi asas. Penambahan pektin meningkatkan kestabilan emulsi terutama pada pH 4 dan pH 5. Emulsi dwi-lapis yang menggunakan pektin ubi keledek boleh digunakan untuk menghasilkan emulsi makanan dengan kestabilan yang baik terhadap tekanan persekitaran (pH dan kandungan garam) dan boleh digunakan untuk pembebasan terkawal bahan aktif dalam makanan dan minuman berfungsi.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE	
	DECLARATION	ii	
	DEDICATION	iii	
	ACKNOWLEDGEMENT	iv	
	ABSTRACT	v	
	ABSTRAK	vi	
	TABLE OF CONTENTS	vii	
	LIST OF TABLES	Х	
	LIST OF FIGURES	xi	
	LIST OF ABBREVIATIONS	xiii	
	LIST OF SYMBOLS	xiv	
1	INTRODUCTION	1	
	1.1 Background of Study	1	
	1.2 Problem Statement	2	
	1.3 Objective of Study	4	
	1.4 Scope of Study	5	
	1.5 Significance of Study	5	
2	LITERATURE REVIEW	6	
	2.1 Introduction to Pectin	6	
	2.1.1 Chemical Structure of Pectin	6	
	2.1.2 Degree of Esterification	7	
	2.1.3 Source of Pectin	9	
	2.1.4 Extraction of Pectin	15	
	2.2 Sweet Potato as Alternative Source of Pectin	16	

	2.2.1 Sweet Potato Cell Wall Material	18
	2.3 Optimization of Pectin Extraction Parameters using Response Surface Methodology	18
	2.4 Emulsions in Food Application	20
	2.4.1 Polysaccharides as Emulsifier	20
	2.4.2 Multilayer Emulsion using Layer-by-layer Technique	23
	2.4.3 Emulsion Stability	25
	2.4.4 Factors Affecting Multilayer Emulsion Stability	27
	2.4.4.1 Effect of Polyelectrolytes Characteristic and Concentration	28
	2.4.4.2 Effect of pH	29
	2.4.4.3 Effect of Salt	30
3	METHODOLOGY	31
	3.1 Introduction	31
	3.2 Materials and Reagents	31
	3.3 Optimization of Pectin Extraction from Sweet Potato Peels	33
	3.3.1 Sweet Potato Cell Wall Material Preparation	33
	3.3.2 Extraction of Pectin	33
	3.3.3 Optimization of Pectin Extraction using Response Surface Method	34
	3.3.4 Statistical Analysis	36
	3.3.5 Analysis of Pectin Yield	36
	3.3.6 Determination of Degree of Esterification	36
	3.4 Characterization of Multilayer Emulsion	37
	3.4.1 Preparation of Multilayer Emulsion	37
	3.4.2 Determination of Particle Size and Zeta-potential	38
	3.4.3 Measurement of Creaming Index	38
4	RESULTS & DISCUSSIONS	40
	4.1 Optimization of Pectin Yield Extracted from Sweet Potato Peels	40

	4.1.1 Model Fitting	40
	4.1.2 Main Effects and Interaction between Parameters	43
	4.1.3 Analysis of the Response Surface Plot	43
	4.1.4 Model Validation	48
	4.2 Determination of Degree of Esterification	49
	4.3 Emulsion Stability	50
	 4.3.1 Effect of Sweet Potato Pectin Concentration on Emulsion Stability 4.3.2 Effect of pH on Emulsion Stability 4.3.3 Effect of Salt on Emulsion Stability 	51 55 59
5	CONCLUSION	64
	5.1 Conclusion	64
	5.2 Recommendation for Future Work	65

REFERENCES

66

LIST OF TABLES

TABLE NO.	TITLE	PAGE	
2.1	Pectin extraction conditions from different sources and its properties	10	
2.2	Proximate composition of different parts of two varieties of sweet potatoes (Ishida <i>et al.</i> , 2000)	17	
2.3	Proximate composition of five varieties of sweet potatoes (Nurdjanah, 2008)	18	
2.4	Advantages and disadvantages of different types of polysaccharides	22	
3.1	Independent variables and their corresponding level	35	
3.2	Experimental design	35	
4.1	The level of the factors and the measured and predicted percentage yield (%)	41	
4.2	ANOVA for quadratic model	42	
4.3	Actual regression coefficient of the quadratic model and the corresponding P-value	43	
4.4	The predicted and actual yield of pectin	49	
4.5	Degree of esterification of sweet potato pectin	50	

LIST OF FIGURES

FIGURE NO.

TITLE

PAGE

2.1	Structure of pectin (Khan et al., 2015)	7
2.2	Schematic diagram illustrating how rhamnose insertions cause kinking of GalA chain; S = neutral sugars (adapted from Sriamornsak, 2002)	7
2.3	a) O/W emulsion b) W/O emulsion (adapted from Mao <i>et al.</i> , 2013)	20
2.4	Steps of producing multilayer emulsion (adapted from Ogawa <i>et al.</i> , 2004)	25
3.1	Flow chart of the overall methodology	32
4.1	Graph of predicted versus actual values of the response (percentage yield of pectin)	42
4.2	3D contour plot showing correlation between temperature (°C) and time (min) to the yield of pectin (%) at a) pH 1 b) pH 1.5 c) pH 2	45
4.3	3D contour plot showing the effect of extraction factor temperature and pH to the yield of pectin (%) when time was kept at a) 40 min b) 70 min c) 100 min	46
4.4	3D contour plot showing the effect of extraction factor time and pH to the yield of pectin (%) when temperature was kept at a) 60° C b) 80° C c) 100° C	47
4.5	FTIR spectroscopy result	50
4.6	Dependence of electrical charge of emulsion droplets (zeta-potential) on sweet potato pectin concentration for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, pH 3.5). Data represents mean (n = 3) \pm standard deviation. Some error bars lay within data points	52
4.7	Dependence of mean particle diameter on sweet potato pectin concentration for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, pH 3.5). Data represents mean ($n = 3$) ± standard deviation. Some error bars lay within data points	53

xi

4.8	Dependence of emulsion creaming index on sweet potato pectin concentration for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, pH 3.5)	54
4.9	Effect of sweet potato pectin concentration $(0 - 1.2 \text{ wt } \%)$ on the creaming stability of emulsion (Opaque upper layer: cream, transparent bottom layer: serum)	54
4.10	Dependence of electrical charge of emulsion droplets on pH for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, 1.2 wt % sweet potato pectin). Data represents mean ($n = 3$) ± standard deviation. Some error bars lay within data points	56
4.11	Dependence of mean particle size on pH for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, 1.2 wt % sweet potato pectin). Data represents mean (n = 3) \pm standard deviation. Some error bars lay within data points	57
4.12	Dependence of emulsion creaming index on pH for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, pH 3.5)	58
4.13	Effect of different pH on creaming stability of a) primary and b) multilayer emulsion (Opaque upper layer: cream, transparent bottom layer: serum)	59
4.14	Dependence of electrical charge of emulsion droplets on salt concentration for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, 1.2 wt % sweet potato pectin). Data represents mean ($n = 3$) ± standard deviation. Some error bars lay within data points	60
4.15	Dependence of mean particle size on salt concentration for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, 1.2 wt % sweet potato pectin). Data represents mean (n = 3) \pm standard deviation. Some error bars lay within data points	61
4.16	Dependence of emulsion creaming index on salt concentration for primary and multilayer emulsions (0.55 wt % WPI, 5 wt % sunflower oil, pH 3.5)	62
4.17	Effect of different salt concentration on creaming stability of a) primary and b) multilayer emulsion (Opaque upper layer: cream, transparent bottom layer: serum)	63
	,	-

xii

LIST OF ABBREVIATIONS

O/W	-	Oil-in-water
W/O	-	Water-in-oil
M-O/W	-	Multilayer oil-in-water
DE	-	Degree of esterification
HM	-	High methoxyl
LM	-	Low methoxyl
CI	-	Creaming index
GalA	-	Galacturonic acid
Rha	-	Rhamnose
0	-	Oxygen
С	-	Carbon
Н	-	Hydrogen
Na^+	-	Sodium ion
Cl	-	Chlorine ion
NaCl	-	Sodium chloride
NaOH	-	Sodium hydroxide
HCl	-	Hydrochloric acid
SDS	-	Sodium dodecyl sulphate
рКа	-	Acid dissociation constant
рН	-	Measure of acidity/basicity
pI	-	Isoelectric point
WPI	-	Whey protein isolate
GC	-	Gas chromatography
SD	-	Standard deviation
n	-	Number of analysis
RSM	-	Response surface methodology

LIST OF SYMBOLS

~	-	Approximately
>	-	More than
<	-	Less than
±	-	Plus minus
α	-	Alpha
β	-	Beta
%	-	Percentage
wt	-	Weight
v/v	-	Volume per volume
М	-	Molar
mM	-	Milimolar
min	-	Minute
S	-	Second
°C	-	Degree celcius
:	-	Ratio
m	-	Meter
mm	-	Milimeter
μm	-	Micrometer
g	-	Gram
mg	-	Miligram
kg	-	Kilogram
L	-	Liter
mL	-	Mililiter
mg/L	-	Miligram per liter
rpm	-	Revolutions per minute
MPa	-	Megapascal
i.d	-	Inside diameter

XV

CHAPTER 1

INTRODUCTION

1.1 Background of Study

Products such as milk, cream, salad dressings, soups, sauces, mayonnaise, butter and margarine are example of emulsions in the food industry. Conventionally, oil-in-water (O/W) emulsion is produced by homogenizing oil and aqueous phase together in addition of one or more emulsifiers (Friberg *et al.*, 2004; McClements, 2004). There are several limitations that can be attained by using current food emulsifier and traditional method of producing emulsion such as restricted stability to pH, salt, dehydration, heating and freezing. These limitations have driven researchers to carry out extended researches to come out with another method to improve the stability of emulsion. One of the methods is creating an interfacial layer around oil droplets that consists of several layers of emulsifiers and/or polyelectrolytes using a layer-by-layer electrostatic deposition technique that produces a multilayer emulsion (Guzey & McClements, 2006). The multiple layers provide strong steric repulsive and electrostatic forces which stabilize the emulsion against variety of environmental conditions such as temperature, pH and salt content (Guzey *et al.*, 2004; Moreau *et al.*, 2003).

According to a study by Djordjevic *et al.* (2007), multilayer emulsion improved the stability of encapsulated limonene against oxidation. Previous studies on multilayer emulsion have been reported for encapsulation of lemon/orange oil, fish oil and β -carotene (Yang *et al.*, 2011; Klinkesorn *et al.*, 2005; Hou *et al.*, 2011)

which were found to improve the stability of the emulsion. In a multilayer emulsion, by manipulating the pH, salt concentration or temperature, the outer layer can simply be detached from the oil droplets. Therefore, provides flexible encapsulation abilities against different environmental conditions (Ogawa *et al.*, 2003; Gu *et al.*, 2005). In food industry, the highly-charged multilayer interface is useful to produce food emulsion that is stable against droplet aggregation and lipid oxidation. Besides, multilayer emulsion can be used as delivery system for controlled or triggered release of active ingredients in functional food (Guzey & McClements, 2006).

Polysaccharides are widely used as emulsifier for the production of food emulsions which include gum arabic, soy soluble polysaccharides (SSP), some galactomannans, modified starches, and cellulose, as well as several types of pectin (Chanamai & McClements 2001; Dickinson, 2003; Nakamura et al., 2004). Pectin is a polysaccharide consists of galacturonic acid that occurs in the cell walls of most plant. Pectin was widely used in the food industry due to its gelling, thickening and stabilizing properties (Vriesmann et al., 2003; Yapo et al., 2007; Takamine et al., 2007). Commercial pectin is often extracted from citrus and apple pomace with yield of 15 to 30% and 10 to 15% respectively (Yapo & Koffi, 2013). Recent study has reported that industrial potato waste contains appreciable amount of rhamnogalacturonan I (hairy region of pectin) (Byg et al., 2012). This opens the possibility to investigate the potential use of other crop residue material such as sweet potato peels, as an alternative pectin source. Several studies have been carried out to investigate pectin extraction from sweet potato using hydrochloric acid (Nurdjanah, 2008); Zhang et al., 2013; Abang Zaidel et al., 2015, Foo et al., 2016), sodium hydroxide (Nurdjanah, 2008; Abang Zaidel et al., 2017) and disodium phosphate (Takamine et al., 2007; Nurdjanah, 2008).

1.2 Problem Statement

Since emulsions are thermodynamically unstable systems, ittend to be stabilized (coalescence, creaming) during food handling and processing. Emulsion breakdown is usually retarded by using emulsifiers, which are surface-active ingredients that adsorb to the surface of freshly formed lipid droplets during homogenization (Moreau *et al.*, 2003). Once adsorbed, itfacilitates further droplet disruption by lowering the interfacial tension, thereby reducing the size of the droplets produced during homogenization. There are various kinds of synthetic and natural emulsifiers that can be legally used in food emulsions, including small-molecule surfactants, phospholipids, proteins, and polysaccharides (Stauffer, 1999; Charlambous & Doxastakis, 1989; Krog, 1997). Each type of emulsifier has its own particular advantages and disadvantages. For example, some emulsifiers are effective at generating small emulsion droplets during homogenization, but are poor at providing long-term stability against droplet aggregation and vice versa (Stang *et al.*, 1994).

Consequently, there is no single emulsifier that is ideal for use in every food product. A number of studies have shown it is possible to improve emulsion stability by combining the beneficial attributes of different types of emulsifiers by forming multilayer emulsion (Ogawa *et al.*, 2003; Mao *et al.*, 2013, Gu *et al.*, 2004; Gu *et al.*, 2005). Multilayer emulsion can be produced by firstly using an ionic emulsifier that facilitates the formation of small droplets during homogenization. Then, an emulsifier with the opposite charge is introduced as the second layer that adsorbed to the droplets surface. The resulting droplets are coated by a two-layer interfacial membrane that may provide improved emulsion stability.

Pectin is a good potential emulsifier for food emulsions because it is already widely utilized in the food industry as an ingredient (Ngouémazong *et al.*, 2015). Commercial pectins are commonly extracted from citrus and apple. However, these two sources are not easily available in Malaysia as compared to sweet potato. It has been reported that sweet potato residues contain about 15% pectin on a dry matter basis (Mei *et al.*, 2010). Sweet potatoes are grown widely in Malaysia and are used to produce starchy food products in large food industry as well as small food business selling sweet potato snacks. Therefore, it is generating a lot of waste that could in turn pollute the environment. By using sweet potato residues as an

alternative source of pectin, the waste can be converted into a value-added product that is profitable while reducing pollution to the environment.

Several studies reported that citric acid which is an organic acid, is an effective solvent for extraction of pectin in terms of the yield and its physicochemical properties (Canteri-Schemin *et al*, 2015; Pinheiro *et al.*, 2008, Kliemann *et al.*, 2009). Besides, citric acid is a natural and safe food additive and is thus more attractive than commonly used strong mineral acids such as nitric, hydrochloric and sulfuric acid for the extraction of pectin (Yapo, 2009). Extraction of pectin from sweet potato peels using citric acid would not only manage the disposal of sweet potato waste, but also reduce the impact of the corrosive effluents to the environment that was caused by the use of conventional acids during pectin extraction.

A lot of study regarding multilayer emulsion using pectin as emulsifier only focused on the commercial apple and citrus pectin (Benjamin *et al*, 2012; Benjamin *et al.*, 2013, Moreau *et al.*, 2003; Ogawa *et al.*, 2004). Therefore, since pectin derived from sweet potato has the potential to be commercialized, this study aims to optimize pectin extraction from sweet potato peels using citric acid and to investigate multilayer emulsion stability as affected by sweet potato pectin.

1.3 Objective of Study

The objectives of this study are;

- 1. To optimize pectin extraction from sweet potato peels using citric acid.
- 2. To study the effect of sweet potato pectin concentration, pH and salt on multilayer emulsion stability.

1.4 Scope of Study

The scopes of this study are;

- Extraction of pectin from sweet potato peels using citric acid at different conditions (temperature 60 to 100°C, time 40 to 100 min, pH 1 to 2) to optimize the sweet potato pectin yield using Response Surface Methodology (RSM).
- Determination of degree of esterification of sweet potato pectin using Fourier Transform Infrared (FTIR) Spectroscopy.
- Investigation on the effect of sweet potato pectin concentration (0 -1.2 wt %), pH (3 - 7) and salt (0 - 400mM NaCl) on the multilayer emulsion stability using Dynamic Light Scattering for particle size and zeta-potential and measurement of creaming index.

1.5 Significance of Study

By conducting this study, sweet potatoes peels can be proven to be an alternative source of pectin that is available in Malaysia. This research can be the first step to the commercialization of sweet potato pectin which may open more opportunities in the food industry. Optimization of pectin extraction carried out in this study may increase the efficiency of the extraction. Besides, this study can provide the method and formulation of multilayer emulsion that utilizes pectin as a food-grade emulsifier. The study of emulsion stability at various environmental conditions can give more understanding regarding the characteristic of WPI-sweet potato pectin interfacial layer. In the future, this knowledge can be applied to control the thickness, structure and composition of the interfacial membrane of multilayer emulsion for food application.

REFERENCES

- Abang Zaidel, D. N., Chronakis, I. S., and Meyer, A. S. (2013). Stabilization of oilin-water emulsions by enzyme catalyzed oxidative gelation of sugar beet pectin. Food Hydrocolloids, 30(1), 19–25.
- Abang Zaidel, D. N., Hamidon, N. H., and Mat Zahir, N. (2017). Extraction and characterization of pectin from sweet potato (Ipomoea batatas) peels using alkaline extraction method. In Acta Horticulturae (pp. 211–218). International Society for Horticultural Science (ISHS), Leuven, Belgium.
- Abang Zaidel, D. N., Zainudin, N. N., Mohd Jusoh, Y. M., and Muhamad., I. I. (2015). Extraction and Characterization of Pectin from Sweet Potato (Ipomoea Batatas) Pulp. Journal of Engineering Science and Technology. 22 29.
- Anthon, G. E., and Barrett, D. M. (2008). Combined enzymatic and colorimetric method for determining the uronic acid and methylester content of pectin: Application to tomato products. Food Chemistry, 110, 239–247.
- Aoki, T., Decker, E. A., and McClements, D. J. (2005). Influence of environmental stresses on stability of O/W emulsions containing droplets stabilized by multilayered membranes produced by a layer-by-layer electrostatic deposition technique. Food Hydrocolloid 19 (2): 209–20.
- Araujo, P. W., & Brereton, R. G. (1996). Experimental design III. Quantification. TrAC Trends in Analytical Chemistry, 15(3), 156–163.
- Barros, A. S., Mafra, I., Ferreira, D., Cardoso, S., Reis, A., da Silva, J. A. L., Delgadillo I., Rutledge D. N., and Coimbra, M. A. (2002). Determination of the degree of methylesterification of pectic polysaccharides by FT-IR using an outer product PLS1 regression. Carbohydrate Polymers, 50, 85–94.
- Benjamin, O., Silcock, P., Beauchamp, J., Buettner, A., and Everett, D. W. (2013). Volatile release and structural stability of beta-lactoglobulin primary and multilayer emulsions under simulated oral conditions. Food Chemistry, 140(1– 2), 124–134.

- Benjamin, O., Silcock, P., Leus, M., and Everett, D. W. (2012). Multilayer emulsions as delivery systems for controlled release of volatile compounds using pH and salt triggers. Food Hydrocolloids. 27, 109–118.
- Bezerra, M. A., Santelli, R. E., Oliveira, E. P., Villar, L. S., and Escaleira, L. A. (2008). Response surface methodology (RSM) as a tool for optimization in analytical chemistry. Talanta, 76(5), 965–977.
- Box, G. E. P., and Wilson, K. B. (1951). On the experimental attainment of optimal conditions. Journal of the Royal Statistical Society, Series B 13, 1-45.
- Burke, S. E., and Barrett, C. J. (2003). Acid–base equilibria of weak polyelectrolytes in multilayer thin films. Langmuir 19(8):3297–303.
- Byg, I., Diaz, J., Ogendal, L. H., Harholt, J., Jørgensen, B., Rolin, C., Svava, R., Ulvskov, P. (2012). Large-scale extraction of rhamnogalacturonan I from industrial potato waste. Food Chem., 131, pp. 1207–1216
- Canteri-Schemin, M. H., Fertonani, H. C. R., Waszczynskyj, N., and Wosiacki, G. (2005). Extraction of pectin from apple pomace. Brazilian Archives of Biology and Technology, 48, 259–266.
- Canteri-Schemin, M.H., Fertonani, H.C.R., Waszczynskyj, N., Wosiacki, G. (2005). Extraction of pectin from apple pomace. Brazilian Archives of Biology and Technology, 48, 259–266
- Caruso, F., and Sukhorukov, G. (2003). Multilayer Thin Films: Sequential Assembly of Nanocomposite Materials; Decher, G., Schlenoff, J. B., Eds.; Wiley-VCH: Weinheim, Germany, pp 331-362.
- Chaharbaghi, E., Khodaiyan, F., and Hosseini, S. S. (2017). Optimization of pectin extraction from pistachio green hull as a new source. Carbohydrate Polymers, 173, 107–113.
- Chanamai, R., and McClements, D. J. (2001). Depletion flocculation of beverage emulsions by gum arabic and modified starch. J Food Sci 66:457–63.
- Chanamai, R., and McClements, D. J. (2002). Comparison of gum arabic, modified starch, and whey protein isolate as emulsifiers: influence of pH, CaCl₂ and temperature. Journal of Food Science, 67, 120–125.
- Charlambous, G., and Doxastakis, G. (1989). Food emulsifiers: chemistry, technology, functional properties and applications. Amsterdam, Holland: Elsevier.

- Chatjigakis, A. K., Pappas, C., Proxenia, N., Kalantzi, O., Rodis, P., and Polissiou, M. (1998). FT-IR spectroscopic determination of the degree of esterification of cell wall pectins from stored peaches and correlation to textural changes. Carbohydrate Polymers, 37, 395–408.
- Chen, Y., Zhang, J. G., Sun, H. J., and Wei, Z. J. (2014). Pectin from Abelmoschus escu- lentus: Optimization of extraction and rheological properties. International Journal of Biological Macromolecules, 70, 498–505.
- Cho, Y. J., and Hwang, J. K. (2000). Modeling the yield and intrinsic viscosity of pectin in acidic solubilization of apple pomace. Journal of Food Engineering, 44, 85-89.
- Chodanowski, P., and Stoll, S. (2001). Polyelectrolyte adsorption on charged particles: Ionic concentration and particle size effects. A Monte Carlo approach. J. Chem. Phys. 115, 4951-4960.
- Damodaran, S. (1996). Amino acids, peptides and proteins. In Food Chemistry, 3rd ed.; Fennema, O. R., Ed.; Dekker: New York, p 321.
- Decher, G. (2003). Multilayer Thin Films: Sequential Assembly of Nanocomposite Materials; Decher, G., Schlenoff, J. B., Eds.; Wiley-VCH: Weinheim, Germany, pp 1-46.
- Decher, G., and Schlenoff, J. B. (2003). Multilayer Thin Films: Sequential Assembly of Nanocomposite Materials; Wiley-VCH: Weinheim, Germany.
- Dickinson, E. (1992). An introduction to food colloids. Oxford: Oxford University Press.
- Dickinson, E. (2003). Hydrocolloids at interfaces and the influence on the properties of dispersed systems. Food Hydrocolloids 17:25–39.
- Dickinson, E. (2011). Mixed biopolymers at interfaces: Competitive adsorption and multilayer structures. Food Hydrocoll. 25, 1966–1983.
- Djordjevic, D., Cercaci, L., Alamed, J., McClements, D. J., and Decker, E. A. (2007). Chemical and physical stability of citral and limonene in sodium dodecyl sulfate-chitosan and gum arabic-stabilized oil-in-water emulsions. Journal of Agricultural and Food Chemistry, 55(9), 3585e3591.
- El-Nawawi, S. A., and Shehata, F. R. (1987). Extraction of pectin from Egyptian orange peel, factors affecting the extraction. Biol. Wastes. 20 (4), pp. 281–290.

- Erni, P., Windhab, E. J., Gunde, R., Graber, M., Pfister, B., Parker, A., and Fischer,
 P. (2007). Interfacial rheology of surface-active biopolymers: Acacia senegal versus hydrophobically modified starch. Biomacromolecules, 8, 3458–3466.
- Ferreira, S. L. C., Bruns, R. E., Ferreira, H. S., Matos, G. D., David, J. M., Brandão, G. C., & dos Santos, W. N. L. (2007). Box-Behnken design: An alternative for the optimization of analytical methods. Analytica Chimica Acta, 597(2), 179– 186.
- Foo, J. X., Abang Zaidel, D. N., and Ismail, N. H. (2016). Effect of Extraction Parameters on the Yield of Sweet Potato Pectin, Proceedings of the 6th International Graduate Conference on Engineering, Science and Humanities, 15-17 August 2016, Universiti Teknologi Malaysia, Johor Bahru, Malaysia, 146-148.
- Friberg, S., Larsson, K., Sjoblom, J. (2004). Food emulsions. 4 ed. New York: Marcel Dekker.
- Garna, H., Mabon, N., Robert, C., Cornet, C., Nott, K., Legros, H., Wathelet, B., and Paquot, M. (2007). Effect of extraction conditions on the yield and purity of apple pomace pectin precipitated but not washed by alcohol. Journal of Food Science, 72, 1–9.
- Giovanni, M. (1983). Response surface methodology and product optimization. Food Technology, 37(11), 41–45.
- Gnanasambandam, R., and Proctor, A. (2000). Determination of pectin degree of esterification by diffuse reflectance Fourier transform infrared spectroscopy. Food Chemistry, 68, 327–332.
- Gu, Y. S., Decker, E. A., and McClements, D. J. (2004). Influence of pH and icarrageenan concentration on physicochemical properties and stability of betalactoglobulin-stabilized oil-in-water emulsions. Journal of Agricultural and Food Chemistry, 52, 3626–3632.
- Gu, Y. S., Regnier, L., and McClements, D. J. (2005). Influence of environmental stresses on stability of oil-in-water emulsions containing droplets stabilized by β-lactoglobulin–ι-carrageenan membranes. J. Colloid Interface Sci. 286, 551–558.
- Guzey, D., and McClements, D. J. (2006). Formation, stability and properties of multilayer emulsions for application in the food industry. Adv.Colloid Interface Sci. 128–130, 227–248.

- Guzey, D., and McClements, D. J. (2007). Impact of electrostatic interactions on formation and stability of emulsions containing oil droplets coated by betalactoglobulin-pectin complexes. Journal of Agricultural and Food Chemistry, 55(2), 475-485.
- Guzey, D., Kim, H. J., and McClements, D. J. (2004). Factors influencing the production of o/w emulsions stabilized by beta-lactoglobulin–pectin membranes. Food Hydrocoll 18 (6): 967–75.
- Hou, Z., Gao, Y., Yuan, F., Liu, Y., Li, C., and Xu, D. (2011). Investigation into the physicochemical stability and rheological properties of β-carotene emulsion stabilized by soybean soluble polysaccharides and chitosan. J. Agric. Food Chem. 58, 8604–8611.
- Hunter, R. J. (1986). Foundations of Colloid Science; Oxford University Press: Oxford, U.K., Vol. 1.
- Ishida, H., Suzuno, H., Sugiyama, N., Innami, S., Tadokoro, T., and Maekawa, A. (2000). Nutritive evaluation on chemical components of leaves, stalks and stems of sweet potatoes (Ipomoea batatas poir). Food Chemistry, 68(3), 359– 367.
- Ismail, N. H. (2017). Optimization and Characterization of Pectin Extracted from Sweet Potato Residues. Master thesis. Universiti Teknologi Malaysia, Skudai.
- Jafari, F., Khodaiyan, F., Kiani, H., and Hosseini, S. S. (2017). Pectin from carrot pomace: Optimization of extraction and physicochemical properties. Carbohydrate Polymers, 157, 1315–1322.
- Joye, D. D., and Luzio, G. A. (2000). Process for selective extraction of pectins from plant material by different pH. Carbohydr. Polym., 43, pp. 337–342.
- Kalapathy, U., and Proctor, A. (2001). Effect of acid extraction and alcohol precipitation conditions on the yield and purity of soy hull pectin. Food Chem., 73: 393-396.
- Kamoun, A., Samet, B., Bouaziz, J., and Cha ^abouni, M. (1999). Application of a rotatable orthogonal central composite design to the optimization of the formulation and utilization of an useful plasticizer for cement. Analusis, 27, 91–96.
- Katsuda, M. S., McClements D. J., Miglioranza, L. H. S., and Decker, E. A. (2008). Physical and oxidative stability of fish oil-in-water emul- sions stabilized with β-lactoglobulin and pectin. J. Agric Food Chem. 56, 5926–5931.

Kertesz, Z. I. (1951). The pectic substances. New York: Interscience Publishers.

- Khan, M., Bibi, N., and Zeb, A. (2015). Optimization of Process Conditions for Pectin Extraction from Citrus Peel. Science, Technology and Development, 34(1), 9–15.
- Kliemann, E., Simas, K. N., Amante, E. R., Teo´ filo, R. F., Ferreira, M. M. C. and Amboni1, R. D. M. C. (2009). Optimisation of pectin acid extraction from passion fruit peel (Passiflora edulis flavicarpa) using response surface methodology. International Journal of Food Science and Technology, 44, 476– 483.
- Klinkesorn, U., Sophanodora, P., Chinachoti, P., Decker, E., and McClements, D. J. (2005). Encapsulation of emulsified tuna oil in two-layered interfacial membranes prepared using electrostatic layer-by-layer deposition. Food Hydrocolloids. 1044-1053, 19.
- Kong, K. Y., and Muthukumar, M. (1998). Monte Carlo study of adsorption of a polyelectrolyte onto charged spheres. J. Chem. Phys. 109, 1522-1527.
- Krog, N. J. (1997). Food Emulsifiers. In Food Emulsions, 3rd ed.; Friberg, S., Larsson, K., Eds.; Dekker: New York, p 141.
- Kulkarni, S. G., and Vijayanand, P. (2010). Effect of extraction conditions on the quality characteristics of pectin from passion fruit peel (Passiflora edulis f. flavicarpa L.). LWT - Food Science and Technology, 43(7), 1026–1031.
- Kyomugasho, C., Christiaens, S., Shpigelman, A., Van Loey, A. M., and Hendrickx, M. E. (2015). FT-IR spectroscopy, a reliable method for routine analysis of the degree of methylesterification of pectin in different fruit- and vegetable-based matrices. *Food Chem.* 176, 82–90.
- Levigne, S., Ralet, M. C., and Thubault, J. F. (2002). Characterisation of pectins extracted from fresh sugar beet under different conditions using an experimental design. Carbohydrate Ploymers, 49, 145–153.
- Li, D. Q., Du, G. M., Jing, W. W., Li, J. F., Yan, J. Y., and Liu, Z. Y. (2015). Combined effects of independent variables on yield and protein content of pectin extracted from sugar beet pulp by citric acid. *Carbohydrate Polymers*, *129* (9), 108–114.
- Liew, S. Q., Chin, N. L., and Yusof, Y. A. (2014). Extraction and Characterization of Pectin from Passion Fruit Peels. Agriculture and Agricultural Science Procedia, 2, 231–236.

- Manrique, G. D., and Lajolo, F. M. (2002). FT-IR spectroscopy as a tool for measuring degree of methyl esterification in pectins isolated from ripening papaya fruit. Postharvest Biology and Technology, 25, 99–107.
- Mao, L., Roos, Y. H., O'Callaghan, D. J., and Miao, S. (2013). Volatile Release from Whey Protein Isolate–Pectin Multilayer Stabilized Emulsions: Effect of pH, Salt, and Artificial SalivasJournal of Agricultural and Food Chemistry 61 (26), 6231-6239.
- Masmoudi, M., Besbes, S., Robert, C., Paquot, M., Blecker, C., and Attia, H. (2008). Optimization of pectin extraction from lemon byproduct with acidified date juice using response surface methodology. Carbohydrate Polymers, 74, 185– 192.
- May, C. D. (1990). Industrial pectins: sources, production and application. Carbohydrate Polymers, 12, 79–84.
- McClements, D. J. (1999). Food Emulsions: Principles, Practice and Techniques; CRC Press: Boca Raton, FL.
- McClements, D. J. (2004). Food Emulsions: Principles, Practice and Techniques, 2nd ed.; CRC Press: Boca Raton, FL.
- McClements, D. J. (2005). Theoretical analysis of factors affecting formation and stability of multilayered colloidal dispersions. Langmuir 21:9777–85.
- McClements, D. J., Decker E. A., and Weiss, J. (2007). Emulsion-based delivery systems for lipophilic bioactive components. J. Food Sci. 72, R109–R124.
- McNamee, B. F., O'Riordan, E. A., and O'Sullivan, M. (1998). Emulsification and encapsulation properties of gum arabic. Journal of Agricultural and Food Chemistry, 46, 4551–4555.
- Mei, X., Mu, T. H., and Han, J. J. (2010). Composition and physicochemical properties of dietary fiber extracted from residues of 10 varieties of sweet potato by a sieving method. Journal of Agricultural and Food Chemistry, 58, 7305–7310.
- Mezdour, S., Cuvelier, G., Cash, M. J., and Michon, C. (2007). Surface rheological properties of hydroxypropyl cellulose at air–water interface. Food Hydrocolloids, 21, 776–781.
- Minjares-Fuentes, R., Femenia, A., Garau, M. C., Meza-Velázquez, J. A., Simal, S., and Rosselló, C. (2014). Ultrasound-assisted extraction of pectins from grape

pomace using citric acid: A response surface methodology approach. Carbohydrate Polymers, 106(1), 179–189.

- Minkov, S., Minchev, A., and Paev, K. (1996). Modelling of the hydrolysis and extraction of apple pectin. Journal of Food Engineering, 29 (1), pp. 107–113.
- Mirhosseini, H., Tan, C., Aghlara, A., Hamid, N., Yusof, S., and Chern, B. (2008). Influence of pectin and CMC on physical stability, turbidity loss rate, cloudiness and flavor release of orange beverage emulsion during storage. Carbohyd Polym 73:83–91.
- Moreau, L., Kim, H. J., Decker, E. A., and McClements, D. J. (2003). Production and characterization of oil-in-water emulsions containing droplets stabilized by beta-lactoglobulin–pectin membranes. J Agric Food Chem 51(22):6612–7.
- Mukhiddinov, Z. K., Khalikov, D. K., Abdusamiev, F. T., and Avloev, C. C. (2000). Isolation and structural characterization of a pectin homo and ramnogalacturonan. Talanta, 53, pp. 171-176.
- Nakamura, A., Takahash, T., Yoshida, R., Maeda, H., and Corredig, M. (2004). Emulsifying properties of soybean soluble polysaccharide. Food Hydrocolloids 18:795–803.
- Nakauma, M., Funami, T., Noda, S., Ishihara, S., Al-Assaf, S., Nishinari, K., Phillips, G. O. (2008). Comparison of sugar beet pectin, soybean soluble polysaccharide, and gum arabic as food emulsifiers. 1. Effect of concentration, pH, and salts on the emulsifying properties. Food Hydrocolloids 22:1254–67.
- Ngouémazong, E. D., Christiaens, S., Shpigelman, A., Van Loey, A., and Hendrickx, M. (2015). The Emulsifying and Emulsion-Stabilizing Properties of Pectin: A Review. Comprehensive Reviews in Food Science and Food Safety, 14(6), 705–718.
- Nilsson, L., and Bergenståhl, B. (2007). Adsorption of hydrophobically modified anionic starch at oppositely charged oil/water interfaces. Journal of Colloid and Interface Science, 308, 508–513.
- Nurdjanah, S. (2008). Extraction and characterisation of pectin from Australian and Indonesian sweet potato. PhD. Thesis. Chemical Sciences & Engineering, Faculty of Engineering, UNSW, Australia.
- O' Hair, S. K. (1984). Farinaceous crops. In: Handbook of Tropical Food Crop. Martin F. W. (Ed), CRC. Press Boca. Ration, F.L. 109-137pp.

- Oakenfull, D. G. (1991). The chemistry of high-methoxyl pectins. In The Chemistry and Technology of Pectin, ed. R.H. Walter. (New York: Academic Press).
- Ogawa, S., Decker, E. A., and McClements, D. J. (2003). Influence of environmental conditions on the stability of oil in water emulsions containing droplets stabilized by lecithin–chitosan membranes. Journal of Agriculture Food Chemistry. 51, 5522–5527.
- Ogawa, S., Decker, E. A., and McClements, D. J. (2004). Production and characterization of O/W emulsions containing droplets stabilized by lecithin–chitosan–pectin mutilayered membranes. J Agric Food Chem; 52 (11): 3595–600.
- Ojeniyi, T., and Tewe, O. O. (2001). Processing and Utilization of sweet potato for food and livestock in Nigeria. Proceeding of 8th STRC, AB Symposium, Ibadan.
- Pasandide, B., Khodaiyan, F., Mousavi, Z. E., and Hosseini, S. S. (2017). Optimization of aqueous pectin extraction from Citrus medica peel. Carbohydrate Polymers, 178(7), 27–33.
- Perez, O. E., Carrera Sanchez, C., Pilosof, A. M. R., and Rodriguez Patino, J. M. (2008). Dynamics of adsorption of hydroxypropyl methylcellulose at the air– water interface. Food Hydrocolloids, 22, 387–402.
- Pinheiro, E. R., Silva, I. M. D. A., Gonzaga, L. V., Amante, E. R., Teófilo, R. F., Ferreira, M. M. C., and Amboni, R. D. M. C. (2008). Optimization of extraction of high-ester pectin from passion fruit peel (Passiflora edulis flavicarpa) with citric acid by using response surface methodology. Bioresource Technology, 99(13).
- Raji, Z., Khodaiyan, F., Rezaei, K., Kiani, H., ad Hosseini, S. S. (2017). Extraction optimization and physicochemical properties of pectin from melon peel. International Journal of Biological Macromolecules, 98, 709–716.
- Randall, R. C., Phillips, G. O., and Williams, P. A. (1988). The role of the proteinaceous component on the emulsifying properties of gum arabic. Food Hydrocolloids 2:131–40.
- Ray, A. K., Bird, P. B., Iacobucci, G. A., and Clark, B. C. (1995). Functionality of gum arabic: fractionation, characterization and evaluation of gum fractions in citrus oil emulsions and model beverages. Food Hydrocolloids 9:123–31.

- Renard, C.M.G.C., Cre´peau, M.J. & Thibault, J.F. (1995). Structure of repeating units in the rhamnogalacturonic backbone of apple, beet and citrus pectins. Carbohydrate Research, 275, 155–165.
- Rolin, C. (1993). Industrial Gums: Polysaccharides and Their Derivative, in: Whistler, R. L., Bemiller J. N. (Eds.), Academic Press, New York, pp. 257– 293.
- Samavati, V. (2013). Polysaccharide extraction from Abelmoschus esculentus: Optimization by response surface methodology. Carbohydrate Polymers, 95(1), 588–597.
- Santos, J. D. G., Espeleta, A. F., Branco, A., and De Assis, S. A. (2013). Aqueous extraction of pectin from sisal waste. Carbohydrate Polymers, 92(2), 1997–2001.
- Schmitt, C., Sanchez, C., Desobry-Banon, S., and Hardy, J. (1998). Structure and techno-functional properties of protein-polysaccharide com- plexes. Crit. ReV. Food Sci. Nutr. 38, 689-753.
- Schonhoff, M. (2003). Layered polyelectrolyte complexes: Physics of formation and molecular properties. Journal of Physics: Condensed Matter, 15, R1781– R1808.
- Scott, G. I., and Maldonado, L. (1999). Sweet Potato facts. A compendium of key figures and analysis for 30 important sweet potato producing countries. C. I. P, Lima Pero U.
- Seidu, J. M., Bobobee, E. Y. H., Kwenin, W. J. K., Tevor, W. J., Mahama, A. A., and Agbeven, J. (2012). ARPN Journal of Agricultural and Biological Science. Vol. 7, No. 6.
- Souza, A. S., dos Santos, W. N. L., and Ferreira, S. L. C. (2005). Application of Box–Behnken design in the optimisation of an on-line pre-concentration system using knotted reactor for cadmium determination by flame atomic absorption spectrometry. Spectrochimica Acta Part B: Atomic Spectroscopy, 60(5), 737–742.
- Sriamornsak, P. (2002). Analysis of selected physicochemical properties of pectin and alginate gels intended for drug delivery. PhD Thesis, Charles Sturt University.
- Sriamornsak, P. (2003). Chemistry of Pectin and its Pharmaceutical Uses: A Review. Silpakorn University International Journal. 3(1):206-228. o

- Srivastava, P., and Malviya, R. (2011). Extraction, Characterization and Evaluation of Orange Peel Waste Derived Pectin as a Pharmaceutical Excipient. The Open Natural Products Journal. 09; 1(1):65-70.
- Stang, M., Karbstein, H., and Schubert, H. (1994). Adsorption kinetics of emulsifiers at oil-water interfaces and their effect on mechanical emulsification. Chem. Eng. Process. 33, 307.
- Stauffer, C. E. (1999). Emulsifiers; Eagen Press: St. Paul, MN.
- Sukhorukov, G. B., Donath, E., Davis, S., Lichtenfeld, H., Caruso, F., Popov, V. I., and Mohawld, H. (1988). Stepwise polyelectrolyte assembly on particle surfaces: a novel approach to colloid design. Polym. Adv. Technol. 9(10-11): 759-767.
- Surh, J., Decker, E. A., and McClements, D. J. (2006). Influence of pH and pectin type on properties and stability of sodium-caseinate stabilized oil-in-water emulsions. Food Hydrocolloids, 20(5), 607–618.
- Surh, J., Gu, Y. S., Decker, E. A., and McClements, D. J. (2005). Influence of environmental stresses on stability of O/M emulsions containing cationic droplets stabilized by SDS-fish gelatin membranes. J. Agric. Food Chem. 53, 4236–4244.
- Taherian, A. R., Fustier, P., and Ramaswamy, H. S. (2007). Effects of added weighting agent and xanthan gum on stability and rheological properties of beverage cloud emulsions formulated using modified starch. Journal of Food Process Engineering, 30, 204–224.
- Takamine, K., Abe, J. I., and Shimono, K. (2007). Physicochemical and gelling characterizations of pectin extracted from sweet potato pulp. Journal of Applied Glycoscience, 54, 211–216.
- Thakur, B. R., Singh, R. K., and Handa, A. K. (1997). Chemistry and uses of pectin-a review. Critical Reviews in Food Science and Nutrition, 37, 47–73.
- Tiwari, A. K., Saha, S. N., Yadav, V. P., Upadhyay, U. K., Katiyar, D. N., and Mishra, T. (2017). Extraction and Characterization of Pectin from Orange Peels. International Journal of Biotechnology and Biochemistry, 13(1), 39–47.
- Tokaev, E. S., Gurov, A. N., Rogov, I. A., and Tolstoguzov, V. B. (1987). Properties of oil/water emulsions stabilized by casein-acid polysaccharide mixtures. Nahrung. 31, 825–834.

- Vera Candioti, L., De Zan, M. M., Cámara, M. S., and Goicoechea, H. C. (2014). Experimental design and multiple response optimization. Using the desirability function in analytical methods development. Talanta, 124, 123–138.
- Virk, B. S., and Sogi, D. S. (2004). Extraction and characterization of pectin from apple pomace (Malus Pumila Cv Amri) peel waste. Int. J. Food Prop. 7, 1–11.
- Von Goeler, F., and Muthukumar, M. (1994). Adsorption of polyelectrolytes onto curved spheres. J. Chem. Phys. 1994, 100, 7796-7803.
- Vriesmann, L. C., Teófilo, R. F., and Lúcia de Oliveira Petkowicz, C. (2012). Extraction and characterization of pectin from cacao pod husks (Theobroma cacao L.) with citric acid. LWT - Food Science and Technology, 49(1), 108– 116.
- Walstra, P. (1993). Principles of emulsion formation. Chem. Eng. Sci. 48, 333-350.
- Williams, P. A., Sayers, C., Viebke, C., Senan, C., Mazoyer, J., and Boulenguer, P. (2005). Elucidation of the emulsification properties of sugar beet pectin. Journal of Agricultural and Food Chemistry, 53, 3592–3597.
- Wollenweber, C., Makievski, A. V., Miller, R., and Daniels, R. (2000). Adsorption of hydroxypropyl methylcellulose at the liquid/liquid interface and the effect on emulsion stability. Colloids and Surfaces A, 172, 91–101.
- Xu, H. N., Liu, Y., and Zhang, L. (2015). Salting-out and salting-in: competitive effects of salt on the aggregation behavior of soy protein particles and their emulsifying properties. Soft Matter, 11(29), 5926–5932.
- Xue, Z. H, Zhang, X., Zhang, Z. J., Liu, J. H., Wang, Y. F., Chen, D. X., and Long, L. S. (2011). Optimization of Pectin Extraction from Citrus Peel by Response Surface Methodology. Food Science. Vol. 32, No. 18.
- Yang, T. S., Liu, T. T., and Hu, T. F. (2011). Effects of lecithin and pectin on riboflavin-photosensitized oxidation of orange oil in a multilayered oil-in-water emulsion. J. Agric. Food Chem. 59, 9344–9350.
- Yapo, B. M. (2009). Biochemical characteristics and gelling capacity of pectin from yellow passion fruit rind as affected by acid extractant nature. Journal of Agricultural and Food Chemistry, 57, 1572-1578.
- Yapo, B. M., Robert, C., Etienne, I., Wathelet, B., and Paquot, M. (2007). Effect of extraction conditions on the yield, purity and surface properties of sugar beet pulp pectin extracts. Food Chemistry, 100, 1356–1364.

- Zhang, C. P., and Mu, T. H. (2011). Optimisation of pectin extraction from sweet potato (Ipomoea batatas, Convolvulaceae) residues with disodium phosphate solution by response surface method. International Journal of Food Science and Technology, 46, 2274–2280.
- Zhang, L., Chen, F., Yang, H., Ye, X., Sun, X., Liu, D., Yang, B., An, H., and Deng,Y. (2012). Effects of temperature and cultivar on nanostructural changes of water soluble pectin in peaches. Carbohydrate Polymers, 87, 816–821.
- Zhang, Y. Y., Mu, T. H., and Zhang, M. (2013). Optimization of acid extraction of pectin from sweet potato residues by response surface methodology and its antiproliferation effect on cancer cells. International Journal of Food Science and Technology, 48, 778–785.