



UNIVERSITI PUTRA MALAYSIA

***BATCH AND FIXED BED ADSORPTION STUDY FOR REMOVAL OF
ACID AND REACTIVE DYES FROM AQUEOUS SOLUTION
USING MODIFIED KENAF CORE***

MAYTHAM KADHIM OBAID AL- MAMOURI

FK 2017 32



**BATCH AND FIXED BED ADSORPTION STUDY FOR REMOVAL OF
ACID AND REACTIVE DYES FROM AQUEOUS SOLUTION
USING MODIFIED KENAF CORE**

By

MAYTHAM KADHIM OBAID AL- MAMOURI

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfillment of the Requirements for the Degree of Master of Science**

April 2017

COPYRIGHT

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



DEDICATION

This thesis is dedicated to my brother Habib, my son Mohammed, my wife, and my family and supports. Without them, none of this would have been possible.

Maytham Kadhim Obaid

January 2017



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the Degree of Master of Science

**BATCH AND FIXED BED ADSORPTION STUDY FOR REMOVAL OF
ACID AND REACTIVE DYES FROM AQUEOUS SOLUTION
USING MODIFIED KENAF CORE**

By

MAYTHAM KADHIM OBAID AL- MAMOURI

April 2017

Chairman : Professor Luqman Chuah Abdullah, PhD
Faculty : Engineering

The extensive use of commercial activated carbon as an adsorbent for the purification of industrial effluent from textile industry is not economically feasible due its high operational cost. Therefore, this research has been undertaken to explore the potential of certain agro based residues to produce suitable adsorbent.

In this research, evaluation of the removal of reactive orange16 (RO16) and acid red 114 (AR114) dyes from aqueous solution was studied in batch and fixed bed column system by using modified kenaf core fibre (MKCF), in which kenaf being one of the agricultural crops used as low-cost adsorbents instead of activated carbon. In this study, kenaf core fibre (KCF) was modified successfully by treating with (3-chloro-2-hydroxypropyl)- trimethylammonium chloride (CHMAC) as quaternization agent.

In batch system, Results showed that the maximum removal of RO16 and AR114 were 97% and 99% respectively. Moreover, the results obtained from the isotherm studies were found to be best fitted with Freundlich isotherm with correlation coefficients (R^2) of 0.9924 for RO16, and isotherm studies were best fitted with Langmuir isotherm with correlation coefficients (R^2) 0.9853 for AR114. It was found that the kinetic study followed the pseudo-second-order kinetic model with correlation coefficients $R^2=0.9997$ and 0.9953 for RO16 and AR114 respectively and the maximum adsorption capacity for RO16 and AR114 were 416.86 mg/g and 238.56 mg/g, respectively.

The fixed bed column experiment was carried out by varying the flow rates, initial concentration of the dyes and the height of the bed. experimental data analysis by using three models Thomas, Yoon- Nelson and Adam- Bohart, It was found that the best color removal percentage increased when there was a decrease in the dye

concentration, low flow rates and an increase in the bed depth for the both dyes studied. The experimental results have shown a good agreement with the theoretical results. This study showed that the low-cost kenaf fibres could be used for dye removal.



Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Master Sains

**KAJIAN PENJERAPAN KELOMPOK DAN LAPISAN TETAP UNTUK
PENYINGKIRAN PEWARNA ASID DAN REAKTIF DARI
LARUTAN AKUEUS DENGAN MENGGUNAKAN
SERAT TERAS KENAFYANG DIUBAHSUAI**

Oleh

MAYTHAM KADHIM OBAID AL- MAMOURI

April 2017

Pengerusi : Profesor Luqman Chuah Abdullah, PhD
Fakulti : Kejuruteraan

Penggunaan secara meluas karbon komersil yang diaktifkan sebagai bahan penjerap bagi penulenan bahan efluen industri adalah tidak begitu sesuai secara ekonomi kerana kos operasinya yang tinggi. Oleh itu, kajian ini telah dijalankan bagi meneroka potensi sisa pertanian tertentu untuk menghasilkan bahan penjerap yang bersesuaian

Dalam cubaan ini, penilaian penyingkiran pewarna orange16 reaktif (RO16) dan merah asid 114 (AR114) daripada larutan akueus dikaji dalam model kumpulan dan turus dasar tetap dengan menggunakan serat teras kenaf diubahsuai (MKCF), di mana kenaf merupakan salah satu daripada tanaman pertanian yang digunakan sebagai bahan penjerap kos-rendah menggantikan karbon teraktif. Di dalam usaha ini, serat teras kenaf (KCF) telah diubahsuai dengan jayanya secara merawat dengan (CHMAC) sebagai ejen kuarterener.

Hasil kajian menunjukkan bahawa penyingkiran maksimum RO16 dan AR114 ialah 97% dan 99% masing-masing pada 30°C. Selain itu, keputusan yang diperolehi daripada kajian isoterma telah dipadankan terbaik dengan isoterma Freundlich dengan pekali korelasi sebanyak (R^2) 0.9924 untuk RO16, dan kajian isoterma telah dipadankan terbaik dengan isoterma Langmuir dengan pekali korelasi (R^2) 0.9853 untuk AR114. Didapati bahawa kajian kinetik mengikuti model kinetik pseudo-order-kedua dengan pekali korelasi $R^2 = 0.9997$ dan 0.9953 untuk RO16 dan AR114 masing-masing; kapasiti penjerapan maksimum bagi RO16 dan AR114 adalah 416.86 dan 232.56 masing-masing.

Ujian penjerapan untuk menentukan kadar penyerapan pewarna reaktif dan berasid. di dalam system turus juga telah dijalankan Eksperimen turus telah dijalankan dengan mengubah kadar aliran, kepekatan awal pewarna dan ketinggian dasar pada. Didapati bahawa peratusan penyingkiran warna meningkat apabila terdapat penurunan kepekatan pewarna, kadar aliran yang rendah dan peningkatan kedalaman dasar untuk kedua-dua pewarna yang dikaji. Dalam eksperimen, kadar aliran turus dikekalkan pada. Kajian ini telah menunjukkan bahawa serat kenaf kos-rendah boleh digunakan untuk penyingkiran pewarna. Kajian penjanaan semula telah dijalankan dan bahan penjerap itu didapati boleh digunakan semula dengan penurunan minimum dalam kapasiti penjerapannya.



ACKNOWLEDGEMENTS

All praises are to almighty Allah, the lord of whole creations, for inspiring and guiding me towards the utmost goodness. I also would like to express my sincere gratitude and appreciation to supervisor Prof. Dr. Luqman Chuah Abdullah and co-supervisor Dr. Siti nurul Ain Binti Md Jamil to them priceless guidance, continued supervision, advice, comment, encouragement and support throughout the research journey. I would like to gratefully acknowledge the technicians in the Department of Chemical and Environmental Engineering and my colleagues for their willingness in helping me. Many thanks and gratitude also goes to the supervisory committee for their guidance and advice. Also, I would like to express my utmost appreciation and gratitude to Universiti Putra Malaysia. Finally, I would like to thank the University of Babylon, Ministry of Higher Education and Scientific Research of Iraq. Sincere apologies to any individual I had unintentionally left off.

Maytham Kadhim Obaid AL- Mamouri

January 2017

I certify that a Thesis Examination Committee has met on 14 April 2017 to conduct the final examination of Maytham Kadhim Obaid on his thesis entitled "Batch and Fixed Bed Adsorption Study for Removal of Acid and Reactive Dyes from Aqueous Solution using Modified Kenaf Core" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

Rozita binti Omar, PhD

Senior Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Zurina binti Zainal Abidin, PhD

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

Ma'an Alkhatib, PhD

Associate Professor
International Islamic University Malaysia
Malaysia
(External Examiner)



NOR AINI AB. SHUKOR, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: 2 June 2017

This thesis was submitted to the Senate of the Universiti Putra Malaysia and has been accepted as fulfillment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Luqman Chuah Abdullah, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

Siti Nurul Ain Binti Md Jamil, PhD

Senior Lecturer
Faculty of Science
Universiti Putra Malaysia
(Member)



ROBIAH BINTI YUNUS, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly referenced;
- this thesis has not been submitted previously or concurrently for any other degree at any institutions;
- intellectual property from the thesis and copyright of thesis are fully-owned by Universiti Putra Malaysia, as according to the Universiti Putra Malaysia (Research) Rules 2012;
- written permission must be obtained from supervisor and the office of Deputy Vice-Chancellor (Research and innovation) before thesis is published (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software

Signature: _____ Date: _____

Name and Matric No.: Maytham Kadhim Obaid Al- Mamouri , GS 45083

Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and the writing of this thesis was under our supervision;
- supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) were adhered to.

Signature: _____

Name of Chairman
of Supervisory
Committee:

Professor Dr. Luqman Chuah Abdullah

Signature: _____

Name of Member
of Supervisory
Committee:

Dr. Siti Nurul Ain Binti Md Jamil

TABLE OF CONTENTS

	Page
ABSTRACT	i
ABSTRAK	iii
ACKNOWLEDGEMENTS	v
APPROVAL	vi
DECLARATION	viii
LIST OF TABLES	xiii
LIST OF FIGURES	xv
LIST OF APPENDICES	xviii
LIST OF ABBREVIATIONS	xix
LIST OF SYMBOLS	xx
CHAPTER	
1 INTRODUCTION	1
1.1 Water pollution	1
1.2 Kenaf	1
1.3 Adsorption of pollutants by using kenaf fibre	2
1.4 Problem statement	2
1.5 Objectives of the Study	3
1.6 Scope of work	3
1.7 Organization of thesis	3
2 LITERATURE REVIEW	5
2.1 Dyes	5
2.1.1 Reactive Dyes	5
2.1.2 Acid Dyes	7
2.2 Effect of dyes pollution on living organisms	8
2.3 days pollution in the world	9
2.4 Methods of dyes treatment in wastewater	10
2.4.1 Chemical methods	10
2.4.2 Physical methods	11
2.4.3 Biological treatments	12
2.5 Quarternisation of lignocellulosic fibre	12
2.6 Factor Affecting Adsorption Capacity	14
2.7 Adsorption techniques	16
2.7.1 Batch Adsorption Method	16
2.7.2 Fixed bed column adsorption Method	16
2.8 Adsorption Isotherm models	17
2.8.1 Langmuir Isotherm Model	17
2.8.2 Freundlich Isotherm Model	18
2.8.3 Temkin Model	19
2.9 Kinetics Study	19
2.10 Intraparticle effective diffusivity	20
2.11 Fixed bed column Adsorption models	21
2.11.1 Thomas model	21
2.11.2 Yoon–Nelson model	22

	2.11.3	Adams-Bohart model	22
3		MATERIALS AND METHODS	24
	3.1	Materials	24
	3.1.1	Chemicals	24
	3.1.2	Methodology Flow Chart	24
	3.1.3	Adsorbent	25
	3.1.4	Adsorbate	26
	3.2	Characterization of modified Kenaf Core fibre	28
	3.2.1	Scanning Electron Microscope (SEM)	28
	3.2.2	Fourier Transform Infrared Spectroscopy (FTIR)	28
	3.2.3	BET Analysis	28
	3.2.4	Particle size distribution	28
	3.3	Batch Adsorption experimental study	28
	3.3.1	Effect of modified Kenaf Core fiber	28
	3.3.2	Effect of pH	29
	3.3.3	Effect of adsorbent Dosage	29
	3.3.4	Effects of Contact Time	29
	3.3.5	Effect of initial dye concentration	29
	3.3.6	Effect of agitation speed	29
	3.3.7	Effect of temperature	30
	3.3.8	Adsorption isotherm studies	30
	3.3.9	Kinetic Study	30
	3.4	Fixed bed column adsorption studies	30
	3.4.1	Effect of flow rate on breakthrough curve	31
	3.4.2	Effect of dye concentration on breakthrough curve	31
	3.4.3	Effect of different bed depths on breakthrough curve	31
	3.5	Regeneration	31
4		RESULTS AND DISCUSSION	32
	4.1	Characterization of modified Kenaf Core fiber	32
	4.1.1	Scanning Electron Microscope (SEM)	32
	4.1.2	Fourier Transform Infrared Spectroscopy (FTIR)	33
	4.1.3	BET Analysis	34
	4.1.4	Particle size distribution	35
	4.2	Batch Adsorption experimental study	35
	4.2.1	Effect of Modified Kenaf Core fibre	35
	4.2.2	Effect of adsorbent Dosage	36
	4.2.3	Effect of pH	37
	4.2.4	Effects of contact time	38
	4.2.5	Effect of initial dye concentration	39
	4.2.6	Effect of agitation speed	41
	4.2.7	Effect of temperature	42
	4.3	Adsorption Isotherm Study	44
	4.3.1	Langmuir Isotherm Model	44
	4.3.2	Freundlich Isotherm Model	45
	4.3.3	Temkin Model	46

4.4	Kinetic Study	49
4.5	Intra-particle diffusion model	52
4.6	Fixed bed column studies	54
4.6.1	Effect of flow rate on breakthrough curve	54
4.6.2	Effect of dye concentration on breakthrough curve	55
4.6.3	Effect of different bed depths on breakthrough curve	56
4.7	Fixed bed column adsorption models	57
4.7.1	Thomas model	57
4.7.2	Yoon–Nelson model	58
4.7.3	Adams-Bohart model	59
4.8	Regeneration	61
5	CONCLUSIONS AND RECOMMENDATIONS FOR FUTURE RESEARCH	63
5.1	Conclusions	63
5.2	Recommendations for future research	63
	REFERENCES	64
	APPENDICES	79
	BIODATA OF STUDENT	86
	LIST OF PUBLICATIONS	87

LIST OF TABLES

Table		Page
1.1	Utilisation of kenaf core fibre as adsorbent	2
2.1	Adsorption capacities of various adsorbents towards reactive and acid dyes	6
2.2	Basic chemical ingredients for kenaf core and bast	12
2.3	Previous researches by using quaternised lignocellulosic biomass for removal of dyes.	14
3.1	All chemicals used for this research	24
3.2	General properties of acid red 114 and reactive orange 16	27
4.1	Analysis of FTIR spectra of NKCF and MKCF	34
4.2	Isotherm constants for RO16 and AR114 on MKCF	48
4.3	Parameters and correlation coefficient (R^2) of pseudo-first order and pseudo-second order kinetic models for adsorption of RO16 dye by MKCF.	52
4.4	Parameters and correlation coefficient (R^2) of pseudo-first order and pseudo-second order kinetic models for adsorption of AR114 dye by MKCF.	52
4.5	Parameters and correlation coefficient (R^2) of intra particle diffusion model for adsorption of RO16 dye by MKCF.	54
4.6	Parameters and correlation coefficient (R^2) of intra particle diffusion model for adsorption of AR114 dye by MKCF.	54
4.7	Thomas model parameters for RO16 dye at different conditions using linear regression analysis	58
4.8	Thomas model parameters for AR114 dye at different conditions using linear regression analysis	58
4.9	Yoon–Nelson model parameters for RO16 dye at different conditions using linear regression analysis	59
4.10	Yoon–Nelson model parameters for AR114 dye at different conditions using linear regression analysis	59

4.11	Adams-Bohart model parameters for RO16 dye at different conditions using linear regression analysis	60
4.12	Adams-Bohart model parameters for AR114 dye at different conditions using linear regression analysis	60



LIST OF FIGURES

Figure		Page
2.1	General chemical structure of reactive dye.	7
2.2	The types and structure the acid dyes.	8
2.3	River water quality trend in Malaysia between 2006 and 2010.	10
2.4	Molecular structure of cellulose.	13
2.5	Scheme lignocellulose quaternisation reaction scheme: (1) cellulose; (2) N (3-chloro-2-hydroxypropyl); (3) trimethylammonium chloride epoxide; (4)	13
3.1	Flow chart of prepare and adsorption experiments	25
3.2	Kenaf core fibre (a) before chemical treatment and (b) after chemical treatment.	26
3.3	Molecular structure of adsorbate: (a) RO16; (b) AR114.	27
4.1	SEM micrograph for (a) NKCF (b) Mercerisation KCF (c) MKCF and (d) MKCF after dyes adsorption.	33
4.2	FTIR spectra for NKCF and MKCF.	34
4.3	Particle Size Distribution for MKCF.	35
4.4	Percentage of dyes (RO16 and AR114) removal by using NKCF and MKCF (Dose=0.1 g/100ml, (Co=100 mg/L, Temp. =30 °C, Speed=150 rpm, Time=24 hr.)	36
4.5	Effect of MKCF dosage on percentage removal of RO16 and AR114 (Co=100 mg/L, Temp. =30 °C, Speed=150 rpm, Time=24 hr., pH=6.5).	37
4.6	Effect of initial pH on percentage removal of RO16 and AR114 by MKCF (Dose=0.1 g/100ml, Co=100 mg/L, Temp=30 °C, Speed=150 rpm, Time=24 hr.).	38
4.7	Effect of contact time on the percentage removal of RO16 dye (Dose=0.1 g/100ml, Temp=30 °C, Speed=150 rpm, pH=6.5).	39
4.8	Effect of contact time on the percentage removal of AR114 dye (Dose=0.1 g/100ml, Temp=30 °C, Speed=150 rpm, pH=6.5).	39

4.9	Effect of initial dye concentration on the percentage removal of RO16 dye (Dose=0.1 g/100ml, Temp=30 °C, Speed=150 rpm, Time=24 hr., pH=6.5).	40
4.10	Effect of initial dye concentration on the percentage removal of AR115 dye (Dose=0.1 g/100ml, Temp=30 °C, Speed=150 rpm, Time=24 hr., pH=6.5).	41
4.11	Effect of agitation speed on the percentage removal of RO16 dye (Dose=0.1 g/100ml, Temp=30 °C, Time=24 hr., pH=6.5).	42
4.12	Effect of agitation speed on the percentage removal of AR114 dye (Dose=0.1 g/100ml, Temp.=30 °C, Time=24 hr. , pH=8).	42
4.13	Effect of temperature on the percentage removal of RO16 dye (Dose=0.1 g/100ml, Speed=150 rpm, Time=24 hr., pH=8).	43
4.14	Effect of temperature on the percentage removal of AR114 dye (Dose=0.1 g/100ml, Speed=150 rpm, Time=24 hr., pH=6.5).	44
4.15	Langmuir adsorption isotherm for RO16.	45
4.16	Langmuir adsorption isotherm for AR114.	45
4.17	Freundlich adsorption isotherm for RO16.	46
4.18	Freundlich adsorption isotherm for AR114.	46
4.19	Temkin adsorption isotherm for RO16.	47
4.20	Temkin adsorption isotherm for AR114.	47
4.21	Adsorption Isotherms for RO16.	48
4.22	Adsorption Isotherms for AR114.	49
4.23	Kinetic study for adsorption of RO16 on MKCF by using pseudo-first-order kinetic model.	50
4.24	Kinetic study for adsorption of AR114 on MKCF by using pseudo-first-order kinetic model.	50
4.25	Kinetic study for adsorption of RO16 on MKCF by using pseudo-second -order kinetic model.	51
4.26	Kinetic study for adsorption of AR114 on MKCF by using pseudo-second-order kinetic model.	51

4.27	Linearized plots of intra particle diffusion studies for sorption of RO16 dye onto MKCF.	53
4.28	Linearized plots of intra particle diffusion studies for sorption of AR114 dye onto MKCF.	53
4.29	Effect of inlet flow rate of RO16 dye on break through curve.	55
4.30	Effect of inlet flow rate of AR114 dye on break through curve.	55
4.31	Effect of inlet RO16 dye concentration on break through curve.	56
4.32	Effect of inlet AR114 dye concentration on break through curve.	56
4.33	Effect of bed depths on break through curve for RO16 dye.	57
4.34	Effect of bed depths on break through curve for AR114 dye.	57
4.35	Adsorption cycles for RO16 on MKCF.	61
4.36	Adsorption cycles for AR114 on MKCF.	62
A-1	Calibration curve of adsorption RO16.	79
A-2	Calibration curve of adsorption AR114.	79
B-1	Langmuir adsorption isotherm for RO16	81
B-2	Freundlich adsorption isotherm for RO16	81
B-3	Temkin adsorption isotherm for RO16	82
C-1	Kinetic study for adsorption of RO16 on MKCF by using pseudo first order kinetic model	84
C-2	Kinetic study for adsorption of RO16 on MKCF by using pseudo second order kinetic model	85

LIST OF APPENDICES

Appendix		Page
A	Calibration Curve for UV-Spectrophotometer	79
B	Calculation of isotherm constants	80
C	Kinetic Studies Calculation	83



LIST OF ABBRIVATIONS

NKCF	Natural kenaf core fibre
MKCF	Modify kenaf core fibre
CHMAC	(3-chloro-2-hydroxypropyl)trimethylammonium chloride
RO16	Reactive orange16
AR114	Acid red114
SSE	Sum of the Squares of the Errors



LIST OF SYMBOLS

q_e	Amount of dye adsorbed per gram of adsorbent at equilibrium
q_m	Maximum adsorption capacity per gram of adsorbent
q_t	Amount of dye adsorbed per gram of adsorbent in time
R^2	Correlation coefficient
C_e	Concentration of solute in solution at equilibrium
C_o	Initial concentration of solute in solution
q_{max}	Equilibrium adsorption capacity (mg/g)
R_L	Dimensionless constant separation factor
K_L	Langmuir constant
K_F	Freundlich constant
$1/n$	an empirical parameter that depends on adsorption rigour
R	constant of gas 8.314 J/mol
T	Absolute temperature
B	Heat of adsorption J/mol
A	Temkin isotherm constant L/g
Q_t	Value of adsorbed at a given time (min)
K_1	Average constant of adsorption operation (1/min) (pseudo-first-order)
k_{id}	is the intra-particle diffusion rate constant (mg/g min ^{1/2})
C	is the intercept
V_{eff}	effluent volume
K_{TH}	Thomas model constant (L/min.mg)
K_{YN}	Yoon-Nelson rate constant (1/min)
K_{AB}	Kinetic constant of Adams–Bohart model (L/mg min)

N_0	saturation concentration from Adams–Bohart model (mg /L)
Z	bed depth of column (cm)
F	linear velocity (cm/ min)



CHAPTER 1

INTRODUCTION

1.1 Water pollution

The problems of environmental pollution, specifically water pollution that affects the aquatic environment, have been an area of major concern for decades now. Water is considered to be the foremost reason for the existence of life on earth. The history of human civilisation shows that all communities live near to water sources. Humans can survive and obtain healthy lives; healthy life is the presence of fresh and clean water (Gupta et al. 2016). In recent years, pollution has become a glaring issue across the world. Pollution is highly detrimental to the environment irrespective of whether it is caused by human activities or natural processes. Water pollution can be regarded as the most crucial environmental pollution problem. It damages the aquatic ecosystems and causes health hazards to those who depend on that polluted water. Industries such as tanning, textile, printing, plastic, and carpet, are some of the main sources of water pollutants (Zurhana et al., 2015). These industries require huge amounts of water for their various operations (Kayode et al., 2015). The contaminated water coming out of these industries is then discharged into rivers, ponds and other water bodies, without any serious care or processing. This is more the case in developing countries where there is a serious lack of strict laws related to environment protection, or the laws that are there have no enforcement at all, which in turn pollute the clean water supplies (UN Water, 2009). In some regions, 50% of the different species of fish that live in freshwater are on the verge of extinction and almost one-third of the amphibians are likely to be extinct (Vié et al., 2009). The rate of extinction of freshwater fishes is five times greater than that of other types (Ricciardi et al., 1999). Even in the developed world, in countries like France, the quality of drinking water is not assured. On testing the quality of drinking water of 3 million people in France, it was found that the quality of drinking water does not match up to the required quality recommended by WHO. It was uncovered that about 97% of the underground water samples do not satisfy the required level for nitrate (UN Water, 2009). In recent years, the concentration of dyes in the contaminated water might reach a level as high as 15% (Shamel, et al. 2016).

1.2 Kenaf

Kenaf is a member of the hibiscus family which it is related to cotton, hemp, and okra. Kenaf has a high growth rate, rising to heights of 12 to 18 feet's in about 4 to 5 months. Its yield of 6 to 10 tons and for new varieties may reach 12 tons of dry weight per acre per year. The Kenaf production in Malaysia is estimated between 3,000 tons to 10,000 tons kenaf fibre annually (Lansah at al., 2016). Which is most likely a native of Southern Asia, Kenaf is also cultivated in Bangladesh, Malaysia, Indonesia, South Africa, Thailand, Vietnam, parts of Africa, and to a small extent, in south-east Europe for its fibre(Wilson et al. 1965).

The key uses of kenaf fibre include the manufacturing of ropes, twines, and coarse clothes. Most of the kenaf fibres are used for animal bedding and feed (Webber, 1993). That could be used as thermal insulators or acoustic insulators for buildings or vehicles. These composites find their use in paper and garment industries due to their property of slow ignition (Rajappan et al., 2015).

1.3 Adsorption of pollutants by using kenaf fibre

Much attention has recently been focused on various biosorbent materials used as an adsorbent for the removal of dyes from aqueous solutions. Natural fibre has become apparently important as a source of adsorbent. Kenaf one of the best adsorbent was used to remove a lot of dyes and heavy metals. Table 1.1 illustrate kenaf core fibre as adsorbent.

Table 1.1 : Utilisation of kenaf core fibre as adsorbent

Material	References
Nickel	Annie et al., 2015
Fluoride	Yusof, 2015
Waxes	Wong, et al., 2013
Lead, Mercury, Copper, Zinc and Cadmium	Dinesh, 2009
Pb (II) and Cr (III) (cationic heavy metals)	Marcus, 2013
Copper (II)	Hasfalinaa et al., 2012

1.4 Problem statement

The extensive use of commercial activated carbon as an adsorbent for the purification of industrial effluent from textile industry is not economically feasible due its high operational cost. Hence, this research has been undertaken to explore the potential of certain agro based residues to produce suitable adsorbent, where the thermal activation process is omitted. (Koay et al., 2014).

Environmental pollution is one of the most significant problems of modern times. The contaminant water from the textile contains hazardous synthetic dyes (Lin et al., 2016). The release of synthetic dyes into water bodies after various industrial operations is unavoidable. This causes severe pollution problems for the environment.

The removal of synthetic colors from the wastewater is usually considered more necessary because it is the synthetic colors that damage the water environment and pose risks to human health (Sadaf et al. 2014). There are several methods of treatment; including chemical, physical and biological, chemical modification on biomass such as quaternisation to produce adsorbent is the solution to this problem.

Adsorption is considered to be the best method for removing dyes from solutions due to its simplicity of design, cost-effectiveness, high efficiency, high availability and its potential to separate a wide range of chemical compounds (Mashhadi et al., 2016). Kenaf is a widely cultivated crop, particularly in the tropics. Kenaf fibers have high mechanical strength high percentage of cellulose which makes it favorite for modified processing to producing adsorbent. Chemical modification of KCF is better than other adsorbents because it is prepared with a minimum of processing and without thermal treatment. Widely used to separate chemical compounds. High efficiency of adsorption

1.5 Objectives

This research is to utilise a locally obtainable material as adsorbent rather than commercial activated carbon for enhancing the quality of industrial effluent and offering further treatment before releasing into drains or other water or drains or for industrial and agricultural uses. The recommended adsorbent (agriculture harvests) is likely to be quite inexpensive in comparison to other materials like carbon. It is available in Malaysia and possibly less costly to prepare, and thus operating costs can be significantly controlled.

1. To prepare and characterise modified kenaf core fibres (MKCF) adsorbent by using a quaternisation agent (3-chloro-2-hydroxypropyl) trimethylammonium chloride (CHMAC)
2. To analyses the viability of using natural and modified kenaf core fibres by quaternisation as adsorbents to eliminate reactive orange 16 and acid red 114 dyes from aqueous solutions.
3. To study the adsorption isotherm and kinetics, by using batch analysis and fixed-bed column analysis.

1.6 Scope of work

In this study, an attempt was made to quaternizing kenaf core fibre and uses it as an adsorbent to adsorb RO16 and AR114 dyes from aqueous solution. The effect of MKCF, pH, dosage, contact time, temperature, speed and concentration studied in detail. In batch, the adsorption isotherm study by using Freundlich, Langmuir and Temkin kinetics studies by used Pseudo-first order, Pseudo-second-order dye and Intraparticle effective diffusivity were studied. In fixed bed column adsorption experiment Parameters: Effect of flow rate, height and concentration. The experimental data Analysis by using Thomas, Yoon-Nelson, and Adams-Bohart models.

1.7 Organisation of thesis

This thesis is made up of 5 chapters in Chapter 1, (Introduction) covers water pollution, textile dyes effluent, history of Kenaf, uses, Kenaf in Malaysia, problem statement, adsorption of pollutants by using kenaf fibre, objectives of the study, scope of this work, and organisation of the thesis. Chapter 2, (Literature Review)

encompasses the acid dye, reactive dye, textile dye effluent treatment. The batch study covers the Langmuir model, Freundlich model and Timkin model, as well as kinetic and intraparticle effective diffusivity. Column study encompasses the Yoon–Nelson method, Adams-Bohart method, and Thomas method. Chapter 3, (Materials and Methods), we have presented the comprehensive list of materials and methods used in our study. Chapter 4, (Results and Discussion), the results and the collected data have been analysed. Chapter 5, (Conclusion) concludes all the observations as well as offers recommendations for future studies.



REFERENCES

- Adamu, A., (2008). Adsorptive removal of reactive azo dyes using industrial residue. Addis Ababa University.
- Adriana, S., F., Leandro, S., O., Victor, F., O., Cibele C.O. A., (2014). Potential use of *crambe abyssinica* press cake as an adsorbent: batch and continuous studies Environmental, *Engineering and Management Journal*, 13: 12, 3025-3036.
- Adya, D., Susmita, M. and Vishal, Kr. V. (2016). Enhanced biodecolorization of textile dyes using an isolated bacterial strain *Bacillus pumilus* HKG212 under improved culture conditions. *J. Biochem Tech.*, 6(3): 962-969.
- Ahmada, M. A., Puada, N. A., Belloa, O. S. (2014). Kinetic equilibrium and thermodynamic studies of synthetic dye removal using pomegranate peel activated carbon prepared by microwave-induced KOH activation. *Water Resources and Industry*, 6: 18–35.
- Ahmad S., Ali A. and Ashfaq A. (2016). Heavy Metal Pollution, Sources, Toxic Effects and Techniques Adopted for Control. *International Journal of Current Research and Academic Review*, 4(6): 39-58.
- Ajay, K. A., Mahendra, S. K., Mahendra, S. K., Chandrashekhar, P. P., Ishwardas, L. M. (2015). Kinetics study on the adsorption of ni^{2+} ions onto fly ash. *Journal of Chemical Technology and Metallurgy*, 50(5): 601-605.
- Akar, T., Tosun, I., Kaynak, Z., Ozkara, E., Yeni, O., Sahin, E. N., et al. (2009). An attractive agro-industrial by-product in environmental cleanup: Dye biosorption potential of untreated olive pomace. *Journal of Hazardous Materials*, 166: 1217–1225.
- Allen, S., J., McKay, G., Khader, K., Y., H., (1989). Intra particle diffusion of a basic dye during adsorption onto sphagnum peat. *Environmental Pollution*, 56 (1): 39-50.
- Al-Degs, Y. S., El-Barghouthi, M. I., El-Sheikh, A. H., and Walker, G. M. (2008). Effect of solution pH, ionic strength, and temperature on adsorption behavior of reactive dyes on activated carbon. *J. Dyes and Pigments*, 77(1): 16-23
- Alex, S. (2016). Cutting out textile pollution. *Chemical and engineering news*, 93(41): 18-19.
- Annabel, F., João, C., Lurdes, C., Maria, J., P., Ana Lopes (2016). Electrochemical wastewater treatment: influence of the type of carbon and of nitrogen on the organic load removal, *Environmental Science and Pollution Research*, pp.: 1-10. DOI: 10.1007/s11356-016-6851-6.

- Annie, K., F., Thandapani, G., Thenmozhi, N., and Sudha, P., N., (2015). Adsorption study: Removal of nickel ions using Kenaf fibre/chitosan biosorbent, *Journal of Chemical and Pharmaceutical Research*, 7(5):410-422.
- Anirudhan, T. S., Unnithan, M. R., Divya, L., & Senan, P. (2007). Synthesis and characterization of polyacrylamide-grafted coconut coir pith having carboxylate functional group and adsorption ability for heavy metal ions. *Journal of Applied Polymer Science*, 104(6): 3670-3681.
- Arami M., Limaee, N. Y., Mahmoodia, N. M. (2008). Evaluation of the adsorption kinetics and equilibrium for the potential removal of acid dyes using a biosorbent. *Chemical Engineering Journal*. 139(1): 2-10.
- Arslan-Alaton, I., Alaton, I., (2007). Degradation of Xenobiotics Originating from the Textile Preparation, Dyeing, and Finishing Industry Using Ozonation and Advanced Oxidation, *Ecotoxicol. Environ. Saf.* 68 (1), 98–107.
- Azmier, A., M., Azreen A., P., N., Solomon, B., O., (2014). Kinetic equilibrium and thermodynamic studies of synthetic dye removal using pomegranate peel activated carbon prepared by microwave-induced KOH activation, *Water Resources and Industry*, 6: 18–35.
- Basha, S. A. and Rajaganesh, K. (2014). Microbial Bioremediation of Heavy Metals from Textile Industry Dye Effluents using Isolated Bacterial Strains. *Int. J. Curr. Microbiol. App.* 3(5): 785-794.
- Basil Wilson, Wadabagei, 12(1): 33-38.
- Bernama (2013). Government identifies six core strategic areas for kenaf industry. *The Sun Daily*. <http://www.thesundaily.my>.
- Bharathi, K., Ramesh, S (2013). Removal of dyes using agricultural waste as lowcost adsorbents: a review. *Applied Water Science*, 3: 773-790
- Bhatta, C. K. and Sarma A., (2003). Adsorption characteristics of the dye, Brilliant Green, on Neem leaf powder. *J. of Dyes and Pigments*. 57 (3): 211-222.
- Bhaumika, M., McCrindleb, R. I., Maitya, A., Agarwala, S., Gupta, V. K. (2016). Polyaniline nanofibers as highly effective re-usable adsorbent for removal of reactive black 5 from aqueous solutions. *Journal of Colloid and Interface Science*, 466: 442–451.
- Broto, C. Oei, Shariff I., Shaobin W., Ha M. A. (2009). Surfactant modified barley straw for removal of acid and reactive dyes from aqueous solution, *Bioresource Technology*, 100 (18): 4292–4295.
- Bouzaida, I., and Rammah, M. B. (2002). Adsorption of acid dyes on treated cotton in a continuous system. *Materials Science and Engineering*, C (21): 151–155.

- Brunauer, S., Emmett, P. H., and Teller, E., (1938). Adsorption of gases in multimolecular layers. *Journal of the American Chemical Society*. 60: 309-319.
- Brunauer, S., Deming, L. S., Deming, Edwards, W. Teller, E. (1940). *J. Am. Chem. Soc.*, 62 (7): 1723–1732.
- Brunauer, S. (1945). The Adsorption of Gases und Vapours. *Journal of Chemical Education*, 21 (1): 52.
- Chinta S.K. and Shrivastava V. K.,(2013). Technical facts and figures of reactive dyes used in Textiles, *I.J.E.M.S.*, 4 (3): 308-312.
- Copaciu, F., Coman V., Simedru, D., Beldean-Galea, S., Opreș, O., and Ristoiu, D. (2013a). Determination of two textile dyes in wastewater by solid phase extraction and liquid chromatography/electrospray ionization tandem mass spectrometry analysis. *Journal of Liquid Chromatography & Related Technologies*, 36(12): 1646–1660.
- Christie, J. M., (2007). Phototropin Blue-Light Receptors. *Annual Review of Plant Biology* (2007), 58: 21–45 removal of anions from aqueous solutions. *Chemical Engineering Journal*, 185–186(0): 274-284.
- Deshannavar, U.B., kalburgi, P.B. sangolli, S.I Shubham, S., and Snehal, C. (2016). Bengal Gram Seed Husk an Adsorbent for Removal of Reactive Blue 25 Dye from Aqueous Solution. *Asian Journal of Chemistry*, 28(5):1074-1078.
- Dempsey, J.M. (1975). *Fiber Crops*. The University Press of Florida. Gainesville, Florida. Pp: 203-304.
- Dongying, Hu, Peng, W., Qianyun, Ma, and Lijuan, W. (2016). Preparation of a cellulose-based adsorbent with covalently attached hydroxypropyl dodecyl dimethyl ammonium groups for the removal of C.I. Reactive Blue 21 dye from aqueous solution. *J. Desalination And Water Treatment*, 57(23): 14986-14996.
- Doble, B. W., Patel S., Wood, G. A., Kockeritz, L. K. and Woodgett, J. R. (2007). Functional redundancy of GSK-3 α and GSK-3 β in Wnt/ β -catenin signaling shown by using an allelic series of embryonic stem cell lines. *Dev. Cell*, 12: 957-971.
- Dolphen, R., Sakkayawong, N., Thiravetyan, P., Thiravetyan, W., (2007). Adsorption of Reactive Red 141 from wastewater onto modified chitin, *J. Hazard. Mater.* 145 250–255.
- Eduardo, M., Cuerda-Correa, A. M. G., (2008). Textural and morphology study of activated carbon fibers prepared from kenaf. *Microporous and Mesoporous Materials*, 111: 523-529.

- El-Ashtoukhy, E-S. Z., Mobarak, A. A. and Fouad, Y. O. (2016). Decolourization of Reactive Blue 19 Dye Effluents by Electrocoagulation in a Batch Recycle New Electrochemical Reactor. *International Journal of electrochemical science*, 11:1883 –1897.
- El-Ashtoukhy, E., S., Z., El-Taweel, Y., A., Abdelwahab, O., and Nassef, E. M. (2013). Treatment of petrochemical wastewater containing phenolic compounds by electrocoagulation using a fixed bed electrochemical reactor. *International Journal of Electrochemical Science* 8, 1534-1550.
- Elkady, M.F., Ibrahim, A.M., Abd El-Latif, M.M., (2011). Assessment of the adsorption kinetics, equilibrium and thermodynamic for the potential removal of reactive red dye using eggshell biocomposite beads, *Desalination*, 278: 412–423.
- Elsagha, A., Moradi O., Fakhrib A., Najafic F., Alizadehd R. and Haddadie V. (2014). Evaluation of the potential cationic dye removal using adsorption by graphene and carbon nanotubes as adsorbents surfaces, *Arabian Journal of Chemistry* <http://dx.doi.org/10.1016/j.arabjc.2013.11.013>.
- Engade, K. and Gupta, S. (2010). Decolorization of Textile Effluent by Immobilized *Aspergillus terreus*. *J. of Petroleum & Environmental Biotechnology*, 1(1):1-3.
- Epolito, W.J., Lee Y.H., Bottomley, L.A. and Pavlostathis, S.G. (2005). Characterization of the textile anthraquinone dye Reactive Blue 4. *Dyes and Pigments*. 67: 935-46.
- Faisal, Fa, Shariff, Ib., and Ha. Megat Ahmad, K., M., (2016). Adsorption of lead (II) onto organic acid modified rubber leaf powder: Batch and column studies, *Process Safety and Environmental Protection*, 100: 1–8.
- Faruq, G., Alamgir, M. A., Rahman, M. M., Motior, M. R., Zakaria, H. P. Marchalina, B. and Mohamed, N. A. (2013). morphological charecterization of kenaf (*hibiscus cannabinus l.*) in Malaysian tropical environment using multivariate analysis. *J. Anim. Plant Sci.* 23(1): 60-67.
- Field C. B., Campbell J. E., and Lobell D. B. (2008). Biomass energy: the scale of the potential resource. *Trends in Ecology & Evolution*, 23(2): 65–72.
- Foo, K.Y., Hameed B.H. (2010). Insights into the modeling of adsorption isotherm systems. *Chemical Engineering Journal*, 156: 2–10.
- Franciele, R. F., Laís, G. de M. da S., Ayres, F. M., Antônio, A. U. de S., Selene, M. A. Guelli U. de S. (2010). Removal of reactive dyes from aqueous solutions using combined coagulation/flocculation and adsorption on activated carbon, Resources. *Conservation and Recycling*, 54(5): 283–290.
- Freundlich, H.M.F. (1906). Uber die adsorption in losungen, *Zeitschrift fur Physikalische. Chemie-Leipzig*, 57(A): 385-470.

- Garg, V. K., and Kaushik, P. (2008). Influence of textile mill wastewater irrigation on the growth of sorghum cultivars. *Applied Ecology and Environmental Research*, 6(1):1–12.
- Gerald Booth (2000). *Dyes, General Survey*. Wiley VCH. doi:10.1002/14356007.a09_073.
- Ghafari, B. and Khezri, S.M (2013). Evaluation of hydrophilic cotton processing wastewater treatment methods and giving the optimum method for it. *Arabian Journal of Geosciences*, 6(8): 2991–2995. DOI 10.1007/s12517-012-0554-1.
- Ghasemi, M., Keshtkar, A.R., Dabbagh, R., Jaber, S. S. (2011). Biosorption of uranium (VI) from aqueous solutions by Ca-pretreated *Cystoseira indica* alga: breakthrough curves studies and modeling. *J. of Hazardous Materials*, 189(1-2): 141-149. doi:10.1016/j.jhazmat.2011.02.011.
- Gimbert F., Morin-Crini N., Renault F., Badot P. M., and Crini G. (2008). Adsorption isotherm models for dye removal by cationized starch-based material in a single component system: Error analysis. *Journal of Hazardous Materials*, 157(1): 34-46.
- Gong, R., Zhu, S., Zhanga, D., Chen, J., Ni, S., & Guan, R. (2008). Adsorption behavior of cationic dyes on citric acid esterifying wheat straw: kinetic and thermodynamic profile. *Desalination*, 230: 220–228.
- Gupta, V. K. Suhas, I. T, Agarwal, S., Singh, R., Chaudhry, M., Harit, A. and Kushwaha, S. (2016). Column operation studies for the removal of dyes and phenols using a low cost adsorbent. *Global Journal Environmental Science and Management*, 2(1): 1-10.
- Hakan, D., Cihan, G. (2016). Adsorption of copper (II) from aqueous solutions on activated carbon prepared from grape bagasse. *Journal of Cleaner Production*, 124: 103–1132.
- Hairul Nazirah Abdul Halim and Nur Suhaili Mohd Yatim, (2011). Removal of Acid Green 25 from Aqueous Solution using Coconut Husk as Adsorbent. *International Conference on Environment and Industrial Innovation IPCBEE*, 12: 268-272.
- Hasfalinaa, C., M., Maryama, R., Z., Luqmanb, C., A., Rashidc, M., (2012). Adsorption of Copper (II) From Aqueous Medium In Fixed-Bed Column By Kenaf Fibres International Conference on Chemistry and Chemical Process (ICCCP 2012), 3: 255–263, <http://dx.doi.org/10.1016/j.apcbee.2012.06.079>.
- Hao, S., Wen, J., Yu, X., & Chu, W. (2013). Effect of the surface oxygen groups on methane adsorption on coals. *Applied Surface Science*, 264(0): 433-442.

- Hoseinzadeh, Edris Mohammad-Reza Samarghandi, Gordon McKay, Naser Rahimi & Javad Jafari (2014). Removal of acid dyes from aqueous solution using potato peel waste biomass: a kinetic and equilibrium study. *Desalination and Water Treatment*, 52: 25-27, DOI: 10.1080/19443994.2013.81035521.
- Hussin Z. M., Talib, N., Hussin, N. M., Hanafiah, M. A. K. M., Khalir, W. K. A. W. M. (2015). Methylene Blue Adsorption onto NaOH Modified Durian Leaf Powder: Isotherm and Kinetic Studies. *American Journal of Environmental Engineering*, 5(3A): 38-43.
- Ho Y.S., McKay, G. (1999). Pseudo-second order model for sorption processes. *Process Biochemistry*, 34: 451–465.
- Ho Y.S. (2006). Review of second-order models for adsorption systems. *Journal of Hazardous Materials*, 136(3), 681–689.
- Ito, T., Adachi, Y., Yamanashi, Y., Shimada, Y., (2016). Long-term natural remediation process in textile dye-polluted river sediment driven by bacterial community changes, *Water Research*, doi: 10.1016/j.watres.2016.05.050. *International Journal of Chemical Engineering*.
- Idan, J., I., Siti, N., A., B., Md. J., Luqman C., A., and Thomas S., Y., C., (2017). Removal of Reactive Anionic Dyes from Binary Solutions by Adsorption onto Quaternized Kenaf Core Fiber, *International Journal of Chemical Engineering*, <https://doi.org/10.1155/2017/9792657>. Vol. 2017 ID 9792657, 13 pages.
- Idan, J., I., Luqman C., A., Siti, N., A., B., Md. J., and Thomas S., Y., C., (2017). Equilibrium, Kinetics and Thermodynamic Adsorption Studies of Acid dyes on Adsorbent Developed from Kenaf Core Fiber. *Adsorption Science and Technology*. Accepted.
- Iscen C. F., I. Kiran, and S. Ilhan (2007). Biosorption of Reactive Black 5 dye by *Penicillium restrictum*: the kinetic study. *Journal of Hazardous Materials*, 143(1-2): 335–340.
- Jagadeesan, V., Basha, Sardhar, S. J. and Josephraj, J. (2013). *Journal of Urban and Environmental Engineering (JUEE)*, 7(1): 30-47.
- Ka Fatemeh., Yo. Habibollah, Gh Ali Asghar., He. N. B., (2016). Thiol-incorporated activated carbon derived from Thiol-incorporated activated carbon derived from fir wood sawdust as an efficient adsorbent for the removal of mercury ion: Batch and fixed-bed column studies. *J. Process Safety and Environmental Protection*, 100(1): 22–35.
- Kayode, A. Ad., Olugbenga, S. B. (2015). Dye sequestration using agricultural wastes as adsorbents. *Water Resources and Industry*, 12(C): 8–24. Doi: 10.1016/j.wri.09.002.

- Kapil M., Charu P., savita D. (2015). Removal of acid blue-7 dye from aqueous solution using water hyacinth as a adsorbent : adsorption equilibrium isotherms, international. *journal of modern trends in engineering and research (ijmter)*,2(8): 2349–9745.
- Khattri, S.D. and Singh, M. K. (2009). Removal of malachite green from dye wastewater using neem sawdust by adsorption. *Journal of Hazardous Materials*, 167(1–3): 1089–1094.
- Koay, Y. S., Ahamad, I. S., Nourouzi, M. M., Abdullah, L. C., and Choong, T. S. Y.,(2014). Development of Novel Low-Cost Quaternized Adsorbent from Palm Oil Agriculture Waste for Reactive Dye Removal. *bio resources*, 9(1): 66-85.
- Kuo, C., Wu, C., Wu, J., (2008). Adsorption of direct dyes from aqueous solutions by carbon nanotubes: Determination of equilibrium, kinetics and thermodynamics parameters. *J Colloid Interface Sci.*, 327(4): 308–315
- Kumar K.V. and Sivanesan S. (2007). Sorption isotherm for safranin onto rice husk: comparison of linear and non-linear methods. *Dyes Pigments* 72: 130–133.
- Langmuir I. (1916). the Constitution and Fundamental Properties of Solids and Liquids. *Journal of American Chemical Society*. 38(33): 2221-2295.
- Lei Y., Lizhi Z., Rong W., Shuren C., ZhiLi D. (2016). A new integrated approach for dye removal from wastewater by polyoxometalates functionalized membranes. *Journal of Hazardous Materials*. <http://dx.doi.org/10.1016/j.jhazmat.09.027>.
- Liao, P., Zhan, Z., Dai, J., (2013). Adsorption of tetracycline and chloramphenicol in aqueous solutions by bamboo charcoal: a batch and fixed-bed column study. *Chem. Eng. J.*, 228: 496–505.
- Lijuan, W., Jian, Li, (2013). Adsorption of C.I, Reactive Red 228 dye from aqueous solution by modified cellulose from flax shive: kinetics, equilibrium, and thermodynamics. *Industrial Crops and Products*, 42(1): 153–158.
- Lima, A., C., A., Nascimento R. F., Francisco S. F., Filhob J. M., (2012). Modified coconut shell fibers: A green and economical sorbent for the removal of anions from aqueous solutions. *Chemical Engineering Journal*, 185–186: 274– 284.
- Lin, S. A., Cheu, P. L., and Chong, C. L. (2010). Effects of alkaline pre-impregnation and pulping on malaysia cultivated kenaf (*hibiscus cannabinus*). *Bio resources*, 5(3): 1446-1462.
- Lin, C. C, Lin Y, Ho J. M. (2016). Adsorption of Reactive Red 2 from aqueous solutions using Fe₃O₄ nanoparticles prepared by co-precipitation in a rotating packed bed. *Journal of Alloys and Compounds*, 666: 153-158. DOI: 10.1016/j.jallcom.2016.01.015.
- Mahapatra, N. N. (2016), textile dyes, India, Woodhead publishing India in textiles.

- Mahmoud, D. K. Salleh, M. A. M. Karim, W. A. W. A., Idris, A. and Abidin, Z. Z. (2012). Batch adsorption of basic dye using acid treated kenaf fibre char: equilibrium, kinetic and thermodynamic studies. *Chemical Engineering Journal*, 181-182: 449–457.
- Malaysian Investment Development Authority (MIDA), Malaysia –Investment Performance 2011, MIDA, Kuala Lumpur, Malaysia 2012. Department of Environment (DOE), Environmental Quality Report 2006–2010, Official Website of Department of Environment, Ministry of Natural Resources and, Environment, Malaysia 2010
- Malik, P. K., & Saha, S. K. (2003). Oxidation of direct dyes with hydrogen peroxide using ferrous ion as catalyst. *Separation and Purification Technology*, 31: 241– 250.
- Malkoc, E., Nuhoglu Y., (2006). Fixed bed studies for the sorption of chromium (VI) onto tea factory waste. *Chem. Eng. Sci.* 61: 4363–4372.
- Marcus, J., Awang, A., M., Y., Ong, S., Y., Lee, S., Y., and Yong, S., H., (2013). kenaf fibres (*hibiscus cannabinus*) as a potential low-cost adsorbent for wastewater treatment, *International Journal of Science, and Technology*, 2(5): 805 – 812
- Marilice, S. B., Guilherme L. D., Julio C.P. V., Silvio L.P. D., Eder, C. L. and Flavio, A. P. (2016). Giombo persimmon seed (GPS) an alternative adsorbent for the removal Toluidine Blue dye from aqueous solutions. *j. Desalination and Water Treatment*, 1-12.
- Marilice, S. B., Mariene, C. R., Guilherme, L. D., Eder, C. L., Silvio, L.P. D. & Flávio, A. P. (2014). *Punica granatum* husk (PGH), a powdered biowaste material for the adsorption of methylene blue dye from aqueous. *Journal Desalination and Water Treatment*, 57: 7.
- Maryam, G., Somaye, M. I, Hamedreza, J. and Gupta, V. K. (2016). Microwave-induced H₂SO₄ activation of activated carbon derived from rice agricultural wastes for sorption of methylene blue from aqueous solution. *Desalination and water treatment*, 57(44): 1-14.
- Merina Paul Das, R. Priyanka, A. M. Rafeequa Zaibunisa, K. Sivagami (2016). Eco Safe Textile Coloration Using Natural Dye, *International. Journal of Pharmaceutical Sciences Review and Research* 32(1): 163-166.
- Mashhadi, S., Hamedreza J., Ghasemi, M., Saleh, T. A., & Gupta, V. K. (2016). Microwave-induced H₂SO₄ activation of activated carbon derived from rice agricultural wastes for sorption of methylene blue from aqueous solution. *j. Desalination and Water Treatment*, 57(44): 21091-21104. DOI: 10.1080/19443994.2015.1119737.
- Miyaha, Y., Lahrichib, A., Idrissia, M., (2016). Removal of cationic dye –Methylene bleu– from aqueous solution by adsorption onto corn cob powder calcined, *J. Mater. Environ. Sci.* 7 (1) 96-104. ISSN: 2028-2508.

- Mohamed Sulyman (2014). Fixed-bed Column Packed with Low-Cost Spent Tea Leaves for the Removal of Crystal Violet from Aqueous Solution, 2014 *5th International Conference on Environmental Science and Technology*, 69(22): 110-118. DOI: 10.7763/IPCBE. 2014. V69. 22.
- Mohsen, N., luqman Ch. A., Thomas Sh. Y. Ch., (2014). Development novel low-cost quaternized adsorbent for palm oil agriculture waste for reactive dye removal. *J. bioresources*, 9(1): 66-85.
- Mohamed, O. A., and Youssouf, D. S. (2014). Waste Water Treatment in Chemical Industries: The Concept and Current Technologies. *Hydrology Current Research*, 5(1): 164. doi:10.4172/2157-7587.100016459.
- Mohamed, M. M. (2004). Acid dye removal: comparison of surfactant-modified mesoporous FSM-16 with activated carbon derived from rice husk. *Journal of Colloid and Interface Science*, 272: 28–34.
- Mohammad, R. S., Mansur, Z., Mohammad, N. S. author, Abdeltif A., Gholam H. S. and Saied B. (2012). Application of acidic treated pumice as an adsorbent for the removal of azo dye from aqueous solutions: kinetic, equilibrium and thermodynamic studies Iranian. *Journal of Environmental Health Science & Engineering*, 29: 9. DOI: 10.1186/1735-2746-9-9.
- Mousa, M. K., and Taha, A. H. (2015). Adsorption of Reactive Blue9 Dye onto Natural and Modified Wheat Straw, *J Chem Eng Process Technol*, 6: 6. <http://dx.doi.org/10.4172/2157-7048.10002602>
- Mustafa, C., (2016). Investigation of the factors affecting acid blue 256 adsorption from aqueous solutions onto red pine sawdust: equilibrium, kinetics, process design, and spectroscopic analysis. *Journal Desalination and Water Treatment*, 57: 12. <http://dx.doi.org/10.1080/19443994.2014.1003974>.
- Mylsamy, S., and Theivarasu, C. (2012). Adsorption of Reactive Dye Using Low Cost Adsorbent: Cocoa (Theobroma Cacao) Shell. *World Journal of Applied Environmental Chemistry*, 1(1): 22-29.
- Mylsamy S., and Theivarasu Ch., (2012). Adsorption of Reactive Dye Using Low Cost Adsorbent: Cocoa (Theobroma Cacao) Shell, *World Journal of Applied Environmental Chemistry*, 1(1): 22-29.
- Namasivayam, C., Kumar D. M., Selvi K., Begum R. A., Vanathi, T., and Yamuna, R.T. (2001). Waste coir pith-a potential biomass for the treatment of dyeing wastewaters. *Biomass and Bioenergy*, 21: 477–483.
- Nancy, E. D., Felipe J. C., Eduardo S., Margarita L., José A. L., & Refugio B. G., (2016). A mass transfer model for the fixed-bed adsorption of ferulic acid onto a polymeric resin: axial dispersion and intraparticle diffusion *Journal Environmental Technology*. 37(15): 1914-1922. DOI: 10.1080/09593330.2015.1135993

- Netpradit, S., Thiravetyan, P., & Towprayoon, S. (2003). Application of 'waste' metal hydroxide sludge for adsorption of azo reactive dyes. *Water Research*, 37: 763–772.
- Netpradit, S., Thiravetyan, P., & Towprayoon, S. (2004a). Adsorption of three azo reactive dyes by metal hydroxide sludge: Effect of temperature, pH, and electrolytes. *Journal of Colloid and Interface Science*, 270: 255–261.
- Nithyaa, K., Asha S., P., S., K., and Ramachandran, T., (2016). Biosorption of hexavalent chromium from aqueous solution using raw and acid-treated biosorbent prepared from Lantana camara fruit, *Desalination and Water Treatment*, DOI: 10.1080/194439941145605
- Nirmal, U., S., Lau, T., W., and Hashim, J., (2014) Interfacial Adhesion Characteristics of Kenaf Fibres Subjected to Different Polymer Matrices and Fibre Treatments, *Journal of Composites*, Vol. (2014). <http://dx.doi.org/10.1155/2014/350737>
- Nithyaa, K., A., S., Senthil P. K., and T. Ramachandran, (2016). Biosorption of hexavalent chromium from aqueous solution using raw and acid-treated biosorbent prepared from Lantana camara fruit, *Desalination and Water Treatment*, DOI: 10.1080/194439941145605
- Ofomaja, A. E., and Ho, Y. S., (2007). Equilibrium sorption of anionic dye from aqueous solution by palm kernel fibre as sorbent. *Dyes Pigments*, 74: 60-66.
- Orlando, U. S., Baes, A. U., Nishijima, W., & Okada, M. (2002). A new procedure to produce lignocellulosic anion exchangers from agricultural waste materials. *Bioresource Technology*, 83(3): 195-198
- Omidi-Khaniabadi, Y., Jafari, A., Nourmoradi, H., Taheri, F., Saeedi, S., (2015). Adsorption of 4-Chlorophenol from Aqueous Solution using Activated Carbon Synthesized from Aloe Vera Green Wastes. *J Adv Environ Health Res*, 3(2): 120-9.
- Opris, I., Santos, L. M., Song, D., Gerhardt, G. A., Berger, T. W., Hampson, R. E. and Sam, A. D. (2013). Prefrontal cortical microcircuits bind perception to executive control. *Sci. Rep.* 3: 2285. doi: 10.1038/srep02285.
- Osugi, M. E., Rajeshwar, K., Ferraz, E. R. A., de Oliveira, D. P., Araújo, Â. R., Zanoni, M.V. B. (2009). Comparison of oxidation efficiency of dispersed dyes by chemical and photoelectrocatalytic chlorination and removal of mutagenic activity. *Electrochim.* 54: 2086–2093.
- Osma, J. F. V. Saravia, J. L. Toca-Herrera, and S. R. Couto, (2007). Sunflower seed shells: A novel and effective low-cost adsorbent for the removal of the diazo dye Reactive Black 5 from aqueous solutions. *Journal of Hazardous Materials*, 147(3): 900–905.

- Parimalam, R., Raj V. and Sivakumar, P., (2011). Adsorption isotherms, kinetics, thermodynamics and desorption studies of reactive orange16 on activated carbon derived from, ARPN, *Journal of Engineering and Applied Sciences*, 6(11): 15-26.
- Perez-Valle, J., Rothe, J., Primo, C., Pastor, M. M., Ariño, J., Pascual-Ahuir, A., Mulet, J. M., Serrano, R. and Yenush, L. (2010). Hal4 and Hal5 protein kinases are required for general control of carbon and nitrogen uptake and metabolism. *Eukaryot Cell*, 9: 1881–90.
- Peng, L., Zhenxue, J., c, Min, Z., He, B., Lei C., (2016). Estimation of shale gas adsorption capacity of the Longmaxi Formation in the Upper Yangtze Platform, China, *Journal of Natural Gas Science and Engineering*, 34: 1034–1043. <http://dx.doi.org/10.1016/j.jngse.2016.07.052>.
- Piccin, J. S., Feris, L. A., Cooper, M., Gutterres, M. (2013). Dye Adsorption by Leather Waste: Mechanism Diffusion, Nature Studies, and Thermodynamic Data. *J. Chem. Eng. Data*, 58: 873-882.
- Rajappan, S., Paramadhayalan (2016). Testing and analysis of kenaf fiber reinforced polymer. *Journal of Chemical and Pharmaceutical Sciences*, (1): 153-156.
- Ramaraju, B., Reddy, P. M. K., Subrahmanyam, C., (2014). Low cost adsorbentsM from agricultural waste for removal of dyes, *Environ. Prog. Sustainable Energy*, 33(1): 38–46. doi:<http://dx.doi.org/10.1002/ep.11742>.
- Renata Č., Audronė G., Kristina A., Danutė K., Jūratė V. (2014). Efficiency of removal of anionic dye and copper(II) from aqueous solutions by activated carbon: effect of temperature and solution composition, *chemija*. 25(1): 5–12.
- Ricciardi, A., and J. B. Rasmussen, (1999). Extinction rates of North American freshwater fauna. *Conservation Biology*, 13:1220-1222.
- Robinson T., McMullan G., Marchant R., Nigam P. (2001). Remediation of dyes in textile effluent: a critical review on current treatment technologies with a proposed alternative. *J. Biores. Tech.*, 77 (3): 247-255.
- Sadafa, S., Bhattib, H. N., Nausheenb, S. and Aminb, M.,(2014). Application of a novel lignocellulosic biomaterial for the removal of Direct Yellow 50 dye from aqueous solution: Batch and column study. *Journal of the Taiwan Institute of Chemical Engineers*, 47(1): 160-170.
- Salman, J. M. Njoku, V. O., Hameed, B.H., (2011). Batch and fixed-bed adsorption of 2, 4-dichlorophenoxyacetic acid onto oil palm frond activated carbon. *Chem. Eng. J.*, 174: 33–40.
- Samantha S. A., Priti A. (2009). Application of natural dyes on textiles. *Indian journal fiber and textile research*, 34: 384-399.

- Samarghandi, M. R., Mansur, Z., Mohammad, N S., Abdeltif, A. , Gholam H. S., and Saied, B., (2012). Application of acidic treated pumice as an adsorbent for the removal of azo dye from aqueous solutions: kinetic, equilibrium and thermodynamic studies. *Iranian Journal of Environmental Health Sciences & Engineering*, 9: 9.
- Sanna, H., Amit, B., Mika S., (2016). A review on modification methods to cellulose-based adsorbents to improve adsorption capacity *Water Research*. 91: 156–173. <http://dx.doi.org/10.1016/j.watres.2016.01.008>.
- Senthilkumaar, S., Kalaamani, P., Porkodi, K., Varadarajan, P. R., & Subburaam, C. V. (2006). Adsorption of dissolved reactive red dye from aqueous phase onto activated carbon prepared from agricultural waste. *Bioresource Technology*, (97): 1618–1625.
- Shamel, A., Khoshraftar, Z., and Alayi, R., (2016). Adsorption of cationic dye from aqueous solution onto sea shell as adsorbent low-cost, Kinetic studies. *Der Pharma Chemica*, 8(5): 60-66.
- Shadeera, R., Nagapadma, M., (2015). Modeling of Fixed Bed Column Studies for Adsorption of Azo Dye on Chitosan Impregnated with a Cationic Surfactant, *International Journal of Scientific & Engineering Research*, 6(2): 530 - 538. <http://www.ijser.org>
- Shahid, M., Azeem K., Muhammad, A., Tariq, M.,, and David, E. C.,(2016). Detoxification of azo dyes by bacterial oxidoreductase enzymes, *Critical Reviews in Biotechnology*, 36(4): 1–13. DOI: 10.3109/07388551.2015.1004518
- Singh, V., A. K. Sharma, D. N. Tripathi, R. Sanghi. (2009). Poly(methylmethacrylate)grafted chitosan: An efficient adsorbent for anionic azo dyes. *J. Hazard. Mater.*,161: 955–966.
- Sirlei Rosa b, Mauro C.M. Laranjeira a, Humberto G. Riel a b, Valfredo T (2007). Favere a Cross-linked quaternary chitosan as an adsorbent for the removal of the reactive dye from aqueous solutions. *Journal of Hazardous Materials*, 155: 253–260.
- Sing, K., S., W., Everett, D., H., Haul, R., A., W., Moscou, L., Pierotti, R., A., Rouquerol, J., and Siemieniowska, T., (1985). Reporting physisorption data for gas/solid systems with special reference to the determination of surface area and porosity (recommendations 1984). *Pure Appl. Chem.* 57(4): 603–619. Doi: 10.1351/pac198557040603.
- Singh S., K., Dhruv, K., Dhruv, M., Dhruv S., (2015). 444Fixed Bed Column Study and Adsorption Modeling on the Adsorption of Malachite Green dye from wastewater using Acid Activated Sawdust, *International Journal of Advanced Research*, 3(7): 521-529.

- Slavik, I., Uhl, W., Börnickd, H., and Worchd, E., (2016). Assessment of SOC adsorption prediction in activated carbon filtration based on Freundlich coefficients calculated from compound properties, *RSC Advances*, 6: 19587-19604. DOI: 10.1039/C5RA21005D.
- Society of Dyers and Colourists (2006). Colour Index International, Fourth Edition Online. www.sdc.org.uk/wp-content/uploads/2013/02/CI_How2RegisterProducts.pdf. Retrieved on 2 December 2016.
- Soni, M., yadav, j. s., sharma, a. k. and srivastava, j. k. (2014). Parametric optimization for adsorption of reactive orange 16 on water hyacinth root powder, *Chemistry and Pharmaceutical Sciences*, 1 (6): 140-147
- Sohrabi, H., and Ameri, E., (2015). Adsorption equilibrium, kinetics, and thermodynamics assessment of the removal of the reactive red 141 dye using sesame waste, *Desalination and Water Treatment*, 1-12.
- Swain, S. K., Patnaik, T., Singh, V. K., Jha, U., Patel, R. K., and Dey, R. K. (2011). Kinetics, equilibrium and thermodynamic aspects of removal of fluoride from drinking water using meso-structured zirconium phosphate. *Chemical Engineering Journal*, 171(3): 1218–1226.
- Su, Y., Jiao, Y., and Dou, C., (2014). Biosorption of methyl orange from aqueous solutions using cationic surfactant-modified wheat straw in batch mode. *Desalination and Water Treatment*, 52: 6145-6155.
- Sunil, K. D., Sachin, A., M., Bhaskar D., K., (2016). Agro-industrial waste: a low cost adsorbent for effective removal of 4-chloro-2-methylphenoxyacetic acid herbicide in batch and packed bed modes, *Environmental Science and Pollution Research*, pp: 1-12, First online: 06 May.
- M.I. Tempkin, V. Pyzhev, Kinetics of ammonia synthesis on promoted iron catalyst, *Acta Phys. Chim. USSR* 12 (1940), 327–356.
- Tesfaye, T., and Semegn E., (2014). Study on effect of different parameters on adsorption efficiency of low cost activated orange peels for the removal of methylene blue dye, *International Journal of Innovation and Scientific Research*. 8 (1): 106-111. <http://www.ijisr.issr-journals.org>
- Tsai, W. T., Chang, C. Y., Lin, M. C., Chien, S. F., Sun, H. F., & Hsieh, M. F. (2001). Adsorption of acid dye onto activated carbons prepared from agricultural waste bagasse by ZnCl₂ activation. *Chemosphere*, 45: 51–58.
- Tseng, R., (2007). Physical and chemical properties and adsorption type of activated carbon prepared from plum kernels by NaOH activation. *Journal of Hazardous Materials*, 147, 1020–1027.
- Tsoumis, G., (1991). Science and Technology of Wood Structure Properties: *Utilization. van Hostrand Reinhold*. New York.

- UN WWAP, (2009). United Nations World Water Assessment Programme. The World Water Development Report 3: *Water in a Changing World*. UNESCO: Paris, France.
- Uzunova, S., Uzunov, I., and Angelova, D., (2013). Liquid-Phase sorption of oil by carbonized rice husks: impact of grain size distribution on grain size distribution on the sorption kinetics. *J. Chem. Technol. Metall.*, 48(5): 505–512.
- Vié, J. C., Hilton-Taylor, C. and Stuart, S.N. (eds.) (2009). *Wildlife in a Changing World – An Analysis of the 2008 IUCN Red List of Threatened Species*. Gland, Switzerland: IUCN. 180 pp. Available at. <http://data.iucn.org/dbtw-wpd/edocs/RL-2009-001.pdf>.
- Voller, V. R., and Prakash, C. (1987). A fixed grid numerical modelling methodology for convection-diffusion mushy region phase-change problems, *International Journal of Heat and Mass Transfer*, 30(8): 1709-1719.
- Yargıç, A., Ş., Şahin R. Z. Y., Özbay, N., and Önal, E., (2013). The Effect of Different Operating Conditions on Removal of Reactive Dye by Green Carbon Adsorption, Digital Proceeding of, *THE ICOEST*, Cappadocia.
- Wang, L., & Li, J., (2013). Adsorption of C.I. Reactive Red 228 dye from aqueous solution by modified cellulose from flax shive: Kinetics, equilibrium, and thermodynamics. *Industrial Crops and Products*, 42(0): 153-158.
- Wang, Y., (2008). cellulose fiber dissolution in sodium hydroxide solution at low temperature: dissolution kinetics and solubility improvement, PhD thesis, Georgia Institute of Technology.
- Weber, W. J. and Morris, J., C., (1962). Advances in water pollution research: removal of biologically resistant pollutant from waste water by adsorption. *International Conference on Water Pollution Symposium*, 2: 231-266.
- Wen, T., Zhao, Z., Shen, C., Li, J., Tan, X., Zeb, A., Xu, A., W., (2016). Multifunctional flexible free-standing titanate nanobelt membranes as efficient sorbents for the removal of radioactive $^{90}\text{Sr}^{2+}$ and $^{137}\text{Cs}^{+}$ ions and oils. *Scientific Reports*, 6, 20920. <http://doi.org/10.1038/srep20920>
- Wong, S., Y., Tan, Y., P., Abdullah, A., H., and Ong, S., T., (2009). Removal of basic blue 3 and reactive orange 16 by adsorption onto quarternized sugar cane bagasse. *The Malaysian Journal of Analytical Sciences*, 13 (2): 185 – 193.
- Wong, Y., C., Lim, S., H., and Atiqah, N., A., (2013). Remediation of industry wastewater effluent by using kenaf as waxes absorbent, *present environment and sustainable development*, 7(1):290-295.

- World Bank, 2015. World Bank East Asia and Pacific Economic Update, April 2015: 491 Adjusting to a changing world; The World Bank. 15 Yean L. Pang, Ahmad Z. Abdullah, Current Status of Textile Industry Wastewater Management and Research Progress in Malaysia: Clean – Soil, Air, Water 2013, 41 (8), 751–764
- Yuh-Shan, H., (2006). Review of second-order models for adsorption systems, *J. Hazard. Mater.* 136; 681–689.
- Yun, L., Jun, L., Yanzhuo, Z., Xiujie, W., and Zhaoming, Z., (2016). Capability of Ammonium Adsorption by Anaerobic Ammonia Oxidation Granular Sludge, *J. Water Air Soil Pollut*, 227: 262. Doi: 10.1007/s11270-016-2965-1.
- Yusof, S., R., M., Zahri, N., A., M., Koay, Y., S., Nourouzi, m., m., Chuah, L., A., Choong, T., S., Y., (2015). Removal of fluoride using modified kenaf as adsorbent. *Journal of engineering science and technology*, 4(1): 11–22.
- Zawani Z., Abdullah, L. C., Abdan K. (2015). Characterization of Kenaf Fibre-Retting Wastewater. *International Journal of Science and Research (IJSR)*, 4(6): 314-317. www.ijsr.net.
- Zaini, N. and Khairul, S. N., K., (2014). Adsorption of Carbon Dioxide on Monoethanolamine (MEA)–Impregnated Kenaf Core Fiber by Pressure Swing Adsorption System (PSA), *Jurnal Teknologi (Sciences & Engineering)* 68(5): 11–16.
- Zollinger, H., (1991). Colour Chemistry Synthesis Properties and Application of Organic. *Dyes and Pigments*, VCH New York, 92-102.
- Zongping, W., Miaomiao, X., Kai H. and Zizheng, L. (2011). Textile Dyeing Wastewater Treatment. *Advances in Treating Textile Effluent*. Textile Dyeing Wastewater Treatment, ISBN: 978-953-307-704-8, InTech, Available from: <http://www.intechopen.com/books/advances-in-treating-textile-effluent/textile-dyeing-wastewatertreatment>.
- Zulfadhly, Z., Mashitah, M. D., and Bhatia, S., (2001). Heavy metals removal in fixed-bed column by the macro fungus *Pycnoporus sanguineus*, *Environ. Pollut.*, 112(3): 463–470
- Zurhana, M., H., Norziyanti, T., Noraini, M., H., Megat, A., K., M., H., Wan, K., A., W., M., K., (2015). Methylene Blue Adsorption onto NaOH Modified Durian Leaf Powder: Isotherm and Kinetic Studies, *American Journal of Environmental Engineering*. 5(3A): 38-43. DOI: 10.5923/c.ajee.201501.07