



UWS Academic Portal

Validation of a density separation technique for the recovery of microplastic and its use on marine & freshwater sediments

Quinn, Brian; Murphy, Fionn; Ewins, Ciaran

Published in: MICRO 2016: Fate and Impact of Microplastics in Marine Ecosystems

DOI: 10.1016/B978-0-12-812271-6.00008-9

Published: 01/12/2016

Link to publication on the UWS Academic Portal

Citation for published version (APA):

Quinn, B., Murphy, F., & Ewins, C. (2016). Validation of a density separation technique for the recovery of microplastic and its use on marine & freshwater sediments. In J. Baztan, B. Jorgensen, S. Pahl, R. Thompson, & J-P. Vanderlinden (Eds.), MICRO 2016: Fate and Impact of Microplastics in Marine Ecosystems: From the Coastline to the Open Sea (pp. 9). Elsevier Limited. https://doi.org/10.1016/B978-0-12-812271-6.00008-9

General rights

Copyright and moral rights for the publications made accessible in the UWS Academic Portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

If you believe that this document breaches copyright please contact pure@uws.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.

VALIDATION OF A DENSITY SEPARATION TECHNIQUE FOR THE RECOVERY OF MICROPLASTIC AND ITS USE ON MARINE & FRESHWATER SEDIMENTS.

MICRO2016, LANZAROTE

Brian Quinn, Fionn Murphy & Ciaran Ewins

Institute of Biomedical & Environmental Health Research (IBEHR), University of the West of Scotland, Paisley, Scotland. Email: brian.guinn@uws.ac.uk





Density Separation Validation

- Claessens et al., (2013) protocol (3:1)
- Brine solutions (4) & water
- Sediment (200-400 μm)
- MP size classes (200-600 μm)
- Different plastic types
- N=9, individually & mixture

Densities of Saturated Brines Solutions			
Solution	Density (g/cm ⁻³)		
water	1.0032		
NaCl	1.1708		
NaBr	1.37		
NaI	1.566		
ZnBr2 (25%)	1.71		
ZnBr2	4.2		

Plastics in validation test			
Plastic	Source	Density (g/cm-3)	
High density Polyethelene (HDPE)	Air waves base	0.941 g/cm ³ .	Construction of the other states and the states
High density Polyethelene (HDPE)	Milk carton	0.941 g/cm ³ .	
Low density Polyethelene (LDPE)	Air waves lid	0.915–0.925 g/cm ³	
Nylon	Thread	1.13-1.15g/cm3	
Polyethelene (PE)	Supermarket bag	0.926–0.940 g/cm ³ .	
Polyethelene terephthalate (PET)	Lucozade bottle	1.38 g/cm ³	
Polypropylene (PP)	Plastic container	0.855 -0.946g/cm3	
Polystyrene (PS)	Coffee lid	0.946 g/cm3	
Polystyrene (PS)	Plastic forks	0.946 g/cm3	
Polyvinyl chloride (PVC) Un Plasticised	Window frame	1.35-1.45 g/cm3.	UNIVERSITY OF TH WEST of SCOTLAN
Polyvinyl chloride (PVC) Plasticised	Wire	1.35-1.45 g/cm3.	INV
polyethylene (180µm)	sigma bottle	0.926–0.940 g/cm ³ .	

(Claessens et al., 2013. Mar. Pollut. Bull. 70(2): 227-233)

Validation results (n=9)



UNIVERSITY OF THE WEST of SCOTLAND

Results: Validation Experiment



Results: Environmental Samples



Freshwater MP / M³



Conclusion

- There are more efficient density solutions out there...
 ZnBr₂ is one of them.
- 1 MP extraction efficiency, 4 time
- Expensive to buy, but overall (including labour) cheaper

Other work...

• Scottish Microplastic Research Group -

http://www.masts.ac.uk/research/masts-community-projects/scottish-microplastic-research-group/

pubs.acs.org/est

- Fionn Murphy Xlf (Thursday)
- Christopher Crawford 1a





3 Fionn Murphy,*^{,†} Ciaran Ewins,[‡] Frederic Carbonnier,[§] and Brian Quinn[†]

⁴[†]Institute of Biomedical and Environmental Health Research (IBEHR), University of the West of Scotland, Paisley PA1 2BE, Scotland s [‡]University of the West of Scotland, Paisley PA1 2BE, Scotland

⁶ [§]Saur Glasgow, Beardmore Street, Dalmuir, Glasgow G81 4SA, Scotland

7 Supporting Information

ABSTRACT: Municipal effluent discharged from wastewater treatment works (WwTW) is suspected to be a significant contributor of microplastics (MP) to the environment as many personal care products contain plastic microbeads. A secondary WwTW (population equivalent 650 000) was sampled for microplastics at different stages of the treatment process to ascertain at what stage in the treatment process the MP are being removed. The influent contained on average 15.70 (±5.23) MP.L⁻¹. This was reduced to 0.25 (±0.04) MP.L⁻¹ in the final effluent, a decrease of 98.41%. Despite this large reduction we calculate that this WwTW is releasing 65 million microplastics into the receiving water every day. A significant proportion of the microplastic accumulated in and was a removed during the grease removal stage (19.67 (±4.51)



MP/2.5 g), it was only in the grease that the much publicised microbeads were found. This study shows that despite the efficient removal rates of MP achieved by this modem treatment plant when dealing with such a large volume of effluent even a modest amount of microplastics being released per liter of effluent could result in significant amounts of microplastics entering the environment. This is the first study to describe in detail the fate of microplastics during the wastewater treatment process.

