

## Robust Ni/Dendritic fibrous SBA-15 (Ni/DFSBA-15) for methane dry reforming: Effect of Ni loadings

C. C. Chong<sup>a</sup>, S. N. Bukhari<sup>a</sup>, Y. W. Cheng<sup>a</sup>, H. D. Setiabudi<sup>a, b</sup>, A. A. Jalil<sup>cd</sup>, C. Phalakornkule<sup>ef</sup>

<sup>a</sup>Faculty of Chemical and Natural Resources Engineering, Universiti Malaysia Pahang, 26300, Gambang, Kuantan, Pahang, Malaysia

<sup>b</sup>Centre of Excellence for Advanced Research in Fluid Flow, Universiti Malaysia Pahang, 26300, Gambang, Kuantan, Pahang, Malaysia

<sup>c</sup>School of Chemical and Energy Engineering, Faculty of Engineering, Universiti Teknologi Malaysia, 81310, UTM, Johor Bahru, Johor, Malaysia

<sup>d</sup>Centre of Hydrogen Energy, Institute of Future Energy, Universiti Teknologi Malaysia, 81310, UTM, Johor Bahru, Johor, Malaysia

<sup>e</sup>Research and Technology Center for Renewable Products and Energy, King Mongkut's University of Technology North Bangkok, Bangkok, 10800, Thailand

<sup>f</sup>Department of Chemical Engineering, King Mongkut's University of Technology North Bangkok, Bangkok, 10800, Thailand

### ABSTRACT

A series of spherical mesoporous Ni/Dendritic Fibrous SBA-15 (Ni/DFSBA-15) catalysts with different Ni loadings (3–15 wt.%) were successfully synthesized and catalytically investigated by methane dry reforming. The XRD and Raman analyses indicated the structural stability of DFSBA-15 regardless of the Ni loading quantity, and the NiO nanocrystalline size increased with increasing Ni loading. The BET analysis showed the surface area of the catalysts decreased upon increment in Ni loading. Meanwhile, the TEM images revealed the distribution of Ni particles over the spherical shape DFSBA-15, with the most homogeneous dispersion was shown by 10Ni/DFSBA15, while Ni agglomeration was observed for 15Ni/DFSBA-15. The optimal catalytic performance and stability was achieved by 10Ni/DFSBA-15 ( $\eta = 93.11\%$ ,  $\eta = 91.76\%$ ,  $\eta = 91.77\%$ ,  $Y_{CO} = 96.35\%$ ,  $S_{CO} = 48.89\%$ ,  $\eta = 46.57\%$  and  $H_2/CO = 0.95$ ) with no sign of deactivation was observed for 30 h time-on-stream, in agreement with the XRD, XPS, and TGA analyses of spent catalysts. The superior catalytic performance by 10Ni/DFSBA-15 could be credited to its strong Si-O-Ni interaction, moderate NiO crystallite size, and homogeneous active metal dispersion. The favorable properties of 10Ni/DFSBA-15 led to a strong synergistic effect between Ni active metal sites and the DFSBA-15 support and thus enhanced the reactivity between two gaseous reactants, CH<sub>4</sub> and CO<sub>2</sub>. The 10 wt.% Ni loading was certified as optimal Ni content to sufficiently suppress the coke deposition on the DFSBA-15 and thus enhance the catalytic activity and stability

**KEYWORDS**

Dendritic Fibrous SBA-15; Ni loadings; metal distribution; methane dry reforming

**DOI:** <https://doi.org/10.1016/j.apcata.2019.117174>

**ACKNOWLEDGEMENT**

This work was financially supported by Universiti Malaysia Pahang (UMP) through Research University Grant ([RDU1803174](#)). Our gratitude also goes to Universiti Malaysia Pahang for the scholarship of Doctoral Research Scheme (C.C. Chong).

## **ACKNOWLEDGMENT**

The authors would like to thank the Faculty of Engineering and Surveying and the Centre of Excellence in Engineered Fibre Composites, University of Southern Queensland for providing laboratory facilities and financial support. They would also like to thank the interdisciplinary Photonics Laboratories (iPL), the University of Sydney for their support in fabricating the NIR FBGs. Finally, special thanks to Universiti Malaysia Pahang together with the Ministry of Higher Education, Malaysia for scholarship support.