## State of the Art in the Optimisation of Wind Turbine Performance Using CFD

Shourangiz-Haghighi, A., Haghnegahdar, M. A., Wang, L., Mussetta, M., Kolios, A. & Lander, M.

Author post-print (accepted) deposited by Coventry University's Repository

**Original citation & hyperlink:** 

Shourangiz-Haghighi, A, Haghnegahdar, MA, Wang, L, Mussetta, M, Kolios, A & Lander, M 2019, 'State of the Art in the Optimisation of Wind Turbine Performance Using CFD', Archives of Computational Methods in Engineering, vol. (In-Press), pp. (In-Press).

https://dx.doi.org/10.1007/s11831-019-09316-0

DOI 10.1007/s11831-019-09316-0 ISSN 1134-3060 ESSN 1886-1784

**Publisher: Springer** 

# *The final publication is available at Springer via http://dx.doi.org/s11831-019-09316-0*

Copyright © and Moral Rights are retained by the author(s) and/ or other copyright owners. A copy can be downloaded for personal non-commercial research or study, without prior permission or charge. This item cannot be reproduced or quoted extensively from without first obtaining permission in writing from the copyright holder(s). The content must not be changed in any way or sold commercially in any format or medium without the formal permission of the copyright holders.

This document is the author's post-print version, incorporating any revisions agreed during the peer-review process. Some differences between the published version and this version may remain and you are advised to consult the published version if you wish to cite from it.

## Archives of Computational Methods in Engineering State of the art in the optimisation of wind turbine performance using CFD --Manuscript Draft--

Manuscript Number:	ARCO-D-18-00267
Full Title:	State of the art in the optimisation of wind turbine performance using CFD
Article Type:	Original Paper
Funding Information:	
Abstract:	Wind energy has received increasing attention in recent years due to its sustainability and geographically wide availability. The efficiency of wind energy utilisation highly depends on the performance of wind turbines, which convert the kinetic energy in wind into electrical energy. In order to optimise wind turbine performance and reduce the cost of next-generation wind turbines, it is crucial to have a view of the state of the art in the key aspects on the performance optimisation of wind turbines using CFD (Computational Fluid Dynamics), which has attracted enormous interest in the development of next-generation wind turbines in recent years. This paper presents a comprehensive review of the state-of-the-art progress on optimisation of wind turbine performance using CFD, reviewing the objective functions to judge the performance of wind turbine, CFD approaches applied in the simulation of wind turbines and optimisation algorithms for wind turbine performance. This paper has been written for both researchers new to this research area by summarising underlying theory whilst presenting a comprehensive review on the up-to-date studies, and experts in the field of study by collecting a comprehensive list of related references where the details of computational methods that have been employed lately can be obtained.
Corresponding Author:	Alireza Shourangiz Haghighi Shiraz University of Technology IRAN, ISLAMIC REPUBLIC OF
Corresponding Author Secondary Information:	
Corresponding Author's Institution:	Shiraz University of Technology
Corresponding Author's Secondary Institution:	
First Author:	Alireza Shourangiz Haghighi
First Author Secondary Information:	
Order of Authors:	Alireza Shourangiz Haghighi
	Mohammad Amin Haghnegahdar
	Lin Wang
	Marco Mussetta
	Athanasios Kolios
	Martin Lander
Order of Authors Secondary Information:	
Author Comments:	This paper practically reviewed CFD (Computational Fluid Dynamics) modelling and its application on the performance optimisation of WTs (wind turbines) for the first time. This paper has been written for both researchers new to this research area by summarising underlying theory whilst presenting a comprehensive review on the up-to-date studies, and experts in the field of study by collecting a comprehensive list of related references where the details of computational methods that have been employed lately can be obtained which resulted in prospecting of high citations.

# State of the art in the optimisation of wind turbine performance using CFD

Alireza Shourangiz Haghighi<sup>1,\*</sup>, Mohammad Amin Haghnegahdar<sup>2</sup>, Lin Wang<sup>3</sup>, Marco Mussetta<sup>4</sup>, Athanasios Kolios<sup>5,6</sup>, Martin Lander<sup>5</sup>

<sup>1</sup>Department of Mechanical and Aerospace Engineering, Shiraz University of Technology, Shiraz, Modarres Boulevard 13876-71557, Iran

<sup>2</sup>Department of Mechanical and Materials Engineering, Queen's University, Kingston (ON) K7L 3N6, Canada

<sup>3</sup>School of Mechanical, Aerospace and Automotive Engineering, Coventry University, Coventry, CV1 5FB,

United Kingdom

<sup>4</sup>Dipartimento di Energia, Politecnico di Milano, via La Masa 34, 20156 Milano, Italy

<sup>5</sup> Centre for Offshore Renewable Energy Engineering School of Water, Energy and Environment, Cranfield University, Cranfield, MK43 0AL, United Kingdom

<sup>6</sup> Department of Naval Architecture, Ocean & Marine Engineering, University of Strathclyde, Henry Dyer Building, 100 Montrose Street, Glasgow G4 0LZ, United Kingdom

## Abstract

Wind energy has received increasing attention in recent years due to its sustainability and geographically wide availability. The efficiency of wind energy utilisation highly depends on the performance of wind turbines, which convert the kinetic energy in wind into electrical energy. In order to optimise wind turbine performance and reduce the cost of next-generation wind turbines, it is crucial to have a view of the state of the art in the key aspects on the performance optimisation of wind turbines using CFD (Computational Fluid Dynamics), which has attracted enormous interest in the development of next-generation wind turbines in recent years. This paper presents a comprehensive review of the state-of-the-art progress on optimisation of wind turbine, CFD approaches applied in the simulation of wind turbines and optimisation algorithms for wind turbine performance. This paper has been written for both researchers new to this research area by summarising underlying theory whilst presenting a comprehensive review on the up-to-date studies, and experts in the field of study by collecting a comprehensive list of related references where the details of computational methods that have been employed lately can be obtained.

Keywords: Wind energy, Wind turbine, Optimisation, Computational Fluid Dynamics (CFD), Optimisation algorithm, Objective function

## **1. Introduction**

The rapid consumption of energy over the past two decades, especially in developing countries, has rapidly increased the depletion of traditional fossil fuel resources and caused significant environmental pollutions. Therefore, in recent years, significant efforts have been devoted to replace traditional fossil fuels with clean renewable energies. Wind energy, a very important branch of clean energy, has gained remarkable attention due to its geographically wide availability and zero pollution [1, 2]. Unlike traditional fossil fuels, the reserve of wind energy is principally endless. A major utilisation of wind energy is by WT (Wind Turbine), a type of device that directly converts the kinetic energy of wind into controllable power such as electricity through the wind-turbine interactions [3]. To this end, the efficiency of wind energy utilisation is highly dependent on the performance of the WT, which should be optimised for maximum wind energy conversion.

The working principle of WTs can be generally described as follows. Driven by the pressure gradient and viscous boundary layer, WT blades are forced by the air to move continuously and part of wind kinetic energy is then converted into the mechanical energy of the turbine [4]. With such produced mechanical energy, WT can generate controllable energies. Thus, the performance of a WT is mainly related to the fluid-structure interactions, which are largely affected by the geometry and materials of the WT [5]. A WT with better geometry and lighter but strong enough materials can convert a greater percentage of wind kinetic into mechanical energy and therefore reduce the unit price of wind power.

The fluid-structure interactions between the wind and the turbine are rather complex, usually involving the complicated inertial movement of the turbine [6,7], turbulent air flow around the turbine [8] and sometimes even gas compressibility [9, 10], which poses great challenges to theoretical studies. Therefore, experimental testing and numerical simulation have been extensively applied to the investigation of the performance optimisation of WTs. In the early stage of performance optimisation of WTs, restricted by the computational resources and theoretical development, most scientific studies and practical exploration of performance optimisation for WTs were conducted by experiments through the trial-and-error approach [11-13]. However, such optimisation strategy is highly time-consuming and costly. With the growth in turbine size, the experimental approach becomes increasingly unaffordable. With the rapid development of computer hardware and numerical algorithms in recent years, numerical simulation has become dominant in the performance optimisation for WTs, which reduces the development cycle significantly [14].

Several numerical approaches have been applied to the performance optimisation of WTs, such as BEM (Blade Element Momentum) [12-14] and CFD (Computational Fluid Dynamics) [15]. BEM is fast in predicting aerodynamic performance and characteristics; however, its results highly depend on the accuracy of the 2D airfoil aerodynamic data, which are difficult to obtain in some cases. CFD is a numerical method that virtually obtains the flow field around the turbine, and it is capable of providing detailed information on air flow and forces on the turbine, making it a valuable tool to predict the aerodynamic performance of WT blades and visualise the flow fields around the blades. CFD has also been deemed as a promising tool to optimize turbine performance accurately due to its high fidelity [16]. A considerable amount of studies and

applications have been dedicated to the performance optimisation of WTs using CFD [17]. Thus, it is highly necessary to review the state-of-the-art progress in this area and point out possible future directions.

Due to the complex aerodynamic shape of WT blades and the rotation of the blades, CFD modelling of WTs is quite challenging and needs special considerations. In general, there are two main approaches to model the rotation of WT blades in CFD, i.e. reference frame [18] and dynamic mesh [19]. In the reference frame scheme, WT blades and pre-generated mesh across the flow field do not move and the flow of the air is transferred to the turbine referenced coordinate [14, 20]. Due to its relatively simple numerical treatment and low computational requirement, the reference frame approach has been widely used in the CFD modelling of WTs [21-23]. However, such approach can only be applied to steady state, and the transient movement of the blades due to the simultaneous change of air condition can be accurately captured, is deemed more accurate for modelling the transient movement of the blades. The trade-off of the dynamic mesh is its highly computational expenses, as the computational mesh needs to be re-generated at every time step [24, 25]. In this paper, a detailed summary of these two CFD approaches for modelling WTs is presented, and the difference, advantages and disadvantages, experimental validation and other aspects are discussed.

So far few review papers regarding this exciting topic are published. Bai and Wang [14] investigated experimental methods and numerical approaches for estimating aerodynamic performance (such as BEM, Enhanced BEM and CFD) for HAWTs (Horizontal Axis Wind Turbines). Bhutta group [26] reviewed several configuration and design methods of VAWTs (Vertical Axis Wind Turbines). Akwa et al. [27] presented a review on the performance of Savonius WTs. However, the CFD-based performance optimisation of WTs is not covered by these papers. To advance the progress on the improvement of WT performance, it is crucial to have a view of recent development in this field. Therefore, in this paper, a comprehensive review on CFD-based performance optimisation of WTs is presented.

This paper is structured as follows. Section 2 reviews the CFD modelling of WTs, including the geometry, meshes, boundary conditions, turbulence model, discretization method and treatment of blade rotation used in the CFD modelling as well as the latest application of CFD on WTs. Sections 3 and 4 review the objective functions and algorithms used in the optimisation of WTs, respectively. Section 5 reviews the up-to-date activities on CFD-based performance optimisation of WTs. Section 6 presents a critical discussion of perspectives for future studies in performance optimisation of WTs using CFD, followed by conclusions in Section 7.

## 2. CFD (Computational Fluid Dynamics) modelling

Due to the advancement of computing resources, CFD has been receiving extensive attention in recent years. CFD is a promising and valuable tool for simulating the aerodynamic characteristics of WT blades and visualising flow fields as well as testing new designs. It provides the flow motion around the blades through solving both continuity and momentum (Navier-Stokes) equations [28-33].

Having identified the problem to solve, there are three main steps in the CFD modelling, i.e. pre-processing, solving and post-processing, as depicted in Fig.1.



Figure 1. Main steps in CFD modelling

The pre-processing stage includes geometry creation, mesh generation, physics definition and solver settings. At the solving stage, Navier-Stokes equations are generally solved with some turbulence modelling to take into account the effects of turbulence. The post-processing stage is used for examining the results with various techniques, such as contour plots, streamlines and vector plots [34-40].

## 2.1. Geometry

To perform CFD modelling of WT blades, the blade geometry needs to be exactly described in a digitised format. WT blades generally have complex geometric shapes with varied spanwise cross-sectional information, i.e. airfoil shape, twist angle and chord distributions. WT blade geometry is generally constructed using CAD (Computer Aided Design) software, such as CATIA [41, 42] and SolidWorks [43, 44].

## 2.2. Mesh

Meshing is a critical part of the CFD modelling and has significant impact on the computational time. It is quite challenging to generate an appropriate mesh for the CFD modelling of WTs due to the complex aerodynamic shape of WT blades. The types of CFD meshes can be roughly categorized into three groups, i.e. structured, unstructured and hybrid meshes.

#### 2.2.1. Structured mesh

In the structured mesh, connection of grids is regular and abutting elements are in particular order. The rectangular and hexahedral grids are typical 2D and 3D structured mesh, respectively, and an example of 2D structured mesh is depicted in Fig. 2 [45]. Structured mesh has advantages in high resolution, easy convergence and low memory usage; however, it is time-consuming and difficult to generate in cases of sophisticated geometries, e.g. highly twisted blades.



Figure 2. Structured mesh (Reproduced from Ref. [45])

#### 2.2.2. Unstructured Meshes

Unstructured mesh refers to the mesh in which the connection of adjacent grids is irregular, and an example of unstructured mesh used in the CFD modelling of WTs is depicted in Fig. 3 [46]. The main advantage of unstructured mesh is its ease of mesh generation for sophisticated geometry; however, it consumes more computational time, as it generally results in higher cell count than structured mesh when filling the same volume.



Figure 3. Unstructured mesh [46] (Reproduced from Ref. [46])

## 2.2.3. Hybrid Meshes

Hybrid mesh is a combination of structured and unstructured meshes, and an example of hybrid mesh is depicted in Fig. 4. In the hybrid mesh, the structured mesh is generally used for important regions (such as boundary layers around the blade), while the unstructured mesh is used elsewhere [47, 48]. The hybrid mesh is capable of combining the benefits of both structured and unstructured meshes, and therefore it has been widely used in the CFD modelling of WTs [49-51].



Figure 4. Hybrid meshes [51] (Reproduced from Ref. [51])

## **2.3. Boundary Conditions**

The size of the computational domain used in the CFD modelling of WTs is generally proportional to the diameter of the rotor. The shape of the computational domain is various as required. The rectangular [46-48] and semi-circular [52-57] domains are generally used for 2D CFD modelling [46-57], while the cubic [58-61], conical [62] and cylindrical [52, 63] domains are typically used for 3D CFD modelling [59-64].

In the CFD modelling of WTs, the far-field wind velocity and atmospheric pressure are generally used as inlet and outlet boundary conditions, respectively. The surfaces of the WT are generally treated as non-slip wall. The top, bottom and side surfaces of the computational domain are generally treated as non-slip wall as well. The typical boundary conditions and computational domain used in CFD modelling of WTs are presented in Fig. 5 [52].



Figure 5. Boundary conditions of computation domain of WTs [52] (Reproduced from Ref. [52])

## 2.4. Turbulence model

Turbulence models are generally used to deal with turbulent flow in the CFD modelling, and choosing an appropriate turbulence model is vital for simulating the flow field around WTs [65, 66]. The turbulence models used in the CFD modelling of WTs can be roughly categorized into three groups, i.e. RANS (Reynolds Average Navier Stokes), LES (Large Eddy Simulation) and hybrid models.

#### 2.4.1. RANS (Reynolds Average Navier Stokes) models

RANS models provide approximate time-averaged solutions to the Navier-Stokes equations, focusing on non-fluctuating and large-scale features of the flow. RANS-based turbulence models can be roughly categorized into two groups, i.e. one-equation and two-equation turbulence models. One-equation RANS turbulence models, such as SA (Spalrat-Allmaras) [67], Prandtl's [68, 69] and Baldwin-Barth [31], are based on the one time-averaged transport equation. It should be noticed that the Baldwin-Barth model and the Prandtl model are rarely used now. Among these models, the SA model, which is insensitive to the near wall treatment and appropriate for modelling wake and complex flow [70, 71], making it become the most commonly used one-equation RANS model.

For two-equation RANS turbulence models, the k- $\varepsilon$  and k- $\omega$  models are widely used in the CFD modelling of WTs. The k- $\varepsilon$  model calculates turbulence kinetic energy (k) and dissipation rate ( $\varepsilon$ ) [72], and it can be further categorized into four different models, i.e. standard, realizable, RNG (Re-normalization group), and Low-Re k- $\varepsilon$  models. k- $\omega$  turbulence model involves the solution of transport equations for the turbulence kinetic energy (k) and the specific rate of dissipation ( $\omega$ ). The most popular of subcategory of this model is k- $\omega$  SST turbulence model, of which results match well with experimental results [73, 74].

## 2.4.2. LES (Large Eddy Simulation)

Initially proposed in 1963 by Smagorinsky to simulate atmospheric air current, LES has been applied to CFD modelling of WTs in recent years. In LES, large eddies are solved explicitly while the small eddies are implicitly accounted by using a SGS (subgrid-scale) model. Large eddies in turbulent flow generally contain most of the turbulent energy and are responsible for most of the turbulent mixing as well as the momentum transfer. These eddies in full detail are directly captured in LES whereas they are modelled through time averaging in RANS, making LES inherently more accurate than RANS [75].

Solis-Gallego et al. [76] performed LES-based CFD modelling for a small wind turbine airfoil at different angles of attack to predict the trailing edge noise of the airfoil. The LES modelling results showed good

agreement with experimental measurements. Wang et al. [77] studied the aerodynamic performance of blunt wind turbine airfoils using LES and compared the numerical results against experimental measurements. Good agreement was achieved between LES results and experimental measurements, and results also indicated that the trailing edge size can affect the separation bubbles and transition process in the boundary layers for the blunt wind turbine airfoils. More examples of applying LES to CFD modelling of wind turbines can be found in Refs. [78, 79].

#### 2.4.3. Hybrid models

Hybrid RANS/LES techniques can be generally categorized into two groups: zonal and non-zonal. The first one takes RANS and LES as a separate model and employs them concurrently. The main concern in this method is about the regions between RANS and LES where some kind of interpolation must be used to provide smooth transition between them. It is likely to be error-prone for trial-and-error technique, particularly for sophisticated geometries. In the second approach, it is not necessary to choose RANS/LES regions [80, 81]. DES (Detached Eddy Simulation), which was first proposed in 1997 and first used in 1999 [82-85], is one of the prominent non-zonal hybrid RANS/LES models. DES treats near-wall regions in a RANS-like manner and the rest of the flow in an LES-like manner, which combines the best aspects of RANS and LES in a single solution strategy [85].

## 2.5. Discretization method

Analytical solutions generally do not exist for many non-linear models (such as CFD models based on NS equations), and therefore one of the way for solving these problems is to approximate the solutions using numerical methods [86, 87]. The numerical discretization techniques used in the CFD modelling can be roughly categorized into three groups, i.e. FEM (Finite Element Method), FVM (Finite Volume Method) and FDM (Finite Difference Method).

## **2.5.1. FEM (Finite Element Method)**

FEM is mainly utilised in the structural analysis, but it is also applicable to fluid dynamics. For instance, ANSYS CFX [88], a widely used commercial CFD software package, is based on FEM. By using the Smooth Piecewise Continuous function, the PDEs (Partial Differential Equations) in the FEM are converted into algebraic equations to approximate unknown quantities. The governing equations are generally multiplied by a weight function and then integrated over the entire domain [89]. The basis of this method is to eliminate the PDEs or simplify the PDEs into ordinary differential equations, which can be then solved by numerical methods.

The solution domain in the FEM is generally divided into finite number of sub-domains, known as elements. A simple function is assumed for the variation of each variable inside each element, and then the summation of them is used to describe the whole field. The FEM is useful for solving PDEs over complicated domains or when the domain is variable [90, 91].

#### 2.5.2. FVM (Finite Volume Method)

FVM is a special case of FEM when the weight function is equal to 1 everywhere in the domain. In the FVM, the integral forms of the governing equations are considered [92], and the solution domain is subdivided into a finite number of contiguous control volumes. The conservation equations are then applied to the centroid of each control volume, at which the computational nodes are located, to obtain the discrete equations for the element [93]. FVM is currently the most versatile discretization technique used in the CFD modelling, and it is suitable for complex geometries and applicable to any type of grids [94].

#### 2.5.3. FDM (Finite Difference Method)

In FDM, difference between amounts of different points at various space and time leads to the approximation of the derivative of a variable by the Taylor series, transforming the governing differential equations into algebraic equations [95].

In order to extend to the entire points of domain, various forms of the derivatives of variables at each point that are related to its neighbourhood points are written, obtaining a set of numerical equations. When this process is exerted to all points of domain, infinite number of terms and very small difference in variables make the equations mathematically accurate [95]. It should be noted that FDM is not inherently appropriate for complexity, and therefore it should be applied to structured grids [96].

#### 2.6. Treatment of blade rotation

The rotation of WT blades can significantly affect the aerodynamic performance of the turbine, and therefore it should be taken into account in the CFD modelling of WTs. The methods used for treating the blade rotation in the CFD modelling can be roughly categorized into three groups, i.e. reference frame, sliding mesh and dynamic mesh, as illustrated in Fig. 6.



Figure 6. Methods used in the treatment of blade rotation

## 2.6.1. Reference frame

The reference frame is the most prevalent method used for treating the rotation of WT blades. According to the number of reference frames is used, this method can be categorized into two groups, i.e. SRF (Single Reference Frame) and MRF (Multiple Reference Frame). In the SRF, the entire computational domain is treated as a single moving reference frame. SRF is simple to implement but it is not capable of handling the problems that involve multiple rotating parts or stationary components (e.g. WT towers). In the MRF, a rotating reference frame is generally used for the region around the rotor blades, and a fixed reference frame is used for the rest of the computational domain. MRF is capable of handling the problems that involve both rotating and stationary parts. Due to its reasonable accuracy and computational efficient, MRF has been widely used in the CFD modelling of WTs [97-99].

#### 2.6.2. Sliding mesh

The sliding mesh method allows adjacent grids to slide relative to one another. In this method, the rotational velocity is constant during each time step, and therefore this method is generally used in steady state flow. The main point of this model is that meshes do not deform by the rotation of reference frame. Cai et al. [100] used sliding mesh technique to investigate interface between static and moving parts in flow domain. Bedon et al. [101] adopted sliding mesh technique to optimize performance of Darrius WT airfoil. More examples of using sliding mesh in CFD modelling of WTs can be found in Refs. [102-104].

#### 2.6.3. Dynamic mesh

CFD models can be coupled with structural models to perform FSI (Fluid Structure Interaction) modelling. FSI modelling of WTs can be performed using two types of coupling scheme, i.e. one-way coupling and two-way coupling. In the one-way coupling, the effects of deformed rotor on the fluid field are ignored, and both reference frame and sliding mesh techniques are applicable to take account of the blade rotation. For the two-way coupling, it is necessary to use dynamic mesh technique to take account of the blade rotation and the dynamic coupling of the fluid and structure. In this method, the mesh is generally updated at each time step, taking account of the deformation of the structure. Cheng et al. [105] investigated effects of blade vibration on aerodynamic load through a two-way FSI modelling using dynamic mesh.

## 2.7. CFD Applications on WTs

As one of pioneers, Sorensen and Hansen [106] simulated two different CFD models using incompressible RANS with  $k-\omega$  SST turbulence model. The model was capable of predicting power curve accurately until 10 m/s wind speed. Beyond this speed, the accuracy significantly drops due to flow separation. Bazilevs et al [107] developed an FSI model based on residual-variation-multiscale formulation. The model coupled fluid flow with airfoil structure based on Kirchhof-Love theory [108, 109], in which the rotational and deflection motion are de-composited. The model was demonstrated to be capable of predicting torque coefficient precisely.

Mohamed et al [110] performed CFD modelling of 25 various airfoils using compressible URANS-based solver in order to identify the suitable airfoil shape. Balduzzi et al [111] analysed fundamental parameters of Darrieus turbine using unsteady URANS-based solver. Through comparing three types of turbulence models, i.e. Standard k- $\varepsilon$ , RNG k- $\varepsilon$  and k- $\omega$  SST, it indicated that the k- $\omega$  SST model has the highest precision among these turbulence models.

Balduzzi et al [112] applied the COSA RANS code to evaluate unsteady performance of the Darrieus rotor blade and compared the CFD results against the BEM results. The torque curve obtained from 3D CFD analysis and BEM analysis showed similar trend, whereas the downstream revolution torque profile was distinct. Grid refinement was then utilized to minimise uncertainty in simulating complex flow phenomena, such as tip vortex flow, dynamic stall and interaction of tip and wake. Wu and Porte-Agel [114] performed a large-eddy simulation of WTs to examine effects of wake flow and casualties. Estimations of power output and forces of WTs were made by the conventional actuator-disk model. The results from the model showed good agreement with the data from Horns Rev wind farm.

Make and Vaz [115] studied the flow over two floating WTs using RANS CFD calculations. In order to minimise the possible uncertainties, numerical sensitivity studies were performed regarding domain size, grid refinement, iterative convergence and turbulence model. Two types of turbulence models, i.e.  $k-\omega$  SST and SA, were used and it demonstrated that the  $k-\omega$  SST model predicted more accurately. In the study, both full-scale and model-scale model were compared against with experimental data, showing good agreement. A comparative RANS solver study between pressure-based (FLUENT) and density-based (COSA) was accomplished by Balduzzi et al [116]. For both cases, a good agreement with experimental data was achieved. Further, sensitivity analysis in grid refinement, domain size and boundary conditions were performed. A work regarding the influence of domain size was accomplished by Rezaeiha et al [117]. In the study, effects

of domain size and azimuthal increment were minimised for 2D and 2.5D simulations for a low-solidity 2bladed VAWT at TSR (tip speed ratio) of 4.5 by using URANS-based solver. Three refinements of grid were performed for grid dependence. It was observed that 10 times the diameter of turbine is the suitable size for locating both inlet and outlet boundaries.

Gebraad et al [118] developed a new numerical model to optimize the turbine yaw settings. The model is capable of well predicting power output for both conventional and optimised yaw settings. A LES model was simulated by Stevenes et al [119] to evaluate alignment angles, and the results from the model matched well with the data from Horns Rec wind farm. The preferable power coefficient was obtained at the alignment angle of  $11^{\circ}$  where wake flow is significantly less effective. More examples of the CFD applications on WTs can be found in Refs. [29, 120-128].

## 3. Objective functions used in optimisation of WTs

The objective functions used in optimisation of WTs can be roughly categorized into four groups, i.e. minimization of the COE (cost of energy), maximization of the annual energy production, minimization of the blade mass and MO (Multidisciplinary Optimisation).

## **3.1.** Minimization of the COE (cost of energy)

Currently, the mostly used objective function in the optimisation of WTs is the minimization of COE, which is defined as [130]:

$$COE = \frac{C_{TA}}{AEP} \tag{1}$$

where  $C_{TA}$  and AEP are the total annual cost and the annual energy production, respectively.

COE of WTs depend on several factors, e.g. installation, electrical cable cost, maintenance, etc. Scale and orientation of the turbine can also affect the COE [131-133].

## **3.2.** Maximization of the AEP (annual energy production)

An aerodynamically efficient blade is the incipient requirement to attain maximum power output of WTs [134-138]. WT blades are generally made of composite materials due to their high stiffness-to-weight ratio and good fatigue performance.

The maximum AEP for a given distribution has been taken as an objective function in many studies on the optimisation of WTs [139-144]. The AEP over the wind speed spectrum is given by [145, 146]:

$$AEP = h_{year} \cdot K_{avl} \int_{V_{in}}^{V_{out}} P(V)F(V)dV$$
<sup>(2)</sup>

where  $h_{year}$  is the number of hours in a year, usually 8760 hours;  $K_{avl}$  represents the availability of the turbine;  $V_{in}$  and  $V_{out}$  are the cut-in and cut-out wind speeds, respectively; P(V) represents the power curve of the WT; F(V) is the wind speed distribution.

## 3.3. Minimization of the blade mass

WT blade structure is generally required to be designed as light as possible, in order to reduce the material cost of the blade and lower both centrifugal and gravity loads on the blade. The minimum blade mass can be taken as an objective function, expressed as:

$$F_{obj} = \min(m_B) \tag{3}$$

where  $F_{obj}$  and  $m_B$  are the objective function and blade mass, respectively.

## 3.4. MO (Multidisciplinary Optimisation)

MO is another important objective function which has been extensively used by many researchers [137, 148-154]. There are numerous inadequacies in single objective approaches, of which purpose is to discover the "best" solution corresponding to the maximum or minimum value of a single objective function. However, most of the actual industrial problems involve multiple objectives, e.g. maximizing reliability, maximizing performance, minimizing the COE, etc. [155, 156]. MO allows decision-makers to consider the trade-offs benefits of different objectives and then prioritise objectives within the short time [157]. The MO techniques have been demonstrated to be accurate and capable of resolving the vast majority of sophisticated industrial optimisation problems [129].

In the MO, it is crucial to identify solutions in the Pareto optimal set. Pinpointing the total Pareto optimal set is practically impossible due to its size. Therefore, a practical method is crucial to investigate the best-known Pareto set that clarifies the Pareto optimal set. Generally, most of the MO methods ought to reach the following three conflicting constraints [159-161], i.e. 1) the best-known Pareto front ought to be as close as feasible to the true Pareto front. 2) the best-known Pareto front must capture the entire spectrum of the Pareto front. This needs deep studying solutions at the extreme ends of the objective function space; and 3) solutions ought to be consistently distributed and diverse over the Pareto front to provide the decision-maker an accurate image of trade-offs.

## 4. Optimisations algorithms

The algorithms used in the optimisation of WT performance can be roughly categorised into three groups, i.e. calculus-based, heuristic and meta-heuristic algorithms.

## 4.1. Calculus-Based optimisation

The basis of calculus-based optimisation is a first/second order objective function, which is differentiable and continuous by converging search space to convex or concave. This method has been categorised into different algorithms such as Generalized Benders Decomposition, backtracking, branch-bound/cut, Extended Cutting Plane, the gradient and Newton based [162,163].

There are two basic optimisation techniques to obtain the optimal solution. The first method is to explore all possible solutions. This calculus-based algorithm, for instance Gradient and Newton-based methods, requires objective function to be simple, differentiable and continuous to bind the search space. Additionally, it is time-consuming in computing and cannot overcome the local extreme point in local search. Therefore, several approaches [164, 165] have been introduced based on global and multi-start process, in which a local search is performed to obtain optimal solution. The second technique is implicit solution such as branch-bound method [166], whereas it has showed poor results in comparing to explicit appraisal in non-convex solution. The relaxation method [167-169] was proposed to solve the initial problem and decrease its complexity. The optimal solution procedure can be then employed to overcome non-convex search space by developing relaxation method.

Various denominations have been given for different types of problems to optimisation model which is referred as MINLP (Mixed-Integer Nonlinear Programming Problem) [170, 171]. Archer et al [176] proposed an approach to solve wake effect. In regard to extend further MINLP technique, the performance criteria and effective factors were wiped out to decrease complexity of the problem.

#### 4.2.1. GBA (Gradient Based Approach)

GBA is the most popular and important calculus-based algorithm applied to the performance optimisation. GBA resolves optimisation problems in the design space based on the gradient of objective and constraint functions [177]. It can be used for both constrained and unconstrained problems with multiple variables. This method begins with an initial design and attempts to search for a local minimum that is closest to the initial design in an iterative way [178, 179]. Amaral et al. [180, 181] presented the aerothermal optimisation of a high-pressure WT using the GBA, maximising the lifetime of a WT blade operating at a very high pressure. Nowak and Wróblewski [182] and Mazaheri et al. [183] investigated the optimum shape of a C3X turbine blade using GBA. Lately, hybrid GBA and GA techniques have been investigated by [184-188]. Bizzarrini et al. [189] compared the results of a hybrid scheme and a GA and concluded that the hybrid technique is more effective due to its higher precision as well as higher sensitivity to local minima. Similar conclusions were also drawn by Varga [186] and Refs. [187-189].

## 4.2. Heuristic optimisation

Heuristic method was first proposed in 1982 by Daniel Kahneman and Amos Tversky [190]. It employs a deterministic or non-deterministic solution process to seek near-optimum solutions for sophisticated problems based on previous experiences. Heuristic methods are useful where attaining the exact optimum solution is impossible. Additionally, they are fast enough and have better performance than Calculus-based optimisation methods [71, 191].

Heuristic methods can be further categorized into two groups, i.e. constructive and iterative methods. The constructive heuristics attempt to create multiple sequential deterministic (or non-deterministic) assemblies of variable, taking account of all defined constraints. Iterative heuristics enhance a complete solution by performing a controlled estimation of local search space of each involved variable. Constructive heuristics are generally faster than iterative heuristics [192-194]; however, they might fail to find a feasible solution in cases of highly constrained problems.

## 4.3. Meta-heuristic algorithms

Meta-heuristics (also known as hyper-heuristics) are higher-level heuristic methods, which achieve a near optimal solution more precisely than common heuristics [195, 196]. Metaheuristic algorithms are generally based on optimisation process observed in the nature, such as PSO (Particle Swarm Optimisation), GA (Genetic Algorithm) and SA (Simulated Annealing).

## 4.3.1. PSO (Particle Swarm Optimisation)

PSO was firstly proposed by Kennedy and Eberhart in 1995, and it was inspired by the social behaviour of bird flocking as well as fish schooling [197, 198]. PSO has been recently applied to the optimisation of WTs [199-201].

Ferrari et al. [130] developed an aerodynamic optimisation model for Savonius VAWT rotors through combining CFD with PSO. Meneses et al. [200] proposed hybrid MILP (Mixed Integer Linear Programming) and PSO method to search for the best location of both ESS (Energy Storage System) and wind power, minimising the power generation costs. Ata [201] proposed the function of PSO in artificial neural network to calculate ESS, obtaining the best set of weights [202-205]. Reddy [206] proposed two different models and the objective functions are considered to be the COE and cost of reserves. The first model includes reserve offers from the conventional thermal generators and the second model includes reserve offers from both thermal generators and demand/consumers.

Liao et al. [208] employed Prelayers, a program that links FAST and the improved PSO algorithm, to optimise blade structural layout Kahla et al. [209] extracted a maximum of power below the fluctuating wind speed with the aid of PSO and proved that the PSO has improved the WT performance.

#### 4.3.2. GA (Genetics Algorithm)

Genetic algorithm is an optimisation technique which imitates Darwin's opinion of the population (the survival of the fittest) over a set of individuals (candidate solutions) that progresses from one generation to another [211]. At the beginning of GA, some chromosomes are erratically opted via the initial population, employing a special search technique. Values are then assigned to the selected chromosomes with respect to the fitness function, and two chromosomes that have the highest fitness value are selected as initial parents. Subsequently, these parents are reproduced to develop a new generation using mutation and crossover operators in a repetitive process [212]. Crossover and mutation operators contribute to perturb the characteristics of parents to create distinct offspring with better characteristics than their parents [213]. The produced generations then substitute their parents in the next reproduction process if they have more promising values than their parents based on the fitness function. The evolution is an iterative process and generally terminates when either a maximum number of generations has been produced or the population has reached a satisfactory fitness level. The typical flowchart of GA is depicted in Fig.7 [214]. GA has the advantage in discovering non-derivable, non-continuous and non-linear domains [215, 15].



Figure 7. Optimisation outline of GA [214]. (Reproduced from [214])

Alpman [216] investigated the effects of choosing the chord length and twist angle distribution for a twobladed stall-regulated HAWT, with GA employed as an optimizer to achieve the highest AEP. Tabatabaeikia et al. [217] accomplished an innovative sequence of optimised numerical simulations through CFD code to recover the exhaust energy of VAWT generators to enhance the performance of the turbine (see Fig. 8), minimising the cost as well as diminishing the noise. Rodrigues et al. [218] designed an offshore WT (as depicted in Fig. 9) consisting of moveable and floating turbines. They employed GA algorithms based on inner loops to optimise the location within the mooring lines. Wang et al. [219] demonstrated that the GA requires lower computational time when comparing to both PSO and DP (Dynamic Programming) in finding the optimum number of thermal generators. Jafaryar et al. [220] proposed an optimised design for the asymmetric blade geometry of VAWT with five blades (see Fig. 10) based on GA. 15 types of NACA airfoils were compared, and the results indicated that NACA 7715 and NACA 4520 performed worst and best respectively among these airfoils.



Figure 8. Optimisation issues of VAWT [217] (Reproduced from [217])



Figure. 9. Three different positioning of moveable WT [218] (Reproduce from [218])



Figure. 10. Detailed schematic of VAWT with five blades [220] (Reproduce from Fig.1 of [220])

Rangi et al. [221] obtained an optimal airfoil through a GA which enhanced the performance of a 26% thick airfoil in steady conditions with both free and forced boundary layer transition. Refs. [222-225] discussed the research studies using hybrid system and claimed that GA is a suitable algorithm for optimizing airfoils. More details about GA in airfoil design can be found in Ref. [226, 227].

## 4.3.3. SA (Simulated Annealing)

SA is a probabilistic single-solution-based search technique inspired by performing the cooling of material in a heat bath (annealing in metallurgy), which was first proposed by Metropolis et al. [228]. The similarity between optimisation process and SA is that potential solution of the considered problems are analogous to the states of a physical system which is undergoing a process of annealing [229]. Local search will normally accept transitions between neighbours of solution when the quality is better than the current state, and the transition is generally modelled as a probabilistic procedure [230]. Elimination of states with lower quality increases until the process reaches the cooling stage [229]. SA has advantages in its ease of implementation and ability to escape local extreme points, making it suitable for solving various sophisticated problems [232-235].

## 5. CFD-based optimisation of WTs

CFD has been applied to optimise WTs, particularly WT blades, which play a vital role in WT performance. CFD-based optimisation of WTs are mainly focused on three aspects, i.e. 1) comprehending behavior of airfoils under fluid flow; 2) investigating effects of shapes and materials of airfoils on airfoil performance; and 3) finding the best shape of airfoil with optimisation algorithms. An illustration on the CFD based optimisation of WTs is depicted in Fig. 11.



Figure 11. An illustration for CFD based optimisation of WTs

The most basic and necessary part of optimisation is to have a deep understanding on the behavior of airfoils under fluid flow. Cai et al [100] simulated a full-machine HAWT under unsteady flow, considering wind shear, tower shadow, etc. The results indicated that the maximum and minimum of aerodynamics loads occur simultaneously during the revolution of blades.

The effects of shapes and materials of airfoils on their aerodynamic performance have been investigated in several studies. Saeed et al. [236] evaluated an airborne WT with NREL Phase IV rotor under various conditions, considering or ignoring shell mounted configuration. The results proved that an airborne WT airfoil with shell mounted configuration performed better when comparing to the one without shell mounted configuration. Zamani et al. [237] conducted a 3D simulation for J-shaped NACA 0015 airfoil to optimise a Darrieus VAWT. Less noise and turbulence was achieved by trapping vorticities at the rear part of blades. Jafaryar et al. [220] combined response surface method and CFD to achieve maximum torque. The optimum asymmetrical airfoil shape showed the same trend as the symmetrical airfoil.

An important aspect of optimising WT airfoils is to use appropriate optimisation algorithm to find the best shape. Ribeiro et al. [238] proposed an airfoil optimisation technique for wind turbines by coupling CFD and optimisation algorithms. In the study, CFD simulations were performed with incompressible RANS equations in steady state using SA turbulence model. The CFD model was coupled with both single and multi-objective GAs to optimise the aerodynamic shape of airfoils. Results indicated that the airfoils obtained with single and multi-objective GAs were similar in shape and aerodynamic coefficients. Bedon et al. [239] proposed an optimisation model for WT airfoils by combining a genetic optimiser, a 2D URANS CFD model,

a fitness calculator and an airfoil generator. The optimisation model was applied to develop a new airfoil shape for Darrieus VAWT blades, and the results indicated that the developed new airfoil shape can improve the aerodynamic performance of the blade. More studies on CFD-based airfoil optimisation can be found in Refs. [112, 240, 241].

## 6. Future development

## 6.1. Hybrid CFD/BEM

The CFD model is valuable to simulate flow filed thoroughly; however, it needs considerable computational time and resources [18]. The BEM technique is efficient to predict the aerodynamic performance of WT blades; however, its accuracy is highly dependent on the airfoil aerodynamic characteristics data, of which experimental data are sometime difficult to obtain [242, 243]. The hybrid CFD/BEM method provides a promising solution to combine the benefits of both CFD and BEM. In this method, the aerodynamic coefficients of 2D airfoils are obtained using CFD, while the aerodynamic loads calculation is performed using BEM. The hybrid CFD/BEM method is capable of predicting aerodynamics performance of WT accurately with reasonable computational time. The flow state especially laminar-turbulent transition around WTs can affect this method considerably. Hence, the further development could consider the laminar-turbulent transition [244, 245].

## 6.2. Innovative numerical technique to reduce computational time of CFD

Innovative numerical techniques have been recently proposed to reduce the computational time of CFD modelling of WT blades. Choosing an appropriate algorithm makes it possible to reduce computational time required by the CFD modelling. These algorithms consider different parameters to maximise the computational efficient. Some novel algorithms such as bat algorithm, shuffled frog leaping algorithm, cuckoo search, scatter search and ant colony optimisation [246, 247] showed satisfactory performance in terms of computational efficient, and the possibility of applying these algorithms to WTs could be further investigated.

## 6.3. Apply CFD to multi-objective optimisation

There are numerous inadequacies in single objective approaches whose purpose is to discover the "best" solution which corresponds to the maximum or minimum value of a single objective function. However, most of the actual industrial problems involve multiple objectives, e.g. maximising reliability, maximising performance, minimising cost, etc. Multi-objective optimisation involves more than one objective functions,

making it more suitable to deal with practical engineering optimisation problems. Therefore, multi-objective optimisation is promising in the performance optimisation of WTs.

## 6.4. Apply CFD to optimise floating WT blades

FOWTs (Floating offshore wind turbines), which were firstly proposed in 1972, have been installed on floating platforms (such as tension-leg, spar and semi-submersible platforms) to generate electricity in deep water [248, 249]. Blue H technologies was the first FOWT installed in Italy, and it has not only achieved the high efficiency but also provided better place for fishing and shipping lanes since 2007 [250-252]. Make et al [115] analyzed effects of scale on FOWTs using RANS CFD simulations. The main purpose of the study was to reduce uncertainties in floating platform.

FOWTs are vulnerable to huge oscillations such as wave- and current-induced hydrodynamic loads as well as wind-induced aerodynamic loads. Accurately predicting the aerodynamic and hydrodynamic loads is important in the design of FOWTs. Therefore, further development of FOWTs would require the development of more reliable aerodynamic and hydrodynamic models for FOWTs. Another work that is worthy investigating is to study the coupled and uncoupled motions comprehensively, particularly the optimisation of the whole system. Further development could also consider numerical studies of unsteady dynamic effects induced by platform motions, e.g. heave, sway, rolling motions, etc.

## 7. Conclusions

This paper critically reviewed CFD (Computational Fluid Dynamics) modelling and its application on the performance optimisation of WTs (wind turbines). The following conclusions can be drawn from the present review.

• With the development of computing resources, CFD has received significant attention in the recent years. CFD is significant in visualising the structure of flow and predicting aerodynamic loads. However, CFD modelling of 3D (three-dimensional) WT blades is still too time-consuming, which is the main barrier for its industrial application. BEM is more efficient in modelling the flow field and computing aerodynamic loads on WT blades. However, the results of BEM highly depend on the accuracy of the airfoil aerodynamic data, of which experimental data are sometime difficult to obtain. The hybrid BEM/CFD method, which combines the benefits of BEM and CFD, is promising in reducing the computational time while preserving prediction precision.

■ MO (Multidisciplinary Optimisation) has been the interesting topic of many investigators in recent studies, as the vast majority of the practical problems involves multiple objectives. MO allows decision-makers

consider the trade-offs between benefits of different objectives and then achieve the optimal design considering multiple objectives.

• The most important algorithm optimisation, such as PSO (Particle Swarm Optimisation), GA (Genetics Algorithm), SA (Simulated Annealing) and GBA (Gradient-Based Approach), were introduced. These topics are addressed by identifying the most important targets and issues in many aspects, including the optimisation formulas, schemes and models. Subsequently, a critical review with the aim of using these algorithms in the performance optimisation of WT with the combination of CFD was investigated. Among the numerous Meta-heuristic algorithm, GA is found to be the most widely applied in the optimisation of WTs.

## **Conflicts of Interest:**

The authors declare that they have no conflict of interest.

## References

[1]T. Y. Liu, P. J. Tavner, Y. Feng, Y. N. Qiu, 2013, Review of recent offshore wind power developments in china, Wind Energy, 16(5), pp.786-803.

[2] Bazmi AA, Zahedi G., 2011, Sustainable energy systems: role of optimization modeling techniques in power generation and supply—a review. Renewable and Sustainable Energy Reviews, 15(8), pp.3480–500.

[3] Benjamin K. Sovacool, Mario Alberto Munoz Perea, Alfredo Villa Matamoros, Peter Enevoldsen, 2016, Valuing the manufacturing externalities of wind energy: assessing the environmental profit and loss of WIND TURBINEs in Northern Europe, Wind Energy, 19(9), pp.1623-1647

[4] Hau, E. (2013). Basic Concepts of Wind Energy Converters. In *Wind Turbines* (pp. 65-78). Springer, Berlin, Heidelberg.

[5] Rui-jing Shi, Xiao-chao Fan, Ying He Comprehensive evaluation index system for wind power utilization levels in wind farms in China, Renewable and Sustainable Energy Reviews 69 (2017) 461-471

[6] David W. MacPhee, Asfaw Beyene, Fluid-structure interaction analysis of a morphing vertical axis WIND TURBINE, Journal of Fluids and Structures 60 (2016) 143–159

[7] David W. MacPhee, Asfaw Beyene, Experimental and Fluid Structure Interaction analysis of a morphing WIND TURBINE rotor, Energy 90 (2015) 1055-1065

[8] J. Jeong, K. Park, S. Jun and D. H. Lee, 2012, "Design optimization of a WIND TURBINE blade to reduce the fluctuating unsteady aerodynamic load in turbulent wind,", Journal of Mechanical Science and Technology 26 pp.827-838.

[9] Linquan Bai, Fangxing Li, Hantao Cui, Tao Jiang, Hongbin Sun, Jinxiang Zhu, Interval optimization based operating strategy for gas-electricity integrated energy systems considering demand response and wind uncertainty, Applied Energy 167 (2016) 270-279

[10] Sovacool, B. K., Burke, M., Baker, L., Kotikalapudi, C. K., & Wlokas, H. (2017). New frontiers and conceptual frameworks for energy justice. Energy Policy, 105, 677-691.

[11] Louis-Charles Forcier, Simon Joncas, 2012, Development of a structural optimization strategy for the design of next generation large thermoplastic WIND TURBINE blades, Structural And Multidisciplinary Optimization, 45(6), pp.889–906.

[12] Jennifer Annoni, Kevin Howard, Peter Seiler, Michele Guala, 2016, An experimental investigation on the effect of individual turbine control on wind farm dynamics, Wind Energy, 19(8), pp.1453-1467.

[13] Nader Sawalhi, Robert B. Randall, Gear Parameter identification in a WIND TURBINE gear box using signal vibrations, Mechanical Systems and signal processing 42 (2014) 368-376

[14] Chi-Jeng Bai, Wei-Cheng Wang, 2016, Review of computational and experimental approaches to analysis of aerodynamic performance in horizontal-axis WIND TURBINEs (HAWIND TURBINEs), Renewable and Sustainable Energy Reviews, 63, pp.506–519.

[15] Raciti Castelli M, Englaro A, Benini E., 2011, The Darrieus WIND TURBINE: proposal for a new performance prediction model based on CFD. Energy, 36(8), pp.4919-4934.

[16] Runa Nivea Pinto, Asif Afzal, Loyan Vinson D'Souza, Zahid Ansari, A. D. Mohammed Samee, Computational Fluid Dynamics in Turbomachinery: A Review of State of the Art, Archives of Computational Methods in Engineering (2016) 1-13.

[17] Hua Yang, Wenzhong Shen, Haoran Xu, Zedong Hong, Chao Liu, Prediction of the WIND TURBINE performance by using BEM with airfoil data extracted from CFD, Renewable Energy 70 (2014) 107-115

[18] Liu Z, WangX, KangS., 2014, "Stochastic performance evaluation of horizontal axis WIND TURBINE blades using non-deterministic CFD simulations,", Energy;73, pp.126–136.

[19] Abhishiktha Tummala, Ratna Kishore Velamati, Dipankur Kumar Sinha, V.Indraja, V. Hari Krishna, 2016, "A review on small scale WIND TURBINEs,", Renewable and Sustainable Energy Reviews 56, pp.1351–1371.

[20] Hsiao F-B,BaiC-J,ChongW-T., 2013, "The performance test of three different horizontal axis WIND TURBINE (HAWIND TURBINE) blade shapes using experimental and numerical methods,", Energies 6(6) pp.2784–2803.

[21] Jian Chen, Hongxing Yang, Mo Yang, Hongtao Xu, Zuohuan Hu, A comprehensive review of the theoretical approaches for the airfoil design of lift-type vertical axis WIND TURBINE, Renewable and Sustainable Energy Reviews 51 (2015) 1709-1720

[22] R. Lanzafame, S. Mauro, M. Messina, WIND TURBINE CFD modeling using a correlation-based transitional model, Renewable Energy 52 (2013) 31-39

[23] Mohammad Hossein Giahi , Ali Jafarian Dehkordi, Investigating the influence of dimensional scaling on aerodynamic characteristics of WIND TURBINE using CFD simulation, Renewable Energy 97 (2016) 162-168

[24] Richard J.A.M. Stevens, Charles Meneveau, 2016, "Flow structure and turbulence in wind Farms," Annu Rev Fluid Mech 49 DOI: 10.1146/annurev-fluid-010816-060206.

[25] Louis Angelo Danao, Okeoghene Eboibi, Robert Howell, An experimental investigation into the influence of unsteady wind on the performance of a vertical axis WIND TURBINE, Applied Energy 107 (2013) 403-407

[26] Bhutta, M. M. A., Hayat, N., Farooq, A. U., Ali, Z., Jamil, S. R., & Hussain, Z. (2012). Vertical axis WIND TURBINE–A review of various configurations and design techniques. *Renewable and Sustainable Energy Reviews*, *16*(4), 1926-1939.

[27] Akwa, J. V., Vielmo, H. A., & Petry, A. P. (2012). A review on the performance of Savonius WIND TURBINEs. *Renewable and sustainable energy reviews*, *16*(5), 3054-3064.

[28] Lin Wang, Xiongwei Liu b, Athanasios Kolios, State of the art in the aeroelasticity of WIND TURBINE blades: Aeroelastic modelling, Renewable and Sustainable Energy Reviews 64 (2016) 195–210

[29] Lin Wang, Robin Quant, Athanasios Kolios, Fluid structure interaction modelling of horizontal-axis WIND TURBINE blades based on CFD and FEA, J. Wind Eng. Ind. Aerodyn. 158 (2016) 11–25

[30] Pierre-Luc Delafin, Takafumi Nishino, Lin Wang, Athanasios Kolios, Effect of the number of blades and solidity on the performance of a vertical axis WIND TURBINE, Journal of Physics: Conference Series 753, 2016, pp. 022033

[31] Baldwin, B. S. and Barth, T. J., 7–10 January 1991. "A one-equation turbulence transport model for high reynolds number wall-bounded flows". In 29th Aerospace Sciences Meeting and Exhibit, no. AIAA 91-0610, American Institute of Aeronautics and Astronautics.

[32]Chen X, Agarwal R. Optimization of flatback airfoils for WIND TURBINE blades using a genetic algorithm with an artificial neural network. In: 48th AIAA aerospace sciences meeting including the new horizons forum and aerospace exposition; 2010. p. 4–7.

[33] Chen X, Agarwal R. Optimization of flat back airfoils for WIND TURBINE blades using a multi-objective genetic algorithm. In: ASME 2012 6th international conference on energy sustainability collocated with the ASME 2012 10<sup>th</sup> international conference on fuel cell science, engineering and technology. American Society of Mechanical Engineers; 2012. p. 1313–24.

[34] Chen XM, Agarwal R. Optimization of flat back airfoils for wind-turbine blades using a genetic algorithm. J Aircraft 2012; 49:622–9.

[35] Ju YP, Zhang CH. Multi-point robust design optimization of WIND TURBINE airfoil under geometric uncertainty. Proc Inst Mech Eng A – J Pow 2012; 226:245–61.

[36] Gunter Reinald Fischer, Timoleon Kipouros, Anthony Mark Savill , 2014, "Multi-objective optimisation of horizontal axis WIND TURBINE structure and energy production using aerofoil and blade properties as design variables,", Renewable Energy 62 pp.506-515.

[37] John Montesano, Hao Chu, Chandra Veer Singh Development of a physics-based multi-scale progressive damage model for assessing the durability of WIND TURBINE blades, Composite Structures 141 (2016) 50-62

[38] Bottasso, C. L., Campagnolo, F., Croce, A., Dilli, S., Gualdoni, F., & Nielsen, M. B. (2014). Structural optimization of WIND TURBINE rotor blades by multilevel sectional/multibody/3D-FEM analysis. *Multibody System Dynamics*, *32*(1), 87-116.

[39] Duvigneau R, Visonneau M. Hybrid genetic algorithms and artificial neural networks for complex design optimization in CFD. Int J Numer Meth Fluids 2004; 44:1257–78

[40] Yin B, Xu D, An Y-r, Chen Y-s. Aerodynamic optimization of 3D wing based on iSIGHT. Appl Math Mech 2008; 29:603–10.

[41] Rašuo, B., Dinulović, M., Veg, A., Grbović, A., & Bengin, A. (2014). Harmonization of new wind turbine rotor blades development process: A review. *Renewable and Sustainable Energy Reviews*, *39*, 874-882.

[42] Kumar, M. S., Krishnan, A. S., & Vijayanandh, R. (2018). Vibrational Fatigue Analysis of NACA 63215 Small Horizontal Axis Wind Turbine blade. *Materials Today: Proceedings*, 5(2), 6665-6674.

[43] Damir Vučina, Ivo Marinić-Kragić, Zoran Milas, Numerical models for robust shape optimization of WIND TURBINE blades, Renewable Energy 87 (2016) 849-862

[44] Kam, T. Y., Su, H. M., & Huang, C. Y. (2017). Quasi-static buckling and first-ply failure loads of shear web reinforced glass-fabric composite wind blades. *Composite Structures*, *160*, 1225-1235.

[45] Cai, X., Pan, P., Zhu, J., & Gu, R. (2013). The analysis of the aerodynamic character and structural response of large-scale wind turbine blades. *Energies*, *6*(7), 3134-3148.

[46]Kok Hoe Wong, Wen Tong Chong, Nazatul Liana Sukiman, Sin Chew Poh, Yui-Chuin Shiah, Chin-Tsan Wang, Performance enhancements on vertical axis WIND TURBINEs using flow augmentation systems: A review, Renewable and sustainable Energy reviews 73 (2017) 904-921

[47] Almohammadi, K.M., Ingham, D.B., Ma, L., Pourkashan, M., 2013. Computational fluid dynamics (CFD) mesh independency techniques for a straight blade vertical axis WIND TURBINE. J. Energy, 58:483-493

[48] Sabaeifard, P., Razzaghi, H., Forouzandeh, A., 2012, Determination of Vertical Axis WIND TURBINEs Optimal Configuration through CFD Simulation, International Conference on Future Environment and Energy IPCBEE, Singapoore, 28:109-113 [49] Alessandro Bianchini, Francesco Balduzzi, Peter Bachant, Giovanni Ferrara, Lorenzo Ferrari, Effectiveness of two-dimensional CFD simulations for Darrieus VAWIND TURBINEs: a combined numerical and experimental assessment, Energy Conversion and Management 136 (2017) 318-328

[50] H.F. Lam, H.Y. Peng, Study of wake characteristics of a vertical axis WIND TURBINE by two- and threedimensional computational fluid dynamics simulations, Renewable Energy 90 (2016) 386-398

[51] Peng, H. Y., & Lam, H. F. (2016). Turbulence effects on the wake characteristics and aerodynamic performance of a straight-bladed vertical axis WIND TURBINE by wind tunnel tests and large eddy simulations. *Energy*, *109*, 557-568.

[52] Kono, T., Nebucho, S., Kogaki, T., Kiwata, T., Kimura, S., & Komatsu, N. (2017). Numerical Analysis of the Effects of Rotating WIND TURBINE Blades on the Aerodynamic Forces Acting on Tower. *Energies*, *10*(1), 121.

[53] Shaheen M, El-Sayed M, Shaaban A, Numerical study of two-bucket Savonius WIND TURBINE cluster. J. Wind Eng Ind Aerodyn 2015; 137:78-98

[54] Zhou, T., Rempfer, D., 2013. Numerical study of detailed flow field and performance of Savonius WIND TURBINEs, J. Renewable Energy, 51:373-381

[55] Sayed, M.A., Kandil, H.A., Shaltot, A., 2012 Aerodynamic analysis of different wind-turbine-blade profiles using finite-volume method, J. Energy Conversion and Management, 64:541-550

[56] Jin, X., Wang, Y., Ju, W., He, J., & Xie, S. (2018). Investigation into parameter influence of upstream deflector on vertical axis wind turbines output power via three-dimensional CFD simulation. *Renewable Energy*, *115*, 41-53.

[57] Tabrizi A.B., Whale J., Lyons T., Urmee T., 2014. Performance and safety of rooftop WIND TURBINEs: Use of CFD to gain insight into inflow conditions, J. Renewable Energy, 67:242-251

[58] Howell R., Qin, N., Edwards J., Durrani N., 2010. Wind tunnel and numerical study of a small vertical axis WIND TURBINE, J. Renewable Energy, 35:412-422

[59] Kalvig, S., Manger, E., Hjertager, B., 2014. Comparing different CFD WIND TURBINE modelling approaches with wind tunnel measurements, J. Physics: Conference Series, 555:1-13

[60] Li, Y., Paik, K.J., Xing, T., Carrica, P.M., 2012. Dynamic overset CFD simulations of WIND TURBINE aerodynamics, J. Renewable Energy, 37: 285-298

[61] Dhert, T., Ashuri, T., & Martins, J. R. (2017). Aerodynamic shape optimization of WIND TURBINE blades using a Reynolds-averaged Navier–Stokes model and an adjoint method. Wind Energy, 20(5), 909-926.

[62] Li, Ch., Zhu, S., Xu, Y-L., Xiao, Y., 2013. 2.5D large eddy simulation of vertical axis WIND TURBINE in consideration of high angle of attack flow, J Renewable Energy, 51:317-330

[63] Yan, C., & Archer, C. L. (2018). Assessing compressibility effects on the performance of large horizontalaxis wind turbines. *Applied Energy*, 212, 33-45.

[64] Hassanzadeh, R. (2017). Best location of the small WIND TURBINE around a single high-rise building. International Journal of Green Energy, 14(2), 196-204.

[65] Beran, P., Stanford, B., & Schrock, C. (2017). Uncertainty Quantification in Aeroelasticity. *Annual Review* of Fluid Mechanics, 49, 361-386.

[66] Göçmen, T., Van der Laan, P., Réthoré, P. E., Diaz, A. P., Larsen, G. C., & Ott, S. (2016). WIND TURBINE wake models developed at the technical university of Denmark: A review. Renewable and Sustainable Energy Reviews, 60, 752-769.

[67] Wu, Z., Cao, Y., Nie, S., & Yang, Y. (2017). Effects of rain on vertical axis wind turbine performance. *Journal of Wind Engineering and Industrial Aerodynamics*, 170, 128-140.

[68] Yu, H. (2017). A critical review on the simulations of wind turbine aerodynamics focusing on hybrid RANS-LES methods. *Energy*, *138*, 257-289.

[69] Kumar, R., Raahemifar, K., & Fung, A. S. (2018). A critical review of vertical axis wind turbines for urban applications. *Renewable and Sustainable Energy Reviews*, 89, 281-291.

[70] Nikolić, V., Shamshirband, S., Petković, D., Mohammadi, K., Ćojbašić, Ž., Altameem, T. A., & Gani, A. (2015). Wind wake influence estimation on energy production of wind farm by adaptive neuro-fuzzy methodology. *Energy*, *80*, 361-372.3

[71] Spalart, P, R., Allmaras, S, R., 1994, A one equation turbulence model for aerodynamic flows, La Recherche Aérospatiale, 1:5-21

[72] Kasmi AE, Masson C., 2008, "An extended k–ε model for turbulent flow through horizontal-axis WIND TURBINEs," J Wind Eng Ind Aerodyn 96(1) pp.103–122.

[73] Wu, X. (2017). Inflow turbulence generation methods. Annual Review of Fluid Mechanics, 49, 23-49.

[74] Rocha PAC, et al., 2014, " $k-\omega$  SST (shear stress transport) turbulence model calibration: a case study on a small scale horizontal axis WIND TURBINE, ". Energy 65 pp.412–418.

[75] Zhiyin, Y. (2015). Large-eddy simulation: Past, present and the future. *Chinese Journal of Aeronautics*, 28(1), 11-24.

[76] Solís-Gallego, I., Meana-Fernández, A., Oro, J. F., Díaz, K. A., & Velarde-Suárez, S. (2018). LES-based numerical prediction of the trailing edge noise in a small wind turbine airfoil at different angles of attack. *Renewable Energy*, *120*, 241-254.

[77] Wang, G., Zhang, L., & Shen, W. Z. (2018). LES simulation and experimental validation of the unsteady aerodynamics of blunt wind turbine airfoils. *Energy*, pp.241-254.

[78] Benard, P., Viré, A., Moureau, V., Lartigue, G., Beaudet, L., Deglaire, P., & Bricteux, L. (2018). Large-Eddy

Simulation of wind turbines wakes including geometrical effects. Computers & Fluids, pp.133-139

[79] Sedaghatizadeh, N., Arjomandi, M., Kelso, R., Cazzolato, B., & Ghayesh, M. H. (2018). Modelling of wind

turbine wake using large eddy simulation. Renewable Energy, 115, 1166-1176.

[80]Jochen Fröhlich, Dominic von Terzi, Hybrid LES/RANS methods for the simulation of turbulent flows, Progress in Aerospace Sciences 49 (2008) 349-377

[81]Y. Benarafa,O. Cioni, F. Ducros, P. Sagaut, RANS/LES coupling for unsteady turbulent flow simulation at high Reynolds number on coarse meshes, Computer Methods in Applied Mechanics and Engineering 195 (2006) 2939-2960

[82] Spalart PR. 2000. Strategies for turbulence modelling and simulations. Int. J. Heat Fluid Flow 21:252-63

[83] Spalart PR, Deck S, Shur ML, Squires KD, Strelets MKh, Travin A. 2006. A new version of detached eddy simulation, resistant to ambiguous grid densities. Theor. Comp. Fluid Dyn. 20:181–95

[84] D'Alessandro, V., Montelpare, S., Ricci, R., & Zoppi, A. (2017). Numerical modeling of the flow over WIND TURBINE airfoils by means of Spalart–Allmaras local correlation based transition model. Energy. 130, 402-419

[85] Vasel-Be-Hagh, A., & Archer, C. L. (2017). Wind farm hub height optimization. Applied Energy, 195, 905-921.

[85] Miller, A., Chang, B., Issa, R., & Chen, G. (2013). Review of computer-aided numerical simulation in wind energy. *Renewable and sustainable energy Reviews*, 25, 122-134.

[86] Zlomusica, Elvir, wind, Handbook of Sustainable Engineering, Springer, 2013, pp.1109-1142

[87] Mycek, P., Pinon, G., Lothodé, C., Dezotti, A., & Carlier, C. (2017). Iterative solver approach for turbine interactions: application to wind or marine current turbine farms. *Applied Mathematical Modelling*, *41*, 331-349.

[88] Madenci, Erdogan, Guven, Ibrahim, The Finite Element Method and Applications in Engineering Using ANSYS, 2015 pp. 35-74, Springer

[89] Albanesi, A., Fachinotti, V., Peralta, I., Storti, B., & Gebhardt, C. (2017). Application of the inverse finite element method to design wind turbine blades. *Composite Structures*, *161*, 160-172.

[90] Chong, W. T., Muzammil, W. K., Wong, K. H., Wang, C. T., Gwani, M., Chu, Y. J., & Poh, S. C. (2017). Cross axis wind turbine: Pushing the limit of wind turbine technology with complementary design. *Applied Energy*, 207, 78-95.

[91]Y. Li, A.M. Castro, T. Sinokrot, W. Prescott, P.M. Carrica, Coupled multi-body dynamics and CFD for WIND TURBINE simulation including explicit wind turbulence, Renewable Energy 76 (2015) 338-361

[92] Zienkiewicz, O.C. and Taylor, R.L., "The Finite Element Method- Vol 2: Solid and Fluid Mechanics,"McGraw-Hill, New York, 1991.

[93] Wen, B., Tian, X., Dong, X., Peng, Z., & Zhang, W. (2017). Influences of surge motion on the power and thrust characteristics of an offshore floating wind turbine. *Energy*, *141*, 2054-2068.

[94] LeVeque, R. J. (1992). Computing Discontinuous Solutions. In *Numerical Methods for Conservation Laws* (pp. 114-121). Birkhäuser, Basel.

[95] K.W. Morton and D.F. Mayers, Numerical Solution of Partial Differential Equations, An Introduction. Cambridge University Press, 2005

[96] Lomax, H., Pulliam, T. H., & Zingg, D. W. (2013). Fundamentals of computational fluid dynamics. Springer Science & Business Media,, Springer-Verlag, 2001, ISBN: 3-540-41607-2

[97] Menegozzo, L., Dal Monte, A., Benini, E., & Benato, A. (2018). Small wind turbines: A numerical study for

aerodynamic performance assessment under gust conditions. Renewable Energy, 121, 123-132.

[98] Moshfeghi, M., Shams, S., & Hur, N. (2017). Aerodynamic performance enhancement analysis of horizontal

axis wind turbines using a passive flow control method via split blade. *Journal of Wind Engineering and Industrial Aerodynamics*, *167*, 148-159.

[99] Ebrahimi, A., & Movahhedi, M. (2018). Wind turbine power improvement utilizing passive flow control with microtab. *Energy*, *150*, 575-582.

[100] Cai, X., Gu, R., Pan, P., Zhu, J., 2016. Unsteady aerodynamics simulation of a full-scale horizontal axis WIND TURBINE using CFD methodology, J. Energy Conversion and Management, 112:146-156

[101] Bedon, G., De Betta, S., Benini, E., 2016, 10WIND TURBINEs, J. Renewable Energy, 94:328-340

[102] Clainche, S. L., & Ferrer, E. (2018). A Reduced Order Model to Predict Transient Flows around Straight

Bladed Vertical Axis Wind Turbines. *Energies*, 11(3), 1-24.

[103] Bazilevs, Y., Korobenko, A., Deng, X., Yan, J., Kinzel, M., & Dabiri, J. O. (2014). Fluid–structure interaction modeling of vertical-axis wind turbines. *Journal of Applied Mechanics*, *81*(8), 081006.

[104] Schaffarczyk, A. P. (2014). Impact of Aerodynamics on Blade Design. In Introduction to Wind Turbine

Aerodynamics (pp. 185-198). Springer, Berlin, Heidelberg.

[105] Cheng, Q., Liu, X., Ji, H. S., Kim, K. C., & Yang, B. (2017). Aerodynamic Analysis of a Helical Vertical Axis Wind Turbine. *Energies*, *10*(4), 575.

[106] Sorensen, N, N. and Hansen, M, O, L., 1998. "Rotor performance predictions using a Navier-Stokes method", American Institute of Aeronautics & Astronautics, 98:52-59.

[107] Bazilevs, Y., Hsu, M, Ch., Kiendel, J., Wuchner, R., Bletzigner, K, U., 2011. "3D simulation of WIND TURBINE rotors at full scale. Part II: Fluid–structure interaction modeling with composite blades" J. Numerical Methods in Fluids, 65:236-253

[108] Bazilevs, Y., Takizawa, K., Tezduyar, T. E., Hsu, M. C., Kostov, N., & McIntyre, S. (2014). Aerodynamic and FSI analysis of wind turbines with the ALE-VMS and ST-VMS methods. *Archives of Computational Methods in Engineering*, 21(4), 359-398.

[109] Maizi, M., Mohamed, M. H., Dizene, R., & Mihoubi, M. C. (2018). Noise reduction of a horizontal wind turbine using different blade shapes. *Renewable Energy*, *117*, 242-256.

[110] Mohamed, M, H., Ali, A, M., Hafiz, A, A., 2015. "CFD analysis for H-rotor Darrieus turbine as a low speed wind energy converter", *Engineering Science and Technology, an International Journal*, 18(1):1-13

[111] Balduzzi, F., Bianchini, A., Maleci, R., Ferrara, G., Ferrari, L., 2016. "Critical issues in the CFD simulation of Darrieus wind turbfines", J. Renewable Energy, 85:419-435

[112] Balduzzi, F., Drofelnik, J., Bianchini, F, A., Ferrara, G., Ferrari, L., Campobasso, M, S., 2017. "Darrieus WIND TURBINE Blade Unsteady Aerodynamics: A Three-Dimensional Navier-Stokes CFD assessment", J. Energy, Accepted Manuscript.

[113] Orlandi, A., Collu, M., Zanforlin, S., Shires, A., 2015, "3D URANS analysis of a vertical axis WIND TURBINE in skewed flows" J. Wind Engineering and Industrial Aerodynamics, 147:77-84

[114] Wu, Y, T., Porte-Agel, F., 2015. "Modeling turbine wakes and power losses within a wind farm using LES: An application to the Horns Rev offshore wind farm", J. Renewable Energy, 75:945-955

[115] Make, M., Vaz, G., 2015. "Analyzing scaling effects on offshore WIND TURBINEs using CFD", J. Renewable Energy, 83:1326-1340

[116] Balduzzi, F., Bianchini, A., Gigante, F, A., Ferrara, G., Campobasso, M, S., Ferrari, L., 2015. "PARAMETRIC AND COMPARATIVE ASSESSMENT OF NAVIER-STOKES CFD METHODOLOGIES FOR DARRIEUS WIND TURBINE PERFORMANCE ANALYSIS", Proceedings of ASME Turbo Expo 2015: Turbine Technical Conference and Exposition, Montréal, Canada

[117] Rezaeiha, A., Kalkman, I., Blocken, B., 2017. "CFD simulation of a vertical axis WIND TURBINE operating at a moderate tip speed ratio: Guidelines for minimum domain size and azimuthal increment", J. Renewable Energy, 107:373-385

[118] Gebrad, P, M, O., Teeuwisse, F, W., van Wingerden, J, W., Fleming, P, A, Ruben, S, D., Marden, J, R., Pao, L, Y., 2014. "A Data-Driven Model for Wind Plant Power Optimization by Yaw Control", 2014 American Control Conference (ACC), Portland, Oregon, USA

[119] Stevenes, R, J, A, M., Gayme, D, F., Meneveau, Ch., 2014, "Large eddy simulation studies of the effects of alignment and wind farm length", J. Renewable and Sustainable Energy, 6:023105-1-14

[120] Naccache, Gabriel, and Marius Paraschivoiu., 2018, "Parametric study of the dual vertical axis wind turbine using CFD." *Journal of Wind Engineering and Industrial Aerodynamics* 172:244-255.

[121] Chen, J., Wang, Q., Zhang, Sh., Eecen, P., Grasso, F., 2016. "A new direct design method of WIND TURBINE airfoils and wind tunnel experiment", Applied Mathematical Modeling, 40(3):2002-2014

[122] Bhargav, M. M. S. R. S., Velamati Ratna Kishore, and Vaitla Laxman. "Influence of fluctuating wind conditions on vertical axis wind turbine using a three dimensional CFD model." *Journal of Wind Engineering and Industrial Aerodynamics* 158 (2016): 98-108.

[123] Pourrajabian, A., Nazemi Afshar, P, A., Ahmadizadeh, M., Wood, D., 2016. "Aero-structural design and optimization of a small WIND TURBINE blade", Renewable Energy 87(2):837-848

[124] Kim, T., Jeon, M., Lee, S., and Shin, H., 2014, "Numerical simulation of flat-back airfoil aerodynamic noise," Renewable Energy, 65:192-201

[125] Roshan, Saeed Zabihzade, Siamak Alimirzazadeh, and Manouchehr Rad. "RANS simulations of the stepped duct effect on the performance of ducted wind turbine." *Journal of Wind Engineering and Industrial Aerodynamics* 145 (2015): 270-279.

[126] Hand, B., Kelly, G., Cashman, A., 2017. Numerical simulation of a vertical axis WIND TURBINE airfoil experiencing dynamic stall at high Reynolds numbers, J. Computers & Fluids, 149:12-30

[127] O'Brien, J, M., Young, T, M., O'Mahoney, D, C., Griffin, P, C., 2017. "Horizontal axis WIND TURBINE research: A review of commercial CFD, FE codes and experimental practices", Progress in Aerospace Sciences, 92, 1-24

[128] Ciri, U., Rotea, M., Santoni, Ch., Leonardi, S., 2017. "Large-eddy simulations with extremum-seeking control for individual WIND TURBINE power optimization", Wind Energy, 20(9), 1617-1634

[129] Jha, S. K., Bilalovic, J., Jha, A., Patel, N., & Zhang, H. (2017). Renewable energy: Present research and future scope of Artificial Intelligence. *Renewable and Sustainable Energy Reviews*, 77, 297-317.

[130] T. Ashuri, M.B. Zaaijer, J.R.R.A. Martins, G.J.W. van Bussel, G.A.M. van Kuik, 2014, "Multidisciplinary design optimization of offshore WIND TURBINEs for minimum levelized cost of energy,", Renewable Energy 68, pp. 893-905.

[131] C. Pérez-Collazo, D. Greaves, G. Iglesias, 2015, "A review of combined wave and offshore wind energy,", Renewable and Sustainable Energy Reviews 42 pp.141–153.

[132] N. Karthikeyan, K. Kalidasa Murugavel, S. Arun Kumar, S. Rajakumar, 2015, Review of aerodynamic developments on small horizontal axis WIND TURBINE blade", Renewable and Sustainable Energy Reviews 42 pp.801–822

[133] Stensgaard Toft Henrik, Branner Kim, et al., 2011, "Defect distribution and reliability assessment of WIND TURBINE blades,". Eng Struct; 33: pp.171–181.

[134] Wenyi Liu, 2016, "Design and kinetic analysis of WIND TURBINE blade-hub-tower coupled system,", Renewable energy 94 pp.547-557.

[135] Shokrieh Mahmood M, Rafiee Roham, 2006, "Simulation of fatigue failure in a full composite WIND TURBINE blade,". Compos Struct 74: pp.332–342.

[136] Maalawi Karam Y, Negm Hani M., 2002, "Optimal frequency design of WIND TURBINE blades,". J Wind Eng Ind Aerodyn; 90, pp.961–986.

[137] Jin Chen, Quan Wang, Wen Zhong Shen, Xiaoping Pang, Songlin Li, Xiaofeng Guo,2013, "Structural optimization study of composite WIND TURBINE blade,", Materials and Design 46 (2013) 247–255

[138] Bazilevs Y, Hsu MC, et al., 2011, "3D simulation of WIND TURBINE rotors at full scale,". Int J Numer Methods Fluids; 65: pp.207–235.

[139] R.H. Barnes, E.V. Morozov K. Shankar, 2015, "Improved methodology for design of low wind speed specific WIND TURBINE blades,", composite structures 119 pp.677-684.

[140] Belessis MA, Stamos DG, Voutsinas SG., 1996, "Investigation of the capabilities of a genetic optimization algorithm in designing WIND TURBINE rotors,". In: Proc European union wind energy conf and exhibition; pp. 124–7.

[141] Hadi Abdollahzadeh, Karim Atashgar, Morteza Abbasi, 2016, "Multi-objective opportunistic maintenance optimization of a wind farm considering limited number of maintenance groups,", Renewable Energy 88 pp.247-261.

[142] Lee K-H, Joo W, Kim K-H, Lee D-H, Lee K-T, Park J. "Numerical optimization using improvement of the design space feasibility for Korean offshore horizontal axis WIND TURBINE blade,". In: European wind energy conference & exhibition EWEC; 2007.

[143] Mendez J, Greiner D. Wind, 2006, "Blade chord and twist angle optimization using genetic algorithms. In: Fifth international conference on engineering computational technology,". Las Palmas de Gran Canaria (Spain), pp. 12–25.

[144] Wang, T. (2012). A brief review on WIND TURBINE aerodynamics. *Theoretical and Applied Mechanics Letters*, 2(6)., pp. 062001.

[145] Diab, F., Lan, H., & Ali, S. (2016). Novel comparison study between the hybrid renewable energy systems on land and on ship. Renewable and Sustainable Energy Reviews, 63, 452-463.

[146] Karim Atashgar, Hadi Abdollahzadeh, 2016, "Reliability optimization of wind farms considering redundancy and opportunistic maintenance strategy,", Energy Conversion and Management 112 pp.445–458.

[147] Santiago Pindado, Enrique Vega, Alejandro Martínez, Encarnación Meseguer, Sebastián Franchini, Imanol Pérez Sarasola, 2011, "Analysis of calibration results from cup and propeller anemometers. Influence on WIND TURBINE Annual Energy Production (AEP) calculations,", Wind Energy 14 pp.119-132.

[148] Sedat Şişbot, Özgü Turgut, Murat Tunç, Ünal Çamdal, 2010, "Optimal positioning of WIND TURBINEs on Gökçeada using multi-objective genetic algorithm,", Wind Energy 13 pp.297-306.

[149] K. Chen, M.X. Song, X. Zhang, S.F. Wang, 2016, "WIND TURBINE layout optimization with multiple hub height WIND TURBINEs using greedy algorithm,", Renewable Energy 96 pp.676-686.

[150]Longyan Wang, Andy C.C. Tan, Michael Cholette, Yuantong Gu, 2016, "Comparison of the effectiveness of analytical wake models for wind farm with constant and variable hub heights,", Energy Conversion and Management 124 pp.189-202.

[151] Feng, J., & Shen, W. Z. (2017). Design optimization of offshore wind farms with multiple types of wind turbines. *Applied Energy*, 205, 1283-1297.

[152] M. Fadaee, M.A.M. Radzi, 2012, "Multi-objective optimization of a stand-alone hybrid renewable energy system by using evolutionary algorithms: A review,", Renewable and Sustainable Energy Reviews 16 pp.3364–3369.

[153]Ali Al-Abadi, özgüur Ertunc, Florian Beyer, Antonio Delgado, "Torque-Matched Aerodynamic Shape Optimization of HAWIND TURBINE Rotor,", 2014, Journal of Physics: Conference Series 555, doi:10.1088/1742-6596/555/1/012003.

[154] Joachim C. Heinz, Niels N. Sørensen, Frederik Zahle, 2016, "Fluid–structure interaction computations for geometrically resolved rotor simulations using CFD,", Wind Energy DOI: 10.1002/we.1976.

[155] Perera, A. T. D., Attalage, R. A., Perera, K. K. C. K., & Dassanayake, V. P. C. (2013). A hybrid tool to combine multi-objective optimization and multi-criterion decision making in designing standalone hybrid energy systems. Applied Energy, 107, 412-425.

[156] Niknam T, Taheri SI, Aghaei J, Tabatabaei S, Nayeripour M. A, 2011, "Modified honey bee mating optimization algorithm for multiobjective placement of renewable energy resources,". Applied Energy 88 pp.4817–4830.

[157] Konak A, Coit DW, Smith AE., 2006, "Multi-objective optimization using genetic algorithms: a tutorial,". Reliability Engineering and System Safety 91 pp.992–1007.

[158] Tezer, T., Yaman, R., & Yaman, G. (2017). Evaluation of approaches used for optimization of stand-alone hybrid renewable energy systems. Renewable and Sustainable Energy Reviews, 73, 840-853.

[159] Md Shahriar Mahbub, Markus Wagner, Luigi Crema, 2016, "Incorporating domain knowledge into the optimization of energy systems,", Applied Soft Computing 47 pp.483-493.

[160] Lorenzo Scappatici, Nicola Bartolini, Francesco Castellani, Davide Astolfi, Alberto Garinei, Marcello Pennicchi, 2016, "Optimizing the design of horizontal-axis small WIND TURBINEs: From the laboratory to market,", Journal of Wind Engineering and Industrial Aerodynamics 154 pp.58-68.

[161] Xin Shen, Jin-Ge Chen, Xiao-Cheng Zhu, Peng-Yin Liu, Zhao-Hui Du, 2015, "Multi-objective optimization of WIND TURBINE blades using lifting surface method,", Energy 90 pp.1111-1121.

[162] Pérez, B., Mínguez, R., & Guanche, R. (2013). Offshore wind farm layout optimization using mathematical programming techniques. Renewable Energy, 53, 389-399.

[163] Molea, L., Di Vitantonio, E., & Frediani, A. (2016). Aerodynamic Design of 'Box Blade'and 'Nonplanar'Wind Turbines. In Variational Analysis and Aerospace Engineering (pp. 333-374). Springer International Publishing.

[164] Horst, R.; Pardalos, P.; van Thoai, N. Introduction to Global Optimization, 2nd ed.; Springer: Berlin, Germany, 2000; p. 357.

[165] Gebraad, P. M. O., Teeuwisse, F. W., Wingerden, J. W., Fleming, P. A., Ruben, S. D., Marden, J. R., & Pao, L. Y. (2016). Wind plant power optimization through yaw control using a parametric model for wake effects—a CFD simulation study. Wind Energy, 19(1), 95-114.

[166] Iqbal, M., Azam, M., Naeem, M., Khwaja, A. S., & Anpalagan, A. (2014). Optimization classification, algorithms and tools for renewable energy: A review. Renewable and Sustainable Energy Reviews, 39, 640-654.

[167] Martí, R.; Gallego, M.; Duarte, A. A branch and bound algorithm for the maximum diversity problem. Eur. J. Oper. Res. 2010, 200, 36–44.

[168] Dinh The Luc. (2016). *Multiobjective Linear Programming: An Introduction*. Springer International Publishing., 49-82

[169] Wolsey, L.A.; Nemhauser, G.L. Integer and Combinatorial Optimization; Wiley-Interscience: Hoboken, NJ, USA, 1999; p. 784.

[170] Douak, M., Aouachria, Z., Rabehi, R., & Allam, N. (2018). Wind energy systems: Analysis of the self-starting physics of vertical axis wind turbine. *Renewable and Sustainable Energy Reviews*, 81, 1602-1610

[171] Suganthi, S. T., Devaraj, D., Ramar, K., & Thilagar, S. H. (2018). An Improved Differential Evolution algorithm for congestion management in the presence of wind turbine generators. *Renewable and Sustainable Energy Reviews*, *81*, 635-642.

[172] Donovan, S. Wind farm optimization. In Proceedings of the 40th Annual Conference of the Operational Research Society of New Zealand, Wellington, New Zealand, 2–3 December 2005; pp. 196–205.

[173] Donovan, S. An improved mixed integer programming model for wind farm layout optimisation. In Proceedings of the 41st Annual Conference of the Operational Research Society of New Zealand, Christchurch, New Zealand, 30 November–1 December 2006; pp. 143–152.

[174] Donovan, S.; Nates, G.; Waterer, H.; Archer, R. Mixed integer programming models for wind farm design. In Proceedings of MIP 2008 Workshop on Mixed Integer Programming, New York, NY, USA, 4–7 August 2008; pp. 1–21.

[175] Donovan, S.B. Whither the Wind Blows: Wind Flow Modelling and Wind Farm Layout Optimisation; The University of Auckland: Auckland, New Zealand, 2008; p. 92.

[176] Archer, R.; Nates, G.; Donovan, S.; Waterer, H. WIND TURBINE interference in a wind farm layout optimization mixed integer linear programming model. Wind Eng. 2011, 35, 165–178.

[177] Kaviani, H., & Nejat, A. (2017). Aeroacoustic and aerodynamic optimization of a MW class HAWIND TURBINE using MOPSO algorithm. *Energy*, *140*, 1198-1215.

[178] Kevin Maki, Ricardo Sbragio, Nickolas Vlahopoulos, 2012, "System design of a WIND TURBINE using a multi-level optimization approach,", Renewable energy 43 pp.101-110.

[179] Yong Chen, 2016, Industrial information integration—A literature review 2006–2015, Journal of Industrial Information Integration 2 pp.30–64.

[180] Sergio Amaral, Tom Verstraete, René Van den Braembussche, Tony Arts, 2010, Design and Optimization of the Internal Cooling Channels of a High Pressure Turbine Blade—Part I: Methodology, J. Turbomach 132 (2) pp.021013.

[181] Tom Verstraete, Sergio Amaral, René Van den Braembussche, Tony Arts, 2010, Design and Optimization of the Internal Cooling Channels of a High Pressure Turbine Blade—Part II: Optimization, J. Turbomach 132 (2) pp.021014.

[182] Grzegorz Nowak, W1odzimierz Wróblewski, 2011, Optimization of blade cooling system with use of conjugate heat transfer Approach, International Journal of Thermal Sciences 50 pp.1770-1781.

[183] K. Mazaheri, M. Zeinalpour, H.R. Bokaei, 2016, Turbine Blade Cooling Passages Optimization Using Reduced Conjugate Heat Transfer methodology, Applied Thermal Engineering 103 pp.1228-1236.

[184] D.M. Culley, S.W. Funke, S.C. Kramer, M.D. Piggott, 2016, Integration of cost modelling within the micrositing design optimisation of tidal turbine arrays, Renewable Energy 85 pp.215-227.

[185] Li Han, Carlos E. Romero, Zheng Yao, 2015, Economic dispatch optimization algorithm based on particle diffusion, Energy Conversion and Management 105 pp.1251–1260.

[186] Andreas Varga, 2013, Computational issues for linear periodic systems: paradigms, algorithms, open problems, International Journal of Control 86 (7) pp.1227-1239.

[188] Grasso F., 2012, Hybrid optimization for WIND TURBINE thick airfoils. In: Proceedings of the 53rd AIAAJASME/ASCE/AHS/ASC structures, structural dynamics and materials conference. AIAA Paper AIAA2012, pp.1-12.

[189] Bizzarrini N, Grasso F, Coiro DP., 2011, Genetic algorithms in WIND TURBINE airfoil design. In: EWEA, EWEC2011. Bruxelles (Belgium) pp.14–27.

[190] Daniel Kahneman, Amos Tversky, and Paul Slovic, eds. (1982) Judgment under Uncertainty: Heuristics & Biases. Cambridge, UK, Cambridge University Press ISBN 0-521-28414-7

[191] Rich, E.A. Automata, Computability and Complexity: Theory and Applications, 1st ed.; Prentice Hall: Upper Saddle River, NJ, USA, 2007; p. 1120.

[192] Dobrić, G., & Đurišić, Ž. (2014). Double-stage genetic algorithm for wind farm layout optimization on complex terrains. *Journal of Renewable and Sustainable Energy*, 6(3), 033127.

[193] Saavedra-Moreno, Salcedo-Sanz S,Paniagua-Tineo, Prieto L,Portilla- Figueras A. Seeding evolutionary algorithms with heuristics for optimal WIND TURBINEs positioning in wind farms. Renewable Energy 2011; 36: 2838–44.

[194] Bryony DuPont, Jonathan Cagan, Patrick Moriarty, 2016, An advanced modeling system for optimization of wind farm layout and WIND TURBINE sizing using a multi-level extended pattern search algorithm, Energy 106 pp.802-814.

[195] L. Suganthi, Anand A. Samuel, 2012, "Energy models for demand forecasting—A review,", Renew Sustain Energy Rev 16, pp.2323-1240.

[196] Theo Gentils, Lin Wang, Athanasios Kolios, Integrated structural optimisation of offshore WIND TURBINE support structures based on finite element analysis and genetic algorithm, Applied Energy 199 (2017) 187-204

[197] Kennedy J, Eberhart R., 1995, "Particle swarm optimization,". In: Proceedings of IEEE international conference on neural networks. Perth (Australia) pp. 1942–1948.

[198]Perez R, Behdinan K., 2007, "Particle swarm approach for structural design optimization,". Comput Struct 85 pp.1579–1588.

[199] Tian, L., Zhao, N., Wang, T., Zhu, W., & Shen, W. (2018). Assessment of inflow boundary conditions for RANS simulations of neutral ABL and wind turbine wake flow. *Journal of Wind Engineering and Industrial Aerodynamics*, 179, 215-228.

[200] Tian, W., Mao, Z., Zhang, B., & Li, Y. (2018). Shape optimization of a Savonius wind rotor with different convex and concave sides. *Renewable Energy*, *117*, 287-299.

[201] Rasit Ata, 2015, Artificial neural networks applications in wind energy systems: a review, Renewable and Sustainable Energy Reviews 49 pp.534–562.

[202] Parada, L., Herrera, C., Flores, P., & Parada, V. (2018). Assessing the energy benefit of using a wind turbine

micro-siting model. Renewable Energy, 118, 591-601.

[203] Liu H, Tian H, Chen C, Li Y., 2013, An experimental investigation of two Wavelet- MLP hybrid frameworks for wind speed prediction using GA and PSO optimization. Electr Power Energy Syst 52:pp.161–173.

[204] R. McKenna, P.Ostmanv.d.Leye, W.Fichtner, Key challenges and prospects for large Wind turbines, Renewable and Sustainable Energy Reviews 53 (2016) 1212–1221

[205] José F. Herbert-Acero, Oliver Probst, Pierre-Elouan Réthoré, Gunner Chr. Larsen and Krystel K. Castillo-Villar, 2014, "A Review of Methodological Approaches for the Design and Optimization of Wind Farms,", Energies, 7, pp. 6930-7016.

[206] S. Surender Reddy, Optimal scheduling of wind-thermal power system using clustered adaptive teaching learning based optimization, Electr Eng pp.1-16., DOI 10.1007/s00202-016-0382-5.

[207] Endo M., 2011, WIND TURBINE airfoil optimization by particle swarm method. Case Western Reserve University

[208] Liao CC, Zhao XL, Xu JZ., 2012, Blade layers optimization of WIND TURBINEs using FAST and improved PSO algorithm. Renew Energy 42: pp.227–233.

[209] Sami Kahla , Youcef Soufi , Moussa Sedraoui, Mohcene Bechouat , 2015, On-Off control based particle swarm optimization for maximum power point tracking of WIND TURBINE equipped by DFIG connected to the grid with energy storage, International journal of hydrogen energy 40 pp.13749 -13758.

[210] Muhyaddin J. H. Rawa, David W. P. Thomas, Mark Sumner, A Review on Recent Development of Photovoltaics and WIND TURBINEs, International Journal of Energy and Power Engineering. Vol. 5, No. 6, 2016, pp. 222-227.

[211] Rasoul Faraji, HamidReza Naji, 2014, "An efficient crossover architecture for hardware parallel implementation of genetic algorithm,", Neurocomputing 128 pp.316–327.

[212] Hernández, J. J., et al. "Evolving aerodynamic airfoils for WIND TURBINEs through a genetic algorithm." Journal of Physics: Conference Series. Vol. 792. No. 1. IOP Publishing, 2017.

[213] Ozge Polat, Ismail H. Tuncer, 2013, "Aerodynamic Shape Optimization of WIND TURBINE Blades Using a Parallel Genetic Algorithm,", Procedia Engineering 61 pp.28-31.

[214] M. Bencherif, B. N. Brahmi, A. Chikhaoui, Optimum Selection of WIND TURBINES, *Science Journal of Energy Engineering*. Vol. 2, No. 4, 2014, pp. 36-46.

[215] Selig MS, Coverstone-Carroll VL., 1996, "Application of a genetic algorithm to WIND TURBINE design,". J Eng Res – ASME 118: pp.22–28.

[216] Emre Alpman, Effect of Selection of Design Parameters on the Optimization of a Horizontal Axis WIND TURBINE via Genetic Algorithm 2014 J. Phys.: Conf. Ser. 524 012044.

[217] Seyedsaeed Tabatabaeikia, Nik Nazri Bin Nik Ghazali, Wen Tong Chong, Behzad Shahizare, Nima Izadyar, Alireza Esmaeilzadeh, Ahmad Fazlizan, Computational and experimental optimization of the exhaust air energy recovery WIND TURBINE generator, Energy Conversion and Management 126 (2016) 862–874.

[218] S.F. Rodrigues, R. Teixeira Pinto, M. Soleimanzadeh, Peter A.N. Bosman, P. Bauer, Wake losses optimization of offshore wind farms with moveable floating WIND TURBINEs, Energy Conversion and Management 89 (2015) 933–941

[219] Wang, T., Wang, L., Zhong, W., Xu, B., & Chen, L. (2012). Large-scale wind turbine blade design and aerodynamic analysis. *Chinese Science Bulletin*, 57(5), 466-472.

[220] M. Jafaryar, R. Kamrani, M. Gorji-Bandpy, M. Hatami, D.D. Ganji, Numerical optimization of the asymmetric blades mounted on a vertical axis cross-flow WIND TURBINE, International Communications in Heat and Mass Transfer 70 (2016) 93–104.

[221]Daniele Ragni, Carlos Simão Ferreira, Giuseppe Correale, 2014, Experimental investigation of an optimized airfoil for vertical-axis WIND TURBINEs, Wind energy 18(9) pp.1629-1643.

[222] Sunanda Sinha, S.S. Chandel, 2014, Review of software tools for hybrid renewable energy systems, Renewable and Sustainable Energy Reviews 32 pp.192–205.

[223] Jianzhou Wang, Shanshan Qin, Shiqiang Jin, Jie Wu, 2015, Estimation methods review and analysis of offshore extreme wind speeds and wind energy resources, Renewable and Sustainable Energy Reviews 42 pp.26–42.

[224] Sunanda Sinha, S.S. Chandel, 2015, Review of recent trends in optimization techniques for solar photovoltaic–wind based hybrid energy systems, Renewable and Sustainable Energy Reviews 50 pp.755–769.

[225] Wai Lip Theo, Jeng Shiun Lim, Wai Shin Ho, Haslenda Hashim, Chew Tin Lee, 2017, Review of distributed generation (DG) system planning and optimisation techniques: Comparison of numerical and mathematical modelling methods, Renewable and Sustainable Energy Reviews 67 pp.531–573.

[226] Bedon, G., Paulsen, U. S., Madsen, H. A., Belloni, F., Castelli, M. R., & Benini, E. (2017). Computational assessment of the DeepWind aerodynamic performance with different blade and airfoil configurations. *Applied Energy*, *185*, 1100-1108.

[227] Md Farhad Ismail, Krishna Vijayaraghavan, 2015, "The effects of aerofoil profile modification on a vertical axis WIND TURBINE performance,", Energy 80, pp. 20-31.

[228] N., Metropolis, A.W., Rosenbluth, M.N., Rosenbluth, A.H., Teller, and E., Teller. Equation of state calculation by fast computing machines. Journal of Chemical Physics, 1953.

[229] S., Kirkpatrick, C.D., Gellat, and M.P., Vecchi. Optimization by simulated annealing. Science, 1983; 220: 671–680.

[230] Aarts, E.; Korst, J. Simulated Annealing and Bultzman Machine A Stochatic Approche to combinatorial Optimization and Neutral Computing; Wiley: Hoboken, NJ, USA, 1989.

[231] Tzanos, John, Kostas Margellos, and John Lygeros. "Optimal WIND TURBINE placement via randomized optimization techniques." *Power systems computation conference (PSCC)*. 2011, pp.1-8

[232] S. Rodrigues, P. Bauer, Peter A.N. Bosman, Multi-objective optimization of wind farm layouts – Complexity, constraint handling and scalability, Renewable and Sustainable Energy reviews 65 (2016) 587-609

[233] Khan, S.A.; Rehman, S. Iterative non-deterministic algorithms in on-shore wind farm design: A brief survey. *Renew. Sustain. Energy Rev.* 2013, *19*, 370–384.

[234] Salcedo-Sanz, S.; Gallo-Marazuela, D.; Pastor-Sánchez, A.; Carro-Calvo, L.; Portilla-Figueras, A.; Prieto, L. Evolutionary computation approaches for real offshore wind farm layout: A case study in Northern Europe. *Expert Syst. Appl.* 2013, *40*, 6292–6297.

[235] Mytilinou, V., & Kolios, A. J. (2017). A multi-objective optimisation approach applied to offshore wind farm location selection. *Journal of Ocean Engineering and Marine Energy*, *3*(3), 265-284.

[236] Saeed, M., Kim, M, H., 2017. Aerodynamic performance analysis of an airborne WIND TURBINE system with NREL Phase IV rotor, J. Energy Conversion and Management, 134:278-289

[237] Zamani, M., Nazari, S., Moshizi S.A., Maghrebi M.J., 2016. Three dimensional simulation of J-shaped Darrieus vertical axis WIND TURBINE. J. Energy, 116: 1243-1255

[238] Ribeiro, A. F. P., Awruch, A. M., & Gomes, H. M. (2012). An airfoil optimization technique for wind

turbines. Applied Mathematical Modelling, 36(10), 4898-4907.

[239] Bedon, G., De Betta, S., & Benini, E. (2016). Performance-optimized airfoil for Darrieus wind turbines. *Renewable Energy*, 94, 328-340.

[240] Wong, K. H., Chong, W. T., Sukiman, N. L., Shiah, Y. C., Poh, S. C., Sopian, K., & Wang, W. C. (2018). Experimental and simulation investigation into the effects of a flat plate deflector on vertical axis wind turbine. *Energy Conversion and Management*, *160*, 109-125.

[241] Li, Q. A., Maeda, T., Kamada, Y., Murata, J., Furukawa, K., & Yamamoto, M. (2015). Effect of number of blades on aerodynamic forces on a straight-bladed Vertical Axis Wind Turbine. *Energy*, *90*, 784-795.

[242] David Wafula Wekesa, Cong Wang, Yingjie Wei, 2016, Empirical and numerical analysis of small WIND TURBINE aerodynamic performance at a plateau terrain in Kenya, Renewable Energy 90 pp. 377-385.

[243] Thanh-Toan Tran, Dong-Hyun Ki, Kang-Sik Bae, 2013, "Extreme Load Estimation for a Large WIND TURBINE Using CFD and Unsteady BEM,", Computational Science and Its Applications – ICCSA 2013, pp.127-142.

[244] Esfahanian, V., Pour, A. S., Harsini, I., Haghani, A., Pasandeh, R., Shahbazi, A., & Ahmadi, G. (2013). Numerical analysis of flow field around NREL Phase II WIND TURBINE by a hybrid CFD/BEM method. *Journal of Wind Engineering and Industrial Aerodynamics*, *120*, 29-36.

[245] Thanh-Toan Tran, Dong-Hyun Kim, 2015, "The aerodynamic Interference effects of a floating offshore WIND TURBINE experiencing platform pitching and yaw motions,", Journal of Mechanical Science and Technology 29 pp.549-561.

[246]Yunus Eroğlu, Serap Ulusam Seçkiner, Design of wind farm layout using ant colony algorithm, Renewable Energy 44 (2012) 53-62

[247]Farhad Pouladi, Amir Mohammad Gilani, Bahareh Nikpour, Hojjat Salehinejad, Jadidoleslam, M., Ebrahimi, A., & Latify, M. A. (2017). Probabilistic transmission expansion planning to maximize the integration of wind power. *Renewable Energy*, *114*, 866-878.

[248] Shen, X., Chen, J., Hu, P., Zhu, X., & Du, Z. (2018). Study of the unsteady aerodynamics of floating wind turbines. *Energy*, *145*, 793-809.

[249] Borg M, Collu M, Kolios A. Offshore floating vertical axis WIND TURBINEs, dynamics modelling state of the art. Part [II]: mooring line and structural dynamics. Renew Sustain Energy Rev 2014;39:1214-25

[249] Lei, H., Zhou, D., Lu, J., Chen, C., Han, Z., & Bao, Y. (2017). The impact of pitch motion of a platform on the aerodynamic performance of a floating vertical axis WIND TURBINE. *Energy*, *119*, 369-383.

[250] Leimeister, M., & Kolios, A. (2018). A review of reliability-based methods for risk analysis and their application in the offshore wind industry. *Renewable and Sustainable Energy Reviews*, *91*, 1065-1076.

[251] Rinne, E., Holttinen, H., Kiviluoma, J., & Rissanen, S. (2018). Effects of turbine technology and land use on wind power resource potential. *Nature Energy*, *3*(6), 494.

[252] Borg M, Collu M. Offshore floating vertical axis WIND TURBINEs, dynamics modelling state of the art. Part {III}: hydrodynamics and coupled modelling approaches. Renew Sustain Energy Rev 2015;46:296-310