

Correction to: Simultaneous multiprocessing in a software-defined heterogeneous FPGA

Nunez-Yanez, J., Amiri, S., Hosseinabady, M., Rodríguez, A., Asenjo, R., Navarro, A., Suarez, D. & Gran, R.

Published PDF deposited in Coventry University's Repository

Original citation:

Nunez-Yanez, J, Amiri, S, Hosseinabady, M, Rodríguez, A, Asenjo, R, Navarro, A, Suarez, D & Gran, R 2018, 'Correction to: Simultaneous multiprocessing in a software-defined heterogeneous FPGA', *The Journal of Supercomputing*.

<https://dx.doi.org/10.1007/s11227-018-2409-3>

DOI 10.1007/s11227-018-2409-3

ISSN 0920-8542

ESSN 1573-0484

Publisher: Springer

Open Access This article is distributed under the terms of the Creative Commons Attribution 4.0 International License

(<http://creativecommons.org/licenses/by/4.0/>), which permits unrestricted use, distribution, and reproduction in any medium, provided you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made.

Copyright © and Moral Rights are retained by the author(s) and/ or other copyright owners. A copy can be downloaded for personal non-commercial research or study, without prior permission or charge. This item cannot be reproduced or quoted extensively from without first obtaining permission in writing from the copyright holder(s). The content must not be changed in any way or sold commercially in any format or medium without the formal permission of the copyright holders.

Correction to: Simultaneous multiprocessing in a software-defined heterogeneous FPGA

Jose Nunez-Yanez¹ · Sam Amiri¹ · Mohammad Hosseinabady¹ ·
Andrés Rodríguez² · Rafael Asenjo² · Angeles Navarro² · Dario Suarez³ ·
Ruben Gran³

© The Author(s) 2018

Correction to: J Supercomput <https://doi.org/10.1007/s11227-018-2367-9>

The presentation of Table 2 was incorrect in the original article. The correct Table 2 is given below. The original article has been corrected.

The original article can be found online at <https://doi.org/10.1007/s11227-018-2367-9>.

✉ Sam Amiri
ma17215@bristol.ac.uk

Jose Nunez-Yanez
j.l.nunez-yanez@bristol.ac.uk

Mohammad Hosseinabady
m.hosseinabady@bristol.ac.uk

Andrés Rodríguez
andres@ac.uma.es

Rafael Asenjo
asenjo@ac.uma.es

Angeles Navarro
angeles@ac.uma.es

Dario Suarez
dario@unizar.es

Ruben Gran
rgran@unizar.es

- ¹ University of Bristol, Bristol, UK
- ² Universidad de Málaga, Málaga, Spain
- ³ Universidad de Zaragoza, Zaragoza, Spain

Table 2 Energy change when the second CPU core is utilised

	AES (%)	HotSpot (%)	GEMM (%)	Nbody (%)
Dynamic with interrupt	- 7.73	+ 22.93	- 1.52	- 1.64
Dynamic without interrupt	- 1.53	+ 2.14	+ 13.64	+ 11.67
LogFit with interrupt	- 19.51	+ 16.54	+ 2.87	+ 6.89
LogFit without interrupt	+ 16.00	+ 10.16	+ 1.12	+ 7.59

Negative values indicate improvement in energy consumption. The lower the better

Open Access This article is distributed under the terms of the Creative Commons Attribution 4.0 International License (<http://creativecommons.org/licenses/by/4.0/>), which permits unrestricted use, distribution, and reproduction in any medium, provided you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made.