



Asian Journal of Physical and Chemical Sciences
2(1): 1-10, 2017; Article no.AJOPACS.31889



SCIENCEDOMAIN *international*
www.sciencedomain.org

Dissipative Heat Transfer of Micropolar Hydromagnetic Variable Electric Conductivity Fluid Past Inclined Plate with Joule Heating and Non-uniform Heat Generation

S. O. Salawu^{1*} and E. O. Fatunmbi²

¹Department of Mathematics, University of Ilorin, Ilorin, Nigeria.

²Department of Mathematics and Statistics, Federal Polytechnic, Ilaro, Nigeria.

Authors' contributions

This work was carried out in collaboration between both authors. Author SOS formulated the problem and the derivation of equation and reviewed the literatures. Author EOF solved the problem, carried out the mathematical analysis, did the tables and graphs and discussions of findings. Both authors read and approved the final manuscript.

Article Information

DOI: 10.9734/AJOPACS/2017/31889

Editor(s):

(1) Mohammad Mehdi Rashidi, Bu-Ali Sina University, Hamedan, Iran.

(2) Shi-Hai Dong, Department of Physics, School of Physics and Mathematics, National Polytechnic Institute, Mexico.

Reviewers:

(1) Fateh Mebarek Oudina, Skikda University, Algeria.

(2) Ajaz Ahmad Dar, Annamalai University, Tamil Nadu, India.

Complete Peer review History: <http://www.sciencedomain.org/review-history/18500>

Original Research Article

Received 29th January 2017
Accepted 5th March 2017
Published 4th April 2017

ABSTRACT

Computational simulations of hydromagnetic dissipative heat transfer of variable electric conductivity of micropolar fluid flow and non-uniform heat absorption or generation with joule heating have been studied in this work. The flow past an inclined surface with an unvarying heat flux. The transformed dimensionless equations of the governing model are solved by Runge-Kutta algorithm coupled with shooting scheme to depict the dimensionless temperature, microrotation and velocity distributions at the border layer. The substantial bodily quantities of the flow are conferred. The results depict that the significance of the coefficient of the skin friction and the Nusselt number increases for uneven electric conductivity and non-homogeneous heat sink or source at the plate.

*Corresponding author: E-mail: kunlesalawu2@gmail.com;

Keywords: Hydromagnetic; micropolar fluid; dissipation; joule heating; heat flux.

1. INTRODUCTION

A micropolar fluid consists of gyratory micro-components which make fluid to display non-Newtonian actions. The formulations of micropolar fluid flow was found helpful in examining body fluids, colloidal suspensions, lubricants, liquid crystals, fluid polymeric, flows in capillaries and microchannels, preservative suspensions and flow of shear turbulent. The presumption of micropolar fluids originated by Eringen [1] have been a lively research area for many years.

Ariman et al. [2] reviewed excellently the model and applications of micropolar fluid. Hoyt and Fabulan [3] carried out experimentally analysis to show that the present of minute Stabilizers polymeric in fluids can decrease the flow effect at the wall up to 25 to 30 percent. The decrease that was described by the hypothesis of micropolar fluids as reported by Power [4], the brain fluid that is an example of body fluids fluid can be sufficiently formulated as micropolar fluids.

Flow of convective fluids containing microstructure have several applications such as dilute polymer fluids solutions, liquid crystals and different kinds of suspensions. The fluid driven by buoyancy forces occur in wide-ranging of uniform fluid flow. Free convective flow of micropolar fluids past a curved or flat surfaces has fascinated the mind of scholars from the time when the flow model was devised. Several studies have accounted and analyzed outcomes on micropolar fluids. [5-7] examined the effect of radiation on magnetohydrodynamics convective heat and mass transfer flow. Ahmadi [8] considered micropolar boundary layer fluid flow along semi-infinite surface using similarity solution to transform the models to ordinary different equations. [9-11] verified the viscous dissipation influences on MHD micropolar flow with ohmic heating, heat generation and chemical reaction.

Many convective flow are caused by heat absorption or generation which may be as a result of the fluid chemical reaction. The occurrence of heat source or sink can affect the fluid heat distribution that alters the rate of deposition of particle in the structures such as semiconductor wafers, electronic chips, nuclear reactors etc. Heat absorption or generation has

been assumed to be temperature dependent heat generation and surface dependent heat generation. Rahman et al. [12] examined the influence of non-homogenous heat absorption or generation and variable electric conductivity on micropolar fluid. It was noticed that the surface dependent heat generation is lower compared to temperature dependent heat generation. [13,14] examined the effect of thermal-diffusion and non-homogenous heat sink/source on radiative micropolar hydromagnetic fluid past a permeable medium.

The influence of dissipation on magnetohydrodynamic fluid and energy transfer processes has become significant industrially. Several engineering practices happen at high temperature with viscous dissipation heat transfer. Such flows have been investigated by Siva and Shanshuddin [15] reported on viscous dissipation heat and mass transfer of hydromagnetic micropolar fluid with chemical reaction. Rawat et al. [16] studied magnetodyrodynamics micropolar fluid of heat and mass transport in a permeable medium broadening plate, chemical reaction, heat flux and variable micro inertia. [17,18] verified steady MHD Micropolar flow fluid with joule heating, viscous dissipation and constant mass and heat fluxes. it was observed that the flow field rises initially within $0 \leq \eta \leq 1$ as the microrotation parameter value increases. Later, the flow field gradually reduces for $\eta > 1$ as the microrotation parameter rises. Also, microrotation changes from negative to positive signs in the border layer. Moreover, Ajaz and Elangovan [19] considered the effect of inclined magnetic field on the oscillatory flow of micropolar fluid in a porous micro-channel under the action of alternating electric field.

Following the above cited literature, the aim is to study the viscous dissipation hydromagnetic micropolar fluid behavior heat transfer over inclined surface in permeable media with heat fluxes and joule heating for high speed fluid in non-even heat absorption/generation. The flow equations are made up of partial differential equations that can be transformed by similarity solution to nonlinear ordinary coupled differential equations. The obtained equations are simulated by Runge-Kutta technique coupled with shooting scheme. Therefore, it is obligatory to study the flow distributions, temperature and microrotation

crosswise the border layer in toting up to the surface wall effect and nusselt number.

2. THE FLOW MATHEMATICAL FORMULATION

Deem convective flow of two-dimensional magnetohydrodynamic viscous, laminar, micropolar fluid through a semi-finite flat surface inclined at an angle α to the vertical. The magnetic field differs in potency as function of x which is taken in y -direction as defined $\vec{B} = (0, B(x))$. The Reynolds number is small while the exterior electric field is taken as zero. Therefore, the applied external magnetic field is high contrasted to the stimulated magnetic field. The density (ρ) of the fluid is inert ($U_\infty = 0$) with the buoyancy forces stimulated the convective motion. The fluid viscosity μ is taken to be unvarying while the body forces and the pressure gradient are neglected.

Follow from the assumption above, the steady convective micropolar fluid flow follow the Boussinesq approximation may be explained by the subsequent equations and geometry.

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0 \quad (1)$$

$$u \frac{\partial u}{\partial x} + v \frac{\partial v}{\partial y} = \left(\frac{\mu + r}{\rho} \right) \frac{\partial^2 u}{\partial y^2} + \frac{r}{\rho} \frac{\partial m}{\partial y} + g_0 \beta (T - T_\infty) \cos \alpha - \frac{\sigma(B(x))^2}{\rho} u - \frac{\nu}{K} u \quad (2)$$

$$u \frac{\partial m}{\partial x} + v \frac{\partial m}{\partial y} = \frac{b}{\rho j} \frac{\partial^2 m}{\partial y^2} - \frac{r}{\rho j} \left(2m + \frac{\partial u}{\partial y} \right) \quad (3)$$

$$u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} = \frac{k}{\rho c_p} \frac{\partial^2 T}{\partial y^2} + \left(\frac{\mu + r}{\rho c_p} \right) \left(\frac{\partial u}{\partial y} \right)^2 + \frac{\sigma(B(x))^2}{\rho c_p} u^2 + \frac{q''}{\rho c_p} \quad (4)$$

Subject to boundary conditions

$$u = 0, v = 0, m = -a \frac{\partial u}{\partial y}, \frac{\partial T}{\partial y} = -\frac{q_w}{k} \text{ at } y = 0 \quad (5)$$

$$u = U_\infty = 0, m = 0, T = T_\infty \text{ as } y \rightarrow \infty$$




Fig. 1. Geometry of the flow

where u and v are the velocity in x and y coordinates respectively, K is the permeability of the porous medium, $\nu = \frac{\mu}{\rho}$ is the kinematic

viscosity, μ is the dynamic viscosity, ρ is the fluid density, m is the microrotation in x and y components, $b = \left(\mu + \frac{r}{2} \right) j$ is the micropolar viscosity, j is the micro-inertial per unit mass which is assumed to be constant, r is the microrotation coefficient, k is the thermal conductivity, T is the fluid temperature, c_p is the specific heat at constant pressure, g is the acceleration due to gravity and β is the thermal expansion coefficient.

A linear correlation involving the surface shear $\frac{\partial u}{\partial y}$ and microrotation function m is picked for

studying the influence of vary surface circumstances for microrotation. When the microrotation term $a = 0$ implies $m = 0$, that is the microelement at the wall are not swiveling but when $a = 0.5$ implies varnishing of the anti-symmetric module of the stress tensor that stand for feeble concentration. This confirm that for a fine particle suspension at the wall, the particle swivel is the same as the fluid velocity but when $a = 1$ shows the turbulent boundary layer flows.

The non-uniform heat absorption or generation is represented as:

$$q''' = \frac{kU_0}{2\nu x} [\lambda(T - T_\infty) + \lambda^*(T_w - T_\infty)e^{-\eta}] \quad (6)$$

where λ^* and λ represent the heat sink/source temperature dependent and space coefficients respectively while T_∞ is the free stream temperature. Here, $\lambda > 0$ and $\lambda^* > 0$ stand for to heat source but $\lambda < 0$ and $\lambda^* < 0$ represent to heat sink.

In this study, it is assumed that the introduced magnetic field strength $B(x)$ is capricious and it is represented as $B(x) = \frac{B_0}{\sqrt{x}}$, where B_0 is constant. Also, the electrical conductivity σ depends on the fluid velocity and is defined as $\sigma = \sigma_0 u$, where σ_0 is constant see [20].

Introducing the following dimensionless variables

$$\begin{aligned} \eta &= y \sqrt{\frac{U_0}{2\nu x}}, \psi = \sqrt{2\nu U_0 x} f(\eta), m \\ &= \sqrt{\frac{U_0^3}{2\nu x}} h(\eta), \theta(\eta) = \frac{T - T_\infty}{T_w - T_\infty} \end{aligned} \quad (7)$$

where U_0 is the reference velocity, ψ is the stream function and

$$T_w - T_\infty = \frac{q_w}{k \sqrt{\frac{2\nu x}{U_0}}}$$

Since $u = \frac{\partial \psi}{\partial y}$ and $v = -\frac{\partial \psi}{\partial x}$ then,

$$u = U_0 f'(\eta), \quad v = -\sqrt{\frac{\nu U_0}{2x}} (f(\eta) - \eta f'(\eta)) \quad (8)$$

Using equations (7) and (8) along with the variable magnetic field, fluid velocity dependent electric conductivity and equation (6) on equation (1)-(5) to obtain,

$$(1 + \delta) f'''' + ff'' + \delta h' + G_r \theta \cos \alpha - M f'^2 - \beta f' = 0 \quad (9)$$

$$\mathcal{E} h'' - 2\delta(2h + f'') + \varepsilon(fh + g'h) = 0 \quad (10)$$

$$\begin{aligned} \theta'' + (1 + \delta) P_r E_c f''^2 + M P_r E_c f'^3 + P_r (f\theta' - \theta f') \\ + (\lambda\theta + \lambda^* e^{-\eta}) = 0 \end{aligned} \quad (11)$$

The boundary conditions becomes

$$\begin{aligned} f = f' = 0, h = -af'', \theta' = -1 \text{ at } \eta = 0 \\ f' = 0, h = 0, \theta = 0 \text{ as } \eta \rightarrow \infty \end{aligned} \quad (12)$$

where $\beta = \frac{2x\nu}{U_0 K}$ is the permeability parameter,

$\delta = \frac{r}{\mu}$ is the vortex viscosity term, $M = \frac{2\sigma_0 B_0^2}{\rho}$

is the magnetic field term, $\varepsilon = \frac{jU_0}{\nu x}$ is the micro-

inertia density term, $E_c = \frac{U_0^2}{(T_w - T_\infty)c_p}$ is the Eckert

number, $G_r = \frac{2gx\beta(T_w - T_\infty)}{U_0^2}$ is the thermal Grasoof

number and $P_r = \frac{\mu c_p}{k}$ is the Prandtl number.

The substantial quantities of engineering concern for this flow are the local skin friction C_f and Nusselt number Nu_u given as:

$$C_f = \frac{2\tau_w}{\rho u_w^2}, \quad Nu = \frac{xq_w}{k(T_w - T_\infty)} \quad (13)$$

τ_w and q_w are respectively taken as

$$\tau_w = \mu \left(\frac{\partial u}{\partial y} \right)_{y=0}, \quad q_w = k \left(\frac{\partial T}{\partial y} \right)_{y=0} \quad (14)$$

Hence,

$$\begin{aligned} C_f &= (2Re_x^{-1})^{\frac{1}{2}} [1 + (1 - a)\delta] f''(0), \quad Nu_x \\ &= (2^{-1} Re_x)^{\frac{1}{2}} \frac{1}{\theta(0)} \end{aligned} \quad (15)$$

The computational values for C_f and Nu_x are obtained from the equations (15).

Table 1. Comparison of $f''(0)$ for $\delta = \varepsilon = G_r = \beta = E_c = 0$, various values of a

a	Cortell [21]	Hayat et al. [22]	Rahman et al. [12]	Present results
.0	0.627547	0.627555	0.627498	0.623534
.2	0.766758	0.766837	0.767066	0.766831
.5	0.889477	0.889544	0.892366	0.891784
.75	0.953786	0.953975	0.956365	0.954523
.0	1.000000	1.000000	1.002125	1.001986

Table 2. Values of $f''(0)$ and $\theta'(0)$ for different values of $M, E_c, \lambda, \lambda^*, \beta$, and δ on (PP-physical parameters)

PP	Values	$f''(0)$	$\theta'(0)$	PP	values	$f''(0)$	$\theta'(0)$
M	1	1.13057	6.51766	δ	0.1	1.22091	5.05342
	3	1.17476	7.95342		0.5	1.26975	5.56323
	5	1.22174	9.24167		1.5	1.01562	6.61431
	7	1.26775	10.44839		3.0	0.82392	7.90954
E_c	0.2	1.12160	6.11801	β	0.007	1.12076	5.83162
	0.5	1.18642	6.55818		0.1	1.12092	5.96995
	0.7	1.23454	6.89076		0.3	1.12274	6.26536
λ	1.0	1.31555	7.46070	λ^*	0.5	1.12617	6.55794
	0.0	0.51587	2.76551		0.0	1.02366	5.49423
	0.1	0.59847	3.17923		0.5	1.12160	6.11801
	0.3	0.81802	4.34817		1.0	1.20955	6.69142
	0.5	1.12160	6.11801	1.5	1.29016	7.22734	

3. RESULTS AND DISCUSSION

The computational results for the nonlinear coupled differential equation are obtainable for the dimensionless microrotation, temperature and velocity distributions. In this study, the following default parameter values are chosen: $a = 0.5, P_r = 0.73, G_r = 2.5, \beta = 0.2, \varepsilon = 2, E_c = 0.2,$

$M = 0.5, \alpha = 30^\circ, \delta = 1, \lambda = 0.5$ and $\lambda^* = 0.5$.

The values are based on the choice of existing studies because of unavailability of investigational figures for vortex viscosity and micro-inertia density parameters, suitable figures are selected to verify the polar effect on flow properties.

Table 1 above represents the computational results, that show the behavior of microrotation parameter a on the fluid flow aspects of the current outcome compared with the presented outcome. The comparison are found to be in an excellent agreement as shown in the tables.

Table 2 above shows the simulated results, that illustrate the effect of some fluid properties on the

heat and fluid flow aspect of the investigation. It is evidence from the table that a rise in the values of parameters $M, E_c, \lambda, \lambda^*$ and β increases the skin friction and the temperature gradient at the wall due to an enhancement in the thermal and flow boundary layer thickness. Also, a rise in values of δ causes shrinking in the flow effect at the wall but enhances the thermal gradient at the wall.

Figs. 2-4 depict the velocity, microrotation and temperature distributions for distinction magnetic field term M values. It is noticed from Fig. 2 that the flow decreases as the values of M increases due to the effect of Lorentz forces that retard the convective fluid motion. Fig. 3, confirmed that as the values of the magnetic field term rises the microrotation near the plate increases but decreases as it moves distance from the plate. Fig. 4 reveals the temperature field increases as the values of M rises, this is because the magnetic field liable to reduce the flow field which reduces heat transfer. The results show that the magnetic field may be use to manage the flow fluid and heat transport properties.

Figs. 5-7 represent the effect of the viscous dissipation parameter that is, Eckert number E_c on the flow, microrotation and temperature. The Eckert number E_c represents the relationship between the kinetic energy in the flow and the enthalpy. It embodies the conversion of kinetic energy into internal energy by work done against the viscous fluid stresses. The positive Eckert number implies cooling of the plate that is, loss of heat from the plate to the fluid. It is noticed that the flow velocity, microrotaion and temperature field increases with a rise in the values of E_c . This causes enhancement in the momentum, micropolar and temperature boundary layer thickness and thereby causes a rise in the profiles.




Fig. 2. Velocity distributions for different values of M




Fig. 3. Microrotation distributions for different values of M

Figs. 8 and 9 illustrate the produces of the vortex viscosity δ on the microrotation and flow velocity field. It can be observed that a rise in the values of δ initial decreases the fluid velocity and microrotation profiles close to the plate at $\eta \leq 2$ and later increases as it moves distance away from the plate in the microrotation and velocity flow field.




Fig. 4. Temperature distributions for different values of M




Fig. 5. Velocity distributions for different values of E_c

Figs. 10 and 11 illustrate the influence of porosity term β on the dimensionless velocity and microrotation distributions. It is evidenced that the flow and microrotation field decreases as the porosity parameter rises, this is as a result of the wall of the plate that gives an additional opposition to the flow mechanism by influencing the fluid to move at a decelerated rate.

Figs. 12-15 represent the microrotation and temperature distributions for vary values of temperature dependent and surface temperature heat absorption or generation terms λ and λ^* . Figs. 12 and 14 show that a rise in the values of λ and λ^* reduces the microrotation close to the plate as the thermal boundary layer decreases and later increases as it moves far away from the plate as the thermal boundary layer get thickly. Also, in Figs. 13 and 15 the temperature profile increases as the parameters values λ and λ^* increases, this is due to a rise in the temperature boundary layer.




Fig. 6. Microrotation distributions for different values of E_c




Fig. 7. Temperature distributions for different values of E_c




Fig. 8. Velocity distributions for different values of δ




Fig. 9. Microrotation distributions for different values of δ




Fig. 10. Velocity distributions for different values of β




Fig. 11. Microrotation distributions for different values of β




Fig. 14. Microrotation distributions for different values of λ^*




Fig. 12. Microrotation distributions for different values of λ




Fig. 15. Temperature distributions for different values of λ^*




Fig. 13. Temperature distributions for different values of λ

4. CONCLUSION

The numerical simulations was carried out for dimensionless boundary layer equations of convective heat transfer in hydromagnetic joule heating, micropolar fluid past heated inclined surface with non-uniform heat sink/source and variable electric conductivity. It was observed from the study that, the magnetic field decreases the flow rate and angular velocity but increases the heat transfer phenomenon while the temperature dependent and surface temperature heat absorption or generation terms as well as viscous dissipation parameter increases the flow, angular velocity and temperature distributions.

The vortex viscosity parameter decreases the flow and microrotation profiles near the wall but later increases the profiles distance away from the wall while porosity resist the flow and microrotation of the fluid by decreasing the profiles.

COMPETING INTERESTS

Authors have declared that no competing interests exist.

REFERENCES

1. Eringen AC. Theory of micropolar fluids. *J. Math. Mech.* 1966;16:1-18.
2. Ariman T, Turk MA, Sylvester ND. Microcontinuum fluid mechanics, a review. *Int. J. Eng. Sci.* 1974;12:273.
3. Hoyt JW, Fabula AG. The effect of additives on fluid friction. US Naval Ordnance Test Station Report; 1964.
4. Power H. Micropolar fluid model for the brain fluid dynamics. In: *Intl. Conf. on bio-fluid mechanics*, U.K.; 1998.
5. Hayat T, Qasim M. Influence of thermal radiation and Joule heating magnetohydrodynamics flow of a Maxwell fluid in the presence of thermophoresis. *Int. J. Heat Mass Transfer.* 2010;53:4780-4788.
6. Bhuvaneswari M, Sivasankaran S, Kim YJ. Exact analysis of radiation convective flow heat and mass transfer over an inclined plate in porous medium. *World Appl. Sci. J.* 2010;10(7):774-778.
7. Ajaz AD, Elangovan K. Thermal diffusion, radiation and inclined magnetic field effects on oscillatory flow in an asymmetric channel in presence of heat source and chemical reaction. *Journal of Nigerian Mathematical Society.* 2016; 35(3):488-509.
8. Ahmadi G. Self-similar solution of incompressible micropolar boundary layer flow over a semi-infinite plate. *Int. J. Eng. Sci.* 1976;14:639-646.
9. Khilap S, Manoj K. Effect of viscous dissipation on double stratified MHD free convection in micropolar fluid flow in porous media with chemical reaction, heat generation and ohmic heating. *Chemical and Process Engineering Research.* 2015; 31:75-80.
10. Ajaz AD, Elangovan K. Effect of inclined magnetic field on the oscillatory flow of micropolar fluid in a porous micro-channel under the action of alternating electric field. *World Journal of Engineering Research and Technology.* 2016;2(6):125-145.
11. Mebarek-Oudina F, Bessaïh R. Oscillatory mixed convection flow in a cylindrical container with rotating disk under axial magnetic field and various electric conductivity walls. *Review of Physics.* 2010;4(1):45-51.
12. Rahman MM, Uddin MJ, Aziz A. Effects of variable electric conductivity and non-uniform heat source (or sink) on convective micropolar fluid flow along an inclined flat plate with surface heat flux. *Int. Journal of Thermal Sciences.* 2009;48: 2331-2340.
13. Mabood F, Ibrahim SM. Effects of sores and non-uniform heat source on MHD non-Darcian convective flow over a stretching sheet in a dissipative micropolar fluid with radiation. *Journal of Applied Fluid Mechanics.* 2016;9(5):2503-2513.
14. Mabood F, Ibrahim SM, Rashidi MM, Shadloo MS, Giulio Lorenzini. Non-uniform heat source/sink and Soret effects on MHD non-Darcian convective flow past a stretching sheet in a micropolar fluid with radiation. *International Journal of Heat and Mass Transfer.* 2016;93:674-682.
15. Siva RS, Shamshuddin MD. Heat and mass transfer on the MHD flow of micropolar fluid in the presence of viscous dissipation and chemical reaction. *Int. Conference on Computational Heat and Mass Transfer.* 2015;127:885-892.
16. Rawat S, Kapoor S, Bhargava R. MHD flow heat and mass transfer of micropolar fluid over a nonlinear stretching sheet with variable micro inertia density, heat flux and chemical reaction in a non-darcy porous medium. *Journal of Applied Fluid Mechanics.* 2016;9(1):321-331.
17. Md. Ziaul Haquea, Md. Mahmud Alam, Ferdows M, Postelnicu A. Micropolar fluid behaviors on steady MHD free convection and mass transfer flow with constant heat and mass fluxes, joule heating and viscous dissipation. *Journal of King Saud University– Engineering Sciences.* 2012; 12(24):71-84.
18. Mebarek-Oudina F, Bessaïh R. Numerical modeling of MHD stability in a cylindrical configuration. *Journal of the Franklin Institute.* 2014;351(2):667–681.
19. Ajaz AD, Elangovan K. Effect of inclined magnetic field on the oscillatory flow of micropolar fluid in a porous micro-channel

- under the action of alternating electric field. World Journal of Engineering Research and Technology. 2016;2(6):125-145.
20. Helmy KA. MHD boundary layer equations for power law fluids with variable electric conductivity. Meccanica. 1995;30:187-200.
21. Cortell R. Viscous flow and heat transfer over a nonlinearly stretching sheet. Appl. Math. Comput. 2007;184:864-873.
22. Hayat T, Abbas Z, Javed T. Mixed convection flow of micropolar fluid over a nonlinearly stretching sheet. Phys. Lett. A. 2008;372:637-647.

© 2017 Salawu and Fatunmbi; This is an Open Access article distributed under the terms of the Creative Commons Attribution License (<http://creativecommons.org/licenses/by/4.0>), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Peer-review history:

The peer review history for this paper can be accessed here:
<http://sciencedomain.org/review-history/18500>