



New Approach for Neighbor Discovery in Mobile Ad Hoc Networks

G.SURESH

M.Tech (CSE)

Nova College of Engineering & Technology
A.P., India.

V A RADHIKA

Assistant Professor, Dept. of Computer Science & Engineering
Nova College of Engineering & Technology
A.P., India.

Dr. J.SRINIVASA RAO

Professor, Dept. of Computer Science & Engineering
Nova College of Engineering & Technology
A.P., India.

Abstract – Multipath directing permits building and utilization of numerous ways meant for routing among a resource and destination pair. The resource repetition misuses and difference in the primary network to give profit, for example, fault tolerance, load balancing, data transfer aggregation, as well as change in QoS measurements, for example, interruption. The three components to a path discovery, multipath routing, path maintenance and traffic distribution. Path discovery includes discovering accessible ways utilizing predefined criteria. A well known metric is way disjointness, a measure of resource contrasting qualities between paths. Traffic dispersion system describes how simultaneously accessible ways are utilized, and how data to the same goal is part and flowed over diverse ways. Path support specifies when and how new paths are procured if the states of at present accessible paths change. We display a choice of these protocols and give a discussion on how multipath strategies might be stretched out to wireless mesh networks. In conclusion we quickly portray the path selection structure in the current proposal for IEEE 802.11s mesh standard. Despite the fact that the proposal does not characterize utilization of multipath routing, its extensible system for path selection gives procurement to such protocols to be implemented.

I. INTRODUCTION

A multipath routing is a method that endeavours the fundamental substantial network resources by using several source destination paths. This is utilized for numeral reasons, as well as end-to-end delay minimising, bandwidth aggregation increasing, enhancing reliability, load balancing, fault-tolerance, and so on. The scheme of utilizing multiple paths has existed intended for some time and it has been explored in dissimilar areas of networking. [1] During this method, the shortest path among two connections is used waiting it fails or else reaches its capability, as calls are routed during a longer, alternate path. In data network the idea of using multiple paths for end-to-end transport first appeared in [2]. The initial distributed multipath algorithm was formulated by Gallager. [3] Depending on the statement of stationary input traffic and rigid network, the computation framework converges to minimise the overall delay in the network. The main disadvantage of Gallager's algorithm is that it is very complicated to implement in the real world, specified that each router needs to contain information of a worldwide constant, which is impossible to determine for all circumstances [4]. Furthermore since the adjustment of parameters in each router is initiated by the destination and is done in iterations, the algorithm tends to come together slowly, or does not come together at all,

consequently restricting its use for networks with stationary or quasi-stationary traffic. On behalf of these reasons, Gallager's system is used for obtaining speculative lower bounds only. The number of improvements to the algorithm has since been projected. [5]

The expansion of Gallager's algorithm using second derivatives was projected to improve the speed of convergence and constraint selection. Here the ATM PNNI pattern [6], every other path may be set up during the reservation process. Once a call fails on a route, the crankback process is started to try multiple alternate paths until a new route is recognized. Inside the Internet, some router implementations may maintain multiple paths with routing protocols such as RIP and OSPF.

Nevertheless the paths are restricted to having equal-costs only. Wireless mesh networks (WMN) engineering have been procurement energy recently due further bolstering its good fortune in certain application ranges, for example, group systems and endeavor spines [7, 8, 9]. A WMN may comprise of portable customers and stationary cross section switches. A system of lattice switches could be utilized to give foundation/spine administrations to work customers. Such a system is known as an Infrastructure WMN (IWMN) [7].

Despite the fact that IWMN is like specially appointed systems in a few regards, for example,

both being multi-hop wireless networks, there are a couple of essential refinements that warrant distinctive steering procedures. Firstly, since mesh routers are stationary, mobility is no more an issue. This implies system topology change is less regular than in Adhoc networks. Also, mesh routing conventions don't have vitality utilization confinements, since mesh routers ought to in all probability be on wired force. Thirdly, the traffic conveyance in a WMN is for the most part skewed. This is on the grounds that most client activity is steered towards/from Internet entryways or application servers on the networks [10]. At last, the IMWN requests better versatility, robust and a scope of different measurements keeping in mind the end goal to viably give infrastructure administrations.

II. WIRELESS AD HOC NETWORKS MULTIPATH ROUTING PROTOCOLS

Various multipath routing conventions have been proposed for ad hoc networks and wireless. Large portions of them focused around the prevalent on-interest routing conventions, DSR [11] and AODV [12]. In this segment we will display a choice of them.

DSR Extension by Napsipuri and Das based on Protocols – A multipath expansion to DSR is introduced in [13]. The principle inspiration of this work is to lessen and proficiently control the recurrence of course revelation surges, since these inherent parts of on-interest convention takes up a lot of accessible system data transfer capacity. The paper exhibits two marginally shifted adaptations of multipath augmentations and a systematic model for assessing the nature of on-interest conventions. The conventions characterize essential source course as the course recognized by the first Route Request (RREQ) message to achieve the end of the line. It is depended on that the essential course speaks to the most brief course more often than not.

Once the essential course is recognized, the end will just answer to those consequent RREQ messages containing course that is connection disjoint to the essential course. At first, movement is directed through the essential course. At the point when a course comes up short, the convention switches to the most brief reinforcement course. Another course revelation is started when all courses have fizzled. In convention 1 of the augmentation, just the source hub is given the decision of exchange courses, accordingly any moderate connection disappointment will result in a makeshift loss of course until the source gets a slip message and switches to another course. Thusly all bundles to the objective upstream from the fizzled connection will be lost for the length of time of the loss of course. Convention 2 allays this issue by permitting halfway hubs to have one

exchange course and switch course when the essential falls flat (Figure 1). Amid the course revelation handle, the end endeavors to supply each one transitional hub in the essential course with a connection disjoint interchange to the end of the line. At the point when a connection falls flat, the first upstream hub with an exchange course devours the blunder message and switches course for all resulting movement. This procedure proceeds until the source hub gets a course slip, when another course revelation is begun.

The major route consists of L_1, L_2, \dots, L_k . Each node in the primary route n_i , has an alternate path P_i to the destination. Alternate routes in [18].

The authors closed, in the wake of performing numerical dissection that, 1. Any type of multipath beats single way directing regarding recurrence of course rediscovery, and 2. Longer interchange ways are less valuable and the execution increase is the less noteworthy utilizing more than two substitute courses.

Split Multipath Routing (SMR) [14] is a likewise multipath variant of DSR. Dissimilar to numerous earlier multipath directing conventions, which keep different ways as reinforcements courses, SMR is intended to use multipath simultaneously by part activity onto two maximally disjoint courses. Two courses said to be maximally disjoint if the quantity of basic connections is least [15].

In SMR, transitional hubs don't answer to Rreqs regardless of the fact that they have courses to the terminus. This is so to build the quantity of Rreqs got at the end. Likewise, middle hubs forward those RREQ parcels got from an alternate connection to the one from which the first RREQ is gotten, given its jump tally is short of what the first RREQ (i.e. has a finer metric). This further expands the quantity of courses got by the end, despite the fact that this takes on at an expense of expanded control overhead. Similarly as with [13], the most brief deferral course, recognized by the first RREQ to touch base at the terminus, is utilized. The objective then chooses the second course as the specific case that is maximally-disjoint to the first course. The creators decided on a for every parcel granularity for allotting activity, contending that the trouble of acquiring system state of a specially appointed system keeps the utilization of more complex assigning plans. At the point when a course fizzles, each section, paying little mind to terminus, in the source's directing table that imparts regular middle of the road hubs to the fall flat course is uprooted. After this if the other course stays substantial, either another course revelation is started or the convention holds up until the second course comes up short, as well. It was demonstrated in recreation that SMR outflanks DSR regarding postponement and bundle drops in

an impromptu system. Moreover, SMR is more effective when new course revelation is started just when both courses are broken, as this plan creates less control overhead. MP-DSR [16] was composed because of Quality-of-Service. It's gone for giving QoS help as far as end-to-end unwavering quality, characterized as the likelihood of having a fruitful information transmission between two portable hubs inside the time period from t_0 to $t_0 + t$, where t_0 is whenever moment. Scientifically, this is characterized as,

$$P(t) = 1 - \prod_{k \in K} (1 - p(k, t))$$

Where K is a situated of hub disjoint ways from the source to the goal. $p(k, t)$ is the way unwavering quality of way k , figured as the result of connection accessibility of every last one of connections in way k . As such, $P(t)$ is the likelihood that no less than one way stays joined for the length of time of t . Given an end-to-end dependability necessity, the convention decides the quantity of ways, m_0 , it needs to find, each of which need to help a base way unwavering quality prerequisite. The course disclosure procedure is begun by the source conveying m_0 RREQ messages. When an intermediate node receives a RREQ, it checks whether the path reliability of the path identified by the RREQ so far still fulfils the required path unwavering quality. In the event that so the RREQ is forwarded to a maximum of m_0 neighbours, else it is disposed of. The end gets all the Rreqs, and chooses a set of hub disjoint ways that join to fulfil a characterized unwavering quality necessity. The set of various ways the goal node picks is not so much the ideal set; the first mixture that fulfils the prerequisite gets chose.

MP-DSR occasionally checks the end-to-end dependability to guarantee the characteristics of the courses. Another course revelation is launched when either the unwavering quality is no more regarded worthy, or when all ways fall flat. It was indicated in re-enactment that MP-DSR has better achievement conveyance rate, control overhead proportion, and lapse degree, over DSR in a 20 mobile node system.

III. MULTIPATH ROUTING IN WIRELESS MESH NETWORKS

Multipath routing in infrastructure mesh networks obliges an alternate methodology to that utilized in ad hoc networks to address the vicinity of stationary backbone routers. In this area we look at two regions of research where we consider multipath routing has incredible potential in enhancing performance in infrastructure mesh routing.

Multi-radio, multi-channel

As the expense of equipment descends, multi-radio and multichannel advances are esteemed by a lot of

people as a reasonable answer for some connection limit and dependability issues [17]. Since base cross section switches have less cost, vitality and asset limitations than specially appointed hubs, the application of the innovation to in IWMN appears to be especially alluring [7]. Various studies [10, 27, 25, 26] have been introduced on the limit and attributes of system utilizing multi-radio and multi-channel hubs. In [18] another metric for directing in multiradio, multi-bounce systems is exhibited. The metric, called Weighted Cumulative ETT (WCETT), was intended to be utilized to choose channel differing ways. It is focused around Expected Transmission Time (ETT), a capacity of the misfortune rate and the data transmission of the connection, and ascertains a weighted normal of EETs of connections in a path. [19] Improves upon the single-way choice in [18] and exhibited a metric for selecting different ways. Channel Aware Multipath (CAM) considers both single way WCETT and a between way impedance file, so course coupling might be lessened. The above studies into multipath steering focus on system estimations as way determination measurements. Despite the fact that channel differing qualities is expanded, spatial differences is overlooked and way unwavering quality could endure thus. Future work here could incorporate the investigation of calculations that join topological disjointness and multi-channel measurements.

IV. APPROXIMATION ALGORITHMS FOR MULTIPATH

In this segment we exhibit two calculations for the Minimum Cost Blocking issue with stationary hubs. The first is an eager calculation and the second one LP-based. We determine the close estimation degree for both of them. We first characterize the idea of "spread" which will be utilized oftentimes within later exchanges and after that rundown a few documentations required to depict the calculations.

Definition: When a hub (or a hub inside a subset of hubs) is on a way, we say that the hub (or the subset of hubs) covers that way. At the point when R_i ways having a place with a hub i are secured, we say that hub i is secured.

Greedy Algorithm and Approximation Ratio

The greedy algorithm chooses the most cost effective node iteratively and in the meantime removes the covered paths and the paths unusable in the future.

Inoperative paths are those originating from a node i with at least R_i paths already blocked, as covering these paths would be insignificant. The algorithm runs until the nodes in T have covered the required paths for all the nodes in V , i.e., T covers at least

Ri paths for node i, where $i = 1, \dots, k$. This situation is termed as "Done" [28].

Algorithm :

1. $T \leftarrow \emptyset$, and mark all paths and nodes as uncovered;

2. While not Done, iterate the following sub-steps:

2.1. For every remaining node in

$V \setminus T$, say, node i, in the current

iteration, compute its effective

number E_i as follows:

$$E_i \leftarrow 0$$

2.1.1. For every node j that is not

Covered yet, compute

$$\min(\max((R_j - Y_j), 0), W_{ij}).$$

Update

E_i as follows:

$$E_i = E_i + \min(\max((R_j - Y_j), 0), W_{ij})$$

2.2. Compute the cost-effective

index α_i as follows:

$$\alpha_i = c_i / E_i$$

2.3. Choose node u with the lowest cost effective index (α_u); Mark every path node u covers as covered; For every effective path p that node u covers, set the price of the effective path, i.e., $\text{price}(p) = \alpha_u$; Iterate through all the currently uncovered nodes; Mark those nodes that have been covered by node u in this iteration as covered; Add node u to T, i.e.,

$$T \leftarrow T \cup u$$

Next we show that Algorithm 6.2 achieves an approximation ratio of $\ln R$,

where $R = \sum R_i$.

Theorem : Algorithm achieves an approximation ratio of $\ln R$.

Proof: The proof is similar to the proof for the ratio of the greedy algorithm for set cover problem in [50]. Suppose the optimum solution has a cost OPT. We number the covered effective paths in the algorithm in the order in which they are covered, and name them as P_1, \dots, P_R . In every iteration in the algorithm, the new optimal solution (selected from $V \setminus T$) that covers the remaining nodes (that are not covered yet) has a cost at most OPT. Among them, there must be one node that has cost-effective index at most OPT/U , where U is the number of uncovered effective paths (otherwise the optimum solution will have a cost greater than OPT). In the iteration that covers path P_j , there are

at least $R-j+1$ paths not yet covered. Because we choose the node with

lowest cost-effective index, we have $\text{price}(P_j) \leq \text{OPT} / R-j+1$.

The total cost of our algorithm will be

$$\text{price}(P_j) \leq (1 + \dots + \dots) \times \text{OPT}$$

$$\leq \text{OPT} \times \ln R$$

If we adopt the algorithm SetCover for partial set cover in [28], which is based on LP relaxation, then we get a new algorithm which is described next.

LP Algorithm and Approximation Ratio

The LP Algorithm uses a function SetCover($P, V \setminus T, c, R_j$), where P is the set of all uncovered paths belonging to node j, c is the array of cost values for nodes in $V \setminus T$ (i.e., $c_j, \forall j \in V \setminus T$). The function SetCover returns the selected sets (nodes) that cover at least R_j paths in P.

Algorithm :

1. $T \leftarrow \emptyset, D \leftarrow \emptyset$

2. While D does not contain all nodes in the graph,

iterate the following sub-steps:

2.1. Choose node j with the highest R_j

value;

Call SetCover($P, V \setminus T, c, R_j$);

2.2. $D \leftarrow D \cup j$

2.3. For every node returned by the

function,

$$T \leftarrow T \cup i$$

2.4. Remove from P, every path that

is covered by the nodes returned

by the function call SetCover;

$$P \leftarrow P \setminus p$$

2.5. For every $i \in V \setminus D$, adjust R_i as

follows:

$$R_i = \max(0, R_i - O_i); \text{ If } R_i$$

becomes 0 (it means that node i

is blocked); $D \leftarrow D \cup i$

Output T.

Algorithm repeatedly blocks a node in every iteration (Step 2), until all nodes are blocked. Note that in Step 2.5 of Algorithm 6.4, O_i is the number of paths belonging to node i that were covered by the set of nodes returned by SetCover.

Theorem 6.5: Algorithm achieves an approximation ratio of $h \times k$, where h is the length (number of nodes in the path) of the longest path.

Proof: The approximation ratio of algorithm Set-Cover is h [28]. Apparently at every iteration the sum of the cost of selected nodes $< h \times \text{OPT}$, so the total cost of the solution returned by Algorithm is $\leq h \times k \times \text{OPT}$.

The approximation ratios obtained above are common performance process for the algorithms. It is complicated to compare the two, i.e., the values $h \times k$ and in R, since they depend on specific problem instances. Furthermore, these ratios are far from tight because accurate analysis is very difficult. It is an open research issue to determine if any better algorithms (algorithms with guaranteed better ratios) exist.

V. ROUTING BASED ON GEOGRAPHIC

Geographic routing conventions [20, 21, 22] use area data, for example, directions to forward parcels. The area of the source, the end, and neighbour hubs are utilized to settle on sending choices. Geographic steering conventions commonly have great adaptability, since almost no directing data is traded in the system. Then again, before directing a bundle, the source hub needs to gather the area of the goal. Thusly, an effective and adaptable area administration is pivotal to the execution of geographic directing, and there have been various results [22, 23, 24]. In framework Wmns, since hubs are stationary, there is next to no requirement for successive area overhauls. Accordingly the execution of area administration no more directs the viability of directing. Multipath directing conventions can profit from geographic routing in that area data could be utilized to build a more precise system topology, so that disjoint ways are all the more effectively recognized.

802.11s Mesh Standard Proposal

802.11s [39] is the IEEE 802.11 standard for remote LAN cross section organizing. The current proposal points out an extensible skeleton for layer two way choice conventions help. Separated from the required convention and metric that all execution must backing for interoperability reasons, the structure permits extra conventions and measurements to be actualized. The default way choice convention in the 802.11s proposal is Hybrid Wireless Mesh Protocol (HWMP). It underpins both on interest and proactive tree-based steering. The benchmark on interest convention is called Radio Metric AODV (RM-AODV). It stretches out AODV [12] to backings utilization of self-assertive way measurements in distinguishing best-metric ways. At the point when a system substance called Root is available in the lattice, a proactive separation vector directing tree might be

kept up. Since the Root knows course to all hubs in the cross section, a way between two hubs might be created rapidly by questioning and steering through the Root. The low way disclosure postpone in this plan implies that the proactive way might be utilized amid on-interest course revelation process. In spite of the fact that the 802.11s proposal does not help multipath in its pattern convention, the way choice structure might be effectively reached out to incorporate multipath empowered conventions and measurements. The lattice hubs can switch between conventions as indicated by their application needs. Given this, how multipath directing could be adjusted into the current proposed cross section system structural engineering/pecking order stays to be examined.

VI. CONCLUSION

In this paper we show the idea of multipath routing with attention on its applications on remote impromptu and cross section systems. We have recorded the profits of utilizing multipath calculations in routing, and depicted its three components, in particular way disclosure, activity appropriation, and way support. We additionally give depictions of various multipath directing plans proposed for remote specially appointed systems, going for demonstrating different methods of using numerous routings in remote systems. A rundown of these conventions is given, highlighting their gimmicks and attributes. We have recognized a few ranges in framework remote lattice organizes that oblige further work. Momentum multipath routing exploration concentrate on multi-radio and multi-channel hubs is to give enhanced measurements to way choice furthermore to address channel assignments and exchanging. One conceivable course is to join channel and spatial differences into way determination calculations. At last, we inspected way determination structure in the joint 802.11s proposal. While the default convention does not use multipath methods, the extensible skeleton implies that new multipath conventions and related measurements may be effectively added to help particular applications. As a part of our ongoing research, we also investigate the approximation algorithms for the Minimum Cost Blocking problem

VII. REFERENCES

- [1]. B. Hurley, C. Seidl, and W. Sewell, "A survey of dynamic routing methods for circuit-switched traffic," *Communications Magazine*, IEEE, vol. 25, pp. 13-21, 1987.
- [2]. N. F. Maxemchuk, "Diversity Routing," in *Proc. IEEE ICC*, San Francisco, CA, 1975.
- [3]. R. Gallager, "A Minimum Delay Routing Algorithm Using Distributed Computation,"

- Communications, IEEE Transactions on [legacy, pre - 1988], vol. 25, pp. 73-85, 1977.
- [4]. S. Vutukury and J. J. Garcia-Luna-Aceves, "A simple approximation to minimum-delay routing," in Proceedings of the conference on Applications, technologies, architectures, and protocols for computer communication. Cambridge, Massachusetts, United States: ACM Press, 1999.
- [5]. D. Bertsekas, E. Gafni, and R. Gallager, "Second Derivative Algorithms for Minimum Delay Distributed Routing in Networks," Communications, IEEE Transactions on [legacy, pre - 1988], vol. 32, pp. 911-919, 1984.
- [6]. "Private Network-Network Interface Specification v.1.1.1," ATM Forum, 2002.
- [7]. I. F. Akyildiz, X. Wang, and W. Wang, "Wireless mesh networks: a survey," Computer Networks, vol. 47, pp. 445-487, 2005.
- [8]. StrixSystems, <http://www.strixsystems.com/>
- [9]. Firetide, <http://www.firetide.com/>
- [10]. A. Raniwala and T.-c. Chiueh, "Architecture and algorithms for an IEEE 802.11-based multi-channel wireless mesh network," INFOCOM 2005. 24th Annual Joint Conference of the IEEE Computer and Communications Societies. Proceedings IEEE, 2005.
- [11]. D. B. Johnson and D. A. Maltz, "Dynamic Source Routing in Ad Hoc Wireless Networks," in Mobile Computing, Imielinski and Korth, Eds.: Kluwer Academic Publishers, 1996.
- [12]. C. Perkins, "Ad hoc On-Demand Distance Vector (AODV) Routing," IETF RFC 3561, 2003.
- [13]. A. Nasipuri and S. R. Das, "On-demand multipath routing for mobile ad hoc networks," Computer Communications and Networks, 1999. Proceedings. Eight International Conference on, Boston, MA, 1999.
- [14]. S. J. Lee and M. Gerla, "Split multipath routing with maximally disjoint paths in ad hoc networks," ICC 2001. IEEE International Conference on Communications, Helsinki, 2001.
- [15]. N. Taft-Plotkin, B. Bellur, and R. Ogier, "Quality-of-service routing using maximally disjoint paths," Quality of Service, 1999. IWQoS '99. 1999 Seventh International Workshop on, London, 1999.
- [16]. R. Leung, J. Liu, E. Poon, A. L. C. Chan, and B. Li, "MP-DSR: a QoS-aware multi-path dynamic source routing protocol for wireless ad-hoc networks," Local Computer Networks, 2001. Proceedings. LCN 2001. 26th Annual IEEE Conference on, Tampa, FL 2001.
- [17]. P. Bahl, A. Adya, J. Padhye, and A. Walman, "Reconsidering wireless systems with multiple radios," SIGCOMM Comput. Commun. Rev., vol. 34, pp. 39-46, 2004.
- [18]. R. Draves, J. Padhye, and B. Zill, "Routing in multi-radio, multi-hop wireless mesh networks," International Conference on Mobile Computing and Networking, Philadelphia, PA, USA, 2004.
- [19]. I. Sheriff and E. Belding-Royer, "Multipath Selection in Multi-radio Mesh Networks," Broadnets, San Jose, 2006.
- [20]. B. Karp and H. T. Kung, "GPSR: greedy perimeter stateless routing for wireless networks," in Proceedings of the 6th annual international conference on Mobile computing and networking. Boston, Massachusetts, United States: ACM Press, 2000.
- [21]. H. Li and M. Singhal, "A scalable routing protocol for ad hoc networks," Vehicular Technology Conference, 2005. VTC 2005-Spring. 2005 IEEE 61st, 2005.
- [22]. Y.-B. Ko and N. H. Vaidya, "Location-aided routing (LAR) in mobile ad hoc networks," Wirel. Netw., vol. 6, pp. 307-321, 2000.
- [23]. D. S. J. De Couto and R. Morris, "Location Proxies and Intermediate Node Forwarding for Practical Geographic Forwarding," MIT Laboratory for Computer Science technical report, 2001.
- [24]. C. T. Cheng, H. L. Lemberg, S. J. Philip, E. van den Berg, and T. Zhang, "SLALoM: a scalable location management scheme for large mobile Adhoc networks," Wireless Communications and Networking Conference, 2002. WCNC2002. 2002 IEEE, 2002.
- [25]. M. Kodialam and T. Nandagopal, "Characterizing the capacity region in multi-radio multi-channel wireless mesh networks," in Proceedings of the 11th annual international conference on Mobile computing and networking. Cologne, Germany: ACM Press, 2005.
- [26]. A. Raniwala, K. Gopalan, and T.-c. Chiueh, "Centralized channel assignment and routing algorithms for multi-channel wireless mesh networks," SIGMOBILE Mob. Comput. Commun. Rev., vol. 8, pp. 50-65, 2004.

- [27]. P. Kyasanur, S. Jungmin, C. Cherreddi, and N. H. Vaidya, "Multichannel mesh networks: challenges and protocols," *Wireless Communications, IEEE* [see also *IEEE Personal Communications*], vol. 13, pp. 30-36, 2006.
- [28]. R. Gandhi, S. Khuller, and A. Srinivasan, "Approximation algorithms for partial covering problems," *Journal of Algorithms*, vol. 53, pp. 55-84, 2004.

AUTHORs PROFILE

Ms. G.Suresh pursuing MTech from Nova College of Engineering & Technology. His Research interest in Data Mining.



Ms. V.Annie Radhika is a qualified person Holding B.Tech & M.Tech Degree in CSE from JNTU Kakinada, She is an Outstanding Administrator & Coordinator. She is working as an Assistant Professor in NOVA College of Engineering Technology .She guided students in doing IBM projects at NOVA ENGINEERING College. Who has Published 2 research Papers in various international Journals and workshops with her incredible work to gain the knowledge for feature errands.



Dr. Srinivas Rao J received Ph D from CMJ University Meghalaya, M.Tech in Computer Science & Engineering from KL University in 2008. INDIA .He is an Outstanding Administrator & Coordinator. He is having 16 years of experience and handled both UG and PG classes. Currently he is working as a Director & Professor in NOVA College of Engineering Technology, Vijayawada, A.P, INDIA . He has Published 42 research Papers in various international Journals and workshops with his incredible work to gain the knowledge for feature errands.

