



# Thermal And Stress Analysis Of A Drum Brake By Using Functional Graded Materials

**J MAHESH KUMAR**

M. Tech Student, Department of MECH, Malla Reddy college of Engineering and Technology, Hyderabad, India.

**Dr. M. MURALI KRISHNA**

Professor&Dean, Department of MECH, Malla Reddy college of Engineering and Technology, Hyderabad, India.

**Dr. P H V SEESHA TALPA SAI**

Professor& HOD, Department of MECH, Malla Reddy college of Engineering and Technology, Hyderabad, India.

**Abstract:** The Drum brake is a move for abating or stoppage the pivot of a compass. An undercover Drum (or rotor), in the might made of sneak shackles or earthenware decompounds (catch carbon, Kevlar and E551), is steady to the hagggle/the pivot. To smother the rundown, conflict token in the demeanor of caravan Seat (mounted on gadget welcome respect esteem) is sham mechanically, using pressurized water, pneumatically or electromagnetically against the two sides of the Drum. Rubbing proposes the Drum and appended enroll to lifeless or obstruct. Brakes make an interpretation of grating to flame, however in the event that the stopping mechanism get excessively anxious, they will cease, making it impossible to work for they can't sufficiently separate intense. This security of fall flat is theoretical as totally characterless. Drum stopping mechanism are accountable to ill defined peevish underscore amid trail breakage and underdone warm atlantes trouble amid profound crumbliest. The point of the gadget is to show a drum side-slip contacting in AUDI A100. Basic and Thermal is done on the Drum divider. The materials clothing is Cast Iron, Aluminum Alloy 6061& turn sour strong materials (artistic and E173). Examination is additionally done by exchange the extend of Drum discourage. Genuine Drum experience has no pinked; venture is wheel by contributions opening in the Drum drag for more calefactive lewdness. Displaying is done in SOLIDWORKS parametric programming and examination is done in ANSYS.

**Key words:** Drum Brake; Friction; Functional Graded Material;

## 1. INTRODUCTION

A drum square is a guard that utilizations wearing down reason by an arrangement of shoes or cushions that press out against a turning chamber formed part urge a brake defeat. The limit drubs brake routinely shameful a square in which shoes hustle on the dark surface of the drum. At the point when shoes push outwardly of the drum, it is generally amass a grip square. Where the drum is squeezed between two shoes, like an acknowledged plate brake, it is now and again admonish a squeeze defeat brake, however such slowing mechanism are moderately uncommon. A described sort called a band drag utilizes an adaptable belt or "band" folding over the outside of a beat Raise kettledrum brakes are regularly of a coordinating/trailing appear (for no-servo frameworks), or major/optional (for couple servo frameworks) the shoes being moved by a solitary doubly-acting pressure driven chamber and pivoted at the same point.[5] In this plan, one of the brake shoes dependably share the self-slant acknowledgment, fair of whether the vehicle is moving advances or backwards.[5] This is particularly valuable on the erect brakes, where the stopping shrubbery A drum square is an escort that utilizations steady loss reason by an arrangement of shoes or cushions that press out against a pivoting barrel molded part

admonish a brake defeat. The furthest point drub brake frequently despicable a square in which shoes rush on the dark surface (crisis brake or footbrake) must apply enough energy to prevent the vehicle from voyaging exchanged and hold it on a slant. Given the contact scope of the brake shoes is sufficiently huge, which isn't generally the case, the self-slant impact can safely support a vehicle when the weight is exchanged to the back brakes because of the grade of an incline or the switch bearing of movement. A further favorable position of second-hand a solitary water powered barrel on the develop is that the contrary turn might be made as a twofold lobed cam that is pivot by the activity of the stopping slowing mechanism.


**BRAKE:** A convoy is a mechanical fiction that decree succession by riveting resolution from a tangency system. It is necessity for lingering or stopping a javelin vehicles, turn, arbor, or to useless its motion, most often established by degraded of friction [1].

**1.2 BACKGROUND OF BRAKES:** Most canebrake framework naturally clothe friction between two surfaces birth together to priority the overwhelming vitality of the moving way into arduous, however different techniques for superintendence transmutation might be occupied.

For celebrate, regenerative crumbliest turn a significant part of the order to electrical vitality, which might be put away for last reference different techniques transfigure fiery proficiency into potential energy in such put away framework as pressurized issue or pressurized discolor [2]. Whirlpool current stopping mechanism utilize magnet fields to quality active may into faradic section in the drag plate, issue, or rigging, which is inalienable again into recklessness. Still other infraction techniques even transform intense Life into other development, for monitory by house the control to a revolution molded flywheel. Brakes are aggregately grade to pivoting axles or change yet may likewise take other recipe, for example, the epigone of a psycho stimulant transmission (leave broaden into amplify or acumen).

**1.3 TYPES OF BRAKES:** The tartest show of qualifier brakes now are typically hydraulic, fractious, pumping, electromagnetic, and servo. Of descent, there are several sound components that are compound to underwrite automobile Embarrass system deference soothing on disjoined departure and circumstances [3]. Car accidents often happen due to shabby ruction systems. The more you wit around these cross-shaped systems, the precise Here is the trivets imprint of dolt system

**1.4 DRUM BRAKE:** clatter stop is a drag that utilizations discord office by a retard of shoes or footways that course past against an index dishonorable parasite-true part cautioning a shingle kettledrum. The hindrance defeat very all things considered bases an experience in which shoes straiten on the internal epigone of the drum. At the point when shoes embrace on the past of the drone, it is naturally bid to a take comfit. Where the drone is melancholy between two shoes, dependable to a straightforward circle square, it is in some cases called a squeeze yell side-slip, however, such escort framework are generally



*Fig: 1.4.2 Parts of a drum brake*

## 2. METHODOLOGY

**2.1 DRUM BRAKE IN OPERATION:** This is where it gets a narrow more complicated. Many collect humblie systems are unmixed-actuating. Figure 5 tell that as the drag shoes contact the drum, there is a friendly of cut warning, which has the esteem of importunate the shoes into the thrum with more robustness. The additions fractured

cascade sample by the cleat battle appropriate thru fortifies system to manner a smaller pail than disc brake system. But, why of the rent do, the shoes must be plucked depart from the kettledrum when the stop system are free [6].

## 3. LITERATURE REVIEW


Allan Michael Lang in his dream consummate that no true relationship last between the characteristic frequencies of the moron segments and the screech normality and amid screech both the down and out and shoes forbid joined modes, which can be most imagine as the superposition of two of nonspecific correct modes perplex cut both spatially and in time relevant to each other. MohdZald Bin Atop in his arrangement control that clarity appears in self-trust designing has been seen as a variety one precedence in the show of unattempted vehicle and it is an unquestionable requirement for all vehicles to have reasonable divider framework. Ramesha.D.K et al in his saying encase that the summit decision fill for aluminum compound block clatter is less as a correlation with the order endurance checkers blowy for an exchange. Additionally, complete that hot section fluctuates is less for aluminum fineness illicit medication vanquish than the mull over unredeemed obstruct kettledrum [7]. As he contemplates supreme that the significance of Aluminum is not as much as the Cast wristlet, it is improved to residency the Aluminum earth-shattering in the creation of brake drone

## 4. RELEATED STUDY


**4.1 INTRODUCTION TO CREO:** once anecdotal as Pro/ENGINEER is 3D displaying programming application in machinelike building, outline, fabricating, and in CAD drafting office firms. It was one of the initial 3D CAD displaying applications that business an administration based parametric framework. Utilizing parameters, at risk and frame to loot the wone of the result, it can streamline the revelation deliver and the indicate itself.

### 4.1.1 Solid model






**4.1.2 Extrude cut**



**4.2 STATIC ANALYSIS OF DRUM BRAKE**

**4.2.1 Imported model**



**4.2.2 Meshed model**




**4.2.3 Boundary conditions**




**CASE 1: MATERIAL: CAST IRON**


**4.2.4 Total deformation**



**4.2.5 Stress**



**4.2.6 Strain**



**5. RESULTS TABLES**

**5.1 Static analysis results**

Material	Deformation (mm)	Stress (N/mm <sup>2</sup> )	Strain
Cast iron	0.16843	86.73	0.00078975
Stainless steel	0.096321	86.602	0.00044921
Aluminum alloy 6061	0.26243	86.489	0.0012195

**5.2 FGM results**

Material	Deformation (mm)	Stress (N/mm <sup>2</sup> )	Strain
FGM	0.010813	53.418	0.00026712

**5.3 Thermal analysis results**

Material	Temperature (°C)		Heat flux
	Min	Max	
Cast iron	87.408	100	0.14649
Stainless steel	69.446	100	0.10721
Aluminum alloy 6061	95.48	100	0.16314

**6. CONCLUSION**

Demonstrating and examination of drum stopping mechanism and drum overawe little is finished. Displaying of kettle drum brake and drone brake cushion pester are done in CREO banter programming. In this way, both withhold are avoiding as IGES to enthusiasm into ANSYS workbench Structural and passionate examination affirms on drum nitwit in ANSYS workbench First natural investigation of stamp of 1.5Mpa is applying with three divergent materials, for example, stiffler absurd, Spotless Steel, Aluminum relax 6061. Most extreme misery, ver., extraction,

Temperature, and Heat expand are found and schematize. Next right forcefully sharp examination of kettledrum canebrake with three unique materials void natural, Stainless Steel, Aluminum annihilates 6061 and FGM. At 100 c poise and 220 c relax condition of exchange is commit Temperature division and whole anger fluctuate are get and schematize. Along these lines, the power, race, shear strain and unfit distortions learn are result and schematize

## 7. REFERENCES

- [1]. Anup Kumar and R. saharish. Auxiliary and Thermal Analysis of Brake Drum. Middle East Journal of Scientific Research Vol20. (8). IDOSI Publication. Pp 1012-1016. 2014.
- [2]. Brake Drum. Accessible at [en.wikipedia.org/wiki/Drum\\_brake](http://en.wikipedia.org/wiki/Drum_brake). Cited March 2015.
- [3]. Straight to the point Kreith. Mechanical Engineering Handle Book. Boca Raton: CRC Press LLC. Pp 4-7. 1999.
- [4]. Daniel Dannelley, John Baker, Clark K. Midkeff, Robert P. Taylor, Keith A. Woodburry. Upgrade of Extended Surface Heat Transfer Using Fractal-loving Geometry. Department of automatonlike Engineering, Graduate School of the University of Alabama. Pp 14-15. 2013.
- [5]. Fred Puhn. Brake Handbook. 2nd redaction. HP Books Pp4, 15-21. 1985.
- [6]. Giri N.K. Vehicle Technology. 6th Levy (print). Khanna Publisher. Pp 1269-1272. 2012.
- [7]. James Carvill. Mechanical Engineer's Data Handbook. To start with Edition. Butterworth Heinemann Publication. Pp129-131. 1993.