Georgia Southern University Digital Commons@Georgia Southern

Georgia Southern University Research Symposium

Apr 24th, 10:45 AM - 12:00 PM

Design and Implementation of an Interactive Animatronic System for Guest Response Analysis

Brian Burns Georgia Southern University, bb02015@georgiasouthern.edu

Follow this and additional works at: https://digitalcommons.georgiasouthern.edu/ research_symposium

Part of the <u>Biomechanical Engineering Commons</u>, <u>Electro-Mechanical Systems Commons</u>, and the <u>Interactive Arts Commons</u>

Recommended Citation

Burns, Brian, "Design and Implementation of an Interactive Animatronic System for Guest Response Analysis" (2015). *Georgia Southern University Research Symposium*. 37. https://digitalcommons.georgiasouthern.edu/research_symposium/2015/2015/37

This presentation (open access) is brought to you for free and open access by the Conferences & Events at Digital Commons@Georgia Southern. It has been accepted for inclusion in Georgia Southern University Research Symposium by an authorized administrator of Digital Commons@Georgia Southern. For more information, please contact digitalcommons@georgiasouthern.edu.





Introduction

• Within entertainment applications, animatronics must be identified as human partners to establish status for dynamic interactions for enhanced acceptance and effectiveness as socially-interactive agents. This research covers the design and implementation for human identification using a depth camera (Carmine from PrimeSense), an open-source middleware (NITE from OpenNI), Java-based Processing and an Arduino microcontroller into an animatronic dragon. Using the data from depth camera, people are identified by approximating a person's skeletal information. Based on the movements of the individual, the program tracks a human body, or bodies, within the camera's field of view. Joint locations, in the tracked human, are isolated for specific usage by the program. Joints include the head, torso, shoulders, elbows, hands, knees and feet. The dragon capabilities include a four degreesof-freedom neck, moving wings, tail, jaw, blinking eyes and sound effects. These outputs instigate a movement in the tracked human, which establishes the cycle of human to animatronic interactions. This animatronic creature design will allow for future research in the effectiveness of interactive elements in themed environments.

Hypothesis

- A people-aware, autonomous, animatronic system can be designed for testing effectiveness of interactive animatronics.
- Interactive, animatronic behavior will be more entertaining than passive behavior.

Guest Feedback • Two small studies have been conducted with elementary school students and college students. No statistical difference was found between passive and interactive behaviors with the children. College students, without prior exposure to Kronos, ranked interactive behavior greater than passive. Passive vs Interactive Modes with College Students without **Prior Exposue to Kronos** 12.0 10.0 8.0 Passive Interactive Lifelike

Survey Question

Design and Implementation of an Interactive **Animatronic for Guest Response Analysis**

Author: Brian Burns, Advisor: Biswanath Samanta, PhD, Collaborator: Justin Hinkley Department of Mechanical Engineering, Georgia Southern University, Statesboro, GA 30460, USA

Design and Fabrication

• The outputs of the dragon include a head with four degrees of freedom, moving jaw, blinking eyes, expanding wings, shifting tail and sound effects.





• The animatronic dragon, Kronos, was custom designed and fabricated for research purposes. The dragon sits atop a table that houses electrical and mechanical components. The table is approximately 32 inches deep and 42.5 inches in width. The dragon is affixed to the table; the majority of the motion capabilities are involved with the head and neck. This allows for the dragon to "watch" humans. Most of the hardware components were housed underneath the table in order to reduce mechanical noise and ease of maintenance and assembly.





Vision and Control

• The key input to the dragon for interactive behavior is the depth camera. The PrimeSense Carmine was chosen for the project and is pictured in the image below.

Infrared projector



• A depth camera holds a large advantage over a color camera in many robotic applications. Instead of identifying objects based on color, objects are identified by pixel locations in space. In the images to the upper right, white pixels represent the closer objects to the camera while the black represents those that are farthest away. The projector emits an irregular pattern of infrared dots of varying intensities. The infrared camera recognizes the pattern and constructs a depth image.







• To the left, is a screen capture of the program tracking the nearest pixel in the infrared image. A blue circle is drawn over the identified pixel.

> The x, y, and z coordinates of the head position are recorded and sent to the microcontroller. The program is capable of tracking multiple people at once.

• All programming utilized OpenNI and NITE middleware libraries inside the Java-based Processing software. The software initiates a "handshake" with the Arduino microcontroller in order to relay the coordinates. The microcontroller serves as the central 'hub' of control and utilizes calibration equations to turn the coordinates into position commands for the motors and actuators, as well as, signals to the audio processor.

→ PC
Arduino Mega 256
↑ Mode Switch
The abo for the behavio
 Sopen- Mechan coordin calibrat was imp success
Peck Bend Output Position (8-bit target)
 Kronos improve life cycl include networ
 I would work or Biswana my fam
V

The Allen E. Paulson College of **Engineering and** Information Technology



ove diagram displays the control flow diagram interactive, animatronic system. The interactive or is a closed loop system while passive behavior -loop.

nical positions were recorded in parallel with the ates of a tracked person in order to develop tion curves. A surface curve equation of best fit plemented into the Arduino microcontroller for sful calibration of people tracking.



Conclusion

has been fully fabricated and implemented. Small ements are being made to improve robustness and le use of the entire system. Future work will the integration of the system into a cloud robotic k and facial expression recognition.

Acknowledgements

like to thank Justin Hinckley for his fantastic n the sculpture of Kronos, Dr. Brian Vlcek and Dr. ath Samanta for the research opportunity, and nily for their continued support and contributions.

Vant to see Kronos in action? Go to: thebrianburns.wordpress.com