



Missouri University of Science and Technology

Scholars' Mine

International Conferences on Recent Advances 1995 - Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics Engineering & Soil Dynamics

06 Apr 1995, 10:35 am - 11:00 am

General Report – Session XII: Machine Foundations and Model Tests

Vijay K. Puri Southern Illinois University, Carbondale, IL

Toyoaki Nogami University of California, La Jolla, CA

Amir Kaynia Norwegian Geotechnical Institute, Oslo, Norway

Follow this and additional works at: https://scholarsmine.mst.edu/icrageesd

Part of the Geotechnical Engineering Commons

Recommended Citation

Puri, Vijay K.; Nogami, Toyoaki; and Kaynia, Amir, "General Report – Session XII: Machine Foundations and Model Tests" (1995). *International Conferences on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics*. 12.

https://scholarsmine.mst.edu/icrageesd/03icrageesd/session18/12

This Article - Conference proceedings is brought to you for free and open access by Scholars' Mine. It has been accepted for inclusion in International Conferences on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics by an authorized administrator of Scholars' Mine. This work is protected by U. S. Copyright Law. Unauthorized use including reproduction for redistribution requires the permission of the copyright holder. For more information, please contact scholarsmine@mst.edu.

General Report - Session XII Machine Foundations and Model Tests

Vijay K. Puri Southern Illinois University Carbondale, IL, USA

Toyoaki Nogami University of California La Jolla, CA, USA Amir Kaynia Norwegian Geotechnical Institute Oslo, Norway

vertical and horizontal modes of vibration.

GENERAL REMARKS

There are seven papers in this session dealing with different aspects of analysis and design of foundations for machines. These papers can generally be placed into the following categories:

- * Analysis of machine foundations.
- * Analysis for control of vibrations.
- * Interaction between adjacent machine foundations.
- * Effect of vibrations due to machine operation on adjacent foundations and structures.
- * Reliability aspects of machine foundation design.

Some papers are broad based and cover more than one aspect.

ANALYSIS OF MACHINE FOUNDATIONS

There are three papers on this topic. A glance through the existing literature reveals that forcing functions of the type P_oe^{iot} have been extensively used in deriving equations for the stiffness and damping parameters for the machine foundation-soil system. (Arnold et al. (1955), Bycroft (1956,1959), Hsieh (1962), Hall (1967) and Dobry and Gazetas (1985, 1986)). These parameters are then used in an appropriate analog for predicting the resonant frequency and amplitude of vibration of the foundation (Das (1992), Prakash and Puri (1988), and Richart, Hall and Woods (1970)). Truong and Moore (1995) have used periodic forcing function of the type

$P(t) = P_oT + P_osin\omega t$

for obtaining the stiffness and damping values for vertical and sliding modes of vibration. They have used the concept of wave propagation in a perfectly elastic half space in developing "new expressions" for stiffness and damping (Hsieh, (1962) and Lysmer and Richart (1966)). The expressions for stiffness and damping are observed to depend on the forcing function. The resonant frequency and the amplitude of vibration are not affected by the forcing function. The authors have also observed that the apparent soil mass participating in vibrations is different for

Mashhor, Abdel-Salam and El-Nggar (1995) have presented a numerical procedure for computing the frequency-dependent impedance matrix for the vertical vibrations of a rigid rectangular footing resting on a homogeneous, isotropic elastic half space, using the boundary element method. The contact interface of the foundation and the soil medium is subdivided rectangular subdivisions. The soil for into soil footing contact surface is assumed as a relaxed boundary. Numerical integration is conducted to obtain the subgrade compliance matrix. The impedance matrix of the subgrade is then obtained by inversion of the compliance matrix. The compliance matrix and the impedance matrix depend on the excitation frequency, the plane configuration of the foundation and the properties of the underlying The results have been soil. presented as impedance function Vs dimensionless frequency plots for several values of poisson's ratio of the soil and aspect ratios of the foundation. The authors have found good agreement with the work of Israil and Banerjee (1990).

Gucunski (1995) has presented the results of a parametric study dealing with the response of a flexible circular foundation embedded into a visco-elastic half-space and a layered halfspace system consisting of a single layer overlying a half-space. The "ring method" approach (Lysmer (1965); Wass (1980)) was used to discretize the foundation into a number of rings. The stiffness matrix of the of the foundation was obtained by the finite difference energy method. The matrix of influence coefficients for the layered system was obtained by following the stiffness matrix approach. The effect stiffness ratio, dimensionless frequency, shear wave velocity ratio, and layer thickness to foundation radius ratio was studied. The results of the study indicate that the response of a flexible foundation to vertical vibrations circular differs significantly from the response of a rigid foundation. The point of application of the load was also found to affect the response .

ANALYSIS FOR CONTROL OF VIBRATIONS

The paper on this subject by Abdel-Rohman and Al-Sanad (1995) discusses the use of a tuned mass damper for controlling the nonlinear vertical vibrations of a foundation resting on a sand deposit. A comparison was made of the response of the foundation with and without the damper. The authors have observed that the tuned mass damper is able to control the amplitude of vertical nonlinear vibrations of the foundation within certain frequency range depending on whether the damper is linear, softening non-linear, or hardening nonlinear.

INTERACTION BETWEEN ADJACENT MACHINE FOUNDATIONS

The interaction between adjacent machine foundations may make the vibration problem rather complex. This interaction may adversely affect the performance of the machines if it is not adequately accounted for in the design. Lee and Bohinsky (1995) conducted a case study to evaluate the interaction effects between two (1995) conducted a case study to identical variable speed rotating machines located on a flexible concrete floor supported on steel beams. Frequency and force response analyses were conducted. The maximum responses including accelerations, velocities, and displacements at bearing level were obtained for the in-phase and out-of-phase operation of the machines. For the particular case investigated the authors have observed significant interaction effect between the two machines. The critical condition was found to occur when the machines operated out-of-phase. The pertinent details about the machines, the dynamic loads, speed of operation and the supporting system are not reported in the paper.

EFFECT OF VIBRATIONS DUE TO MACHINE OPERATION ON ADJACENT FOUNDATIONS AND STRUCTURES

The vibrating foundations may have a harmful effect on adjacent structure and foundations depending on soil conditions, characteristics of the propagated waves, and the types of structures. Svinkin (1995) has presented results of an experimental investigation conducted to study the effect operation of forge hammers on exterior walls of forging shops. The effect of a drop hammer for breaking scrap iron on settlement of column footing supporting crane tracks was also investigated.

Ten forge hammers included in this study were housed in similar structures consisting of one storey braced steel frame construction and exterior brick walls resting on spread footings or column footings with foundation beams. The soil conditions on different sites were different and varied from fine sand to saturated medium sand and clay. The exterior brick walls of the forge hammer housing had severely cracked in some cases. Vertical and horizontal vibrations were measured on column footings and on the brick walls during operation of the forge hammers. Maximum transverse wall vibrations with with amplitudes of 0.7 mm were observed in some cases. The walls were observed to vibrate at operating frequencies of the hammers as well as at their own natural frequencies. Most of cracks in walls could be attributed to vibrations transmitted by the forging hammer operation. The observation on the large drop hammer indicated that nonuniform settlements of column footing occurred due to vibrations transmitted by its operation.

RELIABILITY ASPECTS OF MACHINE FOUNDATION DESIGN

Singh and Das (1995) have emphasized the uncertainties in the deterministic methods

commonly used for design of foundations under dynamic loads. These uncertainties could be physical, statistical, related to the model used for analysis or due to human errors. They have suggested that reliability based design should be incorporated to ensure safety and cost effectiveness. They have also suggested a methodology for reliability based design of non-critical structures.

REFERENCES

Abdel-Rohman, M., and Al-Sanad, H.,(1995)," Control of Vertical Non-linear Vibration s of Foundations", Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics, St. Louis, April 2-7.

Arnold, R.N., Bycroft, G.N. and Warburton, G.B. (1955), "Forced Vibrations of a Body on an Infinite Elastic Solid ", Journal Applied Mechanics, Transactions ASME, Vol. 22, pp. 391 -401.

Bycroft, G.N.(1956), "Forced Vibrations of a Rigid Circular Plate On a Semi-Infinite Elastic Space and on an Elastic Stratum", Philosophical Transactions, Royal Society, Ser. A, Vol. 248, pp. 327-368.

Bycroft, G.N. (1959), "Machine Foundation Vibration" Institution Of Mechanical Engineers, Vol. 173, No. 18, pp. 469-483.

Das, B.M. (1992), "Principles of Soil Dynamics", PWS Kent, Boston.

Dobry, R. and Gazetas, G. (1985), " Dynamic Stiffness and Dampng of Foundations by Simple Methods", Vibration Problems in Geotechnical Engineering, Proceedings of the Symposium Sponsored by the Geotechnical Engineering Division in Conjunction with the ASCE Convention, Detroit, Michigan, October 22, pp. 75-107.

Dobry, R. and Gazetas, G. (1986), " Dynamic Response of Arbitrarily Shaped Foundations", Journal of the Geotechnical Engineering Division, ASCE, Vol. 122, No. 2, February, pp. 126-135.

Gucunski, N.,(1995)," Response of Embedded Circular Flexible Foundation", Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics, St. Louis, April 2-7.

Hall, J. R. (1967)," Coupled Rocking and Sliding Oscillations of Rigid Circular Footings", Proceedings of the International Symposium on Wave Propagation and Dynamic Properties of Earth Materials, Albuquerque, N.M., Aug., pp. 139-147.

Hsieh, T.K. (1962), "Foundation Vibrations", Proceedings, Institution of Civil Engineers, London, England, Vol. 22, pp. 211-226.

Prakash, S., and Puri, V.K. (1988), "Foundations for Machines : Analysis and Design", John Wiley, New York.

Israil, A. and Banerjee, P. (1990), "Effects of Geometrical and Material Properties on the Vertical Vibration of Three Dimensional Foundations by BEM", International Journal of Numerical Analytical Methods in Geomechanics, Vol. 14, pp. 49-70.

Lee, J. P., and Bohinsky, A., (1995), " Interaction of Adjacent Machines", Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics, St. Louis, April 2-7., Vol. 3.

Lysmer, J. (1965), "Vertical Motion of Rigid Footings", U.S. Army Waterways Experiment Station", Report No. 3-115, Vicksburg, Mississippi, pp. 1-137.

Lysmer, J. and Richart, F.E., (1966), " Dynamic Response of Footings to Vertical Loading", Journal of the Soil Mechanics and Foundations Division, ASCE, Vol. 22, No SM1, Jan., pp. 65-91.

Mashhour, M., Abdel-Salam, S., and El-Naggar, S.,(1995)," Dynamics of Massless Rigid Foundation on Elastic Half Space", Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics, St. Louis, April 2-7.

Prakash, S. and Puri, V.K.,(1988)," Foundations for Machines : Analysis and Design", John Wiley. Richart, F.E., Hall, J.R., and Woods, R. (1970), "Vibrations of Soils and Foundations", Prentice Hall, New Jersey.

Singh, G., and Das, Braja M., (1995)," The Reliability Aspects in Dynamic Engineering", Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics, St. Louis, April 2-7.

Svinkin, M. R., (1995)," Vibrations of Impact Machine Foundations and Footing Settlements", Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics, St. Louis, April 2-7.

Truong , H. V. P., and Moore, P. J.,(1995)," Development of New Stiffens and Damping Expressions for Footing Vibrations", Third International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics, St. Louis, April 2-7.

Wass, G., (1980), "Dinamisch Belastete Fundamete auf Geschichtetem Baugrund", VDI Berichte, Nr. 381, pp. 185-189.