



Missouri University of Science and Technology
Scholars' Mine

International Specialty Conference on Cold-Formed Steel Structures

(1982) - 6th International Specialty Conference on Cold-Formed Steel Structures

Nov 16th, 12:00 AM

Composite Steel Deck Diaphragm Slabs – Design Modes

Max L. Porter

Lowell F. Greimann

Follow this and additional works at: <https://scholarsmine.mst.edu/isccss>

 Part of the [Structural Engineering Commons](#)

Recommended Citation

Porter, Max L. and Greimann, Lowell F., "Composite Steel Deck Diaphragm Slabs – Design Modes" (1982). *International Specialty Conference on Cold-Formed Steel Structures*. 1. <https://scholarsmine.mst.edu/isccss/6iccfss/6iccfss-session9/1>

This Article - Conference proceedings is brought to you for free and open access by Scholars' Mine. It has been accepted for inclusion in International Specialty Conference on Cold-Formed Steel Structures by an authorized administrator of Scholars' Mine. This work is protected by U. S. Copyright Law. Unauthorized use including reproduction for redistribution requires the permission of the copyright holder. For more information, please contact scholarsmine@mst.edu.

COMPOSITE STEEL DECK DIAPHRAGM SLABS--DESIGN MODES

by

Max L. Porter^a
Lowell F. Greimann^a

INTRODUCTION

The use of cold-formed steel decking as reinforcement for concrete floor slabs has increased markedly in the past twelve to fifteen years. This kind of composite floor system has two primary advantages: the ability of the steel deck to provide formwork during the casting stages of the concrete and the ability to serve in composite action as tension reinforcement under positive bending. Composite shear transfer devices such as deck embossments or transfer wires provide restraint for horizontal shear which develops at the deck-to-concrete interface. Many other advantages in addition to those mentioned above are given in Reference 1.

Design recommendations for vertical loads applied to formed metal deck composite slabs have been developed at Iowa State University [2]. The design is controlled primarily by one-way behavior; that is, the relatively large bending stiffness of the slab parallels the longitudinal direction of the deck. Previous research at Iowa State University [1-5] has resulted in design equations [2] for predicting the load capacity of one-way steel-deck-reinforced composite slabs subjected to gravity loads. The predominant mode of failure was found to be shear-bond [3]. The design equation for shear-bond capacity prediction was based on a modification of Equation (11-6) of the American Concrete Institute (ACI) Code [6].

For steel deck floor slabs subjected to lateral loads, two types of composite behavior need to be considered: behavior due to vertical (gravity) loads and behavior due to in-plane loads. A general view of such a floor slab system with both composite deck and studs is shown in Figure 1. Past research on composite steel deck slabs has considered the effect of vertical loads on shear-bond behavior but not the effect of in-plane forces. In addition, the behavior of composite slab-to-support beam behavior [7,8,9] needs consideration. These concerns led to research at Iowa State University to determine the in-plane shear strength and failure behavior.

^aProfessor, Civil Engineering Department, Iowa State University, Ames Iowa.




Fig. 1. Typical construction utilizing cold-formed steel decking with composite support beams.

Potential design failure modes are presented in this paper for composite steel-deck-reinforced diaphragm slabs. Whereas previous papers have dealt with steel deck slabs subjected to gravity loads, this paper focuses on such slabs subjected to in-plane shear forces resulting from lateral loads typically produced by wind or earthquakes. All slabs in this investigation were reinforced with cold-formed steel decking. The work described was part of a project sponsored by the National Science Foundation on "Seismic Resistance of Composite Floor Diaphragms" [10].

Previous work on steel deck slabs at Iowa State University sponsored by the American Iron and Steel Institute aided in the formulation of the work in this investigation since certain failure modes observed in gravity-loaded floors are also possible in composite steel deck slabs subjected to diaphragm loading. The objective of this work was to determine the behavioral and strength characteristics of composite steel deck floor systems subjected to in-plane shear. A large test fixture was fabricated on which, to date, nine full-scale composite steel deck slab floors have been tested.

FAILURE MODES

Table 1 lists potential failure modes for composite steel deck diaphragms subjected to in-plane shear. This list is based on research done by Nilson and Ammar [11-15], Luttrell [16-17], Ellifritt and Luttrell [18-19], Apparao [20], Pinkham,† Easley [21], Davies [22], Bryan [23], Porter and Ekberg [24-26], as well as on the test results from this project. The major parameters involved in these failure modes are shear connections (arc spot welds, studs), concrete qualities (strength, depth), diaphragm configuration (orientation, plan dimensions, and thickness), composite deck strength and stiffness, and loading history (cyclic and monotonic). To understand the relative importance of these parameters and to arrive at possible design criteria, the failure modes must be studied and understood. In general, these modes, as applied to the floor slab, are divided into three broad categories:

† C. W. Pinkham, S. B. Barnes and Associates, Los Angeles, California. Personal visit to Iowa State University, April 7, 1977.

Table 1. Failure modes for composite diaphragms.

-
1. Composite Diaphragm
 - a. Shear strength
 1. Diagonal tension
 2. Parallel to deck corrugations
 - b. Stability failure
 - c. Localized failure
 2. Deck/Concrete Interface
 - a. Interfacial shear parallel to the corrugations
 - b. Interfacial shear perpendicular to the corrugations
 1. Pop up (overriding)
 2. Deck fold-over
 3. Diaphragm/Edge Member Interface
 - a. Arc spot welds
 1. Shearing of weld
 2. Tearing and/or buckling of deck around weld
 - b. Concrete rib
 - c. Studs (or other shear connectors)
 1. Shearing of stud
 2. Shear failure of concrete around stud
-

- overall composite diaphragm action,
- steel deck-to-concrete interface behavior, and
- diaphragm-to-edge member interface failure.

Composite Diaphragm Failures

Composite diaphragm failures occur when, at the time of maximum load, the system acts as a composite unit. A diagonal tension failure (Failure Mode 1a-1 in Table 1) is an example of this type of failure. This failure mode, which occurs when the concrete stress reaches its tensile limit, is characterized by diagonal cracks (at an angle of approximately 45°) across the slab (Fig. 2). After this crack forms, the steel deck begins to act as shear reinforcement, transferring the forces across the crack.

Another type of composite diaphragm failure is a direct shearing of the concrete along a line parallel to the deck corrugations (Failure Mode 1a-2) (see Fig. 2). If the concrete covering is thin, this failure will be most likely to occur over an up corrugation, with the ultimate strength depending on the shear strength of the concrete.

Two other failure modes, stability and localized (Failure Modes 1b and 1c), are also possible. A stability failure is typical for metal deck diaphragms with large width-(or span)-to-thickness ratios. However, in composite diaphragms, the concrete effectively prevents out-of-plane buckling due to in-plane loads for the practical span lengths. All of the tests for this research consisted of composite diaphragms of moderate span lengths with only in-plane loading, so the stability failure mode did not occur. Combined in-plane and vertical (gravity) loading may necessitate consideration of this failure mode. A localized failure typically occurs when there is a nonuniform shear distribution in the diaphragm and, consequently, a discrete region of high stress. This failure, which is restricted to a small area, is created by concentrated loads or reactions and/or flexible edge beams.

Deck/Concrete Interface

If the composite deck does not make use of shear connectors (e.g., studs), all of the diaphragm force must be transferred to the concrete by forces at the interface between the steel deck and the concrete, i.e., by interfacial shear forces. Failure by interfacial shear (Failure Mode 2) can occur either parallel or perpendicular to the deck corrugations. Interfacial shear failure parallel to the corrugations (Failure Mode 2a) is similar in character to the shear-bond failure experienced in vertically loaded specimens [3,5].

When failure occurs in the direction perpendicular to the steel deck corrugations, the concrete bears against the inclined face of the cell. Two types of behavior may occur. If the corrugations are stiff enough, the concrete may actually ride up and over them (Failure Mode




Fig. 2. Failure by shearing of the concrete in a) diagonal tension and b) cracks parallel to the corrugations (Failure Mode 1a-1 and 1a-2 in Table 1).

2b-1). If they are flexible, the concrete will flatten out the corrugations, a type of behavior comparable to that of a horizontally loaded simple frame (Failure Mode 2b-2). Which mode occurs depends on the stiffness of the deck corrugations and the relative interfacial shear strength in both the transverse and longitudinal directions.

Diaphragm/Edge Member Interface


Edge connections are frequently made with arc spot welds or studs. With the arc spot welds, the load is transferred through the steel deck. Failure at these points would be a direct shearing of the weld (Failure Mode 3a-1), or a buckling and/or tearing of the deck around the weld (Failure Mode 3a-2). With arc spot welds or short studs that do not extend above the up corrugation, a direct shearing of the concrete rib, resembling an unreinforced corbel, could occur (Failure Mode 3b).

With studs that extend above the up corrugation of the steel deck, the shear force is transferred directly onto the concrete above the deck profile. Failure of this form of connection may be a result of stud shear (Failure Mode 3c-1) or concrete failure around the stud (Failure Mode 3c-2). This second form is usually the result of an inadequate amount of concrete in the down corrugation and/or at the edges.


TEST FACILITY

To study the failure modes, strength, and many other behavioral characteristics of composite steel deck diaphragm slabs, a large test frame facility was constructed. Several types of test frame facilities were evaluated prior to the selection of the final configuration. Samples of three of these potential diaphragm test frames are shown in Fig. 3. To compare the effect of frame stiffness and boundary conditions on the diaphragm stress distributions, a linear finite-element analysis computer program, SAP IV, was used to analyze the proposed frame arrangements indicated in Fig. 3.


A cantilever diaphragm test frame with a fixed edge support was chosen as the final design. In most buildings with a composite floor system, an adjacent slab exists on at least one side which provides in-plane restraint against deformation. Also, the fixed edge support approximately models a continuously attached shear wall. The free edge models a structural steel frame in which the in-plane forces are transferred to the diaphragm along the horizontal member. Stiff edge



(a) Cantilever frame with hinge and roller support



(b) Diagonally loaded frame



(c) Cantilever frame with a fixed edge support

Fig. 3. Plan view of potential test frames and loading configurations.

beams were used for this test frame because they produce a more uniform shear stress distribution in the test diaphragm than do flexible support beams.

A schematic of the test frame facility appears in Fig. 4. As indicated in the figure, the constructed test frame facility consisted of three large reinforced-concrete reaction blocks (for the fixed edge) and three perimeter-framing beams. The frame was designed for a working load of ± 400 kips and a displacement capability of ± 6 inches.

The three blocks were used to support one edge of the composite floor diaphragm. An imbedded steel plate, simulating a rigid-beam flange, was used to attach the steel deck of the floor slab to the reaction blocks. The blocks were anchored to the laboratory test floor with two-inch diameter high-strength bolts, each post-tensioned to 240 kips. The laboratory test floor was a million pound capacity tie-down floor system.

The edge beams for the test frame were made from wide-flange (W) 24×76 steel beams. Web stiffeners were added to prevent rotation of the top flange during large displacements. Friction-type bolted connections were used to join the framing beams together. These bolted connections consisted of flexible "T"-shaped elements instead of pins or hinges. The flexible "T" connections provided a constant frictional restraint during testing.

Two hydraulic double-acting cylinders were used to apply the force to the testing frame. These actuators were front trunnion-mounted and capable of pushing or pulling 200 kips each, giving the test frame a 400-kip capacity. The force was measured by a specially fabricated 200-kip load cell attached in series to the cylinder rod shaft. Pressure gages located at the cylinder ports were used as an indirect measure of the load and served as a visual aid during the testing sequence.

SUMMARY OF TEST SPECIMEN RESULTS

The facilities and instrumentation described in the preceding sections performed very well throughout the test sequence. Nine full-scale composite diaphragm slabs were tested using the cantilever-type test frame. The slabs were $15'4" \times 15'4"$ in out-to-out plan dimensions and ranged in thickness from $3\ 1/2$ inches to $7\ 1/2$ inches (nominally). The first slab specimen tested was used to verify the adequacy of the test frame, controls, instrumentation, and data acquisition systems. No additional supplementary reinforcing was included. All slabs were wet cured for 7-14 days, and then air dried until test time.




Fig. 4. Diaphragm test frame schematic.

Material summarizing behavioral results from the test and potential analyses is given in Reference 10.

Summaries of the important parameters and the experimental results for the diaphragm slab specimens tested are given in Tables 2 and 3, respectively. A reversed cyclic displacement program with progressively increasing displacements was used for all slabs except the first (pilot) specimen, which was loaded horizontally.

Of particular interest among the failure modes that relate to the shear-bond type of behavior is Mode 2.a in Table 1, i.e., interfacial shear parallel to the corrugations. This mode results in horizontal end slip observed at the edge of the specimen for both gravity and in-plane loaded specimens [3,10]. The failure of Slab 6 in Tables 2 and 3 will be described in more detail.

The maximum load for Slab 6, 146.8 kips, was reached at a 0.1-inch displacement. The load-displacement curve is shown in Fig. 5. The mode of failure for this slab was interfacial shear parallel to the corrugations. The most significant observation to make about this slab is that no cracks formed on the top surface of the concrete throughout the entire test. The concrete simply slipped parallel to the corrugations and rotated about a vertical axis as the frame was cycled back and forth. A very high secondary defense plateau formed at 107 kips, after the maximum load (Fig. 5). The load-carrying mechanism in the nonlinear range was frictional interference between the steel deck and concrete. This frictional force was caused by a conflict between the displaced shapes of the steel deck and concrete, i.e., a warpage of the deck cells against the concrete cells. In general, for all the slabs tested, a significant amount of load capacity remained after ultimate failure and a strength and stiffness degradation similar to that shown in Fig. 5 occurred for the other failures.

Further illustrations of this particular failure mode and the test frame arrangement will be given during the oral presentation. Additional work is planned for combining the tests for in-plane and gravity shear-bond failure as well as other failure mode combinations.

Design for Composite Diaphragm Slabs

Each of the failure modes shown in Table 1 must be considered for design of composite deck slabs. Conceivably, the designer needs to consider and evaluate load carrying capacities for each mode and determine the controlling failure mode that will produce the lowest in-plane load capacity. Since many more modes of design exist for composite diaphragm slabs than for simple beams or other component structures, the design formulations needed to arrive at the controlling mode are

Table 2. Summary of parameters for slab specimens.

Slab Number	Concrete Parameters			Steel Deck Parameters				Connections Per Side
	Nominal Thickness (in.)	Actual Thickness ^a (in.)	f' (psi)	Deck Depth (in.)	Thickness (in.)	Yield Strength (ksi)	Ultimate Strength (ksi)	
1	5 1/2	5.38	5634	3	0.034	41.7	53.4	30 studs
2	5 1/2	5.50	5250	3	0.034	41.7	53.4	30 studs
3	5 1/2	5.65	4068	3	0.034	41.7	53.4	60 welds
4	5 1/2	5.28	3849	3	0.034	41.7	53.4	60 welds
5	5 1/2	3.53	2966	1 1/2	0.062	48.2	60.7	30 welds
6	5 1/2	7.44	4549	1 1/2	0.062	48.2	60.7	60 welds
7	5 1/2	5.40	5435	3	0.058	49.7	61.1	60 welds
8	5 1/2	5.47	3345	3	0.035	41.7	53.4	4 studs (each N-S side) 6 studs (each E-W side)
9	5 1/2	5.48	5412	3 (cells) ^b 3 (pan)	0.058 0.057	51.8 52.4	63.2 64.9	60 welds

^aOut-to-out thickness.^bA cellular type deck was used on Slab 9.

Table 3. Summary of experimental results.

Slab Number	Initial Stiffness (KIPs/in.)	V_u (KIPs)	Failure Mode
1	1800	168	Diagonal tension
2	2000	186	Diagonal tension
3	1600	97.8	Interfacial shear
4	1300	87.7	Interfacial shear
5	1700	116	Diagonal tension
6	2600	147	Interfacial shear
7	1500	137	Interfacial shear
8	1100	54.4	Diagonal tension/ shear connector
9	1900	220	Diagonal tension




Fig. 5. Load-displacement diagram for Slab 6.

more lengthy. The design mode becomes even more complex when the loading consists of gravity combined with in-plane loading. Work is underway at Iowa State University to investigate such analyses further and to design recommendations for composite steel deck diaphragm slabs to supplement those design recommendations in Reference 2 for gravity-loaded steel deck slabs.

SUMMARY

The test facility described herein was designed and constructed for testing composite steel deck diaphragms. Nine full-scale (15-foot square) diaphragms were tested using a cantilever-type test frame. The tests followed a displacement program controlled by an MTS closed-loop system.

All slabs were constructed using corrugated, cold-formed steel decking as composite reinforcement for the concrete slabs. The results of the tests will eventually be used to formulate design recommendations for in-plane shear strength for steel deck reinforced slabs. These design recommendations are intended to supplement those proposed in Reference 2 for gravity-loaded steel deck slabs. The results also should aid in establishing test standards for floor slab diaphragm tests and associated instrumentation.

In conclusion, the test frame facility described in this paper performed very well. The failure modes given in Table 1 provide the basis for future design formulations for composite steel deck reinforced floor slabs.

REFERENCES

1. Porter, M. L. and Ekberg, C. E., Jr., "Compendium of ISU Research Conducted on Cold-Formed Steel-Deck-Reinforced Slab Systems," Bulletin 200, Engineering Research Institute, Iowa State University, December 1978.
2. Porter, M. L. and Ekberg, C. E., Jr., "Design Recommendations for Steel Deck Floor Slabs," Journal of the Structural Division, ASCE, Vol. 102, No. ST11, Proc. Paper 12528, November 1976, pp. 2121-2136.
3. Porter, M. L., Ekberg, C. E., Jr., Greimann, L. F. and Elleby, H. A., "Shear-Bond Analysis of Steel-Deck-Reinforced Slabs," Journal of the Structural Division, ASCE, Vol. 102, No. ST12, Proc. Paper 12611, December 1976, pp. 2255-2268.
4. Porter, M. L. and Ekberg, C. E., Jr., "Design vs Test Results for Steel Deck Floor Slabs," Proceedings of Third Specialty Conference on Cold-Formed Steel Structures, Department of Civil Engineering, University of Missouri-Rolla, October 1975, pp. 293-812.
5. Porter, M. L. and Ekberg, C. E., Jr., "Behavior of Steel-Deck Reinforced Slabs," Journal of the Structural Division, ASCE, Vol. 103, No. ST3, Proc. Paper 12826, March 1977, pp. 663-677.
6. American Concrete Institute, Building Code Requirements for Reinforced Concrete, ACI Standard 318-77, Detroit, Michigan: American Concrete Institute, 1977.
7. Grant, J. A., Fisher, J. W. and Slutter, R. G., "Composite Beams with Formed Steel Deck," AISC Engineering Journal, American Institute of Steel Construction, First Quarter 1977, pp. 24-43.
8. Ollgaard, J. G., Slutter, R. G. and Fisher, J. W., "Shear Strength of Stud Connectors in Lightweight and Normal-Weight Concrete," AISC Engineering Journal, American Institute of Steel Construction, 8, No. 2, April 1971, pp. 55-64.
9. American Institute of Steel Construction, Inc., Specification for the Design, Fabrication and Erection of Structural Steel for Building, New York: AISC, 1980.
10. Porter, M. L. and Greimann, L. F., "Seismic Resistance of Composite Floor Diaphragms," ISU-ERI-Ames-80133, Iowa State University, Ames, Iowa, Final Report submitted to National Science Foundation, May 1980, 174 pp.

11. Nilson, A. H., "Shear Diaphragms of Light Gage Steel," Journal of the Structural Division, ASCE 86, No. ST11 (November 1960), 111-140.
12. Nilson, A. H., "Diaphragm Action of Light Gage Steel Construction," AISI Regional Technical Paper (1960).
13. Nilson, A. H. and Ammar, A. R., "Finite Analysis of Metal Deck Shear Diaphragms," Journal of the Structural Division, ASCE 100, No. ST4 (April 1974), 711-726.
14. Ammar, A. A. and Nilson, A. H., "Analysis of Light Gage Steel Shear Diaphragms, Part I," Department of Structural Engineering, Research Report 350, Cornell University (August 1972).
15. Ammar, A. A. and Nilson, A. H., "Analysis of Light Gage Steel Shear Diaphragms, Part II," Department of Structural Engineering, Research Report 351, Cornell University (August 1973).
16. Luttrell, L. D., "Strength and Behavior of Light Gage Steel Shear Diaphragms," Department of Structural Engineering, Cornell Engineering Research Bulletin No. 67-1, Cornell University (July 1967).
17. Luttrell, L. D., "Structural Performance of Light Gage Steel Diaphragms," Department of Structural Engineering, Research Report 319, Cornell University (August 1965).
18. Ellifritt, D. S. and Luttrell, L. D., "Strength and Stiffness of Steel Deck Shear Diaphragms," Proceedings of First Specialty Conference on Cold-Formed Steel Structures, Department of Civil Engineering, University of Missouri-Rolla (August 19-20, 1971).
19. Ellifritt, D. S. and Luttrell, L. D., "Strength and Stiffness of Steel Deck Subjected to In-Plane Loading," West Virginia University Civil Engineering Studies Report 2011, West Virginia University, Morgantown, West Virginia (1968).
20. Apparao, T. V., "Tests on Light Gage Steel Diaphragms," Department of Structural Engineering, Research Report 328, Cornell University, (December 1966).
21. Easley, J. T., "Buckling Formulas for Corrugated Metal Shear Diaphragms," Journal of the Structural Division, ASCE 101, No. ST7, Proc. Paper 11429 (July 1975), 1403-1417.
22. Davies, M. J., "Calculation of Steel Diaphragms Behavior," Journal of the Structural Division, ASCE 102, No. ST7 (July 1976), 1431-1445.
23. Bryan, E. R., The Stressed Skin Design of Steel Buildings. London, England: Crosby Lockwood Staples (1973).

24. Porter, M. L. and Ekberg, C. E., Jr., "Investigation of Cold-Formed Steel-Deck-Reinforced Concrete Floor Slabs," Proceedings of First Specialty Conference on Cold-Formed Steel Structures, Department of Civil Engineering, University of Missouri-Rolla (August 19-20, 1971).
25. Porter, M. L. and Ekberg, C. E., Jr., "Summary of Full-Scale Laboratory Tests of Concrete Slabs Reinforced with Cold-Formed Steel Decking," Preliminary Report, International Association for Bridge and Structural Engineering, Ninth Congress, Zurich, Switzerland (May 8-12, 1972).
26. Porter, M. L., Commentary on the Tentative Recommendations for the Design of Composite Steel Deck Slabs. Manual. Washington, D.C.: American Iron and Steel Institute (December 1974).