

15K thermal buffer using liquid hydrogen

Borges de Sousa P.¹, Martins D.¹, Patrício R.², Linder M.³, Catarino I.¹, Bonfait G.¹

¹CEFITEC, Physics Department, Faculty of Sciences and Technology, Universidade Nova de Lisboa, 2829-516 Caparica, Portugal

²Active Space Technologies, Rua Coronel Veiga Simão, 3025-307 Coimbra, Portugal

³European Space Agency, ESTEC, E0053A, 2200 AG Noordwijk, The Netherlands

A problem that typically arises from the use of complex cryogenic chains used in space applications is the existence of heat bursts during the recycling stages of some components, which can compromise the stability of the entire chain. Instead of using large cryogenic liquid reservoirs to cool the system or to compensate for heat bursts, which is a costly and temporary solution (as the liquid will eventually run out), or over dimensioning the cryocoolers, we propose a more practical solution: the introduction of a thermal buffer to absorb these heat bursts without significant temperature change.

Systems composed of mechanical cryocoolers and a thermal buffer or thermal storage unit have been previously demonstrated, either using high heat capacity materials [1], or taking advantage of the latent heat in a phase transition, may it be solid-solid [2], liquid-vapor [3], or solid-liquid-vapor at the triple point [4, 5]; the choice of material depends on the temperature range. This type of system helps reduce the temperature drift that would occur from turning a cryocooler off (for sensitive measurement purpose), and it can act as a temperature stabilizer in a cryogenic chain.

In the framework of an ESA contract we are developing a thermal buffer operating between 15 and 20 K, capable of absorbing a heat burst of 400 J. It takes advantage of the latent heat at the liquid-vapor transition of hydrogen, while being a closed system. This system is composed by a low temperature liquid H₂ reservoir (~15 cm³) and an expansion volume at room temperature.

As cryogenic chains able to provide cooling down to 50 mK [6] have been investigated as options for XMS on Athena, this kind of device can be used to absorb part of the generated heat bursts. The presented thermal buffer is being designed in order to comply with strict weight, volume and thermal power requirements that allow it to be integrated in the aforementioned cryogenic chain. Challenges that arise from working with hydrogen, such as its storage at low pressure and the ortho-para conversion, as well as working in a microgravity environment, are addressed and solutions are proposed.

This work is supported by the European Space Agency (ESTEC contract 4000108532/12/NL/E and by Fundação para a Ciência e Tecnologia (PTDC/EME-MFE/101448/2008 and PEst-OE/FIS/UI0068/2011). PBS and DM acknowledge the latter institution for granting.

[1] Afonso, J. *et al.*, *Energy Storage Unit: Solid state demonstrators at 20K and 6K*, *Cryogenics* 50 (2010) 522-528

[2] Bugby D. *et al.*, *Development and testing of a 35K cryogenic Thermal Storage Unit*, 41st Aerospace Science Meeting and Exhibit (2003) 1-9

[3] Afonso, J. *et al.*, *Liquid Nitrogen Energy Storage Unit*, *Cryogenics* 51 (2011) 621-629

[4] Charles, I. *et al.*, *Thermal storage unit using the triple point of Hydrogen*, *Cryocoolers* 16 (2011) 575-582

[5] Rijpma, A. P. *et al.*, *A nitrogen triple-point thermal storage unit for cooling a SQUID magnetometer*, *Cryogenics* 45 (2005) 231-239

[6] Duband, L. *et al.*, *SPICA sub-Kelvin cryogenic chains*, *Cryogenics* 52 (2012) 145-151