

University of Kentucky UKnowledge

Soil Science News and Views

Plant and Soil Sciences

1995

# Potential Agronomic Benefits of Wood Ash Application on Reclaimed Surface Mined Lands

David C. Ditsch University of Kentucky, david.ditsch@uky.edu

John H. Grove University of Kentucky, jgrove@uky.edu

William O. Thom University of Kentucky, wthom@uky.edu

Right click to open a feedback form in a new tab to let us know how this document benefits you.

Follow this and additional works at: https://uknowledge.uky.edu/pss\_views Part of the <u>Soil Science Commons</u>

#### **Repository Citation**

Ditsch, David C.; Grove, John H.; and Thom, William O., "Potential Agronomic Benefits of Wood Ash Application on Reclaimed Surface Mined Lands" (1995). *Soil Science News and Views*. 29. https://uknowledge.uky.edu/pss\_views/29

This Report is brought to you for free and open access by the Plant and Soil Sciences at UKnowledge. It has been accepted for inclusion in Soil Science News and Views by an authorized administrator of UKnowledge. For more information, please contact UKnowledge@lsv.uky.edu.

UNIVERSITY OF KENTUCKY COLLEGE OF AGRICULTURE Lexington, KY 40546-0064



# Soil Science News & Views

## Potential Agronomic Benefits of Wood Ash Vol. 16, No. 7, 1995 Application on Reclaimed Surface Mined Lands

D.C. Ditsch, J.H. Grove and W.O. Thom

Wood ash is a by-product generated by paper companies, lumber manufacturing plants and utilities that burn wood products, bark and papermill sludge as a means of disposal and/or energy production. Large quantities of wood ash are generated by these industries since wood generally contains 6 to 10% ash. Most of these ashes are landfilled or discarded in lagoons. However, the increasing expense of landfill disposal has led to increased interest in the land application of industry generated wood ash.

Before commercial fertilizers and agricultural limestone were economically feasible and easily obtained, wood ashes were used to enhance crop production. In fact, the term "potash," which is commonly used today when referring to potassium (K) fertilizer, is derived from the use of wood ash as a source of K. This trend may be reversing in some local areas where the economics of applying wood ash as a soil amendment make this practice more competitive.

The chemical characteristics of industry generated wood ash can be highly variable and are a function of tree species and the part of the tree burned. In general, wood ash has a Calcium Carbonate Equivalent (CCE) ranging from 35 to 85% and is used primarily as a liming amendment. Wood ash also contains variable amounts of many essential plant nutrients, such as phosphorus (P), potassium (K), calcium (Ca), magnesium (Mg), zinc (Zn), copper (Cu), manganese (Mn), sulfur (S), iron (Fe), and boron(B). Phosphorus (0.01-2%), Ca (0.58-70%) and K (0.3-20%) are the plant nutrients in wood ash that are commonly present in quantities large enough to be of agronomic importance. Nitrogen (N)

is also present in wood ash, but only at very low levels.

The land application of any industrial by-product is often regulated by its heavy metal content and potential environmental impact. In addition to the metals already mentioned as plant nutrients, wood ash may contain several other elements such as aluminum (Al), arsenic (As), nickel (Ni) and titanium (Ti). Researchers at Auburn University analyzed 19 boiler ash samples and did not find excessive levels of any metal present. In general, wood ash is always lower in heavy metals than coal fly ash. However, all wood ash samples should be analyzed for heavy metal content before land application.

The physical characteristics of wood ash may make handling the most difficult challenge if ash is to be used as an alternative to agricultural limestone. The small particle

Educational programs of the Kentucky Cooperative Extension Service serve all people regardless of race, color, age, sex, religion, disability, or national origin.

UNIVERSITY OF KENTUCKY, KENTUCKY STATE UNIVERSITY, U.S. DEPARTMENT OF AGRICULTURE, AND KENTUCKY COUNTIES, COOPERATING

size (65-100% passing a 60-mesh screen) and low bulk density of wood ash (average 0.52 g/cm<sup>3</sup> or 0.44 tons/yd3) compared to ground limestone (2 g/cm<sup>3</sup> or 1.7 tons/yd<sup>3</sup>) can be a positive attribute in terms of timely reactivity with the soil. However, the ability to uniformly apply wood ash with conventional spinner spreader equipment is lim-Also, depending upon the ited. CCE of wood ash, the rates of material applied to the land may need to be adjusted to obtain the same neutralizing effect as agricultural limestone.

In the Appalachian coal fields of eastern Kentucky, Trus Joist Mac-Millan has recently constructed the largest single-product engineered lumber plant in the world. At this plant, small diameter yellow poplar (<12" diameter) will be processed into structural building materials using newly emerging technologies. Logs entering the plant are prepared for processing by first being debarked. The yellow poplar bark (referred to as "hog fuel") will be burned in a furnace as an energy source for numerous plant operations, resulting in approximately 6,000 tons of wood ash generated each year.

The Trus Joist MacMillan plant was constructed on a reclaimed surface mine site in Perry County, near many active coal surface mines. Reclaiming these mine sites typically requires the application of agricultural limestone and fertilizers to obtain vegetative cover and achieve the level of plant productivity required by state regulatory agencies. Unfortunately, the geology and remoteness of this coal mining region results in high quality liming materials being expensive because they must be hauled in. Thus, the availability of wood ash as a liming agent is of considerable local interest to the mining industry and to Trus Joist Mac-Millan as an economical and environmentally safe alternative to landfill disposal.

To determine wood ash application rates necessary to adjust mine spoil pH, UK agronomists will initiate greenhouse and field studies in 1995 using mine spoil material from a potential land application site and yellow poplar wood ash generated by the Trus Joist Mac-Millan plant. Plant nutrient and heavy metal uptake, yield, and soil pH measurements will be made over a 2 year period to determine the agronomic benefit of wood ash as a soil amendment.

David C. Ditsch Extension Agronomy Specialist

Page 2

#### COOPERATIVE EXTENSION SERVICE U.S. DEPARTMENT OF AGRICULTURE UNIVERSITY OF KENTUCKY COLLEGE OF AGRICULTURE LEXINGTON, KENTUCKY 40546

OFFICIAL BUSINESS PENALTY FOR PRIVATE USE, \$300

### AN EQUAL OPPORTUNITY EMPLOYER

BULK RATE POSTAGE & FEES PAID USDA PERMIT No. G268

ţ